

RF Exposure Report

FCC ID: 2AVWB-AX1500

RF Exposure Measurement

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b)

Limits for Maximum Permissible Exposure (MPE)

F= Frequency in MHz

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)
Limits for Occupational / controlled Exposures			
300 - 1500	--	--	F/300
1500 – 100000	--	--	5.0
Limits for General population / Uncontrolled Exposure			
300 - 1500	--	--	F/1500
1500 – 100000	--	--	1.0

Friss Formula

Friss Transmission Formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.

EUT Operation condition

EUT was enabled to transmit and receive at lowest, middle and highest channels.

Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance from the antenna should be included in the User manual. So, this device is classified as Mobile device.

1. 2.4G WIFI

Mode	802.11b/g/n20:2412-2462MHz
Detector	PEAK
802.11b	17±1dBm
802.11g	23±1dBm
802.11n20	26±1dBm
802.11n40	25±1dBm

ANT Gain (G)

Antenna A gain : 4.2dBi

Antenna B gain : 4.2dBi

MIMO technology Directional gain=7.21dBi

Antenna gain : 7.21dBi (gain of antenna in linear scale=5.26)

Protocol	ANT Gain(gain of antenna in linear scale)	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)
802.11 b	5.26	2437	18	63.10	0.07	1
802.11 g	5.26	2437	24	251.19	0.26	1
802.11 n20	5.26	2437	27	501.19	0.52	1
802.11 n40	5.26	2437	26	398.11	0.42	1

2. 5G WIFI-Band1

Mode	802.11a/n20/n40/ac20/ac40/ac80: 5150-5250MHz
Detector	AV
802.11a	9±1dBm
802.11n20	9±1dBm
802.11n40	9±1dBm
802.11ac20	9±1dBm
802.11ac40	9±1dBm
802.11ac80	5±1dBm
802.11ax20	9±1dBm
802.11ax40	9±1dBm
802.11ax80	5±1dBm

ANT Gain (G)

Antenna A gain : 4.5dBi

Antenna B gain : 4.5dBi

MIMO technology Directional gain=7.51dBi

Antenna gain : 7.21dBi (gain of antenna in linear scale=5.64)

Protocol	ANT Gain(gain of antenna in linear scale)	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)
802.11 a	5.64	5180	10	10.00	0.01	1
802.11 n20	5.64	5180	10	10.00	0.01	1
802.11 n40	5.64	5190	10	10.00	0.01	1
802.11 ac20	5.64	5180	10	10.00	0.01	1
802.11 ac40	5.64	5190	10	10.00	0.01	1
802.11 ac80	5.64	5210	6	3.98	0.0045	1
802.11 ax20	5.64	5180	10	10.00	0.01	1
802.11 ax40	5.64	5190	10	10.00	0.01	1
802.11 ax80	5.64	5210	6	3.98	0.0045	1

3. 5G WIFI-Band4

Mode	802.11a/n20/n40/ac20/ac40/ac80: 5750-5850MHz
Detector	AV
802.11a	9±1dBm
802.11n20	11±1dBm
802.11n40	11±1dBm
802.11ac20	11±1dBm
802.11ac40	11±1dBm
802.11ac80	5±1dBm
802.11ax20	11±1dBm
802.11ax40	11±1dBm
802.11ax80	5±1dBm

ANT Gain (G)

Antenna A gain : 4.5dBi

Antenna B gain : 4.5dBi

MIMO technology Directional gain=7.51dBi

Antenna gain : 7.21dBi (gain of antenna in linear scale=5.64)

Protocol	ANT Gain(gain of antenna in linear scale)	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)
802.11 a	5.64	5745	10	10.00	0.01	1
802.11 n20	5.64	5745	11	12.59	0.01	1
802.11 n40	5.64	5755	11	12.59	0.01	1
802.11 ac20	5.64	5745	11	12.59	0.01	1
802.11 ac40	5.64	5755	11	12.59	0.01	1
802.11 ac80	5.64	5775	6	3.98	0.0045	1
802.11 ax20	5.64	5745	11	12.59	0.01	1
802.11 ax40	5.64	5755	11	12.59	0.01	1
802.11 ax80	5.64	5775	6	3.98	0.0045	1