

## **FCC ID : 2AVWT-GENPPF**

### **RF EXPOSURE EVALUATION**

According to KDB 447498 D01 v06

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

$$11.1 \text{ Friis transmission formula: } P_d = (P_{out} * G) / (4 * \pi * R^2)$$

Where

Pd= Power density in mW/cm<sup>2</sup>

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1416

R= distance between observation point and center of the radiator in cm

Pd the limit of MPE,  $1\text{mW/cm}^2$ , If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

RF Exposure Information: The radiated output power of this device meets the limits of FCC/IC radio frequency exposure limits. This device should be operated with a minimum separation distance of 20cm (8 inches) between the equipment and a person's body.

## 11.2 Measurement Result

Wifi 2.4G--

Antenna gain: 0.92 dBi

modulation	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
11b	2412	21.20	19 to 22	22	1.24	0.03897	1
	2437	20.22	19 to 22	22	1.24	0.03897	1
	2462	19.87	19 to 22	22	1.24	0.03897	1
11g	2412	18.60	18 to 20	20	1.24	0.02459	1
	2437	18.71	18 to 20	20	1.24	0.02459	1
	2462	18.40	18 to 20	20	1.24	0.02459	1
11n HT20	2412	18.53	18 to 20	20	1.24	0.02459	1
	2437	18.61	18 to 20	20	1.24	0.02459	1
	2462	18.29	18 to 20	20	1.24	0.02459	1
11n HT20	2412	17.99	17 to 20	20	1.24	0.02459	1
	2437	17.90	17 to 20	20	1.24	0.02459	1
	2462	17.80	17 to 20	20	1.24	0.02459	1

BT--

Antenna gain: 0.92 dBi

modulation	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune- up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2 )	Power density Limits (mW/cm2 )
GFSK	2402	2.62	2 to 4	4	1.24	0.00062	1
	2441	2.417	2 to 4	4	1.24	0.00062	1
	2480	3.009	2 to 4	4	1.24	0.00062	1
pi/4- DQPSK	2402	5.415	5 to 6	6	1.24	0.00098	1
	2441	5.117	5 to 6	6	1.24	0.00098	1
	2480	5.832	5 to 6	6	1.24	0.00098	1
8DPSK	2402	5.973	5 to 7	7	1.24	0.00123	1
	2441	5.761	5 to 7	7	1.24	0.00123	1
	2480	6.364	5 to 7	7	1.24	0.00123	1

BLE--

Antenna gain: 0.92 dBi

modulation	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2 )	Power density Limits (mW/cm2 )
BLE_1M	2402	3.653	3 to 5	5	1.24	0.00078	1
	2440	3.393	3 to 5	5	1.24	0.00078	1
	2480	4.064	3 to 5	5	1.24	0.00078	1

Simultaneous Transmission

Mode	$\sum$ max ratios	Limit	Results
WIFI 2.4G+BT	0.0402	1.0	PASS