

型号：4010-001

遥控器

工作电压:12Vdc

工作电流：≤12mA

遥控距离：50-100M（空旷地）

频率：433.92MHZ

频率偏差：±0.2MHZ

材质：塑料

调制方式：ASK（幅移键控）

尺寸：120*72*31 毫米

净重：110 克

蓝牙BOX

工作电压:10-30Vdc

工作电流：≤20A

蓝牙控制距离：10-25m（空旷地）

频率：2402-2480MHz

材质：塑料

调制方式：GFSK（高斯频移键控）

尺寸：224*120.2*44.5 毫米

净重：930 克

使用领域：车船照明灯具、车船警示灯具、车船喇叭等各灯具及其他汽车电子电器与消费类电子电器控制。

This device plies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1)

This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Changes or modifications not expressly approved by the party responsible for compliance could void your authority to operate the equipment.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

-- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

-- Consult the dealer or an experienced radio/TV technician for help.

Model: 4010-001

Remote

Work voltage:12Vdc

Work current: $\leq 12\text{mA}$

Distance : 50-100M (wide space)

Frequency: 433.92MHz

Frequency tolerance: $\pm 0.2\text{MHz}$

Material: plastic

Modulation: ASK (Amplitude Modulation)

Size: 120*72*31mm

Net weight: 110 grams

Bluetooth box

Remote

Work voltage:10-30Vdc

Work current: $\leq 20\text{A}$

Distance : 10-25M (wide space)

Frequency: 2402-2480MHz

Material: plastic

Modulation: GFSK(Gauss frequency Shift Keying)

Size: 224*120.2*44.5mm

Net weight: 930 grams

Application fields: Vehicle and ship lighting lamps, vehicle and ship warning lamps, vehicle and ship horn and other lamps and other automotive electronics and consumer electronics and electrical control.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1)

This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Changes or modifications not expressly approved by the party responsible for compliance could void your authority to operate the equipment.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

-- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

-- Consult the dealer or an experienced radio/TV technician for help.