



**FCC RF EXPOSURE REPORT
CERTIFICATION TEST REPORT**

For

CONSUMER CAMERA

MODEL NUMBER: IPC-A42P-C, IPC-A42P-C-imou, IPC-A42N-C-imou, IPC-A42N-C

FCC ID: 2AVYF-IPC-A4X-C

REPORT NUMBER: 4789973747-2

ISSUE DATE: June 11, 2021

Prepared for

**Hangzhou Huacheng Network Technology Co.,Ltd.
No.2930, Nanhuan Road, Binjiang District, Hangzhou, China**

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com



Revision History

| <u>Rev.</u> | <u>Issue Date</u> | <u>Revisions</u> | <u>Revised By</u> |
|-------------|-------------------|------------------|-------------------|
| V0 | 06/11/2021 | Initial Issue | |



TABLE OF CONTENTS

| | |
|--------------------------------------|---|
| 1. ATTESTATION OF TEST RESULTS..... | 4 |
| 2. TEST METHODOLOGY | 5 |
| 3. FACILITIES AND ACCREDITATION..... | 5 |
| 4. REQUIREMENT | 6 |



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Hangzhou Huacheng Network Technology Co.,Ltd.
 Address: No.2930, Nanhuan Road, Binjiang District, Hangzhou, China

Manufacturer Information

Company Name: Hangzhou Huacheng Network Technology Co.,Ltd.
 Address: No.2930, Nanhuan Road, Binjiang District, Hangzhou, China

EUT Information

EUT Name: CONSUMER CAMERA
 Model Name: IPC-A42P-C
 Series Model: IPC-A42P-C-imou, IPC-A42N-C-imou, IPC-A42N-C
 Model difference: The difference is only the name of the models.
 Sample Received Date: June 7, 2021
 Sample Status: Normal
 Sample ID: 3967062
 Date of Tested: June 7, 2021~ June 8, 2021

| APPLICABLE STANDARDS | |
|----------------------|--------------|
| STANDARD | TEST RESULTS |
| FCC 47CFR§2.1091 | PASS |

Prepared By:

Checked By:

Kebo Zhang
Project Engineer

Shawn Wen
Laboratory Leader

Approved By:

Stephen Guo
Laboratory Manager



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091.

3. FACILITIES AND ACCREDITATION

| | |
|---------------------------|--|
| Accreditation Certificate | <p>A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p>FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p>ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. Body Identifier (CABID) is CN0046.</p> <p>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B , the VCCI registration No. is C-20012 and T-20011</p> |
|---------------------------|--|

Note: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China.

4. REQUIREMENT

LIMIT AND CALCULATION METHOD

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

RF EXPOSURE LIMIT

| Frequency Range (MHz) | E-field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Time E ² , H ² or S (Minutes) |
|-----------------------|----------------------------|-----------------------------------|---|---|
| 0.3 -- 1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34 -- 30 | 824/f | 2.19/f | (180/f ²)* | 30 |
| 30 -- 300 | 27.5 | 0.073 | 0.2 | 30 |
| 300 -- 1500 | -- | -- | f/1500 | 30 |
| 1500 -- 100,000 | -- | -- | 1.0 | 30 |

CALCULATION METHOD

$$S = PG / 4\pi R^2$$

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

**CALCULATED RESULTS**

| WIFI 2.4G (Worst case) | | | | |
|------------------------|--------------------|-------------------------------|------------------------|-------|
| Operating Mode | Max. Tune up Power | Max. Directional Antenna Gain | Power density | Limit |
| | (dBm) | (dBi) | (mW/ cm ²) | |
| WIFI 2.4G | 17 | 2.84 | 0.01917 | 1 |

Note:

1. The Power comes from report operation description.
2. The minimum separation distance of the device is greater than 20 cm.
3. Calculate by WORST-CASE mode.
4. Owing to the maximum Calculated Result is below the limit, so it deemed to comply with the basic restrictions without testing which means that no SAR is required.

END OF REPORT