

RF EXPOSURE REPORT

For

CONSUMER CAMERA

MODEL NUMBER: IPC-F42FP

ADDTIONAL MODEL NUMBER: IPC-TF42F-LC; IPC-F42F-LC; IPC-F42FP-imou; IPC-F42FN-imou; IPC-F42FN; IPC-F42F; LC-TF2F-4M; LC-A32F-4M; F42F; IPC-TF42F-0280B-LC; IPC-TF42F-0360B-LC; IPC-F42F-0600B-LC; IPC-F42F-0280B-imou; IPC-F42FP-0360B-imou; IPC-F42FP-0600B-imou; IPC-F42FN-0280B-imou; IPC-F42FN-0360B-imou; IPC-F42FN-0600B-imou; IPC-F42FP-0280B; IPC-F42FN-0600B; IPC-F42FN-0280B; IPC-F42FN-0360B; IPC-F42FN-0600B

PROJECT NUMBER: 4789796034

REPORT NUMBER: 4789796034-5

FCC ID: 2AVYF-IPC-F42FX

ISSUE DATE: Feb. 20, 2021

Prepared for

Hangzhou Huacheng Network Technology Co., Ltd.

Prepared by

UL-CCIC COMPANY LIMITED

No. 2, Chengwan Road, Suzhou Industrial Park, People's Republic of China

Tel: +86 769 22038881 Fax: +86 769 33244054 Website: www.ul.com



Page 2 of 7

Rev.	Issue Date	Revisions	Revised By
V0	02/20/2021	Initial Issue	






TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	. 4
2.	TEST METHODOLOGY	. 5
3.	FACILITIES AND ACCREDITATION	. 5
4	REQUIREMENT	F



Page 4 of 7

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Hangzhou Huacheng Network Technology Co., Ltd.

Address: No.2930, Nanhuan Road, Binjiang District, Hangzhou, China

Manufacturer Information

Company Name: Hangzhou Huacheng Network Technology Co., Ltd.

Address: No.2930, Nanhuan Road, Binjiang District, Hangzhou, China

EUT Description

Product Name: CONSUMER CAMERA

Model Name: IPC-F42FP

Additional No.: IPC-TF42F-LC; IPC-F42FP-imou; IPC-F42FN-

imou; IPC-F42FN; IPC-F42F; LC-TF2F-4M; LC-A32F-4M; F42F; IPC-TF42F-0280B-LC; IPC-TF42F-0360B-LC; IPC-TF42F-0600B-LC; IPC-F42F-0280B-LC; IPC-F42F-0360B-LC; IPC-F42F-0360B-imou; IPC-F42FP-0360B-imou; IPC-F42FP-080B-imou; IPC-F42FN-0280B-imou;

IPC-F42FN-0360B-imou; IPC-F42FN-0600B-imou; IPC-F42FP-0280B; IPC-F42FP-0360B; IPC-F42FP-0600B; IPC-F42FN-

0280B; IPC-F42FN-0360B; IPC-F42FN-0600B

Sample Number: 3607003

Data of Receipt Sample: Jan. 19, 2021

Date Tested: Jan. 19, 2021~ Feb. 18, 2021

APPLICABLE STANDARDS

STANDARD TEST RESULTS

FCC Guidelines for Human Exposure IEEE

C95.1

Complies

Prepared By: Reviewed By:

Jason Yang Tom Tang

Jason Yang Tom Tang

Engineer Project Associate

Authorized By:

Chris Zhong

Chris Zhong Laboratory Leader



REPORT No.: 4789796034-5 Page 5 of 7

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06 and FCC Guidelines for Human Exposure IEEE C95.1.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4829.01) UL-CCIC COMPANY LIMITED has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1247) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules. IC (IC Designation No.: 25056) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.
------------------------------	---

Note 1: All tests measurement facilities use to collect the measurement data are located at No. 2, Chengwan Road, Suzhou Industrial Park, Suzhou 215122, People's Republic of China

Note 2: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. These measurements below 30MHz had been correlated to measurements performed on an OFS.

Note 3: The test anechoic chamber in UL-CCIC COMPANY LIMITED had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.



Page 6 of 7

4. REQUIREMENT

LIMIT

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure							
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time $ E ^2$, $ H ^2$ or S (minutes)			
0.3-1.34	614	1.63	(100)*	30			
1.34-30	824/f	2.19/f	(180/f2)*	30			
30-300	27.5	0.073	0.2	30			
300-1500			f/150	30			
1500-100,000		-	1.0	30			

Note 1: f = frequency in MHz, * means Plane-wave equivalent power density

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Note 3: The limit value 1.0mW/cm² is available for this EUT.

MPE CALCULATION METHOD

 $S = PG/(4\pi R^2)$

where: S = power density (in appropriate units, e.g. mW/ cm2)

P = power input to the antenna (in appropriate units, e.g., mW) (the measured power value refer to the tune-up document)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)



Page 7 of 7

CALCULATED RESULTS

Radio Frequency Radiation Exposure Evaluation:

1) For SISO mode:

WIFI (Worst case)								
Mode	Tune-up Power(P)		Antenna Gain		Power Density	Limit	Test Result	
11B	(dBm)	(mW)	(dBi)	(Numeric)	(mW/cm2)	(mW/cm2)		
	19.0	79.43	1.79	1.51	0.0239	1	Complies	

Note: The calculated distance is 20cm.

2) For MIMO mode:

WIFI (Worst case)							
Mode	Tune-up Power(P)		Antenna Gain		Power Density	Limit	Test Result
11N HT20	(dBm)	(mW)	(dBi)	(Numeric)	(mW/cm2)	(mW/cm2)	
MIMO	20	100	4.80	3.02	0.0601	1	Complies

Note: The calculated distance is 20cm.

END OF REPORT