

RF EXPOSURE REPORT

For

CONSUMER CAMERA

MODEL NUMBER: IPC-F42FEP-C

ADDTIONAL MODEL NUMBER: IPC-F42FEP-C-imou;IPC-F42FEP-C-0280B-imou; IPC-F42FEP-C-0360B-imou; IPC-F42FEP-C-0600B-imou; IPC-F42FEN-C; IPC-F42FEN-C-imou; IPC-F42FEN-C-0280B-imou; IPC-F42FEN-C-0360B-imou; IPC-F42FEN-C-0600B-imou; LC-K32F-4M-C; IPC-F42FE-C-LC; IPC-F42FE-C-0280B-LC; IPC-F42FE-C-0360B-LC; IPC-F42FE-C-0600B-LC; IPC-F42FEP-C-0280B; IPC-F42FEP-C-0360B; IPC-F42FEP-C-0600B; IPC-F42FEN-C-0280B; IPC-F42FEN-C-0360B; IPC-F42FEN-C-0600B

PROJECT NUMBER: 4790033180-3

REPORT NUMBER: 4790033180-3-4

FCC ID: 2AVYF-IPC-F4XFE-C

ISSUE DATE: Aug 02, 2021

Prepared for

Hangzhou Huacheng Network Technology Co., Ltd.

Prepared by

UL-CCIC COMPANY LIMITED No. 2, Chengwan Road, Suzhou Industrial Park, People's Republic of China Tel: +86 769 22038881 Fax: +86 769 33244054 Website: www.ul.com

| Rev. | Issue Date | Revisions | Revised By |
|------|------------|---------------|------------|
| V0 | 08/02/2021 | Initial Issue | |

TABLE OF CONTENTS

| 1. | ATTESTATION OF TEST RESULTS | 4 |
|----|------------------------------|---|
| 2. | TEST METHODOLOGY | 5 |
| 3. | FACILITIES AND ACCREDITATION | 5 |
| 4. | REQUIREMENT | 6 |

1. ATTESTATION OF TEST RESULTS

Applicant Information

| Company Name: Address: | Hangzhou Huacheng Network Technology Co.,Ltd. No.2930, Nanhuan Road, Binjiang District, Hangzhou, China |
|---|--|
| Manufacturer Information Company Name: Address: | Hangzhou Huacheng Network Technology Co.,Ltd. No.2930, Nanhuan Road, Binjiang District, Hangzhou, China |
| EUT Description | |
| Product Name: | CONSUMER CAMERA |
| Model Name: | IPC-F42FEP-C |
| Additional No. : | IPC-F42FEP-C-imou;IPC-F42FEP-C-0280B-imou; IPC-F42FEP- |
| | C-0360B-imou; IPC-F42FEP-C-0600B-imou; IPC-F42FEN-C; |
| | IPC-F42FEN-C-imou; IPC-F42FEN-C-0280B-imou; IPC-F42FEN- |
| | C-0360B-imou; IPC-F42FEN-C-0600B-imou; LC-K32F-4M-C; |
| | IPC-F42FE-C-LC; IPC-F42FE-C-0280B-LC; IPC-F42FE-C- |
| | 0360B-LC; IPC-F42FE-C-0600B-LC; IPC-F42FEP-C-0280B; |
| | IPC-F42FEP-C-0360B; IPC-F42FEP-C-0600B; IPC-F42FEN-C- |
| | 0280B; IPC-F42FEN-C-0360B; IPC-F42FEN-C-0600B |
| Sample Number: | 4083927 |
| Data of Receipt Sample: | Jul 20, 2021 |
| Date Tested: | Jul 20, 2021~ Aug 02, 2021 |
| | |

| APPLICABLE STANDARDS | | | | | |
|--|--------------|--|--|--|--|
| STANDARD | TEST RESULTS | | | | |
| FCC Guidelines for Human Exposure IEEE | Complies | | | | |
| C95.1 | | | | | |

Prepared By:

Tom Tang

Tom Tang Project Engineer

Authorized By:

Chris Zhong.

Chris Zhong Laboratory Leader Reviewed By:

Leon Wu

Leon Wu Senior Project Engineer

This report shall not be reproduced except in full, without the written approval of UL-CCIC COMPANY LIMITED..

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06 and FCC Guidelines for Human Exposure IEEE C95.1.

3. FACILITIES AND ACCREDITATION

| Accreditation Certificate | A2LA (Certificate No.: 4829.01) UL-CCIC COMPANY LIMITED has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1247) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules. IC (IC Designation No.: 25056) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules. |
|------------------------------|--|
|------------------------------|--|

Note 1: All tests measurement facilities use to collect the measurement data are located at No. 2, Chengwan Road, Suzhou Industrial Park, Suzhou 215122, People's Republic of China

Note 2: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. These measurements below 30MHz had been correlated to measurements performed on an OFS.

Note 3: The test anechoic chamber in UL-CCIC COMPANY LIMITED had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

4. REQUIREMENT

<u>LIMIT</u>

Limits for General Population/Uncontrolled Exposure

| Limits for General Population/Uncontrolled Exposure | | | | | | | |
|---|---|---|---|---|--|--|--|
| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Time E ² , H ² or S (minutes) | | | |
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 | | | |
| 1.34-30 | 824/f | 2.19/f | (180/f2)* | 30 | | | |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 | | | |
| 300-1500 | | | f/150 | 30 | | | |
| 1500-100,000 | | | 1.0 | 30 | | | |
| Note 1: f = frequency in MHz, * means Plane-wave equivalent power density | | | | | | | |

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Note 3: The limit value 1.0mW/cm² is available for this EUT.

MPE CALCULATION METHOD

 $S = PG/(4\pi R^2)$

where: S = power density (in appropriate units, e.g. mW/ cm2)

P = power input to the antenna (in appropriate units, e.g., mW) (the measured power value refer to the tune-up document)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

CALCULATED RESULTS

Radio Frequency Radiation Exposure Evaluation:

1) For SISO mode:

| WIFI (Worst case) | | | | | | | | |
|-------------------|------------------|-------|--------------|-----------|---------------|----------|----------------|--|
| Mode | Tune-up Power(P) | | Antenna Gain | | Power Density | Limit | Test Result | |
| 11B | (dBm) | (mW) | (dBi) | (Numeric) | (mW/cm2) | (mW/cm2) | | |
| | 16.5 | 44.67 | 1.43 | 1.39 | 0.0124 | 1 | Complies | |

Note: The calculated distance is 20cm.

2) For MIMO mode:

| WIFI (Worst case) | | | | | | | | |
|-------------------|------------------|-------|--------------|-----------|---------------|----------|----------------|--|
| Mode | Tune-up Power(P) | | Antenna Gain | | Power Density | Limit | Test Result | |
| 11N HT20 | (dBm) | (mW) | (dBi) | (Numeric) | (mW/cm2) | (mW/cm2) | | |
| | 18 | 63.10 | 4.44 | 2.78 | 0.0349 | 1 | Complies | |

Note: The calculated distance is 20cm.

END OF REPORT