

Report No.: SHEM210400295301

Page: 1 of 81

TEST REPORT

Application No.: SHEM2104002953CR **FCC ID**: 2AVYF-IPC-TA4X-B

Applicant: Hangzhou Huacheng Network Technology Co.,Ltd.

Address of Applicant: No.2930, Nanhuan Road, Binjiang District, Hangzhou, China

Manufacturer: Hangzhou Huacheng Network Technology Co.,Ltd.

Address of Manufacturer: No.2930, Nanhuan Road, Binjiang District, Hangzhou, China

Equipment Under Test (EUT):

EUT Name: CONSUMER CAMERA

Model No.: IPC-TA42P-B-imou,IPC-TA42P-B,IPC-TA42N-B-imou,IPC-TA42N-B¤

Please refer to section 2 of this report which indicates which model was

actually tested and which were electrically identical.

Standard(s): 47 CFR Part 15, Subpart C 15.247

Date of Receipt: 2021-04-09

Date of Test: 2021-04-12 to 2021-04-26

Date of Issue: 2021-04-29

Test Result: Pass*

parlan 2han

Parlam Zhan E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

 Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document. aspx advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443.

邮编: 201612

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612

中国・上海・松江区金都西路588号

t(86-21) 61915666 f(86-21) 61915678 www.sgsgroup.com.cn t(86-21) 61915666 f(86-21) 61915678 e sgs.china@sgs.com

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SHEM210400295301

Page: 2 of 81

Revision Record									
Version Description Date Remark									
00	Original	2021-04-29	/						

Authorized for issue by:		
	hichard Mil	
	Micheal Niu / Project Engineer	
	Darlam Zhan	
	Parlam Zhan / Reviewer	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 3 of 81

2 Test Summary

Radio Spectrum Technical Requirement								
Item	Standard	Method	Requirement	Result				
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass				

Radio Spectrum Matter Part								
Item	Standard	Method	Requirement	Result				
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass				
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass				
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass				
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass				
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass				
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass				
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass				
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass				

Declaration of EUT Family Grouping:

Note: There are series models mentioned in this report, and they are the similar in electrical and electronic characters. Only the model IPC-TA42P-B was tested since their differences were the model number, trade name and appearance.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond

NO.588 West Jindu Road,Songjiang District,Shanghai,China 201612 中国・上海・松江区金都西路588号 邮编: 201612 t(86-21)61915666 f(86-21)61915678 www.sgsgroup.com.cn t(86-21)61915666 f(86-21)61915678 e sgs.china@sgs.com



Report No.: SHEM210400295301

Page: 4 of 81

3 Contents

1 COVER PAGE				Page
3 CONTENTS	1	CO	VER PAGE	1
3 CONTENTS	2	TES	ST SUMMARY	า
4 GENERAL INFORMATION 4.1 DETAILS OF E.U.T. 4.2 POWER LEVEL SETTING USING IN TEST	_			
4.1 DETAILS OF E.U.T. 4.2 POWER LEVEL SETTING USING IN TEST 4.3 DESCRIPTION OF SUPPORT UNITS. 4.4 MEASUREMENT UNCERTAINTY. 4.5 TEST LOCATION. 4.6 TEST FACILITY. 4.7 DEVIATION FROM STANDARDS. 4.8 ABNORMALITIES FROM STANDARD CONDITIONS. 5 EQUIPMENT LIST. 4.8 ABNORMALITIES FROM STANDARD CONDITIONS. 5 EQUIPMENT LIST. 4.6 1.0 ANTENNA REQUIREMENT. 1.0<	3	CO	NTENTS	4
4.1 DETAILS OF E.U.T. 4.2 POWER LEVEL SETTING USING IN TEST 4.3 DESCRIPTION OF SUPPORT UNITS. 4.4 MEASUREMENT UNCERTAINTY. 4.5 TEST LOCATION. 4.6 TEST FACILITY. 4.7 DEVIATION FROM STANDARDS. 4.8 ABNORMALITIES FROM STANDARD CONDITIONS. 5 EQUIPMENT LIST. 4.8 ABNORMALITIES FROM STANDARD CONDITIONS. 5 EQUIPMENT LIST. 4.6 1.0 ANTENNA REQUIREMENT. 1.0<	,	GE	NEDAL INFORMATION	5
4.2 POWER LEVEL SETTING USING IN TEST 4.3 DESCRIPTION OF SUPPORT UNITS 4.4 MEASUREMENT UNCERTAINTY 4.5 TEST LOCATION 4.6 TEST FACILITY 4.7 DEVIATION FROM STANDARDS 4.8 ABNORMALITIES FROM STANDARD CONDITIONS 5 EQUIPMENT LIST 6 RADIO SPECTRUM TECHNICAL REQUIREMENT 6.1 ANTENNA REQUIREMENT 7 RADIO SPECTRUM MATTER TEST RESULTS 7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150kHz-30MHz) 7.2 MINIMUM 6DB BANDWIDTH 7.3 CONDUCTED PEAK OUTPUT POWER 7.4 POWER SPECTRUM DENSITY 7.5 CONDUCTED BAND EDGES MEASUREMENT 7.6 CONDUCTED SAPURIOUS EMISSIONS 7.7 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS 7.8 RADIATED SPURIOUS EMISSIONS 8 TEST SETUP PHOTOGRAPHS	7			
4.3 DESCRIPTION OF SUPPORT UNITS				
4.4 MEASUREMENT UNCERTAINTY 4.5 TEST LOCATION 4.6 TEST FACILITY 4.7 DEVIATION FROM STANDARDS 4.8 ABNORMALITIES FROM STANDARD CONDITIONS 5 EQUIPMENT LIST 6 RADIO SPECTRUM TECHNICAL REQUIREMENT 7 RADIO SPECTRUM MATTER TEST RESULTS 7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ) 7.2 MINIMUM 6DB BANDWIDTH 7.2 MINIMUM 6DB BANDWIDTH 7.3 CONDUCTED PEAK OUTPUT POWER 7.4 POWER SPECTRUM DENSITY 7.5 CONDUCTED BAND EDGES MEASUREMENT 7.6 CONDUCTED SPURIOUS EMISSIONS 7.7 RADIATED SPURIOUS EMISSIONS 8 TEST SETUP PHOTOGRAPHS 8				
4.5 TEST LOCATION 4.6 TEST FACILITY 4.7 DEVIATION FROM STANDARDS 4.8 ABNORMALITIES FROM STANDARD CONDITIONS 5 EQUIPMENT LIST 6 RADIO SPECTRUM TECHNICAL REQUIREMENT 7 RADIO SPECTRUM MATTER TEST RESULTS 7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150kHz-30MHz) 7.2 MINIMUM 6DB BANDWIDTH 7.2 MINIMUM 6DB BANDWIDTH 7.3 CONDUCTED PEAK OUTPUT POWER 7.4 POWER SPECTRUM DENSITY 7.5 CONDUCTED BAND EDGES MEASUREMENT 7.6 CONDUCTED SPURIOUS EMISSIONS 7.7 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS 7.8 RADIATED SPURIOUS EMISSIONS 8 TEST SETUP PHOTOGRAPHS 8				
4.6 TEST FACILITY 4.7 DEVIATION FROM STANDARDS 4.8 ABNORMALITIES FROM STANDARD CONDITIONS 5 EQUIPMENT LIST 6 RADIO SPECTRUM TECHNICAL REQUIREMENT 10 6.1 ANTENNA REQUIREMENT 10 7 RADIO SPECTRUM MATTER TEST RESULTS 1 7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ) 1 7.2 MINIMUM 6DB BANDWIDTH 19 7.3 CONDUCTED PEAK OUTPUT POWER 16 7.4 POWER SPECTRUM DENSITY 17 7.5 CONDUCTED BAND EDGES MEASUREMENT 18 7.6 CONDUCTED SPURIOUS EMISSIONS 15 7.7 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS 22 7.8 RADIATED SPURIOUS EMISSIONS 52 8 TEST SETUP PHOTOGRAPHS 8				
4.7 DEVIATION FROM STANDARDS 2 4.8 ABNORMALITIES FROM STANDARD CONDITIONS 5 5 EQUIPMENT LIST 6 6 RADIO SPECTRUM TECHNICAL REQUIREMENT 10 6.1 ANTENNA REQUIREMENT 10 7 RADIO SPECTRUM MATTER TEST RESULTS 11 7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ) 11 7.2 MINIMUM 6DB BANDWIDTH 15 7.3 CONDUCTED PEAK OUTPUT POWER 16 7.4 POWER SPECTRUM DENSITY 17 7.5 CONDUCTED BAND EDGES MEASUREMENT 16 7.6 CONDUCTED SPURIOUS EMISSIONS 19 7.7 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS 22 7.8 RADIATED SPURIOUS EMISSIONS 52 8 TEST SETUP PHOTOGRAPHS 8				
4.8 ABNORMALITIES FROM STANDARD CONDITIONS 3 5 EQUIPMENT LIST 3 6 RADIO SPECTRUM TECHNICAL REQUIREMENT 10 6.1 ANTENNA REQUIREMENT 10 7 RADIO SPECTRUM MATTER TEST RESULTS 11 7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150kHz-30MHz) 12 7.2 MINIMUM 6DB BANDWIDTH 14 7.3 CONDUCTED PEAK OUTPUT POWER 16 7.4 POWER SPECTRUM DENSITY 17 7.5 CONDUCTED BAND EDGES MEASUREMENT 18 7.6 CONDUCTED SPURIOUS EMISSIONS 19 7.7 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS 22 7.8 RADIATED SPURIOUS EMISSIONS 52 8 TEST SETUP PHOTOGRAPHS 8				
5 EQUIPMENT LIST 6 RADIO SPECTRUM TECHNICAL REQUIREMENT 6.1 ANTENNA REQUIREMENT 7 RADIO SPECTRUM MATTER TEST RESULTS 7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150kHz-30MHz) 7.2 MINIMUM 6DB BANDWIDTH 7.3 CONDUCTED PEAK OUTPUT POWER 7.4 POWER SPECTRUM DENSITY 7.5 CONDUCTED BAND EDGES MEASUREMENT 7.6 CONDUCTED SPURIOUS EMISSIONS 7.7 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS 7.8 RADIATED SPURIOUS EMISSIONS 8 TEST SETUP PHOTOGRAPHS 8		• • • •		
6 RADIO SPECTRUM TECHNICAL REQUIREMENT 10 6.1 ANTENNA REQUIREMENT 10 7 RADIO SPECTRUM MATTER TEST RESULTS 11 7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150kHz-30MHz) 11 7.2 MINIMUM 6DB BANDWIDTH 15 7.3 CONDUCTED PEAK OUTPUT POWER 16 7.4 POWER SPECTRUM DENSITY 17 7.5 CONDUCTED BAND EDGES MEASUREMENT 18 7.6 CONDUCTED SPURIOUS EMISSIONS 19 7.7 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS 22 7.8 RADIATED SPURIOUS EMISSIONS 52 8 TEST SETUP PHOTOGRAPHS 8		_		
6.1 ANTENNA REQUIREMENT 10 7 RADIO SPECTRUM MATTER TEST RESULTS 1 7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150kHz-30MHz) 1 7.2 MINIMUM 6DB BANDWIDTH 15 7.3 CONDUCTED PEAK OUTPUT POWER 16 7.4 POWER SPECTRUM DENSITY 17 7.5 CONDUCTED BAND EDGES MEASUREMENT 18 7.6 CONDUCTED SPURIOUS EMISSIONS 19 7.7 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS 22 7.8 RADIATED SPURIOUS EMISSIONS 52 8 TEST SETUP PHOTOGRAPHS 86	5	EQ	UIPMENT LIST	8
7 RADIO SPECTRUM MATTER TEST RESULTS 1 7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150kHz-30MHz) 1 7.2 MINIMUM 6DB BANDWIDTH 15 7.3 CONDUCTED PEAK OUTPUT POWER 16 7.4 POWER SPECTRUM DENSITY 17 7.5 CONDUCTED BAND EDGES MEASUREMENT 16 7.6 CONDUCTED SPURIOUS EMISSIONS 19 7.7 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS 20 7.8 RADIATED SPURIOUS EMISSIONS 52 8 TEST SETUP PHOTOGRAPHS 86	6	RA	DIO SPECTRUM TECHNICAL REQUIREMENT	10
7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150kHz-30MHz) 1 7.2 MINIMUM 6DB BANDWIDTH 15 7.3 CONDUCTED PEAK OUTPUT POWER 16 7.4 POWER SPECTRUM DENSITY 17 7.5 CONDUCTED BAND EDGES MEASUREMENT 18 7.6 CONDUCTED SPURIOUS EMISSIONS 19 7.7 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS 20 7.8 RADIATED SPURIOUS EMISSIONS 50 8 TEST SETUP PHOTOGRAPHS 80		6.1	Antenna Requirement	10
7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150kHz-30MHz) 1 7.2 MINIMUM 6DB BANDWIDTH 15 7.3 CONDUCTED PEAK OUTPUT POWER 16 7.4 POWER SPECTRUM DENSITY 17 7.5 CONDUCTED BAND EDGES MEASUREMENT 18 7.6 CONDUCTED SPURIOUS EMISSIONS 19 7.7 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS 20 7.8 RADIATED SPURIOUS EMISSIONS 50 8 TEST SETUP PHOTOGRAPHS 80	7	RA	DIO SPECTRUM MATTER TEST RESULTS	11
7.2 MINIMUM 6DB BANDWIDTH 19 7.3 CONDUCTED PEAK OUTPUT POWER 16 7.4 POWER SPECTRUM DENSITY 17 7.5 CONDUCTED BAND EDGES MEASUREMENT 18 7.6 CONDUCTED SPURIOUS EMISSIONS 19 7.7 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS 20 7.8 RADIATED SPURIOUS EMISSIONS 50 8 TEST SETUP PHOTOGRAPHS 80				
7.3 CONDUCTED PEAK OUTPUT POWER 16 7.4 POWER SPECTRUM DENSITY 17 7.5 CONDUCTED BAND EDGES MEASUREMENT 18 7.6 CONDUCTED SPURIOUS EMISSIONS 19 7.7 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS 20 7.8 RADIATED SPURIOUS EMISSIONS 50 8 TEST SETUP PHOTOGRAPHS 80				
7.4 POWER SPECTRUM DENSITY				
7.5 CONDUCTED BAND EDGES MEASUREMENT				
7.7 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS				
7.8 RADIATED SPURIOUS EMISSIONS		7.6	CONDUCTED SPURIOUS EMISSIONS	19
8 TEST SETUP PHOTOGRAPHS8		7.7		
		7.8	RADIATED SPURIOUS EMISSIONS	52
9 FUT CONSTRUCTIONAL DETAILS	8	TES	ST SETUP PHOTOGRAPHS	81
	a	EII.	T CONSTRUCTIONAL DETAILS	81



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 5 of 81

4 General Information

4.1 Details of E.U.T.

Power supply: DC 5V/1A by adapter

Adapter:

Model: NBS05B050100VUU

Input: AC 100-240V~, 50/60Hz, 0.2A

Output: DC 5V 1A

Test voltage: AC 120V/60Hz

Antenna Gain: 2.84dBi(Provided by the manufacturer)

Antenna Type: Integral antenna

Channel Spacing: 5MHz

Modulation Type: 802.11b: DSSS (CCK, DQPSK, DBPSK)

802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)

Number of Channels: 802.11b/g/n(HT20):11

802.11n(HT40):7

Data Rate: 802.11b: 1/2/5.5/11Mbps,

802.11g: 6/9/12/18/24/36/48/54Mbps

802.11n: MCS 0 to 7 for HT20MHz MCS 0 to 7 for HT40MHz

Operation Frequency: 802.11b/g/n(HT20): 2412MHz to 2462MHz

802.11n(HT40): 2422MHz to 2452MHz

4.2 Power level setting using in test

Channel	802.11b	802.11g	802.11n(HT20)	
	Ant 1	Ant 1	Ant 1	
1	Default	Default	Default	
6	Default	Default	Default	
11	Default	Default	Default	
Channel	802.11n(HT40)			
	Ant 1			
3	Default			
6	Default			
9	Default			

4.3 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Laptop	Lenovo	ThinkPad X100e	1
SecureCRT	VanDyke	V 6.2.0	1
Serial port adapter plate	1	Test Plate 3	1



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unautorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮編: 201612





Page: 6 of 81

4.4 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	8.4 x 10 ⁻⁸
2	Timeout	2s
3	Duty Cycle	0.37%
4	Occupied Bandwidth	3%
5	RF Conducted Power	0.6dB
6	RF Power Density	2.9dB
7	Conducted Spurious Emissions	0.75dB
8	RF Radiated Power	5.2dB (Below 1GHz)
0	RF Radiated Power	5.9dB (Above 1GHz)
		4.2dB (Below 30MHz)
9	Padiated Spurious Emission Test	4.5dB (30MHz-1GHz)
9	Radiated Spurious Emission Test	5.1dB (1GHz-18GHz)
		5.4dB (Above 18GHz)
10	Temperature Test	1°C
11	Humidity Test	3%
12	Supply Voltages	1.5%
13	Time	3%

Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 7 of 81

4.5 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

Tel: +86 512 5735 5888 Fax: +86 512 5737 0818

No tests were sub-contracted.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• CNAS (No. CNAS L4354)

CNAS has accredited Compliance Certification Services (Kunshan) Inc. to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• A2LA (Certificate No. 2541.01)

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 2541.01.

• FCC (Designation Number: CN1172)

Compliance Certification Services Inc. has been recognized as an accredited testing laboratory. Designation Number: CN1172.

• ISED (CAB identifier: CN0072)

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

Company Number: 2324E

• VCCI (Member No.: 1938)

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-1600, C-1707, T-1499, G-10216 respectively.

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-758 8307 1443).

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 8 of 81

5 Equipment List

Item	Equipment	Manufacturer	Model	Serial Number	Cal Date	Cal. Due Date
	ducted Emission at Mains Terminals (150		Wiodei	Serial Nulliber	Cai Date	Cai. Due Date
1	EMI Test Receive	R&S	ESCI	100781	02/01/2021	01/31/2022
2	LISN	R&S	ENV216	101604	10/19/2020	10/18/2021
3	LISN	Schwarzbeck	NNLK 8129	8129-143	10/19/2020	10/18/2021
4	Pulse Limiter	R&S	ESH3-Z2	100609	02/01/2021	01/31/2022
5	CE test Cable	Thermax	/	14	10/17/2020	10/16/2021
6	Test Software	Farad	EZ-EMC	CCS-03A1	N.C.R	N.C.R
	Conducted Test	i didu	LZ-LIVIO	000-0071	14.0.11	14.0.11
1	Spectrum Analyzer	Agilent	E4446A	MY44020154	04/17/2020	04/16/2021
'	Spectrum Analyzer	Agilent	E4446A	MY44020154	04/17/2020	04/15/2022
2	Spectrum Analyzer	Keysight	N9020A	MY55370209	12/02/2020	12/01/2021
3	Spectrum Analyzer	Keysight	N9010A	MY56480443	02/01/2021	01/31/2022
4	Signal Generator	Agilent	N5182A	MY50142015	09/25/2020	09/24/2021
5	Radio Communication Test Station	Agrient	MT8000A	6262012849	N/A	N/A
6	Radio Communication Analyzer	Anritsu	MT8821C	6201692222	N/A	N/A
7	Universal Radio Communication Tester	R&S	CMW500	159275	10/19/2020	10/18/2021
8	Universal Radio Communication Tester	R&S	CMW500	167239	04/17/2020	04/16/2021
9	Universal Radio Communication Tester	R&S	CMW500	167239	04/17/2020	04/15/2022
10	Power Meter	Anritsu	ML2495A	1445010	04/17/2020	04/15/2022
11	Power Meter	Anritsu	ML2495A	1445010	04/17/2020	04/10/2021
12	Switcher	CCSRF	FY562	KUS2001M001 -3	10/19/2020	10/18/2021
13	AC Power Source	EXTECH	6605	1570106	N.C.R	N.C.R
14	DC Power Supply	Aglient	E3632A	MY50340053	N.C.R	N.C.R
15	6dB Attenuator	Mini-Circuits	NAT-6-2W	15542-1	N.C.R	N.C.R
16	Power Divider	AISI	IOWOPE2068	PE2068	N.C.R	N.C.R
17	Filter	MICRO-TRONICS	BRM50701	5	N.C.R	N.C.R
18	Conducted test cable	/	RF01-RF04	/	04/16/2020	04/15/2021
19	Conducted test cable	/	RF01-RF04	/	04/15/2021	04/14/2022
20	Software	BST	TST-PASS	N/A	N/A	N/A
21	Temp. / Humidity Chamber	TERCHY	MHK-120AK	X30109	04/16/2020	04/15/2021
22	Temp. / Humidity Chamber	TERCHY	MHK-120AK	X30109	04/15/2021	04/14/2022
23	Thermometer	Anymetre	TH603	CCS007	10/16/2020	10/15/2021
RF R	adiated Test					
1	Spectrum Analyzer	R&S	FSV40	101493	10/19/2020	10/18/2021
2	Signal Generator	Agilent	E8257C	MY43321570	10/19/2020	10/18/2021
3	Loop Antenna	Schwarzbeck	HXYZ9170	9170-108	02/22/2021	02/21/2022
4	Bilog Antenna	TESEQ	CBL 6112D	35403	06/22/2019	06/21/2021
5	Bilog Antenna	SCHWARZBECK	VULB9160	9160-3342	04/13/2021	04/12/2023
6	Horn-antenna(1-18GHz)	Schwarzbeck	BBHA9120D	267	10/26/2020	10/25/2022
7	Horn-antenna(1-18GHz)	ETS-LINDGREN	3117	00143290	02/22/2021	02/21/2023
8	Horn Antenna(18-40GHz)	Schwarzbeck	BBHA9170	BBHA9170171	02/22/2021	02/21/2022
9	Horn-antenna(40-60GHz)	REBES	SAZ-2410-19-S1	06299-01	N/A	N/A
10	Horn-antenna(50-75GHz)	REBES	SAZ-2410-15-S1	01731-01	N/A	N/A
11	Horn-antenna(75-110GHz)	REBES	SAZ-2410-10-S1	01773-09	N/A	N/A



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612 t(86-21) 61915666 f(86-21) 61915678 www.sgsgroup.com.cn t(86-21) 61915666 f(86-21) 61915678 e sgs.china@sgs.com



Report No.: SHEM210400295301

Page: 9 of 81

12	Horn-antenna(110-170GHz)	REBES	SAZ-2410-06-S1	01776-05	N/A	N/A
13	Horn-antenna(140-220GHz)	REBES	SAZ-2410-05-S1	01759-04	N/A	N/A
14	Horn-antenna(220-325GHz)	REBES	SAR-2309-03-S2	06300-01	N/A	N/A
15	Extended waveguide(40-60GHz)	REBES	SWG-19025-FB	06303-01	N/A	N/A
16	Extended waveguide(50-75GHz)	REBES	SWG-15025-FB	01525-09	N/A	N/A
17	Extended waveguide(75-110GHz)	REBES	SWG-10025-FB	01509-01	N/A	N/A
18	Extended waveguide(110-170GHz)	REBES	SWG-06025-FB	06302-01	N/A	N/A
19	Extended waveguide(140-220GHz)	REBES	SWG-05025-FB	06304-01	N/A	N/A
20	Extended waveguide(220-325GHz)	REBES	SWG-03025-FB	06301-01	N/A	N/A
21	Harmonic mixer(110-170GHz)	REBES	STH-06SF-S1	06110-01	N/A	N/A
22	Harmonic mixer(40-60GHz)	REBES	STH-19SF-S1	06937-01	N/A	N/A
23	Waveguide Harmonic Mixer(50-75GHz)	KEYSIGHT	M1970V	MY51390966	N/A	N/A
24	Waveguide Harmonic Mixer(50-75GHz) cable	Silverline	LU18-SMSM-01.00	99612	N/A	N/A
25	Waveguide Harmonic Mixer(75-110GHz)	KEYSIGHT	M1970W	MY51430883	N/A	N/A
26	Vaveguide Harmonic Mixer(75-110GHz) cabl	Silverline	LU18-SMSM-01.00	94202	N/A	N/A
27	Pre-Amplifier(30MHz~18GHz)	LNA	/	/	04/16/2020	04/15/2021
28	Pre-Amplifier(30MHz~18GHz)	LNA	/	/	04/15/2021	04/14/2022
29	Amplifier(18~40GHz)	COM-POWER	PAM-840A	461332	10/23/2020	10/22/2021
30	Low Pass Filter	MICRO-TRONICS	VLFX-950	RV142900829	N.C.R	N.C.R
31	High Pass Filter	Mini-Circuits	VHF-1200	15542	N.C.R	N.C.R
32	Filter (5450MHz~5770 MHz)	MICRO-TRONICS	BRC50704-01	2	N.C.R	N.C.R
33	Filter (5690 MHz~5930 MHz)	MICRO-TRONICS	BRC50705-01	4	N.C.R	N.C.R
34	Filter (5150 MHz~5350 MHz)	MICRO-TRONICS	BRC50703-01	2	N.C.R	N.C.R
35	Filter (885 MHz~915 MHz)	MICRO-TRONICS	BRM14698	1	N.C.R	N.C.R
36	Filter (815 MHz~860 MHz)	MICRO-TRONICS	BRM14697	1	N.C.R	N.C.R
37	Filter (1745 MHz~1910 MHz)	MICRO-TRONICS	BRM14700	1	N.C.R	N.C.R
38	Filter (1922 MHz~1977 MHz)	MICRO-TRONICS	BRM50715	1	N.C.R	N.C.R
39	Filter (2550 MHz)	MICRO-TRONICS	HPM13362	5	N.C.R	N.C.R
40	Filter (1532 MHz~1845 MHz)	MICRO-TRONICS	BRM50713	1	N.C.R	N.C.R
41	Filter (2.4GHz)	MICRO-TRONICS	BRM50701	5	N.C.R	N.C.R
42	RE test cable	1	RE01-RE04	1	04/16/2020	04/15/2021
43	RE test cable	1	RE01-RE04	1	04/15/2021	04/14/2022
44	Software	BST	TST-PASS	N/A	N/A	N/A



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612 t(86-21) 61915666 f(86-21) 61915678 www.sgsgroup.com.cn t(86-21) 61915666 f(86-21) 61915678 e sgs.china@sgs.com





Page: 10 of 81

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is Integral antenna on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.84dBi.

Antenna location: Refer to Appendix(Internal Photos)



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic format documents subject to Terms and Conditions for Electronic Document sat http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing (inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CRN Doccheck@gs.com

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 11 of 81

7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207 Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Fraguency of amission/MUs)	Conducted limit(dΒμV)				
Frequency of emission(MHz)	Quasi-peak	Average			
0.15-0.5	66 to 56*	56 to 46*			
0.5-5	56	46			
5-30	60	50			
*Decreases with the logarithm of the frequency.					

7.1.1 E.U.T. Operation

Operating Environment:


Temperature: 23 °C Humidity: 45 % RH Atmospheric Pressure: 1001 mbar

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation

types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40).

Only the data of worst case is recorded in the report.

7.1.2 Test Setup Diagram





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-758 8307 1443).

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 12 of 81

7.1.3 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50 \text{ohm}/50 \mu\text{H} + 5 \text{ohm}$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic format documents subject to Terms and Conditions for Electronic Document sat http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing (inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CRN Doccheck@gs.com

NO.588 West Jindu Road,Songjiang District,Shanghai,China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 13 of 81



No.	Frequency	QuasiPeak reading	Average reading	Correction factor	QuasiPeak result	Average result	QuasiPeak limit	Average limit	QuasiPeak margin	Average margin	Remark
	(MHz)	(dBuV)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dBuV)	(dBuV)	(dB)	(dB)	
1	0.1579	11.64	0.52	19.46	31.10	19.98	65.57	55.57	-34.47	-35.59	Pass
2	0.1960	10.88	-0.04	19.46	30.34	19.42	63.78	53.78	-33.44	-34.36	Pass
3	0.2282	7.93	0.58	19.47	27.40	20.05	62.51	52.51	-35.11	-32.46	Pass
4*	0.4993	20.16	12.02	19.53	39.69	31.55	56.01	46.01	-16.32	-14.46	Pass
5	1.0881	13.63	4.92	19.55	33.18	24.47	56.00	46.00	-22.82	-21.53	Pass
6	22.0613	1.55	-3.95	20.29	21.84	16.34	60.00	50.00	-38.16	-33.66	Pass




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国 • 上海 • 松江区金都西路588号 邮编: 201612 t(86-21) 61915666 f(86-21) 61915678 www.sgsgroup.com.cn t(86-21) 61915666 f(86-21) 61915678 e sgs.china@sgs.com





Page: 14 of 81





No.	Frequency	QuasiPeak reading	Average reading	Correction factor	QuasiPeak result	Average result	QuasiPeak limit	Average limit	QuasiPeak margin	Average margin	Remark
	(MHz)	(dBuV)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dBuV)	(dBuV)	(dB)	(dB)	
1	0.1774	14.26	3.47	19.43	33.69	22.90	64.61	54.61	-30.92	-31.71	Pass
2	0.4839	8.80	-2.65	19.51	28.31	16.86	56.27	46.27	-27.96	-29.41	Pass
3*	0.9630	14.67	3.96	19.53	34.20	23.49	56.00	46.00	-21.80	-22.51	Pass
4	1.2069	10.39	1.29	19.54	29.93	20.83	56.00	46.00	-26.07	-25.17	Pass
5	2.6015	7.28	-2.01	19.60	26.88	17.59	56.00	46.00	-29.12	-28.41	Pass
6	20.9936	8.68	-0.81	20.26	28.94	19.45	60.00	50.00	-31.06	-30.55	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国 • 上海 • 松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 15 of 81

7.2 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)
Test Method: ANSI C63.10 (2013) Section 11.8.1

Limit: ≥500 kHz

7.2.1 E.U.T. Operation

Operating Environment:


Temperature: 25 °C Humidity: 49 % RH Atmospheric Pressure: 1006 mbar

Test mode a:TX mode Keep the EUT in continuously transmitting mode with all modulation

types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40).

Only the data of worst case is recorded in the report.

7.2.2 Test Setup Diagram



Ground Reference Plane

7.2.3 Measurement Procedure and Data

The detailed test data see: Appendix A for SHEM210400295301



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unautorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮編: 201612





Page: 16 of 81

7.3 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)
Test Method: ANSI C63.10 (2013) Section 11.9.1

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)					
	1 for ≥50 hopping channels					
902-928	0.25 for 25≤ hopping channels <50					
	1 for digital modulation					
	1 for ≥75 non-overlapping hopping channels					
2400-2483.5	0.125 for all other frequency hopping systems					
	1 for digital modulation					
5725-5850	1 for frequency hopping systems and digital modulation					

7.3.1 E.U.T. Operation

Operating Environment:


Temperature: 25 °C Humidity: 50 % RH Atmospheric Pressure: 1007 mbar

Test mode a:TX mode Keep the EUT in continuously transmitting mode with all modulation

types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40).

Only the data of worst case is recorded in the report.

7.3.2 Test Setup Diagram



Ground Reference Plane

7.3.3 Measurement Procedure and Data

The detailed test data see: Appendix A for SHEM210400295301



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fulliest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing (inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, **Certificate**, please contact us at telephone: (86-755) 8307 1443, **Certificate**, please contact us at telephone: (86-755) 8307 1443, **Certificate**, please contact us at telephone: (86-755) 8307 1443, **Certificate**, please contact us at telephone: (86-755) 8307 1443, **Certificate**, please contact us at telephone: (86-755) 8307 1443, **Certificate**, please contact us at telephone: (86-755) 8307 1443, **Certificate**, please contact us at telephone: (86-755) 8307 1443, **Certificate**, please contact us at telephone: (86-75

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮編: 201612



Report No.: SHEM210400295301

Page: 17 of 81

7.4 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)
Test Method: ANSI C63.10 (2013) Section 11.10.2

Limit: ≤8dBm in any 3 kHz band during any time interval of continuous

transmission

7.4.1 E.U.T. Operation

Operating Environment:


Temperature: 25 °C Humidity: 49 % RH Atmospheric Pressure: 1006 mbar

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation

types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40).

Only the data of worst case is recorded in the report.

7.4.2 Test Setup Diagram



Ground Reference Plane

7.4.3 Measurement Procedure and Data

The detailed test data see: Appendix A for SHEM210400295301



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unautorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 18 of 81

7.5 Conducted Band Edges Measurement

47 CFR Part 15, Subpart C 15.247(d) **Test Requirement** Test Method: ANSI C63.10 (2013) Section 11.13.3.2

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 25 Humidity: 50

% RH

§15.209(a) (see §15.205(c)


Atmospheric Pressure: 1007 mbar

Test mode

a:TX mode Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40).

Only the data of worst case is recorded in the report.

7.5.2 Test Setup Diagram



Ground Reference Plane

7.5.3 Measurement Procedure and Data

The detailed test data see: Appendix A for SHEM210400295301



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unautorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612

t(86-21) 61915666 f(86-21) 61915678 www.sqsqroup.com.cn t/86-21)61915666 f/86-21)61915678 e sgs.china@sgs.com



Report No.: SHEM210400295301

Page: 19 of 81

7.6 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in

§15.205(a), must also comply with the radiated emission limits specified in

§15.209(a) (see §15.205(c)



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fulliest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing (inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, **Certificate**, please contact us at telephone: (86-755) 8307 1443, **Certificate**, please contact us at telephone: (86-755) 8307 1443, **Certificate**, please contact us at telephone: (86-755) 8307 1443, **Certificate**, please contact us at telephone: (86-755) 8307 1443, **Certificate**, please contact us at telephone: (86-755) 8307 1443, **Certificate**, please contact us at telephone: (86-755) 8307 1443, **Certificate**, please contact us at telephone: (86-755) 8307 1443, **Certificate**, please contact us at telephone: (86-75

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 20 of 81

7.6.1 E.U.T. Operation

Operating Environment:


Temperature: 25 °C Humidity: 50 % RH Atmospheric Pressure: 1008 mbar

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation

types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40).

Only the data of worst case is recorded in the report.

7.6.2 Test Setup Diagram



Ground Reference Plane

7.6.3 Measurement Procedure and Data

The detailed test data see: Appendix A for SHEM210400295301



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unautorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

NO.588 West Jindu Road,Songjiang District,Shanghai,China 201612 中国・上海・松江区金都西路588号 邮编: 201612 t(86-21)61915666 f(86-21)61915678 www.sgsgroup.com.cn t(86-21)61915666 f(86-21)61915678 e sgs.china@sgs.com



Report No.: SHEM210400295301

Page: 21 of 81

7.7 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.247(d)

Test Method: ANSI C63.10 (2013) Section 6.10.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the ine of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullees extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (85-755) 8307 1443,

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 22 of 81

7.7.1 E.U.T. Operation

Operating Environment:


Temperature: 25 °C Humidity: 49 % RH Atmospheric Pressure: 1007 mbar


Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation


types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40).

Only the data of worst case is recorded in the report.

7.7.2 Test Setup Diagram









Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-758 8307 1443).

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 23 of 81

7.7.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic format documents subject to Terms and Conditions for Electronic Document sat http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing (inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CRN Doccheck@gs.com


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国 • 上海 • 松江区金都西路588号 邮编: 201612 t(86-21) 61915666 f(86-21) 61915678 www.sgsgroup.com.cn t(86-21) 61915666 f(86-21) 61915678 e sgs.china@sgs.com





Page: 24 of 81

Mode:a; Polarization:Horizontal; Modulation:b; bandwidth:20MHz; Channel:Low




No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2378.180	55.83	-3.49	52.34	74.00	-21.66	peak
2	2390.000	54.91	-3.46	51.45	74.00	-22.55	peak
3	2410.800	106.24	-3.39	102.85	74.00	28.85	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 25 of 81

Mode:a; Polarization:Vertical; Modulation:b; bandwidth:20MHz; Channel:Low



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2381.120	55.45	-3.48	51.97	74.00	-22.03	peak
2	2390.000	54.12	-3.46	50.66	74.00	-23.34	peak
3	2413.320	106.27	-3.39	102.88	74.00	28.88	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国 • 上海 • 松江区金都西路588号 邮编: 201612





Page: 26 of 81

Mode:a; Polarization:Horizontal; Modulation:b; bandwidth:20MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2463.200	104.96	-3.23	101.73	74.00	27.73	peak
2	2483.500	54.61	-3.16	51.45	74.00	-22.55	peak
3	2484.950	56.37	-3.15	53.22	74.00	-20.78	peak
4	2500.000	53.48	-3.10	50.38	74.00	-23.62	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 27 of 81

Mode:a; Polarization:Vertical; Modulation:b; bandwidth:20MHz; Channel:High



No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2463.200	105.10	-3.23	101.87	74.00	27.87	peak
2	2483.500	53.29	-3.16	50.13	74.00	-23.87	peak
3	2485.850	54.60	-3.15	51.45	74.00	-22.55	peak
4	2500.000	52.61	-3.10	49.51	74.00	-24.49	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612 t(86-21)61915666 f(86-21)61915678 www.sgsgroup.com.cn t(86-21)61915666 f(86-21)61915678 e sgs.china@sgs.com





Page: 28 of 81

Mode:a; Polarization:Horizontal; Modulation:g; bandwidth:20MHz; Channel:Low



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2385.600	64.56	-3.47	61.09	74.00	-12.91	peak
2	2390.000	64.55	-3.46	61.09	74.00	-12.91	peak
3	2407.440	107.07	-3.40	103.67	74.00	29.67	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国 • 上海 • 松江区金都西路588号 邮编: 201612





Page: 29 of 81

Mode:a; Polarization:Horizontal; Modulation:g; bandwidth:20MHz; Channel:Low



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2385.740	47.06	-3.46	43.60	54.00	-10.40	AVG
2	2390.000	49.66	-3.46	46.20	54.00	-7.80	AVG
3	2409.680	96.32	-3.40	92.92	54.00	38.92	AVG



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 30 of 81

Mode:a; Polarization:Vertical; Modulation:g; bandwidth:20MHz; Channel:Low




No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2387.140	62.55	-3.46	59.09	74.00	-14.91	peak
2	2390.000	62.82	-3.46	59.36	74.00	-14.64	peak
3	2407.440	107.14	-3.40	103.74	74.00	29.74	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 31 of 81

Mode:a; Polarization:Vertical; Modulation:g; bandwidth:20MHz; Channel:Low



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2387.980	46.34	-3.46	42.88	54.00	-11.12	AVG
2	2390.000	48.24	-3.46	44.78	54.00	-9.22	AVG
3	2408.700	96.19	-3.40	92.79	54.00	38.79	AVG



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 32 of 81

Mode:a; Polarization:Horizontal; Modulation:g; bandwidth:20MHz; Channel:High



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2468.450	105.04	-3.21	101.83	74.00	27.83	peak
2	2483.500	64.56	-3.16	61.40	74.00	-12.60	peak
3	2486.900	61.71	-3.15	58.56	74.00	-15.44	peak
4	2500.000	53.72	-3.10	50.62	74.00	-23.38	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its Intervention only and within the limits of Client's Instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing (inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CND occheck@ggs.com


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国 • 上海 • 松江区金都西路588号 邮编: 201612 t(86-21)61915666 f(86-21)61915678 www.sgsgroup.com.cn t(86-21)61915666 f(86-21)61915678 e sgs.china@sgs.com



Report No.: SHEM210400295301

Page: 33 of 81

Mode:a; Polarization:Horizontal; Modulation:g; bandwidth:20MHz; Channel:High



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2465.900	95.36	-3.22	92.14	54.00	38.14	AVG
2	2483.500	49.33	-3.16	46.17	54.00	-7.83	AVG
3	2495.450	43.54	-3.12	40.42	54.00	-13.58	AVG
4	2500.000	41.61	-3.10	38.51	54.00	-15.49	AVG



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612 t(86-21)61915666 f(86-21)61915678 www.sgsgroup.com.cn t(86-21)61915666 f(86-21)61915678 e sgs.china@sgs.com





Page: 34 of 81

Mode:a; Polarization:Vertical; Modulation:g; bandwidth:20MHz; Channel:High




No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2457.350	105.91	-3.24	102.67	74.00	28.67	peak
2	2483.500	65.02	-3.16	61.86	74.00	-12.14	peak
3	2487.650	63.00	-3.15	59.85	74.00	-14.15	peak
4	2500.000	53.43	-3.10	50.33	74.00	-23.67	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its Intervention only and within the limits of Client's Instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing (inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CND occheck@ggs.com

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 35 of 81

Mode:a; Polarization:Vertical; Modulation:g; bandwidth:20MHz; Channel:High



No.	Frequency	y Reading Correct Result Limit		Limit	Margin	Remark	
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2454.650	95.70	-3.26	92.44	54.00	38.44	AVG
2	2483.500	47.65	-3.16	44.49	54.00	-9.51	AVG
3	2484.950	46.10	-3.15	42.95	54.00	-11.05	AVG
4	2500.000	41.18	-3.10	38.08	54.00	-15.92	AVG



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612 t(86-21)61915666 f(86-21)61915678 www.sgsgroup.com.cn t(86-21)61915666 f(86-21)61915678 e sgs.china@sgs.com





Page: 36 of 81

Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:Low



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2383.360	61.37	-3.47	57.90	74.00	-16.10	peak
2	2390.000	66.74	-3.46	63.28	74.00	-10.72	peak
3	2410.380	105.40	-3.39	102.01	74.00	28.01	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国 • 上海 • 松江区金都西路588号 邮编: 201612





Page: 37 of 81

Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2386.720	47.47	-3.46	44.01	54.00	-9.99	AVG
2	2390.000	50.54	-3.46	47.08	54.00	-6.92	AVG
3	2409.680	95.30	-3.40	91.90	54.00	37.90	AVG



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 38 of 81

Mode:a; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2387.560	60.91	-3.46	57.45	74.00	-16.55	peak
2	2390.000	66.13	-3.46	62.67	74.00	-11.33	peak
3	2415.280	105.33	-3.38	101.95	74.00	27.95	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 39 of 81

Mode:a; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2387.000	46.05	-3.46	42.59	54.00	-11.41	AVG
2	2390.000	49.10	-3.46	45.64	54.00	-8.36	AVG
3	2415.140	95.31	-3.38	91.93	54.00	37.93	AVG



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 40 of 81

Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:High



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2466.050	104.56	-3.22	101.34	74.00	27.34	peak
2	2483.500	65.56	-3.16	62.40	74.00	-11.60	peak
3	2485.100	65.42	-3.15	62.27	74.00	-11.73	peak
4	2500.000	52.76	-3.10	49.66	74.00	-24.34	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国 • 上海 • 松江区金都西路588号 邮编: 201612





Page: 41 of 81

Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:High



No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2465.000	94.43	-3.22	91.21	54.00	37.21	AVG
2	2483.500	50.98	-3.16	47.82	54.00	-6.18	AVG
3	2486.150	47.26	-3.15	44.11	54.00	-9.89	AVG
4	2500.000	41.55	-3.10	38.45	54.00	-15.55	AVG



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国 • 上海 • 松江区金都西路588号 邮编: 201612





Page: 42 of 81

Mode:a; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:High



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2455.400	104.75	-3.25	101.50	74.00	27.50	peak
2	2483.500	63.39	-3.16	60.23	74.00	-13.77	peak
3	2485.100	65.08	-3.15	61.93	74.00	-12.07	peak
4	2500.000	52.20	-3.10	49.10	74.00	-24.90	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国 • 上海 • 松江区金都西路588号 邮编: 201612





Page: 43 of 81

Mode:a; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:High



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2455.850	94.82	-3.25	91.57	54.00	37.57	AVG
2	2483.500	48.75	-3.16	45.59	54.00	-8.41	AVG
3	2485.100	46.80	-3.15	43.65	54.00	-10.35	AVG
4	2500.000	40.83	-3.10	37.73	54.00	-16.27	AVG



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 44 of 81

Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:Low



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2386.160	74.40	-3.46	70.94	74.00	-3.06	peak
2	2390.000	72.88	-3.46	69.42	74.00	-4.58	peak
3	2414.020	102.34	-3.39	98.95	74.00	24.95	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国 • 上海 • 松江区金都西路588号 邮编: 201612





Page: 45 of 81

Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:Low



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2384.340	53.46	-3.47	49.99	54.00	-4.01	AVG
2	2390.000	53.71	-3.46	50.25	54.00	-3.75	AVG
3	2410.240	93.61	-3.39	90.22	54.00	36.22	AVG



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 46 of 81

Mode:a; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2386.860	72.79	-3.46	69.33	74.00	-4.67	peak
2	2390.000	70.57	-3.46	67.11	74.00	-6.89	peak
3	2413.320	102.30	-3.39	98.91	74.00	24.91	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国 • 上海 • 松江区金都西路588号 邮编: 201612





Page: 47 of 81

Mode:a; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2387.420	53.09	-3.46	49.63	54.00	-4.37	AVG
2	2390.000	54.22	-3.46	50.76	54.00	-3.24	AVG
3	2414.860	92.57	-3.38	89.19	54.00	35.19	AVG



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国 • 上海 • 松江区金都西路588号 邮编: 201612





Page: 48 of 81

Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:High



No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
_	\ /	\/	/	\ /	\/	\ /	
1	2445.300	102.16	-3.28	98.88	74.00	24.88	peak
2	2483.500	70.97	-3.16	67.81	74.00	-6.19	peak
3	2486.100	70.04	-3.15	66.89	74.00	-7.11	peak
4	2500.000	64.51	-3.10	61.41	74.00	-12.59	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国 • 上海 • 松江区金都西路588号 邮编: 201612





Page: 49 of 81

Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:High



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2436.630	92.92	-3.31	89.61	54.00	35.61	AVG
2	2483.500	53.86	-3.16	50.70	54.00	-3.30	AVG
3	2485.590	53.17	-3.15	50.02	54.00	-3.98	AVG
4	2500.000	45.57	-3.10	42.47	54.00	-11.53	AVG



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 50 of 81

Mode:a; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:High




No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2444.790	103.23	-3.28	99.95	74.00	25.95	peak
2	2483.500	71.09	-3.16	67.93	74.00	-6.07	peak
3	2485.420	72.84	-3.15	69.69	74.00	-4.31	peak
4	2500.000	58.90	-3.10	55.80	74.00	-18.20	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 51 of 81

Mode:a; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:High



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2443.770	92.54	-3.28	89.26	54.00	35.26	AVG
2	2483.500	52.04	-3.16	48.88	54.00	-5.12	AVG
3	2485.590	52.51	-3.15	49.36	54.00	-4.64	AVG
4	2500.000	44.55	-3.10	41.45	54.00	-12.55	AVG



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国 • 上海 • 松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 52 of 81

7.8 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.247(d)

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the ine of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullees extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (85-755) 8307 1443,

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 53 of 81

7.8.1 E.U.T. Operation

Operating Environment:


Temperature: 25 °C Humidity: 49 % RH Atmospheric Pressure: 1006 mbar


Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation


types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40).

Only the data of worst case is recorded in the report.

7.8.2 Test Setup Diagram









Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-758 8307 1443).

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 54 of 81

7.8.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

- 3) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic format documents subject to Terms and Conditions for Electronic Document sat http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing (inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CRN Doccheck@gs.com


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 55 of 81

30MHz-1GHz Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
1	30.9700	2.32	25.38	27.70	40.00	-12.30	100	360	QP
2	141.5500	3.95	19.86	23.81	43.50	-19.69	100	46	QP
3	323.9100	10.34	21.46	31.80	46.00	-14.20	100	275	QP
4	431.5800	6.97	24.04	31.01	46.00	-14.99	200	276	QP
5	518.8800	9.31	25.46	34.77	46.00	-11.23	200	175	QP
6	885.5400	5.13	28.50	33.63	46.00	-12.37	100	360	QP



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 56 of 81

Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
1	103.7200	9.33	18.63	27.96	43.50	-15.54	100	9	QP
2	296.7500	12.20	20.54	32.74	46.00	-13.26	100	360	QP
3	405.3900	10.93	23.66	34.59	46.00	-11.41	100	328	QP
4	431.5800	13.64	24.04	37.68	46.00	-8.32	100	243	QP
5	518.8800	8.77	25.46	34.23	46.00	-11.77	200	360	QP
6	594.5400	7.12	26.44	33.56	46.00	-12.44	100	133	QP



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国 • 上海 • 松江区金都西路588号 邮编: 201612




Report No.: SHEM210400295301

Page: 57 of 81

Above 1GHz

Mode:a; Polarization:Horizontal; Modulation:b; bandwidth:20MHz; Channel:Low



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4824.000	57.79	-10.21	47.58	74.00	-26.42	peak
2	7236.000	56.26	-7.05	49.21	74.00	-24.79	peak
3	9648.000	54.74	-4.77	49.97	74.00	-24.03	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 58 of 81

Mode:a; Polarization:Vertical; Modulation:b; bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4824.000	58.78	-10.21	48.57	74.00	-25.43	peak
2	7236.000	57.09	-7.05	50.04	74.00	-23.96	peak
3	9648.000	54.99	-4.77	50.22	74.00	-23.78	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 59 of 81

Mode:a; Polarization:Horizontal; Modulation:b; bandwidth:20MHz; Channel:middle



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4874.000	58.12	-10.01	48.11	74.00	-25.89	peak
2	7311.000	56.20	-6.93	49.27	74.00	-24.73	peak
3	9748.000	54.34	-4.30	50.04	74.00	-23.96	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 60 of 81

Mode:a; Polarization:Vertical; Modulation:b; bandwidth:20MHz; Channel:middle



No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4874.000	58.58	-10.01	48.57	74.00	-25.43	peak
2	7311.000	56.58	-6.93	49.65	74.00	-24.35	peak
3	9748.000	54.09	-4.30	49.79	74.00	-24.21	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国 • 上海 • 松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 61 of 81

Mode:a; Polarization:Horizontal; Modulation:b; bandwidth:20MHz; Channel:High



No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4924.000	57.74	-9.82	47.92	74.00	-26.08	peak
2	7386.000	56.05	-6.80	49.25	74.00	-24.75	peak
3	9848.000	53.98	-3.84	50.14	74.00	-23.86	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 62 of 81

Mode:a; Polarization:Vertical; Modulation:b; bandwidth:20MHz; Channel:High



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4924.000	57.40	-9.82	47.58	74.00	-26.42	peak
2	7386.000	55.98	-6.80	49.18	74.00	-24.82	peak
3	9848.000	53.79	-3.84	49.95	74.00	-24.05	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 63 of 81

Mode:a; Polarization:Horizontal; Modulation:g; bandwidth:20MHz; Channel:Low



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4824.000	58.09	-10.21	47.88	74.00	-26.12	peak
2	7236.000	55.57	-7.05	48.52	74.00	-25.48	peak
3	9648.000	54.70	-4.77	49.93	74.00	-24.07	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 64 of 81

Mode:a; Polarization:Vertical; Modulation:g; bandwidth:20MHz; Channel:Low



1000	.0002700.00 770	0.00 0100.00	7000.00 3300.00	11200.00 12300	0.00 17000.00	10000.0041112	
No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4824.000	57.43	-10.21	47.22	74.00	-26.78	peak
2	7236.000	56.32	-7.05	49.27	74.00	-24.73	peak
3	9648 000	54 90	-4 77	50 13	74 00	-23 87	neak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 65 of 81

Mode:a; Polarization:Horizontal; Modulation:g; bandwidth:20MHz; Channel:middle



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4874.000	58.07	-10.01	48.06	74.00	-25.94	peak
2	7311.000	55.70	-6.93	48.77	74.00	-25.23	peak
3	9748.000	53.85	-4.30	49.55	74.00	-24.45	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 66 of 81

Mode:a; Polarization:Vertical; Modulation:g; bandwidth:20MHz; Channel:middle



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4874.000	57.99	-10.01	47.98	74.00	-26.02	peak
2	7311.000	56.28	-6.93	49.35	74.00	-24.65	peak
3	9748.000	54.44	-4.30	50.14	74.00	-23.86	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 67 of 81

Mode:a; Polarization:Horizontal; Modulation:g; bandwidth:20MHz; Channel:High



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4924.000	57.41	-9.82	47.59	74.00	-26.41	peak
2	7386.000	56.03	-6.80	49.23	74.00	-24.77	peak
3	9848.000	53.77	-3.84	49.93	74.00	-24.07	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 68 of 81

Mode:a; Polarization:Vertical; Modulation:g; bandwidth:20MHz; Channel:High



No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4924.000	57.50	-9.82	47.68	74.00	-26.32	peak
2	7386.000	55.13	-6.80	48.33	74.00	-25.67	peak
3	9848.000	53.97	-3.84	50.13	74.00	-23.87	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 69 of 81

Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:Low



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4824.000	58.07	-10.21	47.86	74.00	-26.14	peak
2	7236.000	55.78	-7.05	48.73	74.00	-25.27	peak
3	9648.000	55.29	-4.77	50.52	74.00	-23.48	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 70 of 81

Mode:a; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4824.000	57.76	-10.21	47.55	74.00	-26.45	peak
2	7236.000	55.71	-7.05	48.66	74.00	-25.34	peak
3	9648.000	54.99	-4.77	50.22	74.00	-23.78	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 71 of 81

Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:middle



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4874.000	57.62	-10.01	47.61	74.00	-26.39	peak
2	7311.000	56.18	-6.93	49.25	74.00	-24.75	peak
3	9748.000	53.84	-4.30	49.54	74.00	-24.46	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 72 of 81

Mode:a; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:middle



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4874.000	57.66	-10.01	47.65	74.00	-26.35	peak
2	7311.000	55.82	-6.93	48.89	74.00	-25.11	peak
3	9748.000	54.64	-4.30	50.34	74.00	-23.66	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 73 of 81

Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:High



No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4924.000	57.34	-9.82	47.52	74.00	-26.48	peak
2	7386.000	56.30	-6.80	49.50	74.00	-24.50	peak
3	9848.000	54.01	-3.84	50.17	74.00	-23.83	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 74 of 81

Mode:a; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:High



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4924.000	57.30	-9.82	47.48	74.00	-26.52	peak
2	7386.000	55.77	-6.80	48.97	74.00	-25.03	peak
3	9848.000	53.82	-3.84	49.98	74.00	-24.02	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 75 of 81

Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:Low



No. Frequency Reading Correct Result Limit Margin Remark (MHz) (dBuV) Factor(dB/m) (dBuV/m) (dBuV/m) (dB) 4844.000 58.24 74.00 1 -10.1348.11 -25.89peak 2 7266.000 55.65 -7.00 48.65 74.00 -25.35 peak 3 9688.000 54.76 -4.58 50.18 74.00 -23.82 peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document advised that information on the analysis of Cijent's instructions, if any. The Company's sole responsibility is to its Client and this document only and within the limits of Cijent's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing (inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 76 of 81

Mode:a; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low



1000.0002700.00 4400.00 8100.00 5000.00 11200.00 12500.00 14600.00 10000.00m112							
No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4844.000	57.98	-10.13	47.85	74.00	-26.15	peak
2	7266.000	55.67	-7.00	48.67	74.00	-25.33	peak
3	9688.000	54.80	-4.58	50.22	74.00	-23.78	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 77 of 81

Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:middle



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4874.000	57.87	-10.01	47.86	74.00	-26.14	peak
2	7311.000	55.67	-6.93	48.74	74.00	-25.26	peak
3	9748.000	54.39	-4.30	50.09	74.00	-23.91	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 78 of 81

Mode:a; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:middle



No.	Frequency	Reading	Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4874.000	57.87	-10.01	47.86	74.00	-26.14	peak
2	7311.000	55.50	-6.93	48.57	74.00	-25.43	peak
3	9748.000	54.62	-4.30	50.32	74.00	-23.68	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 79 of 81

Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:High



1000.0002700.00 4400.00 6100.00 7800.00 9500.00 11200.00 12900.00 14600.00 18000.00MHz

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4904.000	57.75	-9.89	47.86	74.00	-26.14	peak
2	7356.000	55.39	-6.85	48.54	74.00	-25.46	peak
3	9808.000	53.70	-4.02	49.68	74.00	-24.32	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond


NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM210400295301

Page: 80 of 81

Mode:a; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:High



	0002100.00 1100	.00 0100.00 1	000.00 0000.00	11200:00 12000	.00 1 1000.00	10000:0411112	
No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4904.000	57.75	-9.89	47.86	74.00	-26.14	peak
2	7356.000	55.80	-6.85	48.95	74.00	-25.05	peak
3	9808.000	54.26	-4.02	50.24	74.00	-23.76	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612





Page: 81 of 81

8 Test Setup Photographs

Refer to the < Test Setup photos-FCC>.

9 EUT Constructional Details

Refer to the < External Photos > & < Internal Photos >.

- End of the Report -



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮編: 201612