






Test Mode	Channel	Verdict
11G	HCH	PASS

Pref test Plot






Puw test Plot







Test Mode	Channel	Verdict
11N HT20	LCH	PASS

Pref test Plot






Puw test Plot







Test Mode	Channel	Verdict
11N HT20	MCH	PASS

Pref test Plot






Puw test Plot







Test Mode	Channel	Verdict
11N HT20	HCH	PASS

Pref test Plot






Puw test Plot







Test Mode	Channel	Verdict
11N HT40	LCH	PASS

Pref test Plot






Puw test Plot







Test Mode	Channel	Verdict
11N HT40	MCH	PASS

Pref test Plot






Puw test Plot







Test Mode	Channel	Verdict
11N HT40	HCH	PASS

Pref test Plot





Puw test Plot





7.7. RADIATED TEST RESULTS

7.7.1.LIMITS AND PROCEDURE

LIMITS

Please refer to FCC §15.205 and §15.209 (Transmitter)

Please refer to FCC KDB 558074

Radiation Disturbance Test Limit for FCC (Class B)(9KHz-1GHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Note: 1) At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 Db/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

(2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 Db/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.



Radiation Disturbance Test Limit for FCC (Above 1G)

Frequency (MHz)	Db(Uv/m) (at 3 meters)	
	Peak	Average
Above 1000	74	54

Restricted bands of operation


MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST SETUP AND PROCEDURE

Below 30MHz




The setting of the spectrum analyser

RBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
VBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
Sweep	Auto
Detector	Peak/QP/ Average
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector
6. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 Db lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. For the actual test configuration, please refer to the related item in this test report (Photographs of the Test Configuration)

Below 1G




The setting of the spectrum analyser

RBW	120K
VBW	300K
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 Db lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
6. For the actual test configuration, please refer to the related Item in this test report (Photographs of the Test Configuration)

ABOVE 1G




The setting of the spectrum analyser

RBW	1M
VBW	PEAK:3M AVG: See note6
Sweep	Auto
Detector	Peak/Average(10Hz)
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz, the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements; and 1 MHz resolution bandwidth with video bandwidth $\geq 1/T$ but not less than the setting list in section 7.1 when use peak detector, max hold to be run for at least $[50*(1/Duty\ Cycle)]$ traces for average measurements. For the Duty Cycle need to refer the results in section 7.2.
7. For the actual test configuration, please refer to the related item in this test report (Photographs of the Test Configuration)

X axis, Y axis, Z axis positions :



Note: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (Z axis) data recorded in the report.

7.7.2.RESTRICTED BANDEDGE

TEST ENVIRONMENT

Environment Parameter	Selected Values During Tests
Relative Humidity	65.9%
Atmospheric Pressure:	102Kpa
Temperature	21.6°C


Test Result Table

Test Mode	Channel	Puw(dBm)	Verdict
11B	LCH	<Limit	PASS
	HCH	<Limit	PASS
11G	LCH	<Limit	PASS
	HCH	<Limit	PASS
11N HT20	LCH	<Limit	PASS
	HCH	<Limit	PASS
11N HT40	LCH	<Limit	PASS
	HCH	<Limit	PASS



Test Graphs:

Test Mode	Channel	Polarization	Verdict
11B	LCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	2338.1423	42.41	12.57	54.98	74.00	-19.02	peak
		28.96	12.57	41.53	54.00	-12.47	average
2	2390.0000	41.56	13.07	54.63	74.00	-19.37	peak
		29.03	13.07	42.10	54.00	-11.9	average

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11B	LCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	2339.4362	41.87	12.59	54.46	74.00	-19.54	peak
		28.83	12.59	41.42	54.00	-12.58	average
2	2390.0000	41.37	13.07	54.44	74.00	-19.56	peak
		29.11	13.07	42.18	54.00	-11.82	average

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11B	HCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	2483.5000	40.24	12.97	53.21	74.00	-20.79	peak
2	2499.1199	42.04	13.13	55.17	74.00	-18.83	peak
		29.37	13.13	42.50	54.00	-11.50	average

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11B	HCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	2483.5000	41.20	12.97	54.17	74.00	-19.83	peak
		29.73	12.97	42.70	54.00	-11.3	average
2	2493.2242	43.24	13.04	56.28	74.00	-17.72	peak
		29.23	13.04	42.27	54.00	-11.73	average

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11G	LCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	2348.0060	42.03	12.67	54.70	74.00	-19.3	peak
		28.92	12.67	41.59	54.00	-12.41	average
2	2387.0109	47.76	13.06	60.82	74.00	-13.18	peak
		33.34	13.06	46.40	54.00	-7.6	average
3	2390.0000	46.21	13.07	59.28	74.00	-14.72	peak
		32.97	13.07	46.04	54.00	-7.96	average

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11G	LCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	2345.7370	42.51	12.65	55.16	74.00	-18.84	peak
		28.87	12.65	41.52	54.00	-12.48	average
2	2389.3924	45.65	13.07	58.72	74.00	-15.28	peak
		31.86	13.07	44.93	54.00	-9.07	average
3	2390.0000	43.99	13.07	57.06	74.00	-16.94	peak
		31.47	13.07	44.54	54.00	-9.46	average

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11G	HCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	2483.5000	43.49	12.97	56.46	74.00	-17.54	peak
		30.96	12.97	43.93	54.00	-10.07	average
2	2527.8785	40.72	13.38	54.10	74.00	-19.90	peak
		29.18	13.38	42.56	54.00	-11.44	average

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11G	HCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	2483.5000	45.31	12.97	58.28	74.00	-15.72	peak
		32.05	12.97	45.02	54.00	-8.98	average
2	2541.0426	41.31	13.41	54.72	74.00	-19.28	peak
		29.11	13.41	42.52	54.00	-11.48	average

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11N HT20	LCH	Horizontal	PASS




No.	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (Db)	Result (dBuV/m)	Limit (dBuV/m)	Margin (Db)	Remark
1	2379.0411	44.16	13.05	57.21	74.00	-16.79	peak
		29.55	13.05	42.60	54.00	-11.40	average
2	2390.0000	49.77	13.07	62.84	74.00	-11.16	peak
		37.18	13.07	50.25	54.00	-3.75	average

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11N HT20	LCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	2388.6423	52.41	13.07	65.48	74.00	-8.52	peak
		35.28	13.07	48.35	54.00	-5.65	average
2	2390.0000	50.95	13.07	64.02	74.00	-9.98	peak
		36.73	13.07	49.80	54.00	-4.20	average

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11N HT20	HCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	2483.5000	44.57	12.97	57.54	74.00	-16.46	peak
		30.89	12.97	43.86	54.00	-10.14	average
2	2495.4519	42.19	13.07	55.26	74.00	-18.74	peak
		29.25	13.07	42.32	54.00	-11.68	average

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11N HT20	HCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	2483.5000	47.42	12.97	60.39	74.00	-13.61	peak
		35.34	12.97	48.31	54.00	-5.69	average
2	2484.7631	50.74	12.97	63.71	74.00	-10.29	peak
		34.89	12.97	47.86	54.00	-6.14	average
3	2559.6300	40.79	13.41	54.20	74.00	-19.80	peak
		29.36	13.41	42.77	54.00	-11.23	average

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11N HT40	LCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	2382.9416	46.92	13.06	59.98	74.00	-14.02	peak
		33.84	13.06	46.90	54.00	-7.10	average
2	2388.4361	49.35	13.07	62.42	74.00	-11.58	peak
		34.82	13.07	47.89	54.00	-6.11	average
3	2390.0000	47.45	13.07	60.52	74.00	-13.48	peak
		35.35	13.07	48.42	54.00	-5.58	average

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11N HT40	LCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	2382.1540	46.70	13.06	59.76	74.00	-14.24	peak
		32.34	13.06	45.40	54.00	-8.60	average
2	2385.1356	47.93	13.06	60.99	74.00	-13.01	peak
		33.12	13.06	46.18	54.00	-7.82	average
3	2390.0000	48.63	13.07	61.70	74.00	-12.30	peak
		33.28	13.07	46.35	54.00	-7.65	average

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11N HT40	HCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	2483.5000	44.30	12.97	57.27	74.00	-16.73	peak
		33.57	12.97	46.54	54.00	-7.46	average
2	2485.4607	46.06	12.98	59.04	74.00	-14.96	peak
		32.69	12.98	45.67	54.00	-8.33	average
3	2556.9071	40.95	13.39	54.34	74.00	-19.66	peak
		29.43	13.39	42.82	54.00	-11.18	average
4	-	-	-	-	-	-	peak
		-	-	-	-	-	average

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11N HT40	HCH	Vertical	PASS



No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	2483.5000	51.45	12.97	64.42	74.00	-9.58	peak
		36.33	12.97	49.30	54.00	-4.70	average
2	2490.5013	46.60	13.00	59.60	74.00	-14.40	peak
		32.18	13.00	45.18	54.00	-8.82	average
3	2532.9641	39.86	13.42	53.28	74.00	-20.72	peak
		30.09	13.42	43.51	54.00	-10.49	average

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 3. Measurement = Reading Level + Correct Factor.
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



7.7.3.SPURIOUS EMISSIONS

Test Result Table:

1) For 1GHz~3GHz

Environment Parameter	Selected Values During Tests
Relative Humidity	65.9%
Atmospheric Pressure:	102Kpa
Temperature	21.6°C

Test Mode	Channel	Puw(dBm)	Verdict
11B SISO	LCH	<Limit	PASS
	MCH	<Limit	PASS
	HCH	<Limit	PASS
11G SISO	LCH	<Limit	PASS
	MCH	<Limit	PASS
	HCH	<Limit	PASS
11N HT20	LCH	<Limit	PASS
	MCH	<Limit	PASS
	HCH	<Limit	PASS
11N HT40	LCH	<Limit	PASS
	MCH	<Limit	PASS
	HCH	<Limit	PASS

2) For 3GHz~18GHz

Environment Parameter	Selected Values During Tests
Relative Humidity	55.6%
Atmospheric Pressure:	102.5kPa
Temperature	21.8°C

Test Mode	Channel	Puw(dBm)	Verdict
11B SISO	LCH	<Limit	PASS
	MCH	<Limit	PASS
	HCH	<Limit	PASS
11G SISO	LCH	<Limit	PASS
	MCH	<Limit	PASS
	HCH	<Limit	PASS
11N HT20	LCH	<Limit	PASS
	MCH	<Limit	PASS
	HCH	<Limit	PASS
11N HT40	LCH	<Limit	PASS
	MCH	<Limit	PASS



	HCH	<Limit	PASS
--	-----	--------	------

3) For 18GHz~26.5GHz

Environment Parameter	Selected Values During Tests
Relative Humidity	65.9%
Atmospheric Pressure:	102Kpa
Temperature	21.6°C

Test Mode	Channel	Puw(dBm)	Verdict
11B	MCH	<Limit	PASS

Remark:

21) Through pre-testing all the test modes and test channels, but only the data of the worst case is included in this test report.

4) For 30MHz~1GHz

Environment Parameter	Selected Values During Tests
Relative Humidity	66.0%
Atmospheric Pressure:	102Kpa
Temperature	21.5°C

Test Mode	Channel	Puw(dBm)	Verdict
11B	MCH	<Limit	PASS

Remark:

21) Through pre-testing all the test modes and test channels, but only the data of the worst case is included in this test report.

5) For 9KHz~30MHz

Environment Parameter	Selected Values During Tests
Relative Humidity	66.0%
Atmospheric Pressure:	102Kpa
Temperature	21.5°C

Test Mode	Channel	Puw(dBm)	Verdict
11B	MCH	<Limit	PASS

Remark:


21) Through pre-testing all the test modes and test channels, but only the data of the worst case is included in this test report.



Part I: 1GHz~3GHz

HARMONICS AND SPURIOUS EMISSIONS

Test Mode	Channel	Polarization	Verdict
11B	LCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1196.0000	48.10	-5.56	42.54	74.00	-31.46	peak
2	1398.7500	45.71	-5.67	40.04	74.00	-33.96	peak
3	1535.7500	43.18	-5.75	37.43	74.00	-36.57	peak
4	1796.2500	47.56	-3.80	43.76	74.00	-30.24	peak
5	1997.0000	46.45	-3.02	43.43	74.00	-30.57	peak
6	2730.2500	41.58	-0.49	41.09	74.00	-32.91	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11B	LCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1196.2500	45.27	-5.56	39.71	74.00	-34.29	peak
2	1395.2500	44.09	-5.71	38.38	74.00	-35.62	peak
3	1535.7500	54.52	-5.75	48.77	74.00	-25.23	peak
4	1793.0000	48.94	-3.77	45.17	74.00	-28.83	peak
5	2310.0000	48.63	-1.65	46.98	74.00	-27.02	peak
6	2959.0000	41.29	0.97	42.26	74.00	-31.74	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11B	MCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1199.2500	48.07	-5.56	42.51	74.00	-31.49	peak
2	1395.2500	45.53	-5.71	39.82	74.00	-34.18	peak
3	1537.2500	42.88	-5.74	37.14	74.00	-36.86	peak
4	1799.2500	48.36	-3.84	44.52	74.00	-29.48	peak
5	2060.2500	43.73	-2.64	41.09	74.00	-32.91	peak
6	2961.2500	41.02	1.01	42.03	74.00	-31.97	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11B	MCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1194.7500	47.02	-5.57	41.45	74.00	-32.55	peak
2	1397.0000	43.12	-5.69	37.43	74.00	-36.57	peak
3	1535.7500	54.65	-5.75	48.90	74.00	-25.10	peak
4	1795.7500	48.51	-3.80	44.71	74.00	-29.29	peak
5	2146.2500	45.45	-2.37	43.08	74.00	-30.92	peak
6	2646.5000	43.38	-0.80	42.58	74.00	-31.42	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11B	HCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1199.2500	47.27	-5.56	41.71	74.00	-32.29	peak
2	1398.5000	46.28	-5.67	40.61	74.00	-33.39	peak
3	1535.7500	59.65	-5.75	53.90	74.00	-20.10	peak
4	1792.7500	47.01	-3.77	43.24	74.00	-30.76	peak
5	1994.5000	43.90	-3.04	40.86	74.00	-33.14	peak
6	2894.2500	41.94	0.46	42.40	74.00	-31.60	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11B	HCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1198.7500	44.81	-5.56	39.25	74.00	-34.75	peak
2	1535.7500	54.28	-5.75	48.53	74.00	-25.47	peak
3	1793.2500	46.92	-3.77	43.15	74.00	-30.85	peak
4	1992.5000	45.45	-3.06	42.39	74.00	-31.61	peak
5	2291.7500	50.33	-1.92	48.41	74.00	-25.59	peak
6	2698.2500	44.32	-0.44	43.88	74.00	-30.12	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11G	LCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1197.5000	47.78	-5.56	42.22	74.00	-31.78	peak
2	1397.7500	46.99	-5.68	41.31	74.00	-32.69	peak
3	1536.0000	42.81	-5.75	37.06	74.00	-36.94	peak
4	1795.2500	48.62	-3.79	44.83	74.00	-29.17	peak
5	2175.2500	42.98	-2.32	40.66	74.00	-33.34	peak
6	2853.7500	41.76	0.12	41.88	74.00	-32.12	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11G	LCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1195.2500	45.28	-5.57	39.71	74.00	-34.29	peak
2	1394.5000	43.67	-5.72	37.95	74.00	-36.05	peak
3	1535.7500	54.52	-5.75	48.77	74.00	-25.23	peak
4	1793.7500	46.58	-3.78	42.80	74.00	-31.20	peak
5	2244.0000	48.74	-2.20	46.54	74.00	-27.46	peak
6	2720.2500	42.56	-0.37	42.19	74.00	-31.81	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11G	MCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1188.7500	45.97	-5.58	40.39	74.00	-33.61	peak
2	1397.2500	44.12	-5.69	38.43	74.00	-35.57	peak
3	1535.7500	59.68	-5.75	53.93	74.00	-20.07	peak
4	1797.7500	47.47	-3.82	43.65	74.00	-30.35	peak
5	2177.0000	42.32	-2.33	39.99	74.00	-34.01	peak
6	2606.2500	41.53	-0.46	41.07	74.00	-32.93	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11G	MCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1199.5000	45.81	-5.56	40.25	74.00	-33.75	peak
2	1396.5000	43.74	-5.70	38.04	74.00	-35.96	peak
3	1535.7500	54.51	-5.75	48.76	74.00	-25.24	peak
4	1792.5000	47.38	-3.76	43.62	74.00	-30.38	peak
5	2249.0000	50.81	-2.09	48.72	74.00	-25.28	peak
6	2738.0000	43.67	-0.47	43.20	74.00	-30.80	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11G	HCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1197.5000	47.78	-5.56	42.22	74.00	-31.78	peak
2	1397.7500	46.99	-5.68	41.31	74.00	-32.69	peak
3	1536.0000	42.81	-5.75	37.06	74.00	-36.94	peak
4	1795.2500	48.62	-3.79	44.83	74.00	-29.17	peak
5	2175.2500	42.98	-2.32	40.66	74.00	-33.34	peak
6	2853.7500	41.76	0.12	41.88	74.00	-32.12	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11G	HCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1195.2500	45.28	-5.57	39.71	74.00	-34.29	peak
2	1394.5000	43.67	-5.72	37.95	74.00	-36.05	peak
3	1535.7500	54.52	-5.75	48.77	74.00	-25.23	peak
4	1793.7500	46.58	-3.78	42.80	74.00	-31.20	peak
5	2244.0000	48.74	-2.20	46.54	74.00	-27.46	peak
6	2720.2500	42.56	-0.37	42.19	74.00	-31.81	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11N HT20	LCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1200.0000	45.42	-5.56	39.86	74.00	-34.14	peak
2	1398.5000	46.01	-5.67	40.34	74.00	-33.66	peak
3	1535.7500	59.64	-5.75	53.89	74.00	-20.11	peak
4	1792.2500	49.58	-3.76	45.82	74.00	-28.18	peak
5	2048.0000	42.36	-2.38	39.98	74.00	-34.02	peak
6	2766.0000	41.14	-0.24	40.90	74.00	-33.10	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11N HT20	LCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1194.5000	44.98	-5.57	39.41	74.00	-34.59	peak
2	1394.7500	44.82	-5.72	39.10	74.00	-34.90	peak
3	1535.7500	54.66	-5.75	48.91	74.00	-25.09	peak
4	1792.0000	46.73	-3.76	42.97	74.00	-31.03	peak
5	2227.7500	50.63	-2.18	48.45	74.00	-25.55	peak
6	2788.2500	43.63	-0.32	43.31	74.00	-30.69	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11N HT20	MCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1188.7500	45.97	-5.58	40.39	74.00	-33.61	peak
2	1397.2500	44.12	-5.69	38.43	74.00	-35.57	peak
3	1535.7500	59.68	-5.75	53.93	74.00	-20.07	peak
4	1797.7500	47.47	-3.82	43.65	74.00	-30.35	peak
5	2177.0000	42.32	-2.33	39.99	74.00	-34.01	peak
6	2606.2500	41.53	-0.46	41.07	74.00	-32.93	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11N HT20	MCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1199.5000	45.81	-5.56	40.25	74.00	-33.75	peak
2	1396.5000	43.74	-5.70	38.04	74.00	-35.96	peak
3	1535.7500	54.51	-5.75	48.76	74.00	-25.24	peak
4	1792.5000	47.38	-3.76	43.62	74.00	-30.38	peak
5	2249.0000	50.81	-2.09	48.72	74.00	-25.28	peak
6	2738.0000	43.67	-0.47	43.20	74.00	-30.80	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11N HT20	HCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1194.0000	45.16	-5.57	39.59	74.00	-34.41	peak
2	1399.2500	46.07	-5.66	40.41	74.00	-33.59	peak
3	1535.7500	42.72	-5.75	36.97	74.00	-37.03	peak
4	1796.0000	49.01	-3.80	45.21	74.00	-28.79	peak
5	1997.5000	44.10	-3.01	41.09	74.00	-32.91	peak
6	2875.2500	42.22	0.22	42.44	74.00	-31.56	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11N HT20	HCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1068.0000	44.81	-5.32	39.49	74.00	-34.51	peak
2	1194.0000	44.18	-5.57	38.61	74.00	-35.39	peak
3	1439.5000	47.19	-5.80	41.39	74.00	-32.61	peak
4	1535.7500	54.47	-5.75	48.72	74.00	-25.28	peak
5	1799.7500	47.46	-3.84	43.62	74.00	-30.38	peak
6	2782.7500	42.77	-0.30	42.47	74.00	-31.53	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11N HT40	LCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1199.0000	47.35	-5.56	41.79	74.00	-32.21	peak
2	1399.7500	44.43	-5.66	38.77	74.00	-35.23	peak
3	1535.7500	42.78	-5.75	37.03	74.00	-36.97	peak
4	1794.2500	47.05	-3.78	43.27	74.00	-30.73	peak
5	1991.5000	44.77	-3.07	41.70	74.00	-32.30	peak
6	2858.5000	41.36	0.13	41.49	74.00	-32.51	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11N HT40	LCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1198.2500	46.36	-5.56	40.80	74.00	-33.20	peak
2	1440.2500	44.23	-5.80	38.43	74.00	-35.57	peak
3	1535.7500	54.44	-5.75	48.69	74.00	-25.31	peak
4	1797.7500	48.37	-3.82	44.55	74.00	-29.45	peak
5	2286.0000	50.31	-1.94	48.37	74.00	-25.63	peak
6	2958.5000	41.96	0.96	42.92	74.00	-31.08	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11N HT40	MCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1195.0000	47.66	-5.57	42.09	74.00	-31.91	peak
2	1396.5000	44.81	-5.70	39.11	74.00	-34.89	peak
3	1537.0000	43.22	-5.75	37.47	74.00	-36.53	peak
4	1799.2500	46.07	-3.84	42.23	74.00	-31.77	peak
5	2206.2500	43.69	-2.33	41.36	74.00	-32.64	peak
6	2821.0000	41.78	-0.17	41.61	74.00	-32.39	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11N HT40	MCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1186.7500	46.25	-5.61	40.64	74.00	-33.36	peak
2	1433.5000	46.44	-5.78	40.66	74.00	-33.34	peak
3	1535.7500	54.33	-5.75	48.58	74.00	-25.42	peak
4	1793.2500	49.14	-3.77	45.37	74.00	-28.63	peak
5	2271.7500	49.50	-2.08	47.42	74.00	-26.58	peak
6	2654.7500	44.56	-0.73	43.83	74.00	-30.17	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11N HT40	HCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1197.7500	46.41	-5.56	40.85	74.00	-33.15	peak
2	1394.5000	44.02	-5.72	38.30	74.00	-35.70	peak
3	1535.7500	59.62	-5.75	53.87	74.00	-20.13	peak
4	1798.0000	48.97	-3.82	45.15	74.00	-28.85	peak
5	1993.0000	43.41	-3.06	40.35	74.00	-33.65	peak
6	2761.0000	41.44	-0.27	41.17	74.00	-32.83	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11N HT40	HCH	Vertical	PASS



No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	1196.2500	46.54	-5.56	40.98	74.00	-33.02	peak
2	1535.7500	54.66	-5.75	48.91	74.00	-25.09	peak
3	1798.7500	47.07	-3.83	43.24	74.00	-30.76	peak
4	1993.7500	45.43	-3.05	42.38	74.00	-31.62	peak
5	2290.5000	49.75	-1.93	47.82	74.00	-26.18	peak
6	2658.5000	43.81	-0.69	43.12	74.00	-30.88	peak


- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Part II: 3GHz~18GHz

HARMONICS AND SPURIOUS EMISSIONS

Test Mode	Channel	Polarization	Verdict
11B	LCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	4198.2748	40.73	4.73	45.46	74.00	-28.54	peak
2	7607.4509	38.61	8.66	47.27	74.00	-26.73	peak
3	11903.6130	36.84	12.46	49.30	74.00	-24.70	peak
4	16938.6173	37.23	18.45	55.68	74.00	-18.32	peak
		27.44	18.45	45.89	54.00	-8.11	average
5	17561.1951	36.77	17.92	54.69	74.00	-19.31	peak
		26.51	17.92	44.43	54.00	-9.57	average
6	17902.4878	36.85	18.37	55.22	74.00	-18.78	peak
		26.55	18.37	44.92	54.00	-9.08	average

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For above 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11B	LCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	5807.2259	48.05	5.36	53.41	74.00	-20.59	peak
2	7065.5082	38.18	8.21	46.39	74.00	-27.61	peak
3	11033.5042	37.47	12.24	49.71	74.00	-24.29	peak
4	17024.8781	37.23	18.68	55.91	74.00	-18.09	peak
		27.78	18.68	46.46	54.00	-7.54	average
5	17576.197	38.27	17.78	56.05	74.00	-17.95	peak
		27.13	17.78	44.91	54.00	-9.09	average
6	17975.622	37.38	17.92	55.30	74.00	-18.70	peak
		26.75	17.92	44.67	54.00	-9.33	average

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For above 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11B	MCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	5805.3507	47.24	5.38	52.62	74.00	-21.38	peak
2	6984.8731	37.34	8.18	45.52	74.00	-28.48	peak
3	10358.4198	37.42	10.70	48.12	74.00	-25.88	peak
4	17026.7533	37.38	18.81	56.19	74.00	-17.81	peak
		27.00	18.81	45.81	54.00	-8.19	average
5	17409.3012	37.87	17.56	55.43	74.00	-18.57	peak
		26.72	17.56	44.28	54.00	-9.72	average
6	17998.1248	37.16	18.01	55.17	74.00	-18.83	peak
		27.24	18.01	45.25	54.00	-8.75	average

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For below 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
 The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11B	MCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	5797.8497	45.07	5.39	50.46	74.00	-23.54	peak
2	7054.2568	38.55	8.13	46.68	74.00	-27.32	peak
3	10834.7293	37.18	12.09	49.27	74.00	-24.73	peak
4	17069.8837	37.52	19.19	56.71	74.00	-17.29	peak
		26.87	19.19	46.06	54.00	-7.94	average
5	17456.182	37.06	17.79	54.85	74.00	-19.15	peak
		26.62	17.79	44.41	54.00	-9.59	average
6	17947.4934	36.62	18.50	55.12	74.00	-18.88	peak
		27.40	18.50	45.90	54.00	-8.10	average

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For above 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11B	HCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	4800.2250	41.95	5.67	47.62	74.00	-26.38	peak
2	7629.9537	38.88	8.37	47.25	74.00	-26.75	peak
3	12269.2837	36.92	11.92	48.84	74.00	-25.16	peak
4	16947.9935	36.76	18.37	55.13	74.00	-18.87	peak
		26.96	18.37	45.33	54.00	-8.67	average
5	17379.2974	36.71	18.60	55.31	74.00	-18.69	peak
		26.87	18.60	45.47	54.00	-8.53	average
6	17855.607	36.86	18.14	55.00	74.00	-19.00	peak
		26.19	18.14	44.33	54.00	-9.67	average

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For above 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11B	HCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	3680.7101	39.16	2.88	42.04	74.00	-31.96	peak
2	6099.7625	39.25	5.65	44.90	74.00	-29.10	peak
3	10965.9957	36.43	12.37	48.80	74.00	-25.20	peak
4	17150.5188	37.16	18.27	55.43	74.00	-18.57	peak
		26.54	18.27	44.81	54.00	-9.19	average
5	17707.4634	37.69	17.66	55.35	74.00	-18.65	peak
		27.16	17.66	44.82	54.00	-9.18	average
6	17904.363	37.31	18.35	55.66	74.00	-18.34	peak
		26.77	18.35	45.12	54.00	-8.88	average

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For above 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11G	LCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	4200.1500	40.86	4.77	45.63	74.00	-28.37	peak
2	6062.2578	38.73	5.54	44.27	74.00	-29.73	peak
3	9713.3392	38.18	8.30	46.48	74.00	-27.52	peak
4	16985.4982	36.73	18.77	55.50	74.00	-18.50	peak
		26.18	18.77	44.95	54.00	-9.05	average
5	17619.3274	37.45	17.64	55.09	74.00	-18.91	peak
		27.71	17.64	45.35	54.00	-8.65	average
6	17945.6182	36.77	18.44	55.21	74.00	-18.79	peak
		26.77	18.44	45.21	54.00	-8.79	average

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For above 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11G	LCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	5803.4754	47.53	5.40	52.93	74.00	-21.07	peak
2	7808.1010	39.34	7.98	47.32	74.00	-26.68	peak
3	12004.8756	36.56	12.84	49.40	74.00	-24.60	peak
4	16947.9935	36.98	18.37	55.35	74.00	-18.65	peak
		26.55	18.37	44.92	54.00	-9.08	average
5	17546.1933	37.27	17.82	55.09	74.00	-18.91	peak
		27.19	17.82	45.01	54.00	-8.99	average
6	17859.3574	37.02	18.45	55.47	74.00	-18.53	peak
		26.40	18.45	44.85	54.00	-9.15	average

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For above 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11G	MCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	4200.1500	41.22	4.77	45.99	74.00	-28.01	peak
2	8910.7388	39.67	8.52	48.19	74.00	-25.81	peak
3	14028.2535	36.51	14.65	51.16	74.00	-22.84	peak
4	17197.3997	37.09	18.31	55.40	74.00	-18.60	peak
		26.70	18.31	45.01	54.00	-8.99	average
5	17548.0685	37.21	17.95	55.16	74.00	-18.84	peak
		26.74	17.95	44.69	54.00	-9.31	average
6	17744.9681	36.63	17.98	54.61	74.00	-19.39	peak
		25.83	17.98	43.81	54.00	-10.19	average

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For above 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11G	MCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	3961.9952	39.98	4.49	44.47	74.00	-29.53	peak
2	6861.1076	37.64	7.91	45.55	74.00	-28.45	peak
3	10889.1111	37.70	12.24	49.94	74.00	-24.06	peak
4	16936.7421	37.24	18.43	55.67	74.00	-18.33	peak
		27.84	18.43	46.27	54.00	-7.73	average
5	17563.0704	37.59	17.97	55.56	74.00	-18.44	peak
		26.82	17.97	44.79	54.00	-9.21	average
6	17893.1116	36.32	18.51	54.83	74.00	-19.17	peak
		26.40	18.51	44.91	54.00	-9.09	average

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For above 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11G	HCH	Horizontal	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	4798.3498	41.45	5.76	47.21	74.00	-26.79	peak
2	8584.4481	39.32	6.86	46.18	74.00	-27.82	peak
3	12451.1814	37.55	11.58	49.13	74.00	-24.87	peak
4	17030.5038	36.74	19.03	55.77	74.00	-18.23	peak
		26.26	19.03	45.29	54.00	-8.71	average
5	17381.1726	36.38	18.51	54.89	74.00	-19.11	peak
		26.04	18.51	44.55	54.00	-9.45	average
6	17893.1116	36.50	18.51	55.01	74.00	-18.99	peak
		26.16	18.51	44.67	54.00	-9.33	average

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For above 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11G	HCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	4320.1650	40.82	5.18	46.00	74.00	-28.00	peak
2	5750.9689	44.81	5.29	50.10	74.00	-23.90	peak
3	11219.1524	38.98	11.83	50.81	74.00	-23.19	peak
4	16979.8725	37.69	18.75	56.44	74.00	-17.56	peak
		26.03	18.75	44.78	54.00	-9.22	average
5	17379.2974	35.94	18.60	54.54	74.00	-19.46	peak
		27.44	18.60	46.04	54.00	-7.96	average
6	17896.8621	36.04	18.45	54.49	74.00	-19.51	peak
		26.28	18.45	44.73	54.00	-9.27	average

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For above 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



Test Mode	Channel	Polarization	Verdict
11N HT20	LCH	Horizontal	PASS



No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	(Db)	(dBuV/m)	(dBuV/m)	(Db)	
1	4320.1650	40.04	5.18	45.22	74.00	-28.78	peak
2	6636.0795	37.46	7.57	45.03	74.00	-28.97	peak
3	10851.6065	37.59	12.39	49.98	74.00	-24.02	peak
4	17099.8875	36.91	18.33	55.24	74.00	-18.76	peak
		26.34	18.33	44.67	54.00	-9.33	average
5	17476.8096	37.05	17.80	54.85	74.00	-19.15	peak
		27.03	17.80	44.83	54.00	-9.17	average
6	17984.9981	36.99	17.81	54.80	74.00	-19.20	peak
		26.88	17.81	44.69	54.00	-9.31	average

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
 4. Peak: Peak detector.
 5. AVG: VBW refer to section 7.2.
 6. For above 3GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses. The proper operation of the transmitter prior to adding the filter to the measurement chain.
 21. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.