

Shenzhen Huntkey Electric Co., Ltd

TEST REPORT

SCOPE OF WORK

EMC TESTING-SCA109

REPORT NUMBER

210506172GZU-002

ISSUE DATE

22-May-2022

[REVISED DATE]

[-----]

PAGES

9

DOCUMENT CONTROL NUMBER

© 2017 INTERTEK



TEST REPORT

Applicant Name & Address : Shenzhen Huntkey Electric Co., Ltd
Huntkey Industrial Park,XueXiang Village,Bantian Street,LONGGANG
DISTRICT,518129,ShenZhen,Guangdong,China

Manufacturing Site : 1:Shenzhen Huntkey Electronics Co., Ltd
Huntkey Industrial Park,XueXiang Village,Bantian Street,LONGGANG
DISTRICT,518129,ShenZhen,Guangdong,China
2:HEYUAN HUNTKEY INDUSTRIAL CO., LTD.
Block D, Huntkey Industrial Park No.18, Longling Industrial Area
Yuancheng District Heyuan Guangdong 517000 China

Intertek Report No: 210506172GZU-002
FCC ID: 2AVYR-SCA109

Test standards

47 CFR PART 1, Subpart I, Section 1.1310
KDB 680106 D01 RF Exposure Wireless Charging App v03r01

Sample Description

Product : Wireless charger
Model No. : SCA109
Electrical Rating : Input: 125V, 60Hz, 0.8A
Output:
USB port: DC 5V/2.4A
Wireless charge: up to 10W

Serial No. : Not Labeled
Date Received : 06 May 2021
Date Test : 15 January 2022-20 January 2022
Conducted

Prepared and Checked By

Richard Liu

Richard Liu

Engineer

Approved By:

Dean Liu

Dean Liu

Project Engineer

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT

CONTENT

TEST REPORT **1**

CONTENT **3**

1.0 TEST RESULT SUMMARY **4**

2.0 GENERAL DESCRIPTION..... **5**

 2.1 PRODUCT DESCRIPTION5

 2.2 TEST FACILITY.....5

 2.3 EUT EXERCISING SOFTWARE.....5

 2.4 SPECIAL ACCESSORIES.....5

 2.5 EQUIPMENT MODIFICATION5

 2.6 SUPPORT EQUIPMENT LIST AND DESCRIPTION6

3.0 EMF TEST..... **7**

 3.1 STANDARD REQUIREMENT.....7

 3.2 TEST DATA.....8

4.0 TEST EQUIPMENT LIST **9**

TEST REPORT**1.0 TEST RESULT SUMMARY**

Classification of EUT: Class B

Test Item	Standard	Result
EMF	47 CFR PART 1, Subpart I, Section 1.1310	PASS

Remark:

When determining the test results, measurement uncertainty of tests has been considered. The worst case's test data is input 9V/2A, which is presented in this test report.

TEST REPORT

2.0 General Description

2.1 Product Description

Operating Frequency	112.8kHz-146.1kHz
Type of Modulation:	MSK
Antenna Type	Inductive loop coil antenna
Power Supply:	Input: 125V, 60Hz, 0.8A Output: USB port: DC 5V/2.4A Wireless charge: up to 10W
Power cord:	1m x 2 wires unscreened cable

2.2 Test Facility

Room102/104, No 203, KeZhu Road, Science City, GETDD Guangzhou, China

A2LA Certificate Number 0078.10

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch is accredited by A2LA and Listed in FCC website. FCC accredited test labs may perform both Certification testing under Parts 15 and 18 and Declaration of Conformity testing.

2.3 EUT Exercising Software

N/A

2.4 Special Accessories

N/A

2.5 Equipment Modification

Any modifications installed previous to testing by Shenzhen Huntkey Electric Co., Ltd will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Guangzhou Branch.

TEST REPORT

2.6 Support Equipment List and Description

This product was tested with corresponding support equipment as below:

Support Equipment:

Equipment	Model No.	Rating	Supplier
WPT client	Tx-test2	DC 12V/0.83A,DC 7.5V/1.06A,DC 5V/1A	Shenzhen Huntkey Electric Co., Ltd
1 st Cement resistance	--	2 Ω	Intertek
2 nd Cement resistance	--	2 Ω	Intertek

Cable:

Description	Model No.	Cable length/type	Supplied by
1 st Electric wire	--	0.8 m(unshielded)	Intertek
2 nd Electric wire	--	0.8 m(unshielded)	Intertek

Remark: the WPT client was one of typical client devices, it's selected such that the EUT was fully exercised at maximum power from its transmitter. It will not be sold together.

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above evaluated respectively

Pretest mode	Description	
Standby Mode	kept transmitting continuously	
Charging Mode	CH: Low	WPT client is full load power mode, half full load power mode and saturated charging mode respectively, keep transmitting continuously.
	CH: Middle	
	CH: High	

TEST REPORT

3.0 EMF TEST

3.1 Standard Requirement

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.1m normally can be maintained between the user and the device.

(a) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	F/300	6
1500-100000	--	--	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	F/1500	30
1500-100000	--	--	1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

TEST REPORT

3.2 Test Data

Input Voltage: 125V/60Hz
Ambient Condition: 24°C, 50%RH

Test distance: 15 cm surrounding the device, and 20 cm away from the surface from the coil.

H-Filed Strength:

Test Position	Probe Measure Result (A/m)			50% Limit (A/m)	Limit (A/m)
	Full load power mode	Half full load power mode	Saturated charging mode		
Side 1	0.041	0.039	0.037	0.815	1.63
Side 2	0.040	0.037	0.036	0.815	1.63
Side 3	0.042	0.036	0.035	0.815	1.63
Side 4	0.041	0.036	0.032	0.815	1.63
Top	0.046	0.040	0.040	0.815	1.63

TEST REPORT

4.0 Test Equipment List

Equip. No.	Equipment	Model	Manufacturer	Cal. date	Due date
EM007-03	Exposure Level Tester	ELT-400	NARDA	28/02/2021	27/02/2022

*****End of the test report*****