



Test report No:
 22C0151R-RF-US-P20V01

FCC Exposure TEST REPORT

Product Name	KEY ASM-DR LK & IGN LK
Trademark	SGMW
Model and /or type reference	WS068G1-8000
FCC ID	2AVYXWS068G18000
Applicant's name / address	SAIC GM WULING AUTOMOBILE COMPANY LIMITED 18th,Hexi Road,Liuzhou City, Guangxi Zhuang Autonomous Region, China
Test method requested, standard	FCC 47CFR §2.1093
Verdict Summary	IN COMPLIANCE
Documented by (name / position & signature)	Tim Cao/ Project Engineer <i>Tim Cao</i>
Approved by (name / position & signature)	Jack Zhang/ Manager <i>Jack Zhang</i>
Date of issue	2023-07-03
Report Version	V1.1
Report template No	Template_FCC-MPE-RF-V1.0

INDEX

	page
Competences and Guarantees.....	3
General conditions.....	3
Environmental conditions.....	3
Possible test case verdicts.....	4
Abbreviations.....	4
Document History.....	5
Remarks and Comments.....	5
1 General Information.....	6
1.1 General Description of the Item(s).....	6
1.2 Antenna Information.....	7
2 RF Exposure Evaluation.....	8
2.1 Limits.....	8
2.2 Test Procedure.....	8
2.3 Test Result of RF Exposure Evaluation.....	9

COMPETENCES AND GUARANTEES

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

GENERAL CONDITIONS

Test Location	No. 99, Hongye Road, Suzhou Industrial Park Suzhou, 215006, P.R. China
Date(receive sample)	Dec. 08, 2022
Date (start test)	Dec. 20, 2022
Date (finish test)	Feb. 25, 2023

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.

ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

Ambient temperature	15 °C – 35 °C
Relative Humidity air	30% - 60%

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

POSSIBLE TEST CASE VERDICTS

Test case does not apply to test object	N/A
Test object does meet requirement	P (Pass) / PASS
Test object does not meet requirement	F (Fail) / FAIL
Not measured	N/M

ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

EUT	: Equipment Under Test
QP	: Quasi-Peak
CAV	: CISPR Average
AV	: Average
CDN	: Coupling Decoupling Network
SAC	: Semi-Anechoic Chamber
OATS	: Open Area Test Site
BW	: Bandwidth
AM	: Amplitude Modulation
PM	: Pulse Modulation
HCP	: Horizontal Coupling Plane
VCP	: Vertical Coupling Plane
U_N	: Nominal voltage
T_x	: Transmitter
R_x	: Receiver
N/A	: Not Applicable
N/M	: Not Measured

DOCUMENT HISTORY

Report No.	Version	Description	Issued Date
22C0151R-RF-US-P20V01	V1.0	Initial issue of report.	2023-05-31
22C0151R-RF-US-P20V01	V1.1	Since the product is a handheld device and changed to a low-power exemption method, V1.0 has expired.	2023-07-03

REMARKS AND COMMENTS

1. The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s). These test results on a sample of the device are for the purpose of demonstrating Compliance with FCC 47CFR §2.1093.
2. The measurement result is considered in conformance with the requirement if it is within the prescribed limit, It is not necessary to account the uncertainty associated with the measurement result, unless the specification, standard or customer have special requirements
3. The test results relate only to the samples tested.
4. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification (Suzhou) Co., Ltd.
5. This report will not be used for social proof function in China market.
7. DEKRA declines any responsibility with the following test data provided by customer that may affect the validity of result:
 - Chapter 1.1 General Description of the Item(s);
 - Chapter 1.2 Antenna Information;

1 GENERAL INFORMATION

1.1 General Description of the Item(s)

Product Name..... :	KEY ASM-DR LK & IGN LK
Model No. :	WS068G1-8000
FCC ID :	2AVYXWS068G18000
Software Version :	F12101D0
Hardware Version :	F03H00G015
Manufacturer :	ZHEJIANG WANCHAO ELECTRIC CO.,LTD
Manufacturer Address..... :	No. 79, Quren Road,Nanpian Industrial Park, Quxi Town, Ouhai District, Wenzhou City, Zhejiang Province,P.R.China
Factory :	ZHEJIANG WANCHAO ELECTRIC CO.,LTD
Factory Address..... :	No. 79, Quren Road,Nanpian Industrial Park, Quxi Town, Ouhai District, Wenzhou City, Zhejiang Province,P.R.China

Wireless specification :	N/A
Operating frequency range(s)..... :	434.4MHz
Type of Modulation :	FSK
Number of channel..... :	1

Rated power supply :	Voltage and Frequency	
	<input type="checkbox"/>	AC: 220 - 240 V, 50/60 Hz
	<input type="checkbox"/>	AC: 100 - 240 V, 50/60 Hz
	<input type="checkbox"/>	DC: 3 Vdc
	<input checked="" type="checkbox"/>	Battery: 3 V
	<input type="checkbox"/>	Adapter:
Brand of adapter..... :	N/A	
Adapter model :	N/A	
Mounting position..... :	<input type="checkbox"/>	Table top equipment
	<input type="checkbox"/>	Wall/Ceiling mounted equipment
	<input type="checkbox"/>	Floor standing equipment
	<input type="checkbox"/>	Hand-held equipment
	<input checked="" type="checkbox"/>	Other:Vehicle-Munted quipent

1.2 Antenna Information

Antenna Delivery	<input checked="" type="checkbox"/>	1TX + 1RX	
	<input type="checkbox"/>	2TX + 2RX	
	<input type="checkbox"/>	Others:.....	
Antenna technology	<input checked="" type="checkbox"/>	SISO	
	<input type="checkbox"/>	MIMO	<input type="checkbox"/> CDD
			<input type="checkbox"/> Beam-forming
Antenna Type	<input type="checkbox"/>	External	<input type="checkbox"/> Dipole
			<input type="checkbox"/> Sectorized
			<input checked="" type="checkbox"/>
	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> PCB	
	<input type="checkbox"/>	<input type="checkbox"/> Metal Monopole Antenna	
	<input type="checkbox"/>	<input type="checkbox"/> Ceramic chip	
	<input type="checkbox"/>	<input type="checkbox"/> Others:.....	

2 RF EXPOSURE EVALUATION

2.1 Limits

According to § 1.1307(b)(3)(i)(A)

The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

§ 1.1307(b)(3)(ii)(A)

The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those is paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A)

$P_i = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

2.3 Test Result of RF Exposure Evaluation

Product	:	KEY ASM-DR LK & IGN LK
Test Item	:	RF Exposure Evaluation
Test Site	:	AC-6

Power Density:

Predication of MPE limit at a given distance

Equation from page 19 of OET Bulletin 65, Edition 97-01

$$S = \frac{EIRP}{4\pi R^2}$$

where:

S = power density (in appropriate units, e.g. mW/cm²)

EIRP = equivalent (or effective) isotropically radiated power (in appropriate units, e.g., mW)

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

$$EIRP = p_t \times g_t = (E \times d)^2/30$$

where:

p_t = transmitter output power in watts,

g_t = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- 10^{((dBuV/m)/20)}/10⁶,

d = measurement distance in meters (m)--- 3m.

Field strength = 79.10 dBuV/m @3m

So EIRP = (E x d)²/30= {[10^(79.10/20)/10⁶x3]²/30}x1000mW
 = 0.03mW
 = -15.23 dBm

The tune-up power is 0.5 dB, so the maximum power we used to calculate RF exposure is -14.73 dBm.

Frequency Range (MHz)	Maximum Power (dBuV/m)	EIRP (dBm)	ERP (dBm)	ERP (mW)	Limit (mW)	Verdict
434.4	79.10	-14.73	-16.88	0.021	1	SAR test not required

Conclusion: 434.4MHz SAR was not required.

The End