


Test report No:  
22C0151R-RF-US-P06V01

## FCC TEST REPORT

Product Name	KEY ASM-DR LK & IGN LK
Trademark	SGMW
Model and /or type reference	WS068G1-8000
FCC ID	2AVYXWS068G18000
Applicant's name / address	SAIC GM WULING AUTOMOBILE COMPANY LIMITED 18th,Hexi Road,Liuzhou City, Guangxi Zhuang Autonomous Region, China
Test method requested, standard	CFR 47, FCC Part 15 C ANSI C63.10: 2013
Verdict Summary	IN COMPLIANCE
Tested by (name / position & signature)	Tim Cao/ Project Engineer 
Approved by (name / position & signature)	Jack Zhang/ Manager 
Date of issue	2023-07-03
Report Version	V1.1
Report template No	Template_FCC 15.231-RF-V1.0

## INDEX

	page
General conditions .....	4
Environmental conditions .....	4
Possible test case verdicts .....	5
Abbreviations .....	5
Document History .....	6
Remarks and Comments.....	6
Used Equipment .....	7
Uncertainty .....	8
1 General Information.....	9
1.1 General Description of the Item(s) .....	9
1.2 Antenna Information .....	10
1.3 Channel List .....	11
2 Description of Test Setup .....	12
2.1 Operating mode(s) used for tests.....	12
2.2 Auxiliary equipment / Test software for the EUT.....	12
2.3 Test Configuration / Block diagram used for tests .....	13
2.4 Testing process.....	13
3 Verdict summary section .....	14
3.1 Standards.....	14
3.2 Deviation(s) from the Standard(s) / Test Specification(s).....	14
3.3 Overview of results.....	15
3.4 Test Facility.....	16
4 Test Results.....	17
4.1 Field strength of fundamental .....	17
4.1.1 Limit .....	17
4.1.2 Test Setup.....	18
4.1.3 Test Procedure.....	18
4.2 Field strength of spurious emissions .....	19
4.2.1 Limit .....	19
4.2.2 Test Setup.....	21
4.2.3 Test Procedure.....	21
4.3 DTS Bandwidth .....	22
4.3.1 Limit .....	22
4.3.2 Test Setup.....	22

---

4.3.3 Test Procedure.....	22
4.4 Duration Time.....	23
4.4.1 Limit .....	23
4.4.2 Test Setup.....	23
4.4.3 Test Procedure.....	23
5 Test setup photo and EUT Photo.....	24
6 Appendix A-TEST DATA: Field strength of fundamental .....	25
7 Appendix B-TEST DATA: Field strength of spurious emissions.....	26
8 Appendix C-TEST DATA: 20dB Bandwidth.....	30
9 Appendix D-TEST DATA: Duration Time .....	31

## COMPETENCES AND GUARANTEES

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

**IMPORTANT:** No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

## GENERAL CONDITIONS

Test Location	No. 99, Hongye Road, Suzhou Industrial Park Suzhou, 215006, P.R. China
Date(receive sample)	Dec. 08, 2022
Date (start test)	Dec. 20, 2022
Date (finish test)	Feb. 25, 2023

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.

## ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

Ambient temperature	15 °C – 35 °C
Relative Humidity air	30% - 60%

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

## POSSIBLE TEST CASE VERDICTS

Test case does not apply to test object	N/A
Test object does meet requirement	P (Pass) / PASS
Test object does not meet requirement	F (Fail) / FAIL
Not measured	N/M

## ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

EUT	: Equipment Under Test
QP	: Quasi-Peak
CAV	: CISPR Average
AV	: Average
CDN	: Coupling Decoupling Network
SAC	: Semi-Anechoic Chamber
OATS	: Open Area Test Site
BW	: Bandwidth
AM	: Amplitude Modulation
PM	: Pulse Modulation
HCP	: Horizontal Coupling Plane
VCP	: Vertical Coupling Plane
$U_N$	: Nominal voltage
$T_x$	: Transmitter
$R_x$	: Receiver
N/A	: Not Applicable
N/M	: Not Measured

## DOCUMENT HISTORY

Report No.	Version	Description	Issued Date
22C0151R-RF-US-P06V01	V1.0	Initial issue of report.	2023-05-31
22C0151R-RF-US-P06V01	V1.1	Modify section 4.3.2/4.4.2 test setup diagram, and modify harmonic limits, V1.0 has expired.	2023-07-03

## REMARKS AND COMMENTS

1. The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).
2. These test results on a sample of the device are for the purpose of demonstrating Compliance with CFR 47, FCC Part 15 C, ANSI C63.10:2013.
3. The measurement result is considered in conformance with the requirement if it is within the prescribed limit, It is not necessary to account the uncertainty associated with the measurement result.
4. The test results presented in this report relate only to the object tested.
5. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification (Suzhou) Co., Ltd.
6. This report will not be used for social proof function in China market.
7. DEKRA declines any responsibility with the following test data provided by customer that may affect the validity of result:
  - Chapter 1.1 General Description of the Item(s);
  - Chapter 1.2 Antenna Information
  - Chapter 1.3 Channel List.

## USED EQUIPMENT

### Radiated Emission(30MHz-1GHz) / AC2

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date
EMI Test Receiver	R&S	ESCI	100573	2022.09.17	2023.09.16
Loop Antenna	R&S	HFH2-Z2	833799/003	2022.04.15	2023.04.14
Bilog Antenna	Teseq GmbH	CBL6112D	27613	2022.08.28	2023.08.27
Temperature/Humidity Meter	RTS	RTS-8S	AC3-TH	2022.07.07	2023.07.06
Coaxial Cable	Huber+Suhner	RG 214	AC3-C	2022.03.31	2023.03.30
Dekra test software	Dekra	-	-	-	-

### Radiated Emission(1GHz-40GHz) / AC5

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date
EXA Spectrum Analyzer	Keysight	N9010A	MY48030494	2022.12.08	2023.12.07
Pre-Amplifier	SKET	LNPA_0118G-45	SK2021090101	2022.07.15	2023.07.14
Preamplifier	CHENGYI	EMC184045SE	980263	2022.05.21	2023.05.20
DRG Horn	ETS-Lindgren	3117	00167055	2022.08.29	2023.08.28
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	294	2022.05.19	2023.05.18
Loop Antenna	R&S	HFH2-Z2	833799/003	2022.04.15	2023.04.14
Temperature/Humidity Meter	RTS	RTS-8S	AC5-TH	2022.07.07	2023.07.06
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C1	2022.03.31	2023.03.30
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C2	2022.03.31	2023.03.30
Coaxial Cable	Huber+Suhner	SUCOFLEX 102	AC5-C3	2022.03.31	2023.03.30
Dekra test software	Dekra	-	-	-	-

## UNCERTAINTY

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%. The Uncertainties is compline with standard required as below.

Test item	Uncertainty
Radiated Emission(30MHz~1GHz)	Horizontal: 30MHz~200MHz: 3.50 dB 300MHz~1GHz: 3.60 dB Vertical: 30MHz~200MHz: 3.60 dB 300MHz~1GHz: 3.50 dB
Radiated Emission(1GHz~26.5GHz)	Horizontal: 1GHz~18GHz: 5.00 dB Vertical: 1GHz~18GHz: 4.80 dB
Occupied Bandwidth	±1kHz
Time	N/A

## 1 GENERAL INFORMATION

### 1.1 General Description of the Item(s)

Product Name.....:	KEY ASM-DR LK & IGN LK
Model No. ....:	WS068G1-8000
FCC ID .....	2AVYXWS068G18000
Software Version.....:	F12101D0
Hardware Version .....	F03H00G015
Manufacturter.....:	ZHEJIANG WANCHAOW ELECTRIC CO.,LTD
Manufacturer Address.....:	No. 79, Quren Road,Nanpien Industrial Park, Quxi Town, Ouhai District, Wenzhou City, Zhejiang Province,P.R.China
Factory .....	ZHEJIANG WANCHAOW ELECTRIC CO.,LTD
Factory Address.....:	No. 79, Quren Road,Nanpien Industrial Park, Quxi Town, Ouhai District, Wenzhou City, Zhejiang Province,P.R.China

Wireless specificfition.....:	N/A
Operating frequency range(s).....:	434.4MHz
Type of Modulation.....:	FSK
Number of channel.....:	1

Rated power supply .....	Voltage and Frequency	
	<input type="checkbox"/>	AC: 220 - 240 V, 50/60 Hz
	<input type="checkbox"/>	AC: 100 - 240 V, 50/60 Hz
	<input type="checkbox"/>	DC: 3 Vdc
	<input checked="" type="checkbox"/>	Battery: 3 V
	<input type="checkbox"/>	Adapter: .....
Brand of adapter .....	N/A	
Adapter model .....	N/A	
Mounting position.....:	<input type="checkbox"/> Table top equipment <input type="checkbox"/> Wall/Ceiling mounted equipment <input type="checkbox"/> Floor standing equipment <input type="checkbox"/> Hand-held equipment <input checked="" type="checkbox"/> Other:Vehicle-Munted quipent	

## 1.2 Antenna Information

Antenna Delivery .....	<input checked="" type="checkbox"/>	1TX + 1RX
	<input type="checkbox"/>	2TX + 2RX
	<input type="checkbox"/>	Others:.....
Antenna technology.....	<input checked="" type="checkbox"/>	SISO
	<input type="checkbox"/>	MIMO
	<input type="checkbox"/>	CDD
	<input type="checkbox"/>	Beam-forming
Antenna Type.....	<input type="checkbox"/>	External
	<input type="checkbox"/>	Dipole
	<input type="checkbox"/>	Sectorized
	<input checked="" type="checkbox"/>	Internal
	<input type="checkbox"/>	FPC
	<input checked="" type="checkbox"/>	PCB
	<input type="checkbox"/>	Metal Monopole Antenna
	<input type="checkbox"/>	Ceramic chip
	<input type="checkbox"/>	Others.....

### 1.3 Channel List

SRD Working Frequency							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
01	434.4 MHz	--	--	--	--	--	--

Note: The general description of the Item(s) and channel list in clause 1 are provided and confirmed by the client.

## 2 DESCRIPTION OF TEST SETUP

### 2.1 Operating mode(s) used for tests

During the tests the following operating mode(s) has(have) been used.


Test Mode	Mode1: Transmit
-----------	-----------------

### 2.2 Auxiliary equipment / Test software for the EUT

Auxiliary equipment	Type / Version	Manufacturer	Supplied by
Key Fob Test Bench	N/A	UAES	N/A
Computer	N/A	Lenovo	N/A
Software	Type / Version	Manufacturer	Supplied by
EMC-PKE	N/A	UAES	N/A

## 2.3 Test Configuration / Block diagram used for tests

Test setup Diagram- Radiated Emission



## 2.4 Testing process

1	Setup the EUT shown in Section 2.3.
2	Execute the [EMC-PKE ] on the notebook.
3	Configure the test mode, the test channel, and the data rate.
4	Verify that the EUT works properly.

### 3 VERDICT SUMMARY SECTION

This chapter presents an overview of standards and results. Refer to the next chapters for details of measured test results and applied test levels.

#### 3.1 Standards

Standard	Year	Description
FCC CFR Title 47 Part 15 Subpart C Section 15.231	2021	Periodic operation in the band 40.66-40.70 MHz and above 70 MHz.
ANSI C63.10	2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

#### 3.2 Deviation(s) from the Standard(s) / Test Specification(s)

The following deviation(s) was / were made from the published requirements of the listed standards: N/A.

(Please define the deviations from the standard(s) if applicable)

### 3.3 Overview of results

Requirement – Test case	Basic standard(s)	Verdict	Remark
Field strength of fundamental	FCC 15.231(b)(1)	PASS	Test data please refer to <b>Appendix A</b>
Field strength of spurious emissions	FCC 15.231(b)(1)(2),FCC 15.209	PASS	Test data please refer to <b>Appendix B</b>
20dB Bandwidth	FCC 15.231(c)	PASS	Test data please refer to <b>Appendix C</b>
Duration Time	FCC 15.231(a)(1)	PASS	Test data please refer to <b>Appendix D</b>

### **3.4 Test Facility**

<b>USA</b>	<b>:</b>	<b>FCC Designation Number: CN1199</b>
------------	----------	---------------------------------------

## 4 TEST RESULTS

<b>4.1 Field strength of fundamental</b>	<b>VERDICT: PASS</b>
--	----------------------

<b>4.1.1 Limit</b>		
<b>Standard</b>	FCC Part 15 Subpart C Paragraph 15.231	
Restricted Bands of operation for FCC		
Fundamental frequency (MHz)	Field strength of fundamental ( $\mu$ V/m)	Field strength of fundamental (dB $\mu$ V/m)
40.66-40.70	2250	67.04
70-130	1250	61.93
130-174	1250-3750	61.93-71.48 <sup>1)</sup>
174-260	3750	71.48
260-470	3750-12500	71.48-81.93 <sup>1)</sup>
Above 470	12500	81.93

Note <sup>1)</sup> : Linear interpolations

The field intensity in micro-volts per meter can then be determined by the following equation:  $FI(V/m) = 10 \cdot f_{EUT} \cdot (dBV/m) / 20$ . The FCC specified emission limits were calculated according the EUT operating frequency and obtained by following linear interpolation equations:

For fundamental frequency:

$f_{EUT}$  : EUT Operating Frequency Emission Limit (V/m)

$$= [f_{EUT}(MHz) - 260(MHz)] \times \{ [12500(V/m) - 3750(V/m)] / [470(MHz) - 260(MHz)] \} + 3750(V/m)$$

Other emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20 dB below the level of the fundamental or comply with the radiated emissions limits specified in section 15.209 limit in the table below has to be followed.


Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission level (dBuV/m)=20log Emission level ( $\mu$ V/m)


Fundamental frequency	Field strength of Fundamental
434.4 MHz	AV: 80.84 dBuV/m at 3m distance
	PK: 100.84 dBuV/m at 3m distance

#### 4.1.2 Test Setup

30MHz-1GHz Test Setup:



Above 1GHz Test Setup:



#### 4.1.3 Test Procedure

	References Rule	Chapter	Description
<input checked="" type="checkbox"/>	ANSI C63.10	11.12	Emissions in restricted frequency bands
<input checked="" type="checkbox"/>	ANSI C63.10	11.12.1	Radiated emission measurements
<input checked="" type="checkbox"/>	ANSI C63.10	11.12.2.7	Radiated spurious emission test
	<input checked="" type="checkbox"/> ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
	<input checked="" type="checkbox"/> ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
	<input checked="" type="checkbox"/> ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz

**4.2 Field strength of spurious emissions****VERDICT: PASS****4.2.1 Limit**

Standard	FCC 15.231(b)(1)(2), FCC 15.209	
FCC 15.231		
Fundamental frequency (MHz)	Field strength of spurious emission ( $\mu$ V/m)	Field strength of spurious emission (dB $\mu$ V/m)
40.66-40.70	225	47.04
70-130	125	41.93
130-174	125-375	41.93-51.48 <small>(Note 1)</small>
174-260	375	51.48
260-470	375-1250	51.48-61.93 <small>(Note 1)</small>
Above 470	1250	61.93

Note 1: Linear interpolations

The above field strength limits are specified at a distance of 3 meters. The tighter limits apply at the band edges.

Intentional radiators operating under the provisions of this section shall demonstrate compliance with the limits on the field strength of emissions, as shown in the above table, based on the average value of the measured emissions. As an alternative, compliance with the limits in the above table may be based on the use of measurement instrumentation with a CISPR quasi-peak detector. The specific method of measurement employed shall be specified in the application for equipment authorization. If average emission measurements are employed, the provisions in §15.35 for averaging pulsed emissions and for limiting peak emissions apply. Further, compliance with the provisions of §15.205 shall be demonstrated using the measurement instrumentation specified in that section.

The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in §15.209, whichever limit permits a higher field strength.

## FCC 15.209


Frequency (MHz)	Field strength ( $\mu$ V/m)	Field strength (dB $\mu$ V/m)	Measurement distance (m)
0.009 - 0.49	2400/F(kHz)	48.5 – 13.8	300(Note 1)
0.49 - 1.705	24000/F(kHz)	33.8 - 23	30(Note 1)
1.705 - 30	30	29.5	30(Note 1)
30 - 88	100	40	3(Note 2)
88-216	150	43.5	3(Note 2)
216 - 960	200	46	3(Note 2)
Above 960	500	54	3(Note 2)

Note 2: At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).


Note 3: At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

#### 4.2.2 Test Setup

30MHz-1GHz Test Setup:



Above 1GHz Test Setup:



#### 4.2.3 Test Procedure

	References Rule	Chapter	Description
<input checked="" type="checkbox"/>	ANSI C63.10	11.12	Emissions in restricted frequency bands
<input checked="" type="checkbox"/>	ANSI C63.10	11.12.1	Radiated emission measurements
<input checked="" type="checkbox"/>	ANSI C63.10	11.12.2.7	Radiated spurious emission test
	<input checked="" type="checkbox"/> ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
	<input checked="" type="checkbox"/> ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
	<input checked="" type="checkbox"/> ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz

### 4.3 DTS Bandwidth


**VERDICT: PASS**

#### 4.3.1 Limit

<b>Standard</b>	FCC 15.231(c)
-----------------	---------------

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

#### 4.3.2 Test Setup




#### 4.3.3 Test Procedure

	Reference Rule	Chapter	Description
<input checked="" type="checkbox"/>	ANSI C63.10	6.9	Occupied bandwidth tests
<input checked="" type="checkbox"/>	ANSI C63.10	6.9.2	Occupied bandwidth—relative measurement procedure
	<input type="checkbox"/> ANSI C63.10	6.9.3	Occupied bandwidth—power bandwidth (99%) measurement procedure

**4.4 Duration Time****VERDICT: PASS****4.4.1 Limit****Standard**

FCC Part 15 Subpart C Paragraph 15.247 (b)(3)

(1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

**4.4.2 Test Setup****4.4.3 Test Procedure**

1. According to the follow Test-setup, keep the relative position between the artificial antenna and the EUT.
2. Set the EUT to proper test channel.
3. Single scan the transmission, and read the transmission time.

## 5 TEST SETUP PHOTO AND EUT PHOTO

Remark: The test setup photo and EUT Photo please see appendix.

## 6 APPENDIX A-TEST DATA: FIELD STRENGTH OF FUNDAMENTAL

Frequency (MHz)	Measure Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Type
434.4(X Axis)	79.096	100.84	-21.74	Horizontal	PK
434.4(X Axis)	77.953	100.84	-22.89	Vertical	PK


Frequency (MHz)	Measure Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Type
434.4(X Axis)	79.096	80.84	-1.74	Horizontal	AV
434.4(X Axis)	77.953	80.84	-2.89	Vertical	AV

Note 1:

We have evaluated three orthogonal positions (X , Y , Z ) and the position with the highest emission level(X Axis) was recorded and shown in the report.


## 7 APPENDIX B-TEST DATA: FIELD STRENGTH OF SPURIOUS EMISSIONS

Profile: 22C0151R	Page No.: 1
Engineer: Yuliu	
Site: AC5	Time: 2023/03/21 - 19:52
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)2022	Polarity: Horizontal
EUT: KEY ASM-DR LK & IGN LK	Power: Battery: 3 V
Note: Mode 1 : Transmit at 434.4MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		3910.000	45.657	62.164	-28.343	74.000	-16.508	PK
2		4345.000	51.501	67.310	-22.499	74.000	-15.810	PK
3		4780.000	51.524	66.568	-22.476	74.000	-15.044	PK
4		5205.480	26.729	40.640	-27.271	54.000	-13.912	AV
5	*	5215.000	58.153	72.149	-15.847	74.000	-13.996	PK
6		5650.000	52.747	65.239	-21.253	74.000	-12.492	PK

Profile: 22C0151R	Page No.: 2
Engineer: Yuliu	
Site: AC5	Time: 2023/03/21 - 19:52
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)2022	Polarity: Vertical
EUT: KEY ASM-DR LK & IGN LK	Power: Battery: 3 V
Note: Mode 1 : Transmit at 434.4MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		3910.000	51.408	67.915	-22.592	74.000	-16.508	PK
2		4340.400	27.945	43.760	-26.055	54.000	-15.815	AV
3		4345.000	58.148	73.957	-15.852	74.000	-15.810	PK
4		4771.200	29.141	44.201	-24.859	54.000	-15.060	AV
5		4780.000	59.388	74.432	-14.612	74.000	-15.044	PK
6		5205.520	26.768	40.680	-27.232	54.000	-13.912	AV
7	*	5215.000	59.473	73.469	-14.527	74.000	-13.996	PK
8		5640.120	25.689	38.260	-28.311	54.000	-12.571	AV
9		5650.000	55.945	68.437	-18.055	74.000	-12.492	PK

Profile: 22C0151R	Page No.: 1
Engineer: Yuliu	
Site: AC2	Time: 2023/03/22 - 21:31
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: AC2_3M(30-1000M)	Polarity: Horizontal
EUT: KEY ASM-DR LK & IGN LK	Power: Battery: 3 V
Note: Mode 1 : Transmit at 434.4MHz	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		434.446	79.096	52.850	-21.74	100.84	26.246	QP
2		868.920	35.075	2.240	-45.76	80.84	32.834	QP

Profile: 22C0151R	Page No.: 2
Engineer: Yuliu	
Site: AC2	Time: 2023/03/22 - 21:33
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: AC2_3M(30-1000M)	Polarity: Vertical
EUT: KEY ASM-DR LK & IGN LK	Power: Battery: 3 V
Note: Mode 1 : Transmit at 434.4MHz	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		434.410	77.953	51.850	-22.89	100.84	26.103	QP
2		870.126	35.172	2.300	-45.66	80.84	32.872	QP

## Note:

1. Measured Level = Reading Level + Factor.
2. The test frequency range, 9kHz~30MHz, both of the worst case are at least 20dB below the limits, therefore no data appear in the report.
3. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.
4. As the radiated emission was performed, so conducted emission was not tested.
5. We have evaluated three orthogonal positions (X , Y , Z ) and the position with the highest emission level(X Axis) was recorded and shown in the report.


## 8 APPENDIX C-TEST DATA: 20DB BANDWIDTH

Mode	CH.	Test Freq. (MHz)	20dB Occupied Bandwidth (kHz)	Limit (kHz)	Result
1	00	434.4	98.35	Within band	Pass
 <p>Agilent Spectrum Analyzer - Occupied BW</p> <p>RF   50 Ω AC   SENSE:INT   ALIGN:AUTO   03:57:25 PM Mar 22, 2023</p> <p>Mkr2 434.47004 MHz -50.030 dBm</p> <p>10 dB/div Ref -4.00 dBm</p> <p>Log</p> <p>-14.0 -24.0 -34.0 -44.0 -54.0 -64.0 -74.0 -84.0 -94.0</p> <p>Center 434.4 MHz #Res BW 3 kHz #VBW 10 kHz Span 200 kHz Sweep 27.27 ms</p> <p>Occupied Bandwidth 91.891 kHz</p> <p>Transmit Freq Error 8.300 kHz OBW Power 99.00 %</p> <p>x dB Bandwidth 98.35 kHz x dB -20.00 dB</p> <p>MSG STATUS</p>					

## 9 APPENDIX D-TEST DATA: DURATION TIME

Frequency (MHz)	Duration Time (S)	Limit (S)	Result
434.4	0.255	<5.0	Pass

**Agilent Spectrum Analyzer - Swept SA**



The screenshot shows a spectrum analysis plot with the following parameters:

- RF:** 50 Ω AC
- SENSE:INT:** ALIGN AUTO 04:15:25 PM Mar 22, 2023
- Delta Marker:** ΔMkr1 255.0 ms -0.09 dB
- Y-axis:** 10 dB/div, Ref 0.00 dBm, Log scale from -10 to -90 dB
- X-axis:** Center 434.400000 MHz, Res BW 1.0 MHz, #VBW 3.0 MHz, Sweep 5.000 s (1001 pts), Span 0 Hz
- Marker Labels:** X2, 1Δ2
- Configuration Panel:**
  - Frequency: Auto Tune
  - Center Freq: 434.400000 MHz
  - Start Freq: 434.400000 MHz
  - Stop Freq: 434.400000 MHz
  - CF Step: 1.000000 MHz, Auto
  - Freq Offset: 0 Hz

The End