

Report No.: FCS202005001W01

FCC RF Exposure

EUT Description: Video Controller Model No.: iMGS-MVT04T21 FCC ID: 2AVZ8-MVT04T21

Equipment Type: Fixed apparatus

1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)			
(A) Limits for Occupational/Controlled Exposures							
0.3-3.0	614	1.63	*(100)	6			
3.0–30	1842/f	4.89/f	*(900/f ²)	6			
30–300	61.4	0.163	1.0	6			
300–1500			f/300	6			
1500-100,000			5	6			
	(B) Limits for General Population/Uncontrolled Exposure						
0.3-1.34	614	1.63	*(100)	30			
1.34–30	824/f	2.19/f	*(180/ f ²)	30			
30–300	27.5	0.073	0.2	30			
300–1500			f/1500	30			
1500-100,000			1.0	30			

F = frequency in MHz

Formula: Pd = (Pout*G)/($4* \pi *r^2$)

Where:

Pd = power density in mW/cm^2 ,

Pout = output power to antenna in mW;

G = gain of antenna in linear scale,

 $\pi = 3.14$:

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.



Report No.: FCS202005001W01

2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Test Result of RF Exposure Evaluation

	Output power	Antenna	Power Density	Limit	Result	
	(dBm/mW)	Gain(dBi)	at R=20cm	(mW/cm ²)		
			(mW/cm ²)			
802.11b	13.36/21.68	2.0	0.0068	1.0	Pass	
802.11g	11.04/12.71	2.0	0.0040	1.0	Pass	
802.11n(20MHz)	10.69/11.72	2.0	0.0037	1.0	Pass	
802.11n(40MHz)	10.36/10.86	2.0	0.0034	1.0	Pass	

Turn-up power			
Mode Peak power range(dBm)			
WIFI	10.00-15.00		

	Output power	Antenna	Power Density	Limit	Result
WIFI	(dBm/mW)	Gain(dBi)	at R=20cm	(mW/cm ²)	
			(mW/cm²)		
	15.00/31.62	2.0	0.0100	1.0	Pass

Conclusion: No SAR is required