



FCC TEST REPORT

FCC ID: 2AVZV-S1W05

Product	:	POS SYSTEM
Model Name	:	S1W05,S1W06,S1W07,S1W08,S1W05-X,S1W06-X,S1W07-X,S1W08-X ("X" can be represented 1~9)
Brand	:	CITAQ
Report No.	:	PTC24091003602E-FC05
Prepared for		
CITAQ CO., LTD		
9F&13F., Chuangye Bldg., Keji Middle Road., Hi-Tech Zone, Shantou., Guangdong		
Prepared by		
Precise Testing & Certification Co., Ltd.		
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.		



TEST RESULT CERTIFICATION

Applicant's name : CITAQ CO., LTD

Address : 9F&13F., Chuangye Bldg., Keji Middle Road., Hi-Tech Zone,
Shantou., Guangdong

Manufacture's name : CITAQ CO., LTD

Address : 9F&13F., Chuangye Bldg., Keji Middle Road., Hi-Tech Zone,
Shantou., Guangdong

Product name : POS SYSTEM

Model name : S1W05,S1W06,S1W07,S1W08,S1W05-X,S1W06-X,S1W07-X,S1W08-X ("X" can be represented 1~9)

Test procedure : FCC CFR47 Part 1.1307(b)(1)

Test Date : Sep. 29, 2024 to Oct. 21, 2024

Date of Issue : Oct. 21, 2024

Test Result : PASS

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink, appearing to read 'Jack Zhou'.

Jack Zhou / Engineer

Technical Manager:

A handwritten signature in black ink, appearing to read 'Simon Pu'.

Simon Pu / Manager



Contents

	Page
2 TEST SUMMARY	4
3 GENERAL INFORMATION	5
3.1 GENERAL DESCRIPTION OF E.U.T.	5
4 RF EXPOSURE	6
4.1 REQUIREMENTS	6
4.2 THE PROCEDURES / LIMIT	6
4.3 MPE CALCULATION METHOD	7
4.4 TEST RESULT	7



2 Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	15.247 (i)	PASS
Remark:		
N/A: Not Applicable		



3 General Information

3.1 General Description of E.U.T.

Product Name	:	POS SYSTEM
Model Name	:	S1W05
Additional model	:	S1W06,S1W07,S1W08,S1W05-X,S1W06-X,S1W07-X,S1W08-X ("X" can be represented 1~9)
Specification	:	Bluetooth BDR+EDR; Bluetooth BLE 802.11b/g/n HT20/HT40 802.11a/n HT20/HT40/ac20/ac40/ac80
Operation Frequency	:	2400-2480MHz for BT 2412-2462MHz for 802.11b/g/ n(HT20) 2422-2452MHz for 802.11 n(HT40) 5G Wifi: 5180-5240MHz 5.8G Wifi: 5745-5825MHz
Number of Channel	:	79 channels for BDR+EDR 40 channels For DTS 11 channels for 802.11b/g/ n(HT20) 7 channels for 802.11n(HT40) 4 channels for 802.11a/n20/ac20 5180-5240 MHz 5 channels for 802.11a/n20/ac20 5745MHz~5825MHz 2 channels for 802.11n40/ac40 5190-5230 MHz 2 channels for 802.11n40/ac40 5755MHz~5795MHz 1 channels for 802.11 ac80
Type of Modulation	:	GFSK, $\pi/4$ -DQPSK,8DPSK For DSS GFSK, For DTS DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n/a/ac
Antenna installation	:	FPC antenna
Antenna Gain	:	2.4G:1.95 dBi 5G:3.11 dBi
Power supply	:	Adapter: SOY-2400250-332-A Input: AC100-240V 50/60Hz 1.5A Output: DC 24V 2.5A
Hardware Version	:	N/A
Software Version	:	N/A



4 RF Exposure

Test Requirement : FCC Part 1.1307(b)(1)

Evaluation Method : KDB 447498 D01 General RF Exposure Guidance v06

4.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

4.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density



4.3 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2} \theta\phi$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

4.4 Test Result

Mode	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Tune up tolerance (dBm)	Max Tune Up Power (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)	Result
2480(3DH5)	1.57	9.09	9.09±1	10.2094	0.003182	1	Pass
2480(BLE_1 M)	1.57	8.67	8.67±1	9.2683	0.002889	1	Pass
2437(11N40S ISO)	1.57	13.25	13.25±1	26.6073	0.008293	1	Pass
5.2G	2.05	15.74	15.74±1	47.2063	0.019219	1	Pass
5.8G	2.05	12.28	12.28±1	21.2814	0.008664	1	Pass

Note:

1. Calculate in the worst-case mode.
2. Max. Tune Up Power is declared by manufacturer, and used to calculate.
3. WIFI and BT can't transmit simultaneously.

*******THE END REPORT*******