

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	ALARM SYSTEM
Model Name	X1, MK-X1, X1 Wi-Fi 2G PLUS, X1 Wi-Fi 3G PLUS, X1 2G PLUS, X1 3G PLUS
FCC ID	2AVZYX1

2. EVALUATION METHOD AND LIMIT

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (Minutes)
0.3 -- 1.34	614	1.63	(100)*	30
1.34 -- 30	824/f	2.19/f	(180/f ²)*	30
30 -- 300	27.5	0.073	0.2	30
300 -- 1500	--	--	f/1500	30
1500 -- 100,000	--	--	1.0	30

*Note:

1. f= Frequency in MHz * Plane-wave Equivalent Power Density
2. The averaging time for General Population/Uncontrolled exposure to fixed transmitters is not applicable for mobile and portable transmitters. See 47 CFR §§2.1091 and 2.1093 on source-based time-averaging requirement for mobile and portable transmitters.

$$S = PG / 4\pi R^2$$

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

A minimum test separation distance ≥ 20 cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits. The distance must be at least 20 cm and fully supported by the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of § 2.1091(d)(2). In cases where cable losses or other attenuations are applied to determine compliance, the most conservative operating configurations and exposure conditions must be evaluated.

WIFI: Antenna Gain=2.5dBi (Numeric 1.78), $\pi=3.14$

Frequency	Output Power	Output Power	Power Density	Power Density Limit
MHz	dBm	mW	mW/cm ²	mW/cm ²
2412	13.76	23.77	0.008	1

GSM&UMTS:

Test Mode	Output Power (dBm)	Output Power (mW)	Antenna Gain (dBi)	Antenna Gain (Linear)	Power Density (mW/cm2)	Limit (mW/cm2)
GPRS 850	26.88	487.53	1.52	1.42	0.138	0.56
PCS 1900	24.60	251.19	2.20	1.66	0.083	1.00
UMTS BAND V	23.82	240.99	1.90	1.55	0.074	0.56
UMTS Band II	21.52	141.91	2.30	1.70	0.048	1.00

433: Antenna Gain=3dBi (Numeric 2), $\pi=3.14$

Frequency	Output Power	Output Power	Power Density	Power Density Limit
MHz	dBm	mW	mW/cm ²	mW/cm ²
433.2	-21.73	0.0067	0.0000027	0.29





Note:

1. Only the worst case recorded.
2. Cellular network and WIFI don't work at the same time.
3. The WIFI and 433 can transmit simultaneously.

$$0.008/1+0.0000027/0.29=0.008<1$$

4. Cellular network of 2G and 433 can transmit simultaneously.

$$0.138/0.56+0.0000027/0.29=0.246<1$$

5. Cellular network of 3G and 433 can transmit simultaneously.

$$0.074/0.56+0.0000027/0.29=0.132<1$$



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118