FCC ID: 2AW22-AIRIAL

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]· $[\sqrt{f(GHZ)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- f(GHZ) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BR+EDR:

Antenna Type: FPC Antenna Antenna Gain: -2.99 dBi

| Modulation | Channel Freq. (GHz) | Conducte d power (dBm) | Conducted power (mW) | Tune-up power (dBm) | Max tune-up power (dBm) | Max tune-up power (mW) | Distance (mm) | Result calculation | 1g SAR Exclusion threshold | SAR test exclusion |
|---------------|---------------------------|------------------------------|----------------------|---------------------------|----------------------------------|---------------------------------|------------------|--------------------|----------------------------------|-----------------------|
| GFSK | 2.402 | 2.20 | 1.660 | 3±1 | 4.0 | 2.512 | <5 | 0.77860 | 3.00 | YES |
| | 2.441 | 4.11 | 2.576 | 4±1 | 5.0 | 3.162 | <5 | 0.98813 | 3.00 | YES |
| | 2.480 | 2.65 | 1.841 | 3±1 | 4.0 | 2.512 | <5 | 0.79114 | 3.00 | YES |
| π/4- DQPSK | 2.402 | 2.17 | 1.648 | 3±1 | 4.0 | 2.512 | <5 | 0.77860 | 3.00 | YES |
| | 2.441 | 3.99 | 2.506 | 3±1 | 4.0 | 2.512 | <5 | 0.78490 | 3.00 | YES |
| | 2.480 | 2.69 | 1.858 | 3±1 | 4.0 | 2.512 | <5 | 0.79114 | 3.00 | YES |
| 8DPSK | 2.402 | 2.13 | 1.633 | 3±1 | 4.0 | 2.512 | <5 | 0.77860 | 3.00 | YES |
| | 2.441 | 4.04 | 2.535 | 4±1 | 5.0 | 3.162 | <5 | 0.98813 | 3.00 | YES |
| | 2.480 | 2.71 | 1.866 | 3±1 | 4.0 | 2.512 | <5 | 0.79114 | 3.00 | YES |

Conclusion:

Signature:

For the max result: 0.98813≤ 3.0 for 1-g SAR, No SAR is required.

NAME AND TITLE (Please print or type): Alex /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126 P.R. China

Date: 2021-07-20