



FCC §15.247 (i), §2.1091 – RF Exposure

FCC ID:2AW2NID-DF10B

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: f is frequency in MHz

* = Power density limit is applicable at frequencies greater than 100 MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

* = Plane-wave equivalent power density



MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=0.2m

TEST RESULTS

Modulation	Channel Freq. (MHz)	Conduct ed power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Antenna Gain Numeric	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
802.11b	2.412	9.01	9±1	10.00	10.00	1.19	0.00237	1
	2.437	9.50	9±1	10.00	10.00	1.19	0.00237	1
	2.462	9.03	9±1	10.00	10.00	1.19	0.00237	1
802.11g	2.412	7.39	8±1	9.00	7.94	1.19	0.00188	1
	2.437	8.31	8±1	9.00	7.94	1.19	0.00188	1
	2.462	8.01	8±1	9.00	7.94	1.19	0.00188	1
802.11n20	2.412	6.86	7±1	8.00	6.31	1.19	0.00149	1
	2.437	7.51	7±1	8.00	6.31	1.19	0.00149	1
	2.462	7.46	7±1	8.00	6.31	1.19	0.00149	1
802.11n40	2.412	5.78	6±1	7.00	5.01	1.19	0.00119	1
	2.437	6.64	6±1	7.00	5.01	1.19	0.00119	1
	2.462	5.69	6±1	7.00	5.01	1.19	0.00119	1

Conclusion:

For the max result : $0.00237 \leq 1.0$, compliance with FCC's RF Exposure.

Summary: Since the ERP (effective radiated power) operated at < 1.5 GHz is less than 1.5 watts and > 1.5 GHz is less than 3 watts, the routine environmental evaluation is not required, and the MPE result calculated for this device complies with the MPE limit as specified in 47 CFR §1.1310.