



# MPE ESTIMATION

FCC ID: 2AW3Z-CIIRGB

## 1, Limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm <sup>2</sup> )	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

Note: F= Frequency in MHz

## 2, Estimation Result

Mode	Frequency (MHz)	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )
BLE	2402	3.237	3±1(4)	2.51	-0.58	0.87	0.00043

$$Pd = \frac{Pout * G}{4\pi r^2} ;$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report **HK2103090822-E**, antenna gain=-0.58dBi

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.00043 mW/cm<sup>2</sup> which is < 1.0mW/cm<sup>2</sup>, RF Exposure testing is not required.

-----The End-----