

RF Exposure evaluation

FCC ID: 2AW4A-EYEDASHAI

1. Reference

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

4. Antenna Information

EYEDASH AI can only use antennas certificated as follows provided by manufacturer;

Antenna No.	Model No. of antenna:	Type of antenna:	Gain of the antenna (Max.)	Frequency range:
2.4GWIFI	/	FPC ANT	3.0 dBi for 2400-2500MHz	
GSM/WCDMA/LTE	/	FPC ANT	GSM850:2.25dBi; GSM1900:1.54dBi; WCDMA BAND II:1.54dBi; WCDMA BAND VI:1.92dBi; WCDMA BAND V:2.25dBi; LTE BAND 2:1.54dBi; LTE BAND 4:1.95dBi; LTE BAND 5:2.25dBi; LTE BAND 7:2.82dBi; LTE BAND 12:3.02dBi; LTE BAND 13:4.18dBi; LTE BAND 25:1.54dBi; LTE BAND (814-824) 26:2.28dBi; LTE BAND (824-849) B26:2.25dBi; LTE BAND 38:2.01dBi; LTE BAND 41:2.85dBi;	

5. Manufacturing Tolerance

2.4GHz WIFI(Peak)

Frequency (MHz)	11b		
	2412	2437	2462
Target (dBm)	5.0	5.0	5.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
Frequency (MHz)	11g		
	2412	2437	2462
Target (dBm)	5.0	5.0	5.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
Frequency (MHz)	11n(HT20)		
	2412	2437	2462
Target (dBm)	5.0	5.0	5.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
Frequency (MHz)	11n(HT40)		
	2422	2437	2452
Target (dBm)	5.0	5.0	5.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

Contains ID:XMR201903EG25G

Operating Band	Max Conducted Average Output Power (dBm)	Max Tune-up
GSM 850	25.81	26.0
GSM 1900	22.81	23.0
WCDMA B2	25.0	25.5
WCDMA B4	25.0	25.5
WCDMA B5	25.0	25.5
LTE Band 2	25.0	25.5
LTE Band 4	25.0	25.5
LTE Band 5	25.0	25.5
LTE Band 7	25.0	25.5
LTE Band 12	25.0	25.5
LTE Band 13	25.0	25.5
LTE Band 25	25.0	25.5
LTE B26(814-824)	25.0	25.5
LTE B26(824-849)	25.0	25.5
LTE Band 38	25.0	25.5
LTE Band 41	25.0	25.5

6. Standalone MPE Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
2.4GWIFI	6.0	3.9811	3.0	1.9953	0.0016	1.0000
GSM 850	26.0	398.1072	2.25	1.6788	0.0106	0.5495
GSM 1900	23.0	199.5262	1.54	1.4256	0.0090	1.0000
WCDMA B2	25.5	354.8134	1.54	1.4256	0.0090	1.0000
WCDMA B4	25.5	354.8134	1.92	1.5560	0.0098	1.0000
WCDMA B5	25.5	354.8134	2.25	1.6788	0.0106	0.5509
LTE Band 2	25.5	354.8134	1.54	1.4256	0.0090	1.0000
LTE Band 4	25.5	354.8134	1.95	1.5668	0.0099	1.0000
LTE Band 5	25.5	354.8134	2.25	1.6788	0.0106	0.5498
LTE Band 7	25.5	354.8134	2.82	1.9143	0.0120	1.0000
LTE Band 12	25.5	354.8134	3.02	2.0045	0.0126	0.4665
LTE Band 13	25.5	354.8134	4.18	2.6182	0.0165	0.5197
LTE Band 25	25.5	354.8134	1.54	1.4256	0.0090	1.0000
LTE B26(814-824)	25.5	354.8134	2.28	1.6904	0.0106	0.5431
LTE B26(824-849)	25.5	354.8134	2.25	1.6788	0.0106	0.5498
LTE Band 38	25.5	354.8134	2.01	1.5885	0.0100	1.0000
LTE Band 41	25.5	354.8134	2.85	1.9275	0.0121	1.0000

Remark:

1. Output power (Peak) including turn-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer.

7. simultaneous MPE Result

2.4GWIFI MPE (Ratio)	LTE B13 MPE (Ratio)	simultaneous MPE (Ratio)	MPE Limits (Ratio)
0.0016	0.0317	0.0333	1.0000

8. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----