

## **AES-CELLIOT-AVT9152MOD**

### **Cellular IoT Module with BLE**

## FEATURES

### Cellular IoT (Nordic nRF9160)

- 3GPP R13 Cat-M1 & NB1 compliant
- 3GPP R14 NB1 & NB2 compliant
- Output power: -40dBm to 23 dBm
- -108 dBm sensitivity (LTE-M)
- -114 dBm sensitivity (CAT-NB1/NB2)
- B3, B4, B13, B20 (Cat-M1)
- B3, B20 (NB1)
- GPS antenna port for active/passive antenna
- ARM® Cortex® -M33
- ARM® TrustZone®
- IPv4, IPv6 stack
- 1 MB flash and 256 kB RAM
- Supports SIM or eSIM
- Up to 10 GPIOs
- Up to 4 ADC Inputs
- SPI
- I2S
- UART

### BLE (Nordic nRF52840)

- BT5.0
- Output power: -20dBm to +8dBm
- -95 dBm sensitivity (1Mbps BLE mode)

- On-board chip antenna for BLE
- ARM® Cortex®-M4 32-bit processor with FPU, 64 MHz
- ARM® TrustZone®
- 1 MB flash and 256 kB RAM
- NFC
- USB 2.0
- Up to 13 GPIOs
- Up to 4 ADC Inputs
- SPI
- I2S
- UART

### General

- 26 x 28 x 3 mm
- Operating voltage: 3.2 to 5V

## APPLICATIONS

- Logistic & asset tracking
- Vending machine
- POS terminal
- Smart building automation
- Medical devices
- Beacon based application


## 1. DESCRIPTION

This module supports IoT applications that require both NB-IoT and BLE connectivity by utilizing industry-leading low power devices from Nordic - nRF9160 and nRF52840.

It is specifically designed for direct connection to the battery as its power source. The on-board BLE antenna provides ease of development, while the NB-IoT antenna feed is pulled to the edge for maximum end product packaging flexibility. Options are available for either passive or active GPS antenna.

Both nRF9160 and nRF52840 come with ARM® processor and 1 MB flash, 256 kB RAM. GPIOs, ADCs, I2S, SPI and UARTs interfaces from both ICs are made available at the module's edge connectors.

The 2 ICs are interconnected with IOs for signaling. User has the flexibility of selecting either one of the IC to be the device Master.



## 2. PIN ASSIGNMENTS

### 2.1. Edge Connector

1	VSS	50
2	nRF52_P0.10/NFC2	49
3	nRF52_P0.09/NFC1	48
4	VSS	47
5	nRF52_P0.02/AIN0	46
6	nRF52_P0.03/AIN1	45
7	nRF52_SWDCLK	44
8	nRF52_SWDIO	43
9	nRF52_P0.18/nRST	42
10	VSS	41
11	nRF52_P0.04/AIN2	40
12	nRF52_P0.05/AIN3	39
13	nRF52_P0.19	38
14	+3V_OUT	37
15	VSS	36
16	MODULE_ON	35
17	nRF52_P0.21	34
18	nRF52_P0.22	
19	nRF52_P0.23	
20	nRF52_P0.24	
21	nRF52_P1.00	
22	nRF52_VBUS	
23	nRF52_D-	
24	nRF52_D+	
25	nRF91_P0.25	
26	nRF91_P0.24	
27	nRF91_P0.23	
28	nRF91_P0.22	
29	nRF91_P0.21	
30	nRF91_P0.20	
31	VSS	
32	VDD_SUPPLY	
33	VDD_SUPPLY	

**Pin Descriptions**


Pin Number	Pin Name	Pin Type	Description
1	VSS	GND	Ground
2	nRF52_P0.10/NFC2	DIO/AI	nRF52 General-purpose digital I/O/ NFC Antenna Input
3	nRF52_P0.09/NFC1	DIO/AI	nRF52 General-purpose digital I/O/ NFC Antenna Input
4	VSS	GND	Ground
5	nRF52_P0.02/AIN0	DIO/AI	nRF52 General-purpose digital I/O/ Analog Input
6	nRF52_P0.03/AIN1	DIO/AI	nRF52 General-purpose digital I/O/ Analog Input
7	nRF52_SWDCLK	DI	nRF52 Debug Port Clock
8	nRF52_SWDIO	DIO	nRF52 Debug Port Data
9	nRF52_P0.18/nRST	DIO/DI	nRF52 General-purpose digital I/O/ Reset Input (active low)
10	VSS	GND	Ground
11	nRF52_P0.04/AIN2	DIO/AI	nRF52 General-purpose digital I/O/ Analog Input
12	nRF52_P0.05/AIN3	DIO/AI	nRF52 General-purpose digital I/O/ Analog Input
13	nRF52_P0.19	DIO	nRF52 General-purpose digital I/O
14	+3V_OUT	PWR	+3V, 200mA power output from module
15	VSS	GND	Ground
16	MODULE_ON	DI	Module Power On Input. Connect to VDD_SUPPLY to turn on the module, VSS to turn off the module.
17	nRF52_P0.21	DIO	nRF52 General-purpose digital I/O
18	nRF52_P0.22	DIO	nRF52 General-purpose digital I/O
19	nRF52_P0.23	DIO	nRF52 General-purpose digital I/O/ Analog Input
20	nRF52_P0.24	DIO	nRF52 General-purpose digital I/O/ Analog Input
21	nRF52_P1.00	DIO	nRF52 General-purpose digital I/O/ Analog Input
22	nRF52_VBUS	PWR	nRF52 USB Port Power Input
23	nRF52_D-	USB	nRF52 USB negative port
24	nRF52_D+	USB	nRF52 USB positive port
25	nRF91_P0.25	DIO	nRF91 General-purpose digital I/O
26	nRF91_P0.24	DIO	nRF91 General-purpose digital I/O
27	nRF91_P0.23	DIO	nRF91 General-purpose digital I/O
28	nRF91_P0.22	DIO	nRF91 General-purpose digital I/O
29	nRF91_P0.21	DIO	nRF91 General-purpose digital I/O
30	nRF91_P0.20	DIO	nRF91 General-purpose digital I/O

Pin Number	Pin Name	Pin Type	Description
31	VSS	GND	Ground
32	VDD_SUPPLY	PWR	3.2V – 5V power supply to module
33	VDD_SUPPLY	PWR	3.2V – 5V power supply to module
34	nRF91_P0.13/AIN0	DIO/AI	nRF91 General-purpose digital I/O/ Analog Input
35	nRF91_P0.14/AIN1	DIO/AI	nRF91 General-purpose digital I/O/ Analog Input
36	nRF91_P0.15/AIN2	DIO/AI	nRF91 General-purpose digital I/O/ Analog Input
37	nRF91_P0.16/AIN3	DIO/AI	nRF91 General-purpose digital I/O/ Analog Input
38	nRF91_nRST	DI	nRF91 Reset Input (active low, open collector/drain)
39	nRF91_SWDCLK	DI	nRF91 Debug Port Clock
40	nRF91_SWDIO	DIO	nRF91 Debug Port Data
41	VSS	GND	Ground
42	nRF91_SIMRST	DO	nRF91 SIM Card Reset Output
43	nRF91_SIMDET	DI	nRF91 SIM Card Presence Detect Input
44	nRF91_SIMCLK	DO	nRF91 SIM Card Clock Output
45	nRF91_SIMIO	DIO	nRF91 SIM Card Data I/O
46	nRF91_SIM1V8	PWR	nRF91 SIM Card Power Supply (1.8V nominal)
47	VSS	GND	Ground
48	VSS	GND	Ground
49	LTE_ANT	RF	nRF91 LTE Antenna Port
50	VSS	GND	Ground

**Note:** Please refer to Nordic nRF52840 and nRF9160 Datasheets and User Guides for detail function of each pin.

## 2.2. GPS Receiver Input Connector

A  $\mu$ FL connector (J1) is provided for user to connect to an external GPS antenna. J1 is connected to GPS receiver input port of nRF9160.



The receiver supports GPS L1/CA reception. In Nordic's white paper "nWP033- nRF9160 Antenna and RF Interface Guidelines", it is recommended to use active GPS antenna with LNA gain >15dB.

A 3V supply is provided to power external active GPS antenna via J1. It can be enabled via setting MAPGPIO0 (pin 55 of nRF9160) to high. User may refer to "nRF91 AT Commands" for detail programming of this pin.

## 2.3. INTERCONNECTS BETWEEN nRF9160 AND nRF52840

Some interconnecting signals between nRF9160 and nRF52840 had been provided to aid communication/control between the 2 devices.

	nRF9160	nRF52840
<b>GPIOs</b>	nRF91_P0.17 nRF91_P0.18 nRF91_P0.19	nRF52_P0.15 nRF52_P0.17 nRF52_P0.20
<b>LTE Modem Coexistence Interface</b>	nRF91_COEX0 nRF91_COEX1 nRF91_COEX2	nRF52_P1.13 nRF52_P1.11 nRF52_P1.15
<b>Sub-system Reset</b>	nRF91_nRST nRF91_P0.27	nRF52_P0.13 nRF52_nRST

**3. ABSOLUTE MAXIMUM RATINGS**

	Min	Max	Unit
Supply Voltage (VDD_SUPPLY)	-0.3	5.5	V
Voltage on any Digital/Analog pin	-0.3	3.3	V
USB Supply Voltage (nRF52_VBUS)	-0.3	5.8	V
LTE Antenna Input RF Level		10	dBm
GPS Antenna Input RF Level		-15	dBm
Storage temperature range	-40	95	°C

**4. ELECTRICAL SPECIFICATIONS****Module**

	Min	Typ	Max	Unit
Supply Voltage (VDD_SUPPLY)	3.2	3.8	5.0	V
USB Supply Voltage (nRF52_VBUS)	4.35	5	5.5	V
Operating Temperature	-40	25	85	°C

**LTE Modem Operation**

	Min	Typ	Max	Unit
Frequency Range	699		2200	MHz
Max Output Power (LTE Cat-M/NB1/NB2)		23		dBm
Min Output Power (LTE Cat-M/NB1/NB2)		-40		dBm
Receiver Sensitivity, Low Band (LTE Cat-M)	-103	-108		dBm
Receiver Sensitivity, Mid Band (LTE Cat-M)	-103	-107		dBm
Receiver Sensitivity, Low Band (LTE Cat-NB)	-108	-114		dBm
Receiver Sensitivity, Mid Band (LTE Cat-NB)	-108	-113		dBm
Peak Current Consumption, CAT-M1 TX sub frame, Pout=23dBm, normal operating condition		365		mA
Peak Current Consumption, CAT-NB1 TX sub Frame, Pout=23dBm, normal operating condition		275		mA
Sleep Current Consumption, CAT-M1/NB1, PSM Floor Current		2.7		µA

	Min	Typ	Max	Unit
eDRX average current, 81.92 s, one PO/PTW, PTW = 2.56 s, radio resource control (RRC) mode, Cat-M1		18		µA
Average Current Cat-M1, Uplink 180 kbit/s, Pout 23 dBm, RMC settings as per 3GPP TS 36.521-1 Annex A.2, radio resource control (RRC) mode		115		mA
Average Current Cat-NB1, Pout 23 dBm, BPSK, 1SC, 3.75 kHz, TX 80% RX 10% ("TX intensive"), RMC settings as per 3GPP TS 36.101 Annex A.2.4, radio resource control (RRC) mode		225		mA

### GPS Operation

	Min	Typ	Max	Unit
Acquisition Sensitivity, Cold Start		-145.5		dBm
Acquisition Sensitivity, Hot Start		-147		dBm
Tracking Sensitivity		-155		dBm
Acquisition Time (Time to First Fix (TTFF)), Cold Start, Open Sky, Typical		36		s
Acquisition Time, Hot Start, Open Sky, Typical		1.3		s
Typical Peak Current, Continuous Tracking, without Power Saving Mode		45.5		mA
Current Consumption, Continuous Tracking, Power Saving Mode		9.8		mA
Average Current, Single Shot, One Fix every 2 minutes		2.5		mA

### Bluetooth IC Operation

	Min	Typ	Max	Unit
Frequency Range	2402		2480	MHz
Max Output Power		8		dBm
Min Output Power		-20		dBm
Receiver Sensitivity, 1 Mbps BLE Ideal Transmitter, Packet Length ≤ 37bytes, BER=1E-320		-95		dBm
Transmit Current, Pout=8dBm, 1 Mbps BLE mode, Clock = HFXO, Regulator = DC/DC		16.4		mA
Receive Current, 1 Mbps BLE mode, Clock = HFXO, Regulator = DC/DC		6.26		mA

	Min	Typ	Max	Unit
Interface Supply Voltage		3.0		V
Input High Voltage	2.1		3.0	V
Input Low Voltage	0		0.9	V
Output High Voltage, Standard Drive 0.5mA, High Drive 5mA	2.6		3.0	V
Output Low Voltage, Standard Drive 0.5mA, High Drive 5mA	0		0.4	V

**Note:** Please refer to Nordic nRF52840 and nRF9160 Datasheets and User Guides for detail characteristics and functions of nRF52840 and nRF9160.

**Output Voltages**

	Min	Typ	Max	Unit
+3V_OUT	2.9	3.0	3.1	V
+3V_OUT Current	0		200	mA
Voltage at J1 (GPS Receiver Input)	2.9	3.0	3.1	V
Output Current at J1	0		25	mA
nRF91_SIM_1V8	1.7	1.8	1.9	V

**Others**

	Min	Typ	Max	Unit
MODULE_ON High Voltage		VDD_SUPPLY		V
MODULE_ON Low Voltage		VSS		V

## 5. MECHANICAL SPECIFICATIONS

## 5.1. Mechanical Dimensions





Figure 4 AVT9152 Mechanical Dimensions


## 5.2. Recommended Footprint




## 6. DESIGN GUIDELINES

Please take note of following guidelines when designing Host PCB:

- There should be no copper pattern at the area underneath Bluetooth SMD antenna, on all layers of PCB. Orientate the Module with the “no-copper area” at one corner of Host PCB, so that Bluetooth signal radiated from the SMD antenna is not blocked by adjacent components.




- There are some exposed test pads at bottom side of module, for internal testing purpose. Cover all patterns and via holes with soldermask on Host PCB, on the layer that is immediately below the Module, to avoid shorting with test pads above them.
- The pin LTE\_ANT on Module's edge connector is for connection to customer's choice of LTE antenna. The RF trace on Host PCB connecting to this pin should be of  $50\Omega$  impedance.
- If LTE antenna is not a  $50\Omega$  antenna, e.g. FPC or SMD antenna, place up to 4 segments of R-C matching network between LTE\_ANT and antenna. The matching components should be placed as close to antenna as possible. Default values of R1, R2, R3 and R4 are  $0\Omega$  while C1, C2, C3 and C4 are not mounted. User can optimize their values with antenna and casing in place.




Reach Further™

- If LTE antenna is of external swivel type, it is probably a  $50\Omega$  antenna. A  $\pi$  matching network (C1/R1/C2) between LTE\_ANT and antenna will be adequate. The matching components should be placed as close to antenna as possible. Default values of R1 is  $0\Omega$  while C1 and C2 are not mounted. User can optimize their values with antenna and casing in place.



- It is recommended to include a series resistor on the USB supply for improved immunity to transient overvoltage during VBUS connection.



- nRF91\_nRST is internally pulled up to 2.2V. Do not attach external pull-up resistor, or drive the pin high with voltage higher than 2.2V.
- Inside the module, there are two 100uF ceramic capacitors on VDD\_SUPPLY line to cater for current surge during LTE modem operation. User can add more capacitors to VDD\_SUPPLY if the battery has limited discharge current rating.
- Ensure adequate decoupling capacitors on power lines to avoid EMC issue.

## 7. APPLICATION EXAMPLE – TRACKING DEVICE




Figure 5 Example of Tracking Device using AVT9152

## 8. REGULATORY INFORMATION

The product had been certified to conform with following Standards:  
FCC, CE, ACMA and BQB.

For certifications of LTE modem (nRF9160) with PTCRB, GCF, various local authorities and telecom operators, please refer to Nordic semiconductor's website.

### 8.1. FCC

**FCC ID: 2AW4N00AVT9152MOD00**

**Contains FCC ID: 2ANPO00NRF9160**

To reuse nRF9160's FCC ID (2ANPO00NRF9160), please observe maximum antenna gain requirement in nRF9160's TCB report.

#### FCC Interference Statement

This product has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This product generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this product does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

FCC Caution: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This device and its antenna(s) must not be co-located or operating in conjunction with any other antenna or transmitter.

**FCC Radiation Exposure Statement:**

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance **20cm** between the radiator & your body.

**This module is intended for OEM integrators under the following conditions:**

1. This module is certified pursuant to Part 15 rules section(15.247).
2. This module is limited to host model number: AES-CELLIOT-AVT9152KIT, Brand: Avnet.
3. This module has been approved to operate with the antenna types listed below, with the maximum permissible gain indicated.

Frequency Band	Antenna Type	Gain(dBi)
2400-2483.5MHz	SMD Antenna	1.5

**4. Label and compliance information****Label of the end product:**

The host product must be labeled in a visible area with the following "Contains FCC ID: 2AW4N00AVT9152MOD00".

The end product shall bear the following 15.19 statement: This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

**5. Information on test modes and additional testing requirements**

Separate approval is required for all other operating configurations, including portable configurations with respect to Part 2.1093 and different antenna configurations.

The information on how to configure test modes for host product evaluation for different operational conditions for a stand-alone modular transmitter in a host, versus with multiple, simultaneously transmitting modules or other transmitters in a host can be found at KDB Publication 996369 D04.

**6. Additional testing, Part 15 Subpart B disclaimer**

Appropriate measurements (e.g. 15B compliance) and if applicable additional equipment authorizations (e.g. SDoC) of the host product to be addressed by the integrator/manufacturer.

This module is only FCC authorized for the specific rule part 15.247 listed on the grant, and the host product manufacturer is responsible for compliance to any other FCC rules that apply to the host product as being Part 15 Subpart B compliant.

**7. The user manual of the end product should include:**

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

The antenna(s) used for this transmitter must be installed to provide a separation distance of at least **20 cm** from all persons.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This device and its antenna(s) must not be co-located or operating in conjunction with any other antenna or transmitter.

## 8.2. BQB

**Declaration ID: D051401**

## 9. ORDER CODE

AES-CELLIOT-AVT9152MOD

## 10. STORAGE, PACKAGING AND MANUFACTURING

### 10.1. Storage

AVT9152 module is stored in a vacuum-sealed bag. MSL of the module is rated at 3. Storage requirements are as shown below.

1. Calculated shelf life in the vacuum-sealed bag: 12 months at <40°C and 90%RH.
2. After the vacuum-sealed bag is opened, devices that will be subjected to reflow solder or other high temperature processes must be:
  - Mounted within 168 hours at factory environment of ≤30°C and 60%RH, or
  - Stored as per J-STD-033.
3. Devices require baking before mounting, if any circumstance below occurs.
  - When ambient temperature is 23°C±5°C and humidity indication card shows that humidity is >10% when opening the vacuum-sealed bag.
  - Device mounting cannot be finished within 168 hours at factory conditions of ≤30°C and 60%RH, or devices are not stored as per J-STD-033.
4. If baking is required, refer to IPC/JEDEC J-STD-033 for bake procedure.

### 10.2. Packaging

AVT9152 module is packaged in reel of 300pcs. Diameter of reel is 330mm.

There is 4 reels/CTN or 1200pcs/CTN.

### 10.3. Manufacturing

Recommended reflow profile is as shown below.

