


Test report No: 4913207.56

TEST REPORT

Radio Spectrum Matters (RF)

| | |
|---------------------------------|---|
| Identification of item tested | Connected Baby Monitor |
| Trademark | PHILIPS AVENT |
| Model and /or type reference | SCD971/xx, SCD973/xx (xx=00, 01, , 99) |
| FCC/IC ID | FCC ID: 2AW4T-SCD97XBA; IC: 135T-SCD97XBA |
| HVIN | SCD971BA, SCD973BA |
| Features | Adaptor part (ASSA105A-050100): Input: 100-240 Vac, 50/60 Hz, 0,35 A, Output: 5.0 Vdc, 1.0 A, 5.0 W; BU part: Input: 5.0 Vdc, 1.0 A |
| Applicant's name / address | Philips Electronics Hong Kong Limited Level 19, Tower I, Grand Century Place, 193 Prince Edward Road West, Mongkok, Kowloon, Hong Kong |
| Test method requested, standard | FCC CFR Title 47 Part15 Subpart C Section 15.247; KDB558074 D01v05r02; RSS-Gen Issue 5; RSS-247 Issue 3 |
| Verdict Summary | COMPLIANCE |
| Tested by (name & signature) | Harry Deng  |
| Approved by (name & signature) | Tim Yan  |
| Date of issue | 2024-05-22 |
| Report template No | TRF_EMС 2017-06- FCC_Part15C_247 |

INDEX

| | page |
|--|------|
| General conditions | 3 |
| Uncertainty..... | 3 |
| Environmental conditions | 3 |
| Possible test case verdicts | 3 |
| Definition of symbols used in this test report | 4 |
| Abbreviations | 4 |
| Document History | 4 |
| Remarks and Comments | 4 |
| 1 General Information | 5 |
| 1.1 General Description of the Item(s)..... | 5 |
| 1.2 Test data..... | 6 |
| 1.3 The environment(s) in which the EUT is intended to be used..... | 7 |
| 2 Description of Test Setup | 8 |
| 2.1 Operating mode(s) used for tests | 8 |
| 2.2 Port(s) of the EUT | 8 |
| 2.3 Support / Auxiliary equipment / unit / software for the EUT..... | 8 |
| 2.4 Test Configuration / Block diagram used for tests | 8 |
| 3 Verdict summary section | 9 |
| 3.1 Standards | 9 |
| 3.2 Deviation(s) from the Standard(s) / Test Specification(s)..... | 9 |
| 3.3 Overview of results..... | 9 |
| 3.4 Measurement procedure | 11 |
| 4 Transmitter Test Results | 12 |
| 4.1 AC Power Line Conducted Emission..... | 12 |
| 4.2 Emissions in non-restricted frequency bands | 15 |
| 4.3 Emissions in restricted frequency bands | 38 |
| 4.4 Band Edge | 42 |
| 4.5 Duty cycle | 49 |
| 4.6 DTS Bandwidth | 53 |
| 4.7 Fundamental emission output power..... | 60 |
| 4.8 Power Density..... | 62 |
| 5 Identification of the Equipment Under Test..... | 67 |
| Annex 1 – Measurement Uncertainty | 68 |
| Annex 2 - Used Equipment | 69 |
| Annex 3 - Test Photos | 70 |

GENERAL CONDITIONS

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.
5. This report will not be used for social proof function in China market.

UNCERTAINTY

For all measurements where guidance for the calculation of the instrumentation uncertainty of a measurement is specified in EN 55016-4-2 (CISPR 16-4-2), EN/IEC 61000-4 series or a product standard, the measurement instrumentation uncertainty has been calculated and applied in accordance with these standards.

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

| | |
|-----------------------|------------------|
| Ambient temperature | 15 °C – 35 °C |
| Relative Humidity air | 30% - 60% |
| Atmospheric pressure | 86 kPa – 106 kPa |

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

POSSIBLE TEST CASE VERDICTS

| | |
|---|-----------------|
| Test case does not apply to test object | N/A |
| Test object does meet requirement | P (Pass) / PASS |
| Test object does not meet requirement | F (Fail) / FAIL |
| Not measured | N/M |

DEFINITION OF SYMBOLS USED IN THIS TEST REPORT

| | | | |
|--|--------------------------|-----------|---|
| <input checked="" type="checkbox"/> Indicates that the listed condition, standard or equipment is applicable for this report/test/EUT. | | | |
| <input type="checkbox"/> Indicates that the listed condition, standard or equipment is not applicable for this report/test/EUT. | | | |
| Decimal separator used in this report | <input type="checkbox"/> | Comma (,) | <input checked="" type="checkbox"/> Point (.) |

ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

| | | |
|-------|---|-----------------------------|
| EUT | : | Equipment Under Test |
| QP | : | Quasi-Peak |
| CAV | : | CISPR Average |
| AV | : | Average |
| CDN | : | Coupling Decoupling Network |
| SAC | : | Semi-Anechoic Chamber |
| OATS | : | Open Area Test Site |
| BW | : | Bandwidth |
| AM | : | Amplitude Modulation |
| PM | : | Pulse Modulation |
| HCP | : | Horizontal Coupling Plane |
| VCP | : | Vertical Coupling Plane |
| U_N | : | Nominal voltage |
| T_x | : | Transmitter |
| R_x | : | Receiver |
| N/A | : | Not Applicable |
| N/M | : | Not Measured |

DOCUMENT HISTORY

| Report nr. | Date | Description |
|------------|------------|----------------|
| 4913207.56 | 2024-05-22 | First release. |
| | | |

REMARKS AND COMMENTS

The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).

1 GENERAL INFORMATION

1.1 General Description of the Item(s)

| | |
|-------------------------------|---|
| Description of the item | Connected Baby Monitor |
| Trademark..... | PHILIPS AVENT |
| Model / Type number..... | SCD971/xx, SCD973/xx (xx=00, 01, , 99) |
| FCC/IC ID | FCC ID: 2AW4T-SCD97XBA; IC: 135T-SCD97XBA |
| HVIN | SCD971BA, SCD973BA |
| Ratings..... | Adaptor part (ASSA105A-050100): Input: 100-240 Vac, 50/60 Hz, 0,35 A, Output: 5.0 Vdc, 1.0 A, 5.0 W; BU: Input: 5.0 Vdc, 1.0 A |
| Manufacturer..... | Philips Consumer Lifestyle B.V. Tussendiepen 4, 9206 AD Drachten, The Netherlands |
| Factory | Sky Light Electronic (ShenZhen) Limited No. 8 Building 1F-5F & 9 Building 1F-2F, AnTuoShan High-tech Industrial Park, XinSha Road, Shajing, Bao'An, 518104, Shenzhen, People's Republic of China |

RF specification (base on client's declaration)

| | |
|---|---|
| Operating frequency range(s)..... | 2412-2462 MHz (802.11 b/g/n HT20) |
| Type of Modulation | 802.11b:DSSS(DBPSK/DQPSK/CCK); 802.11g/n:OFDM(BPSK/QPSK/16QAM/64QAM) |
| Maximum RF output power (conducted) | 15.80 dBm; |
| E.I.R.P. | 18.09 dBm; |
| Antenna type..... | Integral Antenna |
| Antenna gain..... | 2.29 dBi |
| Number of channel | 11 (802.11 b/g/n HT20) |
| Operating Temperature Range..... | 0 - 40 °C |

| Rated power supply | Voltage and Frequency | Reference poles | | | | |
|--------------------------|--|-------------------------------------|--------------------------|--------------------------|-------------------------------------|--------------------------|
| | | L1 | L2 | L3 | N | PE |
| | <input checked="" type="checkbox"/> AC: 100-240 V, 50/60 Hz | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| | <input type="checkbox"/> DC: | | | | | |
| Mounting position..... | <input type="checkbox"/> Battery: | | | | | |
| | <input type="checkbox"/> Table top equipment | | | | | |
| | <input checked="" type="checkbox"/> Wall/Ceiling mounted equipment | | | | | |
| | <input type="checkbox"/> Floor standing equipment | | | | | |
| | <input type="checkbox"/> Hand-held equipment | | | | | |
| | <input type="checkbox"/> Other: | | | | | |

Intended use of the Equipment Under Test (EUT)

The apparatus as supplied for the test is Connected Baby Monitor which intended for residential use, the product contains electronic circuitry but without earth connection.

According to manufacturer's declaration, models are identical except for the colour of appearance.

Letters xx can be 00 to 99 specified the product code which would not affect the EMC test result.

Hence, model SCD971/26 was chosen for full test and the corresponding test data are also representative of the other model as well.

Copy of marking plate:

No provide.

1.2 Test data

| | |
|----------------------------------|--|
| Test Location | DEKRA Testing and Certification (Shanghai) Ltd. Guangzhou Branch Block 5, No.3, Qiyun Road, Huangpu District, Guangzhou, Guangdong, China FCC Designation Number: CN1324; ISED CAB identifier: CN0130 |
| Test sample number | 4913207-8 (conducted sample), 4913207-9 (radiated sample), |
| Date of receipt of test item | 2023-12-18 |
| Date (s) of performance of tests | 2023-12-18 to 2024-02-29 |

1.3 The environment(s) in which the EUT is intended to be used

The equipment under test (EUT) is intended to be used in the following environment(s):

| | |
|-------------------------------------|--|
| <input checked="" type="checkbox"/> | Residential (domestic) environment. |
| <input checked="" type="checkbox"/> | Commercial and light-industrial environment. |
| <input type="checkbox"/> | Industrial environment. |

2 DESCRIPTION OF TEST SETUP

2.1 Operating mode(s) used for tests

During the tests the following operating mode(s) has(have) been used.

| Operating mode | Operating mode description | Used for methos | |
|----------------|--------------------------------|-------------------------------------|-------------------------------------|
| | | Conducted | Radiated |
| 1 | Transmitting at 802.11b mode | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| 2 | Transmitting at 802.11g mode | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| 3 | Transmitting at 802.11n20 mode | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| 4 | | <input type="checkbox"/> | <input type="checkbox"/> |

Supplemental information: ---

2.2 Port(s) of the EUT

| Port name and description | Connected to / Termination | Cable | | |
|---------------------------|----------------------------|-----------------------------|-------------------------------------|--------------------------|
| | | Length used during test [m] | Attached during test | Shielded |
| AC input | AC mains | 0 | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| | | | <input type="checkbox"/> | <input type="checkbox"/> |
| | | | <input type="checkbox"/> | <input type="checkbox"/> |

Supplemental information: ---

2.3 Support / Auxiliary equipment / unit / software for the EUT

The EUT has been tested with the following auxiliary equipment / unit / software:

| Auxiliary equipment / unit / software | Type / Version | Manufacturer | Supplied by |
|---------------------------------------|----------------|--------------|-------------|
| Laptop | Latitude 5488 | DELL | DEKRA |
| | | | |

Supplemental information: ---

2.4 Test Configuration / Block diagram used for tests

Refer to Annex 3.

3 VERDICT SUMMARY SECTION

This chapter presents an overview of standards and results. Refer to the next chapters for details of measured test results and applied test levels.

3.1 Standards

| Standard | Year | Description |
|---|------|--|
| FCC CFR Title 47 Part 15 Subpart C Section 15.247 | 2024 | Operation within the bands 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz. |
| KDB 558074 D01 v05r02 | 2019 | Guidance for performing compliance measurements on Digital Transmission System (DTS) operating under section 15.247 |
| RSS-Gen Issue 5 Amendment 1 | 2019 | General Requirements for Compliance of Radio Apparatus |
| RSS-247 Issue 3 | 2023 | Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices |
| ANSI C63.10 | 2013 | American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices |

3.2 Deviation(s) from the Standard(s) / Test Specification(s)

The following deviation(s) was / were made from the published requirements of the listed standards: N/A.

3.3 Overview of results

| FCC measurement | | | |
|---|---------------------------|---------|--------|
| Requirement – Test case | Basic standard(s) | Verdict | Remark |
| AC Power Line Conducted Emission | FCC 15.207 | PASS | --- |
| Emissions in non-restricted frequency bands | FCC 15.247(d), FCC 15.209 | PASS | --- |
| Emissions in restricted frequency bands | FCC 15.247(b)(3) | PASS | --- |
| Duty cycle | ANSI C63.10:2013 | PASS | --- |
| Band Edge | FCC 15.247(d) | PASS | --- |
| Fundamental emission output power | FCC 15.247(d), FCC 15.209 | PASS | --- |
| DTS Bandwidth | FCC 15.247(a)(2) | PASS | --- |
| Power Spectral Density | FCC 15.247(e) | PASS | --- |
| Antenna Requirement | FCC 15.203 | PASS | --- |
| <u>Supplementary information:</u> --- | | | |

| ISED measurement | | | |
|---|--------------------------------|---------|--------|
| Requirement – Test case | Basic standard(s) | Verdict | Remark |
| AC Power Line Conducted Emission | RSS-Gen Issue 5 Section 8.8 | PASS | --- |
| Emissions in restricted frequency bands | RSS-Gen Issue 5 Section 8.9 | PASS | --- |
| Emissions in non-restricted frequency bands | RSS-247 Issue 2 Section 5.5 | PASS | --- |
| Duty cycle | ANSI C63.10:2013 | PASS | --- |
| Band Edge | RSS-Gen Issue 5 Section 8.10 | PASS | --- |
| Fundamental emission output power | RSS-247 Issue 2 Section 5.4(d) | PASS | --- |
| DTS Bandwidth | RSS-Gen Issue 5 Section 6.7 | PASS | --- |
| Power Spectral Density | RSS-247 Issue 2 Section 5.2(b) | PASS | --- |
| Antenna Requirement | RSS-Gen Issue 5 Section 6.8 | PASS | --- |
| <u>Supplementary information:</u> --- | | | |

The measurement result is considered in conformance with the requirement if it is within the prescribed limit. It is not necessary to calculate the uncertainty associated with the measurement result.

3.4 Measurement procedure

The EUT was controlled by laptop through the telnet port with USB-type C cable. After connected, run the software "SecureCRT" supplied by manufacturer to control the EUT work in required test mode as below table.

| Mode | Frequency (MHz) | Power setting |
|-------------|--------------------|---------------|
| WLAN b | 2412 | 17 dBm |
| | 2437 | 17 dBm |
| | 2462 | 17 dBm |
| WLAN g | 2412 | 17 dBm |
| | 2437 | 17 dBm |
| | 2462 | 17 dBm |
| WLAN n HT20 | 2412 | 17 dBm |
| | 2437 | 17 dBm |
| | 2462 | 17 dBm |

4 TRANSMITTER TEST RESULTS


| | |
|---|----------------------|
| 4.1 AC Power Line Conducted Emission | VERDICT: PASS |
|---|----------------------|

Limits

| FCC Part 15 Subpart C Paragraph 15.207 | | | | |
|--|-----------------------------------|-----------------------------------|-------|-------------|
| Frequency range [MHz] | Limit: QP [dB(µV) ¹⁾] | Limit: AV [dB(µV) ¹⁾] | IF BW | Detector(s) |
| 0,15 - 0,50 | 66 - 56 ²⁾ | 56 - 46 ²⁾ | 9 KHz | QP, AV |
| 0,50 - 5,0 | 56 | 46 | 9 KHz | QP, AV |
| 5,0 - 30 | 60 | 50 | 9 KHz | QP, AV |

¹⁾ At the transition frequency, the lower limit applies.
²⁾ The limit decreases linearly with the logarithm of the frequency.

Test Configuration




Performed measurements

| Port under test | Terminal | | | | | | | | | | | | | | | |
|--|-------------------------------------|--------------------------|-------------------------------------|---|--------------------------|--------------|--------------------------|----|--|--|--|--|--|--|--|--|
| <input checked="" type="checkbox"/> AC mains input power | <input checked="" type="checkbox"/> | N | <input checked="" type="checkbox"/> | L1 | <input type="checkbox"/> | L2 | <input type="checkbox"/> | L3 | | | | | | | | |
| <input type="checkbox"/> DC input power | <input type="checkbox"/> | Positive (+) | | | <input type="checkbox"/> | Negative (-) | | | | | | | | | | |
| Test method applied | <input checked="" type="checkbox"/> | Artificial mains network | | | | | | | | | | | | | | |
| | <input type="checkbox"/> | Voltage probe | | | | | | | | | | | | | | |
| Test setup | <input checked="" type="checkbox"/> | Table top | <input type="checkbox"/> | Artificial hand applied | | | | | | | | | | | | |
| | <input type="checkbox"/> | Floor standing | <input type="checkbox"/> | Other: Refer to the Annex 2 for test setup photo(s). | | | | | | | | | | | | |
| Operating mode(s) used | Mode 1, Mode 2, Mode 3 | | | | | | | | | | | | | | | |
| Envirment condition (temperature; humidiry) | 22.0 °C; 52.0 % | | | | | | | | | | | | | | | |
| Remark | --- | | | | | | | | | | | | | | | |

| | |
|----------------|-----------------------------|
| Model | SCD971/26 (BU part) |
| Operation Mode | Mode 1 |
| Test voltage | 120 Vac, 60 Hz (worst case) |

Results

Live




Remarks:

- 1) Level (final measurement) = received value + transducer (Lisn+cable)
- 2) Delta = Level – Limit

No other significant emissions were measured at the frequency range of interest employing both the QP and AV detectors.

Neutral



Remarks:

- 1) Level (final measurement) = received value + transducer (Lisn+cable)
- 2) Delta = Level – Limit

No other significant emissions were measured at the frequency range of interest employing both the QP and AV detectors.




| | |
|--|----------------------|
| 4.2 Emissions in non-restricted frequency bands | VERDICT: PASS |
|--|----------------------|

| Emissions Limit 15.209(a) | | | |
|---------------------------|-----------------------|-------------------------|--------------------------|
| Frequency (MHz) | Field strength (µV/m) | Field strength (dBµV/m) | Measurement distance (m) |
| 0.009 - 0.49 | 2400/F(kHz) | 48.5 – 13.8 | 300 (Note 1) |
| 0.49 - 1.705 | 24000/F(kHz) | 33.8 - 23 | 30 (Note 1) |
| 1.705 - 30 | 30 | 29.5 | 30 (Note 1) |
| 30 - 88 | 100 | 40 | 3 (Note 2) |
| 88 - 216 | 150 | 43.5 | 3 (Note 2) |
| 216 - 960 | 200 | 46 | 3 (Note 2) |
| Above 960 | 500 | 54 | 3 (Note 2) |

Note 1: At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).

Note 2: At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

Test Configuration



Performed measurements


| | | |
|------------------------|---|-----------------------|
| Port under test | Enclosure port | |
| Test method applied | <input type="checkbox"/> | Conducted measurement |
| | <input checked="" type="checkbox"/> | Radiated measurement |
| Test setup | Refer to the Annex 3 for test setup photo(s). | |
| Operating mode(s) used | Mode 1, Mode 2, Mode 3 | |
| Remark | The test frequency range, 9kHz~30MHz, 18GHz~26GHz, both of the worst case are at least 20dB below the limits, therefore no data appear in the report. | |

Results of 30 – 1000 MHz

| | |
|----------------|---------------------|
| Model | SCD971/26 (BU part) |
| Operation Mode | Mode 1 |
| Test voltage | 120 Vac, 60 Hz |

Results

Horizontal




| Freq (MHz) | Reading (dBuV) | C.F (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin=limit-result (dB) |
|------------|----------------|----------|-----------------|----------------|--------------------------|
| 54.64 | 9.93 | 14.40 | 24.33 | 40.00 | 15.67 |
| 114.52 | 13.87 | 11.88 | 25.75 | 43.50 | 17.75 |
| 155.36 | 9.55 | 14.87 | 24.42 | 43.50 | 19.08 |
| 204.96 | 12.25 | 11.39 | 23.64 | 43.50 | 19.86 |
| 607.79 | 8.31 | 23.55 | 31.86 | 46.00 | 14.14 |
| 833.32 | 6.01 | 26.69 | 32.70 | 46.00 | 13.30 |

Remarks:

- 1) C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
- 2) Result = Reading + C.F (Correction Factor)

No other significant emissions were measured at the frequency range of interest employing the QP detectors.

Vertical



| Freq (MHz) | Reading (dBuV) | C.F (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin=limit-result (dB) |
|------------|----------------|----------|-----------------|----------------|--------------------------|
| 31.40 | 20.50 | 13.04 | 33.54 | 40.00 | 6.46 |
| 58.00 | 13.85 | 14.18 | 28.03 | 40.00 | 11.97 |
| 112.52 | 17.21 | 11.67 | 28.88 | 43.50 | 14.62 |
| 127.22 | 15.69 | 13.01 | 28.70 | 43.50 | 14.80 |
| 197.89 | 14.90 | 11.75 | 26.65 | 43.50 | 16.85 |
| 839.18 | 7.67 | 26.85 | 34.52 | 46.00 | 11.48 |

Remarks:

- 1) C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
- 2) Result = Reading + C.F (Correction Factor)


No other significant emissions were measured at the frequency range of interest employing the QP detectors.

Results of 1 – 18 GHz

| | |
|----------------|---------------------|
| Model | SCD971/26 (BU part) |
| Operation Mode | Mode 1 @2412 MHz |
| Test voltage | 120 Vac, 60 Hz |

Results

Horizontal




Remarks:

- 1) Due to the spectrum display limitation, the unit dB μ V in test figure is dB μ V/m actually.
- 2) Y-Value (dB μ V/m) = received value (dB μ V) + Correction Factor (Antenna factor (dB μ V/m) + Cable loss (dB) - Preamp gain (dB))

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Vertical



Remarks:


- 1) Due to the spectrum display limitation, the unit dB μ V in test figure is dB μ V/m actually.
- 2) Y-Value (dB μ V/m)= received value (dB μ V)+ Correction Factor (Antenna factor (dB μ V/m)+ Cable loss (dB)- Preamp gain (dB))

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

| | |
|----------------|---------------------|
| Model | SCD971/26 (BU part) |
| Operation Mode | Mode 1 @2437 MHz |
| Test voltage | 120 Vac, 60 Hz |

Results

Horizontal




Remarks:

- 1) Due to the spectrum display limitation, the unit dB μ V in test figure is dB μ V/m actually.
- 2) Y-Value (dB μ V/m)= received value (dB μ V)+ Correction Factor (Antenna factor (dB μ V/m)+ Cable loss (dB)- Preamp gain (dB))

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Vertical



Remarks:


- 1) Due to the spectrum display limitation, the unit dB μ V in test figure is dB μ V/m actually.
- 2) Y-Value (dB μ V/m)= received value (dB μ V)+ Correction Factor (Antenna factor (dB μ V/m)+ Cable loss (dB)- Preamp gain (dB))

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

| | |
|----------------|---------------------|
| Model | SCD971/26 (BU part) |
| Operation Mode | Mode 1 @2462 MHz |
| Test voltage | 120 Vac, 60 Hz |

Results

Horizontal




Remarks:

- 1) Due to the spectrum display limitation, the unit dB μ V in test figure is dB μ V/m actually.
- 2) Y-Value (dB μ V/m)= received value (dB μ V)+ Correction Factor (Antenna factor (dB μ V/m)+ Cable loss (dB)- Preamp gain (dB))

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Vertical



Remarks:


- 1) Due to the spectrum display limitation, the unit dB μ V in test figure is dB μ V/m actually.
- 2) Y-Value (dB μ V/m)= received value (dB μ V)+ Correction Factor (Antenna factor (dB μ V/m)+ Cable loss (dB)- Preamp gain (dB))

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

| | |
|----------------|---------------------|
| Model | SCD971/26 (BU part) |
| Operation Mode | Mode 2 @2412 MHz |
| Test voltage | 120 Vac, 60 Hz |

Results

Horizontal




Remarks:

- 1) Due to the spectrum display limitation, the unit dB μ V in test figure is dB μ V/m actually.
- 2) Y-Value (dB μ V/m)= received value (dB μ V)+ Correction Factor (Antenna factor (dB μ V/m)+ Cable loss (dB)- Preamp gain (dB))

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Vertical



Remarks:


- 1) Due to the spectrum display limitation, the unit dB μ V in test figure is dB μ V/m actually.
- 2) Y-Value (dB μ V/m)= received value (dB μ V)+ Correction Factor (Antenna factor (dB μ V/m)+ Cable loss (dB)- Preamplifier gain (dB))

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

| | |
|----------------|---------------------|
| Model | SCD971/26 (BU part) |
| Operation Mode | Mode 2 @2437 MHz |
| Test voltage | 120 Vac, 60 Hz |

Results

Horizontal




Remarks:

- 1) Due to the spectrum display limitation, the unit dB μ V in test figure is dB μ V/m actually.
- 2) Y-Value (dB μ V/m) = received value (dB μ V) + Correction Factor (Antenna factor (dB μ V/m)) + Cable loss (dB) - Preamp gain (dB)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Vertical



Remarks:


- 1) Due to the spectrum display limitation, the unit dB μ V in test figure is dB μ V/m actually.
- 2) Y-Value (dB μ V/m)= received value (dB μ V)+ Correction Factor (Antenna factor (dB μ V/m)+ Cable loss (dB)- Preamp gain (dB))

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

| | |
|----------------|---------------------|
| Model | SCD971/26 (BU part) |
| Operation Mode | Mode 2 @2462 MHz |
| Test voltage | 120 Vac, 60 Hz |

Results

Horizontal




Remarks:

- 1) Due to the spectrum display limitation, the unit dBuV in test figure is dBuV/m actually.
- 2) Y-Value (dBuV/m)= received value (dBuV)+ Correction Factor (Antenna factor (dBuV/m)+ Cable loss (dB)- Preamp gain (dB))

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Vertical



Remarks:


- 1) Due to the spectrum display limitation, the unit dB μ V in test figure is dB μ V/m actually.
- 2) Y-Value (dB μ V/m)= received value (dB μ V)+ Correction Factor (Antenna factor (dB μ V/m)+ Cable loss (dB)- Preamplifier gain (dB))

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

| | |
|----------------|---------------------|
| Model | SCD971/26 (BU part) |
| Operation Mode | Mode 3 @2412 MHz |
| Test voltage | 120 Vac, 60 Hz |

Results

Horizontal




Remarks:

- 1) Due to the spectrum display limitation, the unit dB μ V in test figure is dB μ V/m actually.
- 2) Y-Value (dB μ V/m) = received value (dB μ V) + Correction Factor (Antenna factor (dB μ V/m)) + Cable loss (dB) - Preamp gain (dB)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Vertical



Remarks:


- 1) Due to the spectrum display limitation, the unit dB μ V in test figure is dB μ V/m actually.
- 2) Y-Value (dB μ V/m)= received value (dB μ V)+ Correction Factor (Antenna factor (dB μ V/m)+ Cable loss (dB)- Preamp gain (dB))

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

| | |
|----------------|---------------------|
| Model | SCD971/26 (BU part) |
| Operation Mode | Mode 3 @2437 MHz |
| Test voltage | 120 Vac, 60 Hz |

Results

Horizontal




Remarks:

- 1) Due to the spectrum display limitation, the unit dB μ V in test figure is dB μ V/m actually.
- 2) Y-Value (dB μ V/m) = received value (dB μ V) + Correction Factor (Antenna factor (dB μ V/m)) + Cable loss (dB) - Preamp gain (dB)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Vertical



Remarks:


- 1) Due to the spectrum display limitation, the unit dB μ V in test figure is dB μ V/m actually.
- 2) Y-Value (dB μ V/m)= received value (dB μ V)+ Correction Factor (Antenna factor (dB μ V/m)+ Cable loss (dB)- Preamp gain (dB))

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

| | |
|----------------|---------------------|
| Model | SCD971/26 (BU part) |
| Operation Mode | Mode 3 @2462 MHz |
| Test voltage | 120 Vac, 60 Hz |

Results

Horizontal




Remarks:

- 1) Due to the spectrum display limitation, the unit dB μ V in test figure is dB μ V/m actually.
- 2) Y-Value (dB μ V/m)= received value (dB μ V)+ Correction Factor (Antenna factor (dB μ V/m)+ Cable loss (dB)- Preamp gain (dB))

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Vertical



Remarks:

- 1) Due to the spectrum display limitation, the unit dB μ V in test figure is dB μ V/m actually.
- 2) Y-Value (dB μ V/m)= received value (dB μ V)+ Correction Factor (Antenna factor (dB μ V/m)+ Cable loss (dB)- Preamp gain (dB))

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

4.3 Emissions in restricted frequency bands

VERDICT: PASS

Restricted Bands of operation of FCC

| Frequency (MHz) | Frequency (MHz) | Frequency (MHz) | Frequency (GHz) |
|---------------------|-----------------------|-----------------|-----------------|
| 0.090 – 0.110 | 16.42 – 16.423 | 399.9 – 410 | 4.5 – 5.15 |
| 0.495 – 0.505 | 16.69475 – 16.69525 | 608 – 614 | 5.35 – 5.46 |
| 2.1735 – 2.1905 | 16.80425 – 16.80475 | 960 – 1240 | 7.25 – 7.75 |
| 4.125 – 4.128 | 25.5 – 25.67 | 1300 – 1427 | 8.025 – 8.5 |
| 4.17725 – 4.17775 | 37.5 – 38.25 | 1435 – 1626.5 | 9.0 – 9.2 |
| 4.20725 – 4.20775 | 73 – 74.6 | 1645.5 – 1646.5 | 9.3 – 9.5 |
| 6.215 – 6.218 | 74.8 – 75.2 | 1660 – 1710 | 10.6 – 12.7 |
| 6.26775 – 6.26825 | 108 – 121.94 | 1718.8 – 1722.2 | 13.25 – 13.4 |
| 6.31175 – 6.31225 | 123 – 138 | 2200 – 2300 | 14.47 – 14.5 |
| 8.291 – 8.294 | 149.9 – 150.05 | 2310 – 2390 | 15.35 – 16.2 |
| 8.362 – 8.366 | 156.52475 – 156.52525 | 2483.5 – 2500 | 17.7 – 21.4 |
| 8.37625 – 8.38675 | 156.7 – 156.9 | 2690 – 2900 | 22.01 – 23.12 |
| 8.81425 – 8.81475 | 162.0125 – 167.17 | 3260 – 3267 | 23.6 – 24.0 |
| 12.29 – 12.293 | 167.72 – 173.2 | 3332 – 3339 | 31.2 – 31.8 |
| 12.51975 – 12.52025 | 240 – 285 | 3345.8 – 3358 | 36.43 – 36.5 |
| 12.57675 – 12.57725 | 322 – 335.4 | 3600 – 4400 | |
| 13.36 – 13.41 | | | |

Restricted Bands of operation for IC

| | | | |
|---------------------|-----------------------|-----------------|---------------|
| 0.090 - 0.110 | 13.36 - 13.41 | 960 - 1427 | 9.0 - 9.2 |
| 0.495 - 0.505 | 16.42 - 16.423 | 1435 - 1626.5 | 9.3 - 9.5 |
| 2.1735 - 2.1905 | 16.69475 - 16.69525 | 1645.5 - 1646.5 | 10.6 - 12.7 |
| 3.020 - 3.026 | 16.80425 - 16.80475 | 1660 - 1710 | 13.25 - 13.4 |
| 4.125 - 4.128 | 25.5 - 25.67 | 1718.8 - 1722.2 | 14.47 - 14.5 |
| 4.17725 - 4.17775 | 37.5 - 38.25 | 2200 - 2300 | 15.35 - 16.2 |
| 4.20725 - 4.20775 | 73 - 74.6 | 2310 - 2390 | 17.7 - 21.4 |
| 5.677 - 5.683 | 74.8 - 75.2 | 2483.5 - 2500 | 22.01 - 23.12 |
| 6.215 - 6.218 | 108 - 138 | 2655 - 2900 | 23.6 - 24.0 |
| 6.26775 - 6.26825 | 149.9 - 150.05 | 3260 - 3267 | 31.2 - 31.8 |
| 6.31175 - 6.31225 | 156.52475 - 156.52525 | 3332 - 3339 | 36.43 - 36.5 |
| 8.291 - 8.294 | 156.7 - 156.9 | 3345.8 - 3358 | Above 38.6 |
| 8.362 - 8.366 | 162.0125 - 167.17 | 3500 - 4400 | |
| 8.37625 - 8.38675 | 167.72 - 173.2 | 4500 - 5150 | |
| 8.41425 - 8.41475 | 240 - 285 | 5350 - 5460 | |
| 12.29 - 12.293 | 322 - 335.4 | 7250 - 7750 | |
| 12.51975 - 12.52025 | 399.9 - 410 | 8025 - 8500 | |
| 12.57675 - 12.57725 | 608 - 614 | -- | |


Restricted Band Emissions Limit

| Frequency (MHz) | Field strength ($\mu\text{V/m}$) | Field strength ($\text{dB}\mu\text{V/m}$) | Measurement distance (m) |
|-----------------|------------------------------------|---|--------------------------|
| 0.009 - 0.49 | 2400/F(kHz) | 48.5 – 13.8 | 300 (Note 1) |
| 0.49 - 1.705 | 24000/F(kHz) | 33.8 - 23 | 30 (Note 1) |
| 1.705 - 30 | 30 | 29.5 | 30 (Note 1) |
| 30 - 88 | 100 | 40 | 3 (Note 2) |
| 88 - 216 | 150 | 43.5 | 3 (Note 2) |
| 216 - 960 | 200 | 46 | 3 (Note 2) |
| Above 960 | 500 | 54 | 3 (Note 2) |

Note 1: At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).

Note 2: At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

Test Configuration



Performed measurements

| | | |
|------------------------|---|-----------------------|
| Port under test | Enclosure port | |
| Test method applied | <input type="checkbox"/> | Conducted measurement |
| | <input checked="" type="checkbox"/> | Radiated measurement |
| Test setup | Refer to the Annex 3 for test setup photo(s). | |
| Operating mode(s) used | Mode 1, Mode 2, Mode 3 | |
| Remark | RBW: 1 MHz, VBW: 3 MHz | |

For BU part

Mode 1

| Operation channel (MHz) | Frequency (MHz) | Polar | Max Peak Value (dBuV/m) | Peak limit (dBuV/m) | Max AV Value (dBuV/m) | AV limit (dBuV/m) |
|-------------------------|-----------------|-------|-------------------------|---------------------|-----------------------|-------------------|
| 2412 | 2346.89 | H | 60.05 | 74 | --- | --- |
| | 2313.77 | H | --- | --- | 50.88 | 54 |
| | 2388.29 | V | 60.81 | 74 | --- | --- |
| | 2386.94 | V | --- | --- | 52.52 | 54 |
| 2462 | 2484.06 | H | 60.03 | 74 | --- | --- |
| | 2488.38 | H | --- | --- | 47.43 | 54 |
| | 2486.53 | V | 62.40 | 74 | --- | --- |
| | 2487.19 | V | --- | --- | 49.59 | 54 |

Mode 2

| Operation channel (MHz) | Frequency (MHz) | Polar | Max Peak Value (dBuV/m) | Peak limit (dBuV/m) | Max AV Value (dBuV/m) | AV limit (dBuV/m) |
|-------------------------|-----------------|-------|-------------------------|---------------------|-----------------------|-------------------|
| 2412 | 2389.64 | H | 61.24 | 74 | --- | --- |
| | 2386.55 | H | --- | --- | 47.29 | 54 |
| | 2389.46 | V | 69.96 | 74 | --- | --- |
| | 2390.00 | V | --- | --- | 50.47 | 54 |
| 2462 | 2483.64 | H | 61.81 | 74 | --- | --- |
| | 2484.68 | H | --- | --- | 47.81 | 54 |
| | 2483.68 | V | 73.28 | 74 | --- | --- |
| | 2483.50 | V | --- | --- | 52.74 | 54 |

Mode 3

| Operation channel (MHz) | Frequency (MHz) | Polar | Max Peak Value (dBuV/m) | Peak limit (dBuV/m) | Max AV Value (dBuV/m) | AV limit (dBuV/m) |
|-------------------------|-----------------|-------|-------------------------|---------------------|-----------------------|-------------------|
| 2412 | 2389.82 | H | 61.73 | 74 | --- | --- |
| | 2389.73 | H | --- | --- | 47.44 | 54 |
| | 2388.92 | V | 68.63 | 74 | --- | --- |
| | 2390.00 | V | --- | --- | 50.15 | 54 |
| 2462 | 2486.47 | H | 61.56 | 74 | --- | --- |
| | 2485.39 | H | --- | --- | 47.50 | 54 |
| | 2484.17 | V | 72.42 | 74 | --- | --- |
| | 2482.61 | V | --- | --- | 42.69 | 54 |

4.4 Band Edge


VERDICT: PASS

| Standard | FCC Part 15 Subpart C Paragraph 15.247(d) |
|-------------------------------------|---|
| RF Output power (Detection methods) | Limit(dB) |
| RF Output power(Average detector) | 30dBc(Note1) |
| RF Output power(PK detector) | 20dBc(Note2) |

Note 1: If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD by level in 100 kHz (i.e., 30 dBc).

Note 2: If the maximum peak conducted output power procedure was used, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD by level in 100 kHz (i.e., 20 dBc).


Test Configuration



Performed measurements

| | | |
|------------------------|---|-----------------------|
| Port under test | Antenna port | |
| Test method applied | <input checked="" type="checkbox"/> | Conducted measurement |
| | <input type="checkbox"/> | Radiated measurement |
| Test setup | Refer to the Annex 3 for test setup photo(s). | |
| Operating mode(s) used | Mode 1, Mode 2, Mode 3 | |
| Remark | RBW=100 kHz, VBW=300 kHz | |

BU part
Results of mode 1 @2412 MHz




Inband Peak

| Frequency (MHz) | Level (dBm) |
|-----------------|-------------|
| 2412.0000 | 5.1 |

Measurements

| Frequency (MHz) | Level (dBm) | Margin (dB) | Limit (dBm) | Result |
|-----------------|-------------|-------------|-------------|--------|
| 2397.425000 | -37.6 | 22.7 | -14.9 | PASS |
| 2397.475000 | -37.6 | 22.7 | -14.9 | PASS |
| 2397.525000 | -37.6 | 22.7 | -14.9 | PASS |
| 2397.775000 | -37.9 | 23.0 | -14.9 | PASS |
| 2397.725000 | -38.0 | 23.1 | -14.9 | PASS |
| 2398.225000 | -38.3 | 23.4 | -14.9 | PASS |
| 2397.575000 | -38.4 | 23.5 | -14.9 | PASS |
| 2397.825000 | -38.6 | 23.7 | -14.9 | PASS |
| 2398.475000 | -38.7 | 23.8 | -14.9 | PASS |
| 2398.075000 | -38.7 | 23.8 | -14.9 | PASS |
| 2397.675000 | -38.7 | 23.8 | -14.9 | PASS |
| 2397.975000 | -38.8 | 23.9 | -14.9 | PASS |
| 2397.375000 | -38.8 | 23.9 | -14.9 | PASS |
| 2397.925000 | -38.8 | 23.9 | -14.9 | PASS |
| 2397.325000 | -38.8 | 23.9 | -14.9 | PASS |

Results of mode 1 @2462 MHz




Inband Peak

| Frequency (MHz) | Level (dBm) |
|-----------------|-------------|
| 2462.0000 | 4.8 |

Measurements

| Frequency (MHz) | Level (dBm) | Margin (dB) | Limit (dBm) | Result |
|-----------------|-------------|-------------|-------------|--------|
| 2487.025000 | -44.1 | 29.0 | -15.2 | PASS |
| 2486.975000 | -44.5 | 29.4 | -15.2 | PASS |
| 2487.075000 | -45.3 | 30.2 | -15.2 | PASS |
| 2483.625000 | -45.4 | 30.3 | -15.2 | PASS |
| 2491.025000 | -45.5 | 30.3 | -15.2 | PASS |
| 2488.425000 | -45.7 | 30.5 | -15.2 | PASS |
| 2488.375000 | -45.7 | 30.5 | -15.2 | PASS |
| 2487.325000 | -45.7 | 30.6 | -15.2 | PASS |
| 2483.675000 | -45.8 | 30.7 | -15.2 | PASS |
| 2490.975000 | -45.9 | 30.7 | -15.2 | PASS |
| 2491.075000 | -46.1 | 30.9 | -15.2 | PASS |
| 2498.075000 | -46.1 | 30.9 | -15.2 | PASS |
| 2487.375000 | -46.1 | 31.0 | -15.2 | PASS |
| 2485.275000 | -46.1 | 31.0 | -15.2 | PASS |
| 2485.325000 | -46.2 | 31.0 | -15.2 | PASS |

Results of mode 2 @2412 MHz




Inband Peak

| Frequency (MHz) | Level (dBm) |
|-----------------|-------------|
| 2412.0000 | 4.7 |

Measurements

| Frequency (MHz) | Level (dBm) | Margin (dB) | Limit (dBm) | Result |
|-----------------|-------------|-------------|-------------|--------|
| 2399.175000 | -24.1 | 8.8 | -15.3 | PASS |
| 2399.225000 | -24.7 | 9.4 | -15.3 | PASS |
| 2399.125000 | -24.9 | 9.5 | -15.3 | PASS |
| 2399.875000 | -25.4 | 10.1 | -15.3 | PASS |
| 2399.825000 | -25.5 | 10.2 | -15.3 | PASS |
| 2399.525000 | -25.8 | 10.5 | -15.3 | PASS |
| 2399.275000 | -25.8 | 10.5 | -15.3 | PASS |
| 2399.475000 | -26.1 | 10.8 | -15.3 | PASS |
| 2397.325000 | -26.2 | 10.9 | -15.3 | PASS |
| 2397.275000 | -26.3 | 10.9 | -15.3 | PASS |
| 2397.875000 | -26.3 | 11.0 | -15.3 | PASS |
| 2399.925000 | -26.6 | 11.3 | -15.3 | PASS |
| 2399.425000 | -26.6 | 11.3 | -15.3 | PASS |
| 2397.925000 | -26.8 | 11.4 | -15.3 | PASS |
| 2398.975000 | -26.8 | 11.4 | -15.3 | PASS |

Results of mode 2 @2462 MHz




Inband Peak

| Frequency (MHz) | Level (dBm) |
|-----------------|-------------|
| 2462.0000 | 4.6 |

Measurements

| Frequency (MHz) | Level (dBm) | Margin (dB) | Limit (dBm) | Result |
|-----------------|-------------|-------------|-------------|--------|
| 2483.875000 | -32.0 | 16.6 | -15.4 | PASS |
| 2483.825000 | -32.5 | 17.1 | -15.4 | PASS |
| 2483.925000 | -32.6 | 17.2 | -15.4 | PASS |
| 2483.525000 | -33.2 | 17.9 | -15.4 | PASS |
| 2483.575000 | -33.3 | 17.9 | -15.4 | PASS |
| 2484.175000 | -34.0 | 18.6 | -15.4 | PASS |
| 2484.125000 | -34.1 | 18.7 | -15.4 | PASS |
| 2484.825000 | -34.3 | 18.9 | -15.4 | PASS |
| 2484.525000 | -34.3 | 18.9 | -15.4 | PASS |
| 2484.475000 | -34.4 | 19.0 | -15.4 | PASS |
| 2484.875000 | -34.4 | 19.0 | -15.4 | PASS |
| 2483.625000 | -34.6 | 19.2 | -15.4 | PASS |
| 2483.975000 | -35.0 | 19.6 | -15.4 | PASS |
| 2484.225000 | -35.1 | 19.7 | -15.4 | PASS |
| 2486.375000 | -35.3 | 19.9 | -15.4 | PASS |

Results of mode 3 @2412 MHz




Inband Peak

| Frequency (MHz) | Level (dBm) |
|-----------------|-------------|
| 2412.0000 | 4.8 |

Measurements

| Frequency (MHz) | Level (dBm) | Margin (dB) | Limit (dBm) | Result |
|-----------------|-------------|-------------|-------------|--------|
| 2398.225000 | -22.6 | 7.4 | -15.2 | PASS |
| 2398.275000 | -22.8 | 7.6 | -15.2 | PASS |
| 2399.825000 | -23.0 | 7.8 | -15.2 | PASS |
| 2399.775000 | -23.0 | 7.8 | -15.2 | PASS |
| 2398.175000 | -23.4 | 8.2 | -15.2 | PASS |
| 2399.725000 | -24.1 | 8.9 | -15.2 | PASS |
| 2399.575000 | -24.2 | 9.0 | -15.2 | PASS |
| 2399.175000 | -24.2 | 9.0 | -15.2 | PASS |
| 2399.925000 | -24.5 | 9.4 | -15.2 | PASS |
| 2399.875000 | -24.7 | 9.5 | -15.2 | PASS |
| 2399.975000 | -24.8 | 9.6 | -15.2 | PASS |
| 2398.325000 | -24.8 | 9.7 | -15.2 | PASS |
| 2396.375000 | -25.0 | 9.8 | -15.2 | PASS |
| 2399.125000 | -25.1 | 9.9 | -15.2 | PASS |
| 2399.225000 | -25.2 | 10.0 | -15.2 | PASS |

Results of mode 3 @2462 MHz



Inband Peak

| Frequency (MHz) | Level (dBm) |
|-----------------|-------------|
| 2462.0000 | 4.5 |


Measurements

| Frequency (MHz) | Level (dBm) | Margin (dB) | Limit (dBm) | Result |
|-----------------|-------------|-------------|-------------|--------|
| 2485.425000 | -32.2 | 16.7 | -15.5 | PASS |
| 2485.475000 | -32.4 | 16.8 | -15.5 | PASS |
| 2484.175000 | -32.6 | 17.1 | -15.5 | PASS |
| 2483.675000 | -32.7 | 17.2 | -15.5 | PASS |
| 2483.725000 | -32.7 | 17.2 | -15.5 | PASS |
| 2485.375000 | -32.7 | 17.2 | -15.5 | PASS |
| 2484.125000 | -32.8 | 17.3 | -15.5 | PASS |
| 2483.625000 | -32.8 | 17.3 | -15.5 | PASS |
| 2483.775000 | -32.9 | 17.4 | -15.5 | PASS |
| 2483.525000 | -32.9 | 17.4 | -15.5 | PASS |
| 2483.575000 | -33.1 | 17.6 | -15.5 | PASS |
| 2484.225000 | -33.4 | 17.9 | -15.5 | PASS |
| 2483.825000 | -33.4 | 17.9 | -15.5 | PASS |
| 2485.775000 | -33.6 | 18.1 | -15.5 | PASS |
| 2484.475000 | -33.6 | 18.1 | -15.5 | PASS |

4.5 Duty cycle

VERDICT: PASS

Test Configuration



Performed measurements

| | | |
|------------------------|---|-----------------------|
| Port under test | Antenna port | |
| Test method applied | <input checked="" type="checkbox"/> | Conducted measurement |
| | <input type="checkbox"/> | Radiated measurement |
| Test setup | Refer to the Annex 3 for test setup photo(s). | |
| Operating mode(s) used | Mode 1, Mode 2, Mode 3 | |
| Remark | --- | |


Results for BU part

| Test Mode | Tx On (ms) | Tx On + Tx Off (ms) | Duty Cycle |
|-----------|------------|---------------------|------------|
| Mode 1 | --- | --- | 100% |

Note 1: T means the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control Level for the tested mode of operation.

Note 2: According to KDB 558074, when test for Radiated Emission Band Edge and Radiated Emission, for average detector set: $VBW \geq 1/T$ will be used.

Gated Trace



Level in dBm


Time in s

Legend: Gated Trace (Blue), Overall (Green), Limit (Red)

| Test Mode | Tx On (ms) | Tx On + Tx Off (ms) | Duty Cycle |
|-----------|------------|---------------------|------------|
| Mode 2 | --- | --- | 100% |

Note 1: T means the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control Level for the tested mode of operation.


Note 2: According to KDB 558074, when test for Radiated Emission Band Edge and Radiated Emission, for average detector set: $VBW \geq 1/T$ will be used.



| Test Mode | Tx On (ms) | Tx On + Tx Off (ms) | Duty Cycle |
|-----------|------------|---------------------|------------|
| Mode 3 | --- | --- | 99.93% |

Note 1: T means the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control Level for the tested mode of operation.

Note 2: According to KDB 558074, when test for Radiated Emission Band Edge and Radiated Emission, for average detector set: $VBW \geq 1/T$ will be used.



4.6 DTS Bandwidth


VERDICT: PASS

Standard

FCC Part 15 Subpart C Paragraph 15.247 (a)(2)

Systems using digital modulation techniques operate in the 2400-2483.5 MHz .The minimum 6 dB bandwidth shall be at least 500 kHz

Test Configuration



Performed measurements

| | | |
|------------------------|---|-----------------------|
| Port under test | Antenna port | |
| Test method applied | <input checked="" type="checkbox"/> | Conducted measurement |
| | <input type="checkbox"/> | Radiated measurement |
| Test setup | Refer to the Annex 3 for test setup photo(s). | |
| Operating mode(s) used | Mode 1, Mode 2, Mode 3 | |
| Remark | RBW=100 kHz, VBW=300 kHz | |


Results for BU part

| Mode | CH. | Test Freq. (MHz) | 6dB Occupied Bandwidth (MHz) | Limit (kHz) | Result |
|------|-----|---------------------|---------------------------------|----------------|--------|
| 1 | 1 | 2412 | 9.75 | >500 | Pass |
| | 11 | 2462 | 9.35 | >500 | Pass |

6dB Occupied Bandwidth


Mode 1 / CH1 (2412MHz)

6 dB Bandwidth



Mode 1 / CH11 (2462MHz)


6 dB Bandwidth



| Mode | CH. | Test Freq. (MHz) | 99% Occupied Bandwidth (MHz) | Limit | Result |
|------|-----|---------------------|---------------------------------|------------------------|--------|
| 1 | 1 | 2412 | 12.90 | Within frequency range | Pass |
| | 11 | 2462 | 12.70 | Within frequency range | Pass |


99% Occupied Bandwidth
Mode 1 / CH1 (2412 MHz)

99 % Bandwidth



Mode 1 / CH11 (2462 MHz)


99 % Bandwidth



| Mode | CH. | Test Freq. (MHz) | 6dB Occupied Bandwidth (MHz) | Limit (kHz) | Result |
|------|-----|---------------------|---------------------------------|----------------|--------|
| 2 | 1 | 2412 | 16.45 | >500 | Pass |
| | 11 | 2462 | 16.15 | >500 | Pass |


6dB Occupied Bandwidth
Mode 2 / CH1 (2412MHz)

6 dB Bandwidth



Mode 1 / CH11 (2462MHz)


6 dB Bandwidth



| Mode | CH. | Test Freq. (MHz) | 99% Occupied Bandwidth (MHz) | Limit | Result |
|------|-----|---------------------|---------------------------------|------------------------|--------|
| 2 | 1 | 2412 | 16.60 | Within frequency range | Pass |
| | 1 | 2462 | 16.70 | Within frequency range | Pass |


99% Occupied Bandwidth
Mode 2 / CH1 (2412 MHz)

99 % Bandwidth



Mode 2 / CH11 (2462 MHz)


99 % Bandwidth



| Mode | CH. | Test Freq. (MHz) | 6dB Occupied Bandwidth (MHz) | Limit (kHz) | Result |
|------|-----|---------------------|---------------------------------|----------------|--------|
| 3 | 1 | 2402 | 17.15 | >500 | Pass |
| | 11 | 2480 | 16.50 | >500 | Pass |


6dB Occupied Bandwidth
Mode 3 / CH1 (2412MHz)

6 dB Bandwidth



Mode 3 / CH11 (2462MHz)


6 dB Bandwidth



| Mode | CH. | Test Freq. (MHz) | 99% Occupied Bandwidth (MHz) | Limit | Result |
|------|-----|---------------------|---------------------------------|------------------------|--------|
| 3 | 1 | 2412 | 17.60 | Within frequency range | Pass |
| | 11 | 2462 | 17.80 | Within frequency range | Pass |


99% Occupied Bandwidth
Mode 3 / CH1 (2412 MHz)

99 % Bandwidth



Mode 3 / CH11 (2462 MHz)

99 % Bandwidth



4.7 Fundamental emission output power


VERDICT: PASS

| Standard | | FCC Part 15 Subpart C Paragraph 15.247 (b)(3); RSS-247 Issue 2 Section 5.4(d) |
|-------------------------------------|---|--|
| <input checked="" type="checkbox"/> | GTX <6dBi | Pout≤30dBm |
| <input type="checkbox"/> | GTX >6dBi | |
| <input type="checkbox"/> | Non-Fix point-point | Pout≤30-(GTX -6) |
| <input type="checkbox"/> | Fix point-point | Pout≤30-[(GTX-6)]/3 |
| <input type="checkbox"/> | Point-to-multipoint | Pout≤30-(GTX-6) |
| <input type="checkbox"/> | Overlap Beams | Pout≤30-[(GTX-6)]/3 |
| <input type="checkbox"/> | Aggregate power transmitted simultaneously on all beams | Pout≤30-[(GTX-6)]/3 |
| <input type="checkbox"/> | singby LE directional beam | Pout≤30-[(GTX-6)]/3+8dB |

Note 1 : GTX directional gain of transmitting antennas.

Note 2 : Pout is maximum peak conducted output power .

Test Configuration



Performed measurements

| | | |
|------------------------|---|-----------------------|
| Port under test | Antenna port | |
| Test method applied | <input checked="" type="checkbox"/> | Conducted measurement |
| | <input type="checkbox"/> | Radiated measurement |
| Test setup | Refer to the Annex 3 for test setup photo(s). | |
| Operating mode(s) used | Mode 1, Mode 2, Mode 3 | |
| Remark | --- | |

Results for BU part


| Mode | Channel | Test Frequency (MHz) | Power Output (dBm) | EIRP (dBm) | Limit (dBm) | Result |
|--------|---------|----------------------|--------------------|------------|-------------|--------|
| Mode 1 | 1 | 2412 | 15.05 | 17.34 | ≤30 | Pass |
| | 6 | 2437 | 15.34 | 17.63 | ≤30 | Pass |
| | 11 | 2462 | 15.15 | 17.44 | ≤30 | Pass |
| Mode 2 | 1 | 2412 | 15.80 | 18.09 | ≤30 | Pass |
| | 6 | 2437 | 15.75 | 18.04 | ≤30 | Pass |
| | 11 | 2462 | 15.54 | 17.83 | ≤30 | Pass |
| Mode 3 | 1 | 2412 | 15.49 | 17.78 | ≤30 | Pass |
| | 6 | 2437 | 15.62 | 17.91 | ≤30 | Pass |
| | 11 | 2462 | 15.49 | 17.78 | ≤30 | Pass |

4.8 Power Density

VERDICT: PASS

| | |
|----------------------------------|---|
| Standard | FCC Part 15 Subpart C Paragraph 15.247 (b)(3) |
| Power Spectral Density≤8dBm/3kHz | |

Test Configuration




Performed measurements

| | |
|------------------------|---|
| Port under test | Antenna port |
| Test method applied | <input checked="" type="checkbox"/> Conducted measurement |
| | <input type="checkbox"/> Radiated measurement |
| Test setup | Refer to the Annex 3 for test setup photo(s). |
| Operating mode(s) used | Mode 1, Mode 2, Mode 3 |
| Remark | RBW=100 kHz, VBW=300 kHz |


Results for BU part

| Mode | Channel | Test Frequency (MHz) | Power Output (dBm) | Limit (dBm/3kHz) | Result |
|--------|---------|----------------------|--------------------|------------------|--------|
| Mode 1 | 1 | 2412 | 2.793 | ≤8 | Pass |
| | 6 | 2437 | 2.458 | ≤8 | Pass |
| | 11 | 2462 | 2.509 | ≤8 | Pass |
| Mode 2 | 1 | 2412 | 2.623 | ≤8 | Pass |
| | 6 | 2437 | 2.768 | ≤8 | Pass |
| | 11 | 2462 | 2.321 | ≤8 | Pass |
| Mode 3 | 1 | 2412 | 2.527 | ≤8 | Pass |
| | 6 | 2437 | 1.732 | ≤8 | Pass |
| | 11 | 2462 | 2.175 | ≤8 | Pass |


Test figure:
Mode 1 @channel 1




Mode 1 @channel 6




Mode 1 @channel 11




Mode 2 @channel 1




Mode 2 @channel 6




Mode 2 @channel 11




Mode 3 @channel 1



Mode 3 @channel 6



Mode 3 @channel 11



5 IDENTIFICATION OF THE EQUIPMENT UNDER TEST

The photographs show the tested device.

Refer to documents 4913207_BU_External photo and 4913207_BU_Internal photo.

ANNEX 1 – MEASUREMENT UNCERTAINTY

| Test Item | Uncertainty |
|-----------------------------------|-------------|
| AC Power Lines Conducted Emission | ±2.82dB |
| Occupied Channel Bandwidth | ±0.7% |
| RF Output power, conducted | ±0.6dB |
| Power Spectral Density, Conducted | ±0.6dB |
| Unwanted Emissions, Conducted | ±0.7dB |
| Radiated Emission (9kHz - 30MHz) | ±3.58dB |
| Radiated Emission (30 - 300MHz) | ±4.72dB |
| Radiated Emission (300 - 1000MHz) | ±4.88dB |
| Radiated Emission (1 - 18GHz) | ±4.66dB |
| Radiated Emission (18 - 26GHz) | ±4.52dB |
| Radiated Emission (26 – 40 GHz) | ±4.95dB |
| Temperature | 1.0 °C |
| Humidity | 6% |

ANNEX 2 - USED EQUIPMENT

Continuous disturbances conducted (150 kHz to 30 MHz)

| Item | Instrumentation | Manufacturer | Model No. | Serial No. | DEKRA No. | Cal. Due date |
|------|-----------------|-----------------|-----------|------------|-----------|---------------|
| 1 | EMI Receiver | R&S | ESCI | 101206 | G/L858 | 2024/07/02 |
| 2 | LISN | R&S | ENV216 | 101336 | G/L859 | 2024/07/02 |
| 3 | Shielding Room | Changzhou Feite | / | / | G/L861 | 2024/05/31 |

Emissions in non-restricted frequency bands/ Emissions in restricted frequency bands

| Item | Instrumentation | Manufacturer | Model No. | Serial No. | DEKRA No. | Cal. Due date |
|------|---|--------------|-----------|------------|-----------|---------------|
| 1 | EMI receiver | R&S | ESCI | 101205 | G/L857 | 2024/07/02 |
| 2 | Antenna (30MHz-3GHz) | SCHWARZBECK | VULB9163 | 506 | G/L864 | 2024/06/04 |
| 3 | Chamber | ETS | / | / | G/L856 | 2024/06/10 |
| 4 | Antenna (1GHz-18GHz) | R&S | HF907 | 102306 | G/L1236 | 2024/04/10 |
| 5 | Horn antenna preamplifier | Schwarzbeek | SCU-18 | 102234 | G/L1236-1 | 2025/02/03 |
| 6 | Spectrum analyzer | R&S | FSV | SN101012 | G/L1235 | 2025/01/09 |
| 7 | HF antenna (18 – 26.5 GHz) | ETS | 3160-09 | 00164643 | G/L1237 | 2025/02/28 |
| 8 | High frequency antenna preamplifier (18 – 26.5 GHz) | Schwarzbeck | SCU-26 | 1879064 | G/L1237-1 | 2025/01/24 |
| 9 | Broadband horn antenna (15 – 40 GHz) | Schwarzbeck | BBHA9170 | 00908 | GZ1901 | 2024/05/06 |
| 10 | Annular magnetic field antenna | TESEQ | HLA6121 | 540045 | GZ1905 | 2024/05/12 |

Duty cycle/Band Edge/Fundamental emission output power/DTS Bandwidth/Power Spectral Density

| Item | Instrumentation | Manufacturer | Model | Serial no. | DEKRA No. | Cal Due date |
|------|-------------------|--------------|---------|------------|-----------|--------------|
| 1 | Spectrum analyzer | R&S | FSV | SN101012 | G/L1235 | 2025/01/09 |
| 2 | Chamber | ETS | / | / | G/L856 | 2024/06/10 |
| 3 | OSP | R&S | OSP 150 | 101907 | GZ1894 | 2025/02/01 |

ANNEX 3 - TEST PHOTOS

Refer to document 4913207_BU_Test setup.

--- END ---