



# RF EXPOSURE EVALUATION REPORT

**APPLICANT** : Guangdong Wintek Science and Technology  
Co., Ltd.

**PRODUCT NAME** : Exhaust Fan

**MODEL NAME** : 7148-01-AX

**BRAND NAME** : Home NetWerks

**FCC ID** : 2AW5J-7148-01-AX

**STANDARD(S)** : 47CFR 2.1091  
KDB 447498

**RECEIPT DATE** : 2020-06-23

**TEST DATE** : 2020-06-30 to 2020-07-21

**ISSUE DATE** : 2020-09-07

Edited by: Chen Bilian  
Chen Bilian (Rapporteur)

Approved by: Peng Huarui  
Peng Huarui (Supervisor)

**NOTE:** This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





# DIRECTORY

- 1. Technical Information..... 3
- 1.1 Applicant and Manufacturer Information..... 3
- 1.2 Equipment under Test (EUT) Description..... 3
- 1.3 Applied Reference Documents ..... 4
- 2. Device Category and RF Exposure Limit ..... 5
- 3. RF Output Power..... 6
- 4. RF Exposure Assessment..... 7
- Annex A General Information..... 8

Change History		
Version	Date	Reason for Change
1.0	2020-09-07	First edition



# 1. Technical Information

**Note:** Provide by applicant.

## 1.1 Applicant and Manufacturer Information

<b>Applicant:</b>	Guangdong Wintek Science and Technology Co., Ltd.
<b>Applicant Address:</b>	The fifth building, NO.1 Avenue Luoshui, Xinglong Road, Xingtan town, Shunde, Foshan, Guangdong China 528325
<b>Manufacturer:</b>	Guangdong Wintek Science and Technology Co., Ltd.
<b>Manufacturer Address:</b>	The fifth building, NO.1 Avenue Luoshui, Xinglong Road, Xingtan town, Shunde, Foshan, Guangdong China 528325

## 1.2 Equipment under Test (EUT) Description

<b>Product Name:</b>	Exhaust Fan
<b>Serial No.:</b>	(N/A, marked #1 by test site)
<b>Hardware Version:</b>	7148-01-AX
<b>Software Version:</b>	Linkplay.4.4.223844
<b>Frequency Bands:</b>	WLAN 2.4GHz: 2412MHz ~ 2472MHz Bluetooth: 2402 ~ 2480MHz 433.92MHz
<b>Modulation Mode:</b>	Bluetooth: GFSK WLAN 2.4GHz: 802.11b: DSSS; 802.11g/n HT20: OFDM
<b>Antenna Type:</b>	WLAN 2.4GHz: Dipole Antenna Bluetooth: Dipole Antenna 433.92MHz: PCB Antenna
<b>Antenna Gain:</b>	WLAN 2.4GHz: 1.6dBi Bluetooth: 1.6dBi 433.92MHz: -3.0dBi



### 1.3 Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title	Method determination /Remark
1	47 CFR§2.1091	Radio Frequency Radiation Exposure Assessment: mobile devices	No deviation
2	KDB 447498 D01v06	General RF Exposure Guidance	No deviation

**Note 1:** The test item is not applicable.

**Note 2:** Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.



## 2. Device Category and RF Exposure Limit

Per user manual, Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

### Mobile Devices:

47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

### General Population/Uncontrolled Exposure:

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

**Table 1—Limits for Maximum Permissible Exposure (MPE)**

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

f = frequency in MHz\* = Plane-wave equivalent power density

### 3. RF Output Power

#### <WLAN 2.4GHz>

2.4GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-up Power	Duty Cycle %
	802.11b 1Mbps		CH 1	2412	<b>17.87</b>	18.00
CH 7			2442	17.68	18.00	
CH 13			2472	17.47	18.00	
802.11g 6Mbps		CH 1	2412	17.47	18.00	93.33
		CH 7	2442	17.58	18.00	
		CH 13	2472	17.31	18.00	
802.11n-HT2 0 MCS0		CH 1	2412	17.43	18.00	92.91
		CH 7	2442	17.49	18.00	
		CH 13	2472	17.13	18.00	

#### <Bluetooth>

Mode	Channel	Frequency (MHz)	Average power (dBm)
			GFSK
Bluetooth LE	CH 00	2402	8.96
	CH 19	2440	<b>9.13</b>
	CH 39	2480	8.76
Tune-up Limit			9.5

Mode	Channel	Frequency (MHz)	Average power (dBm)		
			1Mbps	2Mbps	3Mbps
Bluetooth classic	CH 00	2402	2.54	-3.22	-3.13
	CH 39	2441	2.70	-3.44	-3.31
	CH 78	2480	2.41	-3.78	-4.00
Tune-up Limit			3.00	-3.00	-3.00

#### <433MHz Mode >

Frequency(MHz)	Max. Emission E(dB $\mu$ V/m)	Max. Emission (W)	Time-averaging EIRP (mW)
433.92MHz	76.93	0.0070	0.01480

**Note 1:** The modular for 433.92MHz approach to certain low power transmitters that has low radiation, therefore the power density of 433.92MHz mode closes to zero.

**Note 2:** The output power is refer from the report SZ20060271W01/W02/W03/W04.

## 4. RF Exposure Assessment

### ➤ Standalone Transmission Assessment:

Bands	Frequency (MHz)	Maximum Tune-up Power (dBm)	Antenna Gain (dBi)	EIRP (mW)	Power Density (mW/cm <sup>2</sup> )	Limit for MPE (mW/cm <sup>2</sup> )
WLAN 2.4GHz	2412	18.00	1.6	91.20	0.018	1.0
Bluetooth	2440	9.5	1.6	12.88	0.003	1.0

### Note:

1. According to KDB 447498, SAR test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring assessment, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.
2. MPE calculate method

$$\text{Power Density} = \text{EIRP}/4\pi R^2$$

Where: EIRP = P+G

P = Output Power (dBm)

G = Antenna Gain (dBi)

R = Separation Distance (20cm)

### ➤ Simultaneous Transmission Assessment:

#### Multi-Band Simultaneous Transmission Consideration

Simultaneous Transmission Consideration	Position	Applicable Combination
	Hand/Body	WLAN 2.4GHz/Bluetooth+433.92MHz

1. This device contains transmitters that may operate simultaneously, therefore simultaneous transmission analysis is required.
2. The worst condition for WLAN & Bluetooth will be calculated for transmitting simultaneously.  
Formula:  $\text{Result} = \text{Power density}_1 / \text{limit}_1 + \text{Power density}_2 / \text{limit}_2 \leq 1$ .

Transmission Bands	Power Density/ SAR	Limit	Simultaneous Transmission Result
WLAN 2.4GHz	0.018	1	0.018
433.92MHz	0	0.289	

### ➤ Conclusion:

According to 47 CFR §2.1091, this device complies with human exposure basic restrictions.



## Annex A General Information

### 1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Laboratory Address:	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

### 2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

### 3. Facilities and Accreditations

The FCC designation number is CN1192, the test firm registration number is 226174.

————— END OF REPORT —————