

Mode: Mode 1/ IEEE 802.11a CDD  
 Temp. /Hum.:23.9°C/59%RH  
 Test Engineer: Zhang Zishan

Channel :5200MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-30

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2236.9671	57.62	40.24	-17.38	74.00	33.76	200	198	Horizontal
2	4332.7291	59.20	47.67	-11.53	74.00	26.33	200	198	Horizontal
3	4868.3585	60.86	51.83	-9.03	74.00	22.17	100	156	Horizontal
4	7987.9985	51.53	51.20	-0.33	68.30	17.10	100	63	Horizontal
5	9270.4088	50.39	52.56	2.17	68.30	15.74	100	329	Horizontal
6	10396.112	61.46	66.37	4.91	68.30	1.93	100	34	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4941.2427	-8.41	54.26	45.85	54.00	8.15	200	290	Vertical
2	10402.812	5.68	41.91	47.59	NA	NA	199	304	Vertical

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2646.0808	64.07	47.16	-16.91	68.30	21.14	100	25	Vertical
2	2910.1138	63.08	46.85	-16.23	68.30	21.45	100	358	Vertical
3	4941.2427	62.88	54.47	-8.41	74.00	19.53	200	290	Vertical
4	5617.8272	60.58	54.73	-5.85	68.30	13.57	200	191	Vertical
5	6208.4636	56.96	53.11	-3.85	68.30	15.19	200	143	Vertical
6	10397.5497	64.47	70.15	5.68	68.30	-1.85	200	344	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4868.3585	-9.03	47.28	38.25	54.00	15.75	100	156	Horizontal
2	10401.5314	4.91	42.88	47.79	NA	NA	100	343	Horizontal

Mode: Mode 1/ IEEE 802.11a CDD

Temp. /Hum.:23.9°C/59%RH

Test Engineer: Zhang Zishan

Channel :5240MHz

Power supply:AC120V/60Hz

Test Date: 2023-04-30

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1321.7902	62.48	40.51	-21.97	74.00	33.49	200	30	Horizontal
2	4935.0544	58.70	50.05	-8.65	74.00	23.95	200	148	Horizontal
3	6486.9359	53.74	50.72	-3.02	68.30	17.58	200	345	Horizontal
4	9854.1068	48.83	53.48	4.65	68.30	14.82	100	56	Horizontal
5	10479.4974	58.52	63.46	4.94	68.30	4.84	200	16	Horizontal
6	13891.1114	44.51	50.66	6.15	68.30	17.64	100	329	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4935.0544	-8.65	48.16	39.51	54.00	14.49	200	148	Horizontal
2	10480.8599	4.94	43.76	48.70	NA	NA	138	41.7	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1875.2969	61.49	39.57	-21.92	68.30	28.23	200	2	Vertical
2	3179.6475	61.48	45.63	-15.85	68.30	22.17	100	1	Vertical
3	4962.5578	61.29	53.06	-8.23	74.00	20.44	200	286	Vertical
4	5589.6362	59.62	53.88	-5.74	68.30	13.92	100	236	Vertical
5	6119.7650	57.24	52.48	-4.76	68.30	15.32	100	78	Vertical
6	10476.6221	61.56	66.54	4.98	68.30	1.76	200	310	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4962.5578	-8.23	48.52	40.29	54.00	13.71	200	286	Vertical

Mode: Mode 1/ IEEE 802.11a CDD

Temp. /Hum.:23.9°C/59%RH

Test Engineer: Zhang Zishan

Channel :5260MHz

Power supply:AC120V/60Hz

Test Date: 2023-04-30

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1059.1324	62.11	37.75	-24.36	74.00	36.25	100	299	Horizontal
2	1249.5937	59.08	37.54	-21.54	68.30	30.76	200	211	Horizontal
3	4930.9289	59.49	50.87	-8.62	74.00	23.13	100	173	Horizontal
4	9812.4141	48.13	52.59	4.46	68.30	15.71	200	20	Horizontal
5	10519.7525	60.85	65.78	4.93	68.30	2.52	200	40	Horizontal
6	17544.2555	45.89	50.46	4.57	68.30	17.84	100	129	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4930.9289	-8.62	49.36	40.74	54.00	13.26	100	173	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1059.1324	63.45	41.16	-22.29	74.00	32.34	100	15	Vertical
2	1715.7770	60.59	39.74	-20.85	68.30	28.06	200	220	Vertical
3	2919.0524	63.81	47.54	-16.27	68.30	20.26	100	15	Vertical
4	4969.4337	61.41	53.30	-8.11	74.00	20.20	200	299	Vertical
5	5648.7686	61.09	54.72	-6.37	68.30	13.08	100	282	Vertical
6	10519.7525	62.57	66.80	4.73	68.30	0.95	200	317	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4969.4337	-8.11	51.29	43.18	54.00	10.82	200	299	Vertical

Mode: Mode 1/ IEEE 802.11a CDD

Temp. /Hum.:23.9°C/59%RH

Test Engineer: Zhang Zishan

Channel :5280MHz

Power supply:AC120V/60Hz

Test Date: 2023-04-30

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1235.8420	58.02	36.11	-21.91	74.00	37.89	100	242	Horizontal
2	2659.8325	59.34	41.80	-17.54	68.30	26.50	200	253	Horizontal
3	5680.3976	55.81	49.93	-5.88	68.30	18.37	200	202	Horizontal
4	8742.7803	49.44	50.38	0.94	68.30	17.92	200	119	Horizontal
5	10561.4452	59.39	63.69	4.30	68.30	4.61	200	39	Horizontal
6	13304.5381	44.11	49.88	5.77	74.00	24.12	200	286	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	13304.5381	5.77	34.67	40.44	54.00	13.56	200	286	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1055.6945	61.20	38.82	-22.38	74.00	34.68	100	15	Vertical
2	2649.5187	61.88	45.03	-16.85	68.30	22.77	100	15	Vertical
3	3170.0213	62.94	47.11	-15.83	68.30	20.69	100	25	Vertical
4	5051.9440	61.36	53.65	-7.71	74.00	19.85	100	220	Vertical
5	5586.8859	60.06	54.27	-5.79	68.30	13.53	100	287	Vertical
6	10555.6945	62.89	66.70	3.81	68.30	1.60	200	317	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	5051.9440	-7.71	53.67	45.96	54.00	8.04	100	220	Vertical

Mode: Mode 1/ IEEE 802.11a CDD  
 Temp. /Hum.:23.9°C/59%RH  
 Test Engineer: Zhang Zishan

Channel :5320MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-16

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1248.9061	58.91	37.35	-21.56	68.30	30.95	100	320	Horizontal
2	4529.3787	59.17	48.30	-10.87	74.00	25.70	100	192	Horizontal
3	5711.3389	56.31	50.74	-5.57	68.30	17.56	200	202	Horizontal
4	8015.3144	51.53	51.41	-0.12	68.30	16.89	200	247	Horizontal
5	10636.2045	61.15	65.99	4.84	74.00	8.01	200	41	Horizontal
6	13504.3755	44.76	50.59	5.83	68.30	17.71	100	70	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4529.3787	-10.87	49.27	38.40	54.00	15.60	100	192	Horizontal
2	10640.8235	4.84	46.40	51.24	54.00	2.76	139	41.7	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1873.9217	62.38	40.44	-21.94	68.30	27.86	100	360	Vertical
2	3181.7102	60.88	45.03	-15.85	68.30	23.27	100	15	Vertical
3	4932.9916	62.80	54.43	-8.37	74.00	19.57	200	282	Vertical
4	5595.8245	60.36	54.73	-5.63	68.30	13.57	200	194	Vertical
5	10649.1436	64.55	69.27	4.72	74.00	4.73	200	346	Vertical
6	13906.9259	44.63	51.44	6.81	68.30	16.86	200	346	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4932.9916	-8.37	53.19	44.82	54.00	9.18	200	282	Vertical
2	10640.0479	4.72	44.57	49.29	54.00	4.71	186	349.9	Vertical

Mode: Mode 1/ IEEE 802.11a CDD

Temp. /Hum.:23.9°C/59%RH

Test Engineer: Zhang Zishan

Channel :5500MHz

Power supply:AC120V/60Hz

Test Date: 2023-04-16

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	3819.79	59.45	44.14	-15.31	74.00	29.86	200	45	Horizontal
2	4827.791	59.60	48.22	-11.38	74.00	25.78	100	163	Horizontal
3	6461.4952	53.99	49.12	-4.87	68.30	19.18	200	75	Horizontal
4	9851.2314	48.21	52.91	4.70	68.30	15.39	200	0	Horizontal
5	11001.3752	57.63	61.28	3.65	74.00	12.72	100	344	Horizontal
6	13911.2389	44.60	50.94	6.34	68.30	17.36	100	148	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4827.791	-11.38	49.61	38.23	54.00	15.77	100	163	Horizontal
2	11001.6983	3.65	41.24	44.89	54.00	9.11	100	348.4	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2638.5173	70.93	52.23	-18.70	68.30	16.07	100	360	Vertical
2	4924.053	62.22	51.36	-10.86	74.00	22.64	200	291	Vertical
3	5820.6651	59.35	52.10	-7.25	68.30	16.20	100	141	Vertical
4	6868.046	55.18	50.02	-5.16	68.30	18.28	100	237	Vertical
5	10999.9375	61.15	65.70	4.55	74.00	8.30	200	344	Vertical
6	13905.4882	45.02	51.83	6.81	68.30	16.47	200	11	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4924.053	-10.86	51.67	40.81	54.00	13.19	200	291	Vertical
2	11000.0978	4.55	39.90	44.45	54.00	9.55	186	17.7	Vertical

Mode: Mode 1/ IEEE 802.11a CDD

Channel :5580MHz

Temp. /Hum.:23.9°C/59%RH

Power supply:AC120V/60Hz

Test Engineer: Zhang Zishan

Test Date: 2023-04-16

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1059.82	63.31	37.95	-25.36	74.00	36.05	100	345	Horizontal
2	2652.9566	60.13	40.97	-19.16	68.30	27.33	200	128	Horizontal
3	3999.9375	63.23	48.61	-14.62	74.00	25.39	200	344	Horizontal
4	5817.2272	56.79	49.69	-7.10	68.30	18.61	200	198	Horizontal
5	10508.251	48.20	53.45	5.25	68.30	14.85	200	75	Horizontal
6	11156.6446	52.87	55.97	3.10	74.00	18.03	200	298	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	3999.9375	-14.62	54.16	39.54	54.00	14.46	200	344	Horizontal
2	11161.4914	3.10	39.76	42.86	54.00	11.14	178	309.9	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1059.1324	64.52	41.24	-23.28	74.00	32.76	200	30	Vertical
2	2908.7386	64.00	45.94	-18.06	68.30	22.36	200	345	Vertical
3	6052.3815	60.71	52.94	-7.77	68.30	15.36	100	80	Vertical
4	10423.4279	48.32	53.47	5.15	68.30	14.83	100	240	Vertical
5	11159.5199	58.29	61.11	2.82	74.00	12.89	200	16	Vertical
6	13909.8012	44.44	51.24	6.80	68.30	17.06	100	351	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	11161.1323	2.82	42.85	45.67	54.00	8.33	186	321	Vertical

Mode: Mode 1/ IEEE 802.11a CDD  
 Temp. /Hum.:23.9°C/59%RH  
 Test Engineer: Zhang Zishan

Channel :5700MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-16

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1326.6033	62.06	39.05	-23.01	74.00	34.95	200	41	Horizontal
2	3195.4619	64.64	48.05	-16.59	68.30	20.25	200	70	Horizontal
3	4781.0351	61.61	50.15	-11.46	74.00	23.85	200	335	Horizontal
4	7985.1231	51.32	50.93	-0.39	68.30	17.37	200	15	Horizontal
5	9881.4227	48.80	53.04	4.24	68.30	15.26	200	202	Horizontal
6	10496.7496	47.99	53.38	5.39	68.30	14.92	200	300	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4781.0351	-11.46	51.35	39.89	54.00	14.11	200	335	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1057.7572	63.63	40.31	-23.32	74.00	33.69	200	40	Vertical
2	1718.5273	61.03	39.06	-21.97	68.30	29.24	200	22	Vertical
3	2928.6786	67.32	49.37	-17.95	68.30	18.93	100	2	Vertical
4	5793.1616	62.39	54.82	-7.57	68.30	13.48	100	226	Vertical
5	9785.0981	48.11	52.58	4.47	68.30	15.72	100	292	Vertical
6	11396.7371	50.35	53.33	2.98	74.00	20.67	100	339	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	11401.5234	2.98	36.09	39.07	54.00	14.93	100	343.3	Vertical



Mode: Mode 1/ IEEE 802.11a CDD

Temp. /Hum.:21.5°C/65%RH

Test Engineer: Zhang Zishan

Channel :5720MHz

Power supply:AC120V/60Hz

Test Date: 2023-05-16

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1064.9	60.99	36.54	-24.45	74.00	37.46	200	143	Horizontal
2	2662.1	63.21	44.15	-19.06	68.30	24.15	200	48	Horizontal
3	4000.25	61.61	47.56	-14.05	74.00	26.44	200	171	Horizontal
4	4221.35	66.08	52.72	-13.36	74.00	21.28	200	182	Horizontal
5	6201.9	57.27	51.26	-6.01	68.30	17.04	200	16	Horizontal
6	11824.5	47.29	51.15	3.86	74.00	22.85	100	271	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4221.35	-13.36	47.28	33.92	54.00	20.08	200	182	Horizontal
2	11824.5	3.86	35.55	39.41	54.00	14.59	100	271	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1062.7000	64.57	39.40	-25.17	74.00	34.60	100	203	Vertical
2	1745.8000	66.08	43.02	-23.06	68.30	25.28	200	182	Vertical
3	2646.1500	69.34	50.28	-19.06	68.30	18.02	200	173	Vertical
4	2927.2000	63.30	45.49	-17.81	68.30	22.81	200	152	Vertical
5	5966.5000	60.77	54.37	-6.40	68.30	13.93	100	312	Vertical
6	11451.9000	49.88	53.52	3.64	74.00	20.48	200	360	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	11439.9705	3.64	35.79	39.43	54.00	14.57	117	342.8	Vertical

Mode: Mode 1/ IEEE 802.11a CDD  
 Temp. /Hum.:23.9°C/59%RH  
 Test Engineer: Zhang Zishan

Channel :5745MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-16

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2552.5691	57.43	38.78	-18.65	68.30	29.52	200	345	Horizontal
2	4781.0351	62.02	49.99	-12.03	74.00	24.01	100	178	Horizontal
3	6058.5698	58.50	51.25	-7.25	68.30	17.05	200	139	Horizontal
4	8025.3782	50.90	50.75	-0.15	74.00	23.25	200	241	Horizontal
5	10498.1873	47.90	53.33	5.43	68.30	14.97	200	211	Horizontal
6	13291.599	45.91	51.54	5.63	74.00	22.46	200	26	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4781.0351	-12.03	54.64	42.61	54.00	11.39	100	178	Horizontal
2	8025.3782	-0.15	39.64	39.49	54.00	14.51	200	241	Horizontal
3	13291.599	5.63	32.96	38.59	54.00	15.41	200	26	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2651.5814	63.92	45.41	-18.51	68.30	22.89	200	3	Vertical
2	4964.6206	61.81	51.37	-10.44	74.00	22.63	200	296	Vertical
3	5648.081	65.89	57.28	-8.61	68.30	11.02	100	139	Vertical
4	6009.7512	62.78	55.79	-6.99	68.30	12.51	100	139	Vertical
5	10401.8627	47.55	53.22	5.67	68.30	15.08	100	337	Vertical
6	11481.5602	50.98	53.86	2.88	74.00	20.14	100	337	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4964.6206	-10.44	52.46	42.02	54.00	11.98	200	296	Vertical
2	11490.0324	2.88	35.53	38.41	54.00	15.59	200	196.9	Vertical

Mode: Mode 1/ IEEE 802.11a CDD  
 Temp. /Hum.:23.9°C/59%RH  
 Test Engineer: Zhang Zishan

Channel :5785MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-16

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	3856.9196	61.84	46.30	-15.54	74.00	27.70	200	179	Horizontal
2	4225.4657	61.52	47.39	-14.13	74.00	26.61	200	306	Horizontal
3	5687.2734	59.16	50.66	-8.50	68.30	17.64	200	188	Horizontal
4	6068.196	58.79	51.60	-7.19	68.30	16.70	200	150	Horizontal
5	9963.3704	49.73	53.00	3.27	68.30	15.30	100	242	Horizontal
6	11570.6963	47.55	50.91	3.36	74.00	23.09	200	65	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	11570.6963	3.36	34.62	37.98	54.00	16.02	200	65	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2922.4903	67.73	49.75	-17.98	68.30	18.55	100	344	Vertical
2	3856.9196	62.34	46.46	-15.88	74.00	27.54	100	158	Vertical
3	4517.6897	61.52	48.68	-12.84	74.00	25.32	100	18	Vertical
4	5581.3852	64.52	56.02	-8.50	68.30	12.28	100	137	Vertical
5	6055.8195	65.45	58.04	-7.41	68.30	10.26	100	137	Vertical
6	11575.0094	52.26	55.42	3.16	74.00	18.58	200	214	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4517.6897	-12.84	53.27	40.43	54.00	13.57	100	18	Vertical
2	11569.9844	3.16	35.36	38.52	54.00	15.48	199	173.3	Vertical

Mode: Mode 1/ IEEE 802.11a CDD  
 Temp. /Hum.:23.9°C/59%RH  
 Test Engineer: Zhang Zishan

Channel :5825MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-16

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1266.0958	59.57	37.14	-22.43	68.30	31.16	100	251	Horizontal
2	4591.949	61.02	47.69	-13.33	74.00	26.31	100	172	Horizontal
3	5613.7017	59.01	50.24	-8.77	68.30	18.06	100	162	Horizontal
4	5928.6161	61.51	54.10	-7.41	68.30	14.20	200	201	Horizontal
5	9865.6082	48.69	53.17	4.48	68.30	15.13	100	2	Horizontal
6	13912.6766	44.26	50.60	6.34	68.30	17.70	200	267	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2661.2077	70.94	52.41	-18.53	68.30	15.89	100	357	Vertical
2	3883.7355	64.21	48.49	-15.72	74.00	25.51	100	163	Vertical
3	5554.5693	64.76	56.16	-8.60	68.30	12.14	200	173	Vertical
4	5919.6775	65.41	58.20	-7.21	68.30	10.10	100	133	Vertical
5	9760.6576	48.88	53.18	4.30	68.30	15.12	100	90	Vertical
6	10479.4974	48.23	53.25	5.02	68.30	15.05	100	236	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	3883.7355	-15.72	57.68	41.96	54.00	12.04	100	163	Vertical

Mode: Mode 1/ IEEE 802.11ax HE40 CDD

Channel :5190MHz

Temp. /Hum.:20.5°C/70%RH

Power supply:AC120V/60Hz

Test Engineer: Zhang Zishan

Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1062.15	61.13	36.77	-24.36	74.00	37.23	100	3	Horizontal
2	2649.45	57.18	39.73	-17.45	68.30	28.57	200	17	Horizontal
3	4000.25	59.69	46.35	-13.34	74.00	27.65	200	17	Horizontal
4	5041.4	59.32	51.52	-7.80	74.00	22.48	200	158	Horizontal
5	10376.65	55.02	57.29	2.27	68.30	11.01	100	356	Horizontal
6	16176.1	47.03	52.16	5.13	74.00	21.84	100	58	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	5041.181	-7.80	50.53	42.73	54.00	11.27	146	169.9	Horizontal
2	16176.1	5.13	38.48	43.61	54.00	10.39	100	58	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1064.9	60.36	38.24	-22.12	74.00	35.76	100	68	Vertical
2	1375.1	58.31	37.47	-20.84	74.00	36.53	200	322	Vertical
3	2426.15	60.40	42.55	-17.85	68.30	25.75	200	182	Vertical
4	5109.6	61.23	54.53	-6.70	74.00	19.47	200	39	Vertical
5	5586.45	58.84	53.04	-5.80	68.30	15.26	200	39	Vertical
6	10370.9	58.13	60.92	2.79	68.30	7.38	100	71	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	5084.828	-6.70	52.42	45.72	54.00	8.28	166	93	Vertical

Mode: Mode 1/ IEEE 802.11ax HE40 CDD

Channel :5230MHz

Temp. /Hum.:20.5°C/70%RH

Power supply:AC120V/60Hz

Test Engineer: Zhang Zishan

Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1057.75	60.54	36.18	-24.36	74.00	37.82	100	344	Horizontal
2	2648.35	59.25	41.80	-17.45	68.30	26.50	200	216	Horizontal
3	4223.55	64.04	52.04	-12.00	74.00	21.96	200	13	Horizontal
4	5089.8	57.19	50.43	-6.76	74.00	23.57	100	167	Horizontal
5	10460.6	53.33	56.64	3.31	68.30	11.66	100	353	Horizontal
6	17535.4	46.97	54.59	7.62	68.30	13.71	100	60	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4243.4762	-12.00	55.25	43.25	54.00	10.75	172	17	Horizontal
2	5081.55	-6.76	50.49	43.73	54.00	10.27	161	176.5	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1062.7	59.30	37.12	-22.18	74.00	36.88	200	2	Vertical
2	1406.45	58.19	37.39	-20.80	74.00	36.61	100	19	Vertical
3	3185.7	61.94	46.08	-15.86	68.30	22.22	100	30	Vertical
4	5001.25	60.58	52.99	-7.59	74.00	21.01	200	92	Vertical
5	5579.3	58.98	53.04	-5.94	68.30	15.26	100	223	Vertical
6	10461.75	59.98	63.52	3.54	68.30	4.78	200	330	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4999.0788	-7.59	50.02	42.43	54.00	11.57	144	96.1	Vertical
2	10462.3512	6.54	40.92	47.46	NA	NA	199	162.7	Vertical

Mode: Mode 1/ IEEE 802.11ax HE40 CDD  
 Temp. /Hum.:20.5°C/70%RH  
 Test Engineer: Zhang Zishan

Channel :5270MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1064.35	59.53	35.17	-24.36	74.00	38.83	200	9	Horizontal
2	3192.85	58.27	43.12	-15.15	68.30	25.18	200	62	Horizontal
3	4395.7	57.45	46.96	-10.49	74.00	27.04	200	193	Horizontal
4	4960	58.81	50.21	-8.60	74.00	23.79	200	138	Horizontal
5	10543.4	53.14	56.45	3.31	68.30	11.85	100	359	Horizontal
6	17494	46.12	54.33	8.21	68.30	13.97	200	67	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4960	-8.60	52.27	43.67	54.00	10.33	200	138	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1056.1	60.06	37.68	-22.38	74.00	36.32	200	0	Vertical
2	2650	60.47	43.63	-16.84	68.30	24.67	200	4	Vertical
3	4000.25	59.44	46.40	-13.04	74.00	27.60	200	345	Vertical
4	5061.75	57.21	49.70	-7.51	74.00	24.30	100	169	Vertical
5	10549.15	51.89	54.92	3.03	68.30	13.38	200	68	Vertical
6	17498.6	45.60	54.96	9.36	68.30	13.34	200	313	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	5061.75	-7.51	50.39	42.88	54.00	11.12	100	169	Vertical

Mode: Mode 1/ IEEE 802.11ax HE40 CDD

Channel :5310MHz

Temp. /Hum.:20.5°C/70%RH

Power supply:AC120V/60Hz

Test Engineer: Zhang Zishan

Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1063.25	60.10	35.73	-24.37	74.00	38.27	100	17	Horizontal
2	1748	62.76	40.70	-22.06	68.30	27.60	100	221	Horizontal
3	2642.85	64.05	46.56	-17.49	68.30	21.74	200	267	Horizontal
4	4000.25	60.07	46.73	-13.34	74.00	27.27	200	308	Horizontal
5	10613.55	58.51	60.88	2.37	74.00	13.12	100	204	Horizontal
6	16194.5	46.65	52.85	6.20	74.00	21.15	200	262	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	10615.6325	5.40	45.64	51.04	54.00	2.96	122	158.4	Horizontal
2	16194.5	6.20	38.55	44.75	54.00	9.25	200	262	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1061.05	62.52	40.29	-22.23	74.00	33.71	100	15	Vertical
2	2655.5	62.66	45.82	-16.84	68.30	22.48	100	38	Vertical
3	3192.3	62.37	46.50	-15.87	68.30	21.80	200	360	Vertical
4	5027.65	60.19	52.51	-7.68	74.00	21.49	200	79	Vertical
5	5382.95	60.30	53.30	-7.00	74.00	20.70	100	292	Vertical
6	10611.25	55.95	57.85	1.90	74.00	16.15	200	301	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	5040.3828	-7.68	50.26	42.58	54.00	11.42	151	99.1	Vertical
2	5397.3612	-7.00	49.60	42.60	54.00	11.40	133	317.4	Vertical
3	10621.0738	4.90	44.11	49.01	54.00	4.99	200	282.7	Vertical



Mode: Mode 1/ IEEE 802.11ax HE40 CDD

Channel :5510MHz

Temp. /Hum.:20.5°C/70%RH

Power supply:AC120V/60Hz

Test Engineer: Zhang Zishan

Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1056.1	61.13	35.78	-25.35	74.00	38.22	100	38	Horizontal
2	4000.25	61.42	46.80	-14.62	74.00	27.20	200	14	Horizontal
3	4221.9	67.91	53.65	-14.26	74.00	20.35	200	14	Horizontal
4	5285.6	60.82	50.42	-10.40	68.30	17.88	200	312	Horizontal
5	11013.75	48.75	52.30	3.55	74.00	21.70	200	14	Horizontal
6	17497.45	46.91	55.16	8.25	68.30	13.14	100	149	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4221.9	-14.26	59.34	45.08	54.00	8.92	200	14	Horizontal
2	11018.8512	3.55	39.78	43.33	54.00	10.67	200	15.8	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1374.55	60.59	38.65	-21.94	74.00	35.35	200	342	Vertical
2	2664.3	62.20	43.65	-18.55	68.30	24.65	100	356	Vertical
3	3176.9	61.72	44.43	-17.29	68.30	23.87	200	47	Vertical
4	5810.3	59.96	52.57	-7.39	68.30	15.73	100	234	Vertical
5	11021.8	54.17	58.53	4.36	74.00	15.47	100	324	Vertical
6	17617.05	48.56	55.90	7.34	68.30	12.40	100	230	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	11018.451	4.36	44.51	48.87	54.00	5.13	162	337.2	Vertical

Mode: Mode 1/ IEEE 802.11ax HE40 CDD

Channel :5550MHz

Temp. /Hum.:20.5°C/70%RH

Power supply:AC120V/60Hz

Test Engineer: Zhang Zishan

Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1058.85	62.07	36.71	-25.36	74.00	37.29	200	343	Horizontal
2	2641.75	64.17	45.01	-19.16	68.30	23.29	200	279	Horizontal
3	4163.05	65.15	50.93	-14.22	74.00	23.07	200	161	Horizontal
4	5281.2	63.04	52.66	-10.38	68.30	15.64	200	0	Horizontal
5	9654.45	48.90	52.31	3.41	68.30	15.99	100	233	Horizontal
6	17498.6	46.18	54.44	8.26	68.30	13.86	200	68	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4162.6288	-14.22	60.79	46.57	54.00	7.43	179	140.2	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1058.3	61.10	37.79	-23.31	74.00	36.21	200	314	Vertical
2	2640.1	64.79	46.11	-18.68	68.30	22.19	200	346	Vertical
3	4163.05	64.43	49.74	-14.69	74.00	24.26	100	174	Vertical
4	5824.05	56.96	49.75	-7.21	68.30	18.55	100	235	Vertical
5	11108.05	49.82	53.36	3.54	74.00	20.64	200	15	Vertical
6	17471	45.30	54.26	8.96	68.30	14.04	200	15	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4162.5078	-14.69	64.90	50.21	54.00	3.79	140	179.9	Vertical
2	11098.7298	6.54	43.33	49.87	54.00	4.13	180	190.4	Vertical

Mode: Mode 1/ IEEE 802.11ax HE40 CDD  
 Temp. /Hum.:20.5°C/70%RH  
 Test Engineer: Zhang Zishan

Channel :5670MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1056.65	61.85	36.50	-25.35	74.00	37.50	100	14	Horizontal
2	2648.35	61.32	42.19	-19.13	68.30	26.11	200	271	Horizontal
3	3178.55	58.11	41.57	-16.54	68.30	26.73	200	65	Horizontal
4	4000.25	60.96	46.34	-14.62	74.00	27.66	200	313	Horizontal
5	5283.4	59.71	49.32	-10.39	68.30	18.98	200	33	Horizontal
6	17694.1	48.69	54.14	5.45	68.30	14.16	200	300	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1059.4	61.34	38.07	-23.27	74.00	35.93	200	53	Vertical
2	1406.45	59.68	37.66	-22.02	74.00	36.34	200	20	Vertical
3	2931.05	60.00	42.07	-17.93	68.30	26.23	200	345	Vertical
4	4000.25	56.42	42.10	-14.32	74.00	31.90	100	48	Vertical
5	5775.65	59.07	51.37	-7.70	68.30	16.93	100	191	Vertical
6	17518.15	46.26	55.26	9.00	68.30	13.04	200	174	Vertical

----- The following blanks -----

Mode: Mode 1/ IEEE 802.11ax HE40 CDD

Temp. /Hum.:20.5°C/70%RH

Test Engineer: Zhang Zishan

Channel :5710MHz

Power supply:AC120V/60Hz

Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1064.9	62.60	38.15	-24.45	74.00	35.85	100	179	Horizontal
2	1207.9	63.37	39.60	-23.77	74.00	34.40	100	179	Horizontal
3	2459.15	59.29	39.31	-19.98	68.30	28.99	200	51	Horizontal
4	3999.7	61.51	47.46	-14.05	74.00	26.54	200	173	Horizontal
5	4245	65.66	52.46	-13.20	74.00	21.54	200	183	Horizontal
6	15047.95	45.06	52.87	7.81	68.30	15.43	100	107	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4223.867	-13.20	45.61	32.41	54.00	21.59	200	179.7	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1000	60.70	36.30	-24.40	74.00	37.70	200	345	Vertical
2	1875.6	60.41	38.23	-22.18	68.30	30.07	100	201	Vertical
3	2406.9	61.53	42.54	-18.99	68.30	25.76	200	164	Vertical
4	2657.7	69.43	50.38	-19.05	68.30	17.92	100	210	Vertical
5	5970.35	58.46	52.07	-6.39	68.30	16.23	200	305	Vertical
6	14550	45.15	53.89	8.74	68.30	14.41	100	218	Vertical

----- The following blanks -----

Mode: Mode 1/ IEEE 802.11ax HE40 CDD

Temp. /Hum.:20.5°C/70%RH

Test Engineer: Zhang Zishan

Channel :5755MHz

Power supply:AC120V/60Hz

Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1062.7	60.41	35.17	-25.24	74.00	38.83	100	18	Horizontal
2	2664.3	59.12	39.83	-19.29	68.30	28.47	200	128	Horizontal
3	4000.25	60.52	45.57	-14.95	74.00	28.43	200	343	Horizontal
4	5689.3	57.54	49.04	-8.50	68.30	19.26	200	181	Horizontal
5	9790.15	46.68	51.16	4.48	68.30	17.14	200	227	Horizontal
6	14955.95	45.07	52.02	6.95	68.30	16.28	100	69	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1064.35	60.87	37.85	-23.02	74.00	36.15	200	65	Vertical
2	1376.2	58.63	36.60	-22.03	74.00	37.40	100	8	Vertical
3	2651.1	63.98	45.47	-18.51	68.30	22.83	100	30	Vertical
4	5689.3	63.20	54.54	-8.66	68.30	13.76	100	140	Vertical
5	6067.15	60.22	52.79	-7.43	68.30	15.51	100	85	Vertical
6	17504.35	44.88	54.16	9.28	68.30	14.14	200	243	Vertical

----- The following blanks -----

Mode: Mode 1/ IEEE 802.11ax HE40 CDD  
 Temp. /Hum.:20.5°C/70%RH  
 Test Engineer: Zhang Zishan

Channel :5795MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1064.35	60.46	35.21	-25.25	74.00	38.79	200	339	Horizontal
2	2642.85	62.76	43.61	-19.15	68.30	24.69	200	360	Horizontal
3	4000.25	60.84	45.89	-14.95	74.00	28.11	200	317	Horizontal
4	5686.55	56.73	48.22	-8.51	68.30	20.08	200	241	Horizontal
5	5881.25	61.99	54.59	-7.40	68.30	13.71	200	156	Horizontal
6	17477.9	45.55	53.61	8.06	68.30	14.69	100	182	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1063.25	62.33	39.28	-23.05	74.00	34.72	100	346	Vertical
2	2652.2	66.03	47.51	-18.52	68.30	20.79	100	16	Vertical
3	3168.1	60.81	43.19	-17.62	68.30	25.11	100	356	Vertical
4	5672.25	61.84	53.20	-8.64	68.30	15.10	100	144	Vertical
5	5881.8	67.49	60.08	-7.41	68.30	8.22	100	133	Vertical
6	17495.15	45.01	54.31	9.30	68.30	13.99	200	15	Vertical

----- The following blanks -----

Mode: Mode 1/ IEEE 802.11ax HE80 CDD

Channel :5210MHz

Temp. /Hum.:20.5°C/70%RH

Power supply:AC120V/60Hz

Test Engineer: Zhang Zishan

Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2639.55	60.70	43.19	-17.51	68.30	25.11	200	319	Horizontal
2	4226.85	65.92	53.92	-12.00	74.00	20.08	200	16	Horizontal
3	5109.05	60.21	53.69	-6.52	74.00	20.31	100	169	Horizontal
4	6375.15	54.41	50.78	-3.63	68.30	17.52	200	38	Horizontal
5	10430.7	54.75	57.72	2.97	68.30	10.58	100	38	Horizontal
6	17452.6	47.31	55.14	7.83	68.30	13.16	100	15	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4243.7938	-12.00	55.54	43.54	54.00	10.46	200	18	Horizontal
2	5086.7208	-6.52	48.70	42.18	54.00	11.82	148	187.5	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1058.85	62.92	40.62	-22.30	74.00	33.38	100	15	Vertical
2	2641.75	66.36	49.36	-17.00	68.30	18.94	100	15	Vertical
3	5081.55	65.93	58.84	-7.09	74.00	15.16	200	90	Vertical
4	10431.85	57.78	61.30	3.52	68.30	7.00	100	9	Vertical
5	16913.25	48.69	55.50	6.81	68.30	12.80	200	88	Vertical
6	17488.25	47.04	56.24	9.20	68.30	12.06	200	131	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	5082.2852	-7.09	55.58	48.49	54.00	5.51	165	101.9	Vertical

Mode: Mode 1/ IEEE 802.11ax HE80 CDD  
 Temp. /Hum.:20.5°C/70%RH  
 Test Engineer: Zhang Zishan

Channel :5290MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1057.75	61.55	37.19	-24.36	74.00	36.81	100	15	Horizontal
2	2188	57.52	39.79	-17.73	68.30	28.51	100	239	Horizontal
3	4231.25	65.53	53.54	-11.99	74.00	20.46	200	310	Horizontal
4	5429.7	57.53	51.01	-6.52	74.00	22.99	200	161	Horizontal
5	10590.55	50.88	53.48	2.60	68.30	14.82	100	162	Horizontal
6	15719.55	47.77	52.42	4.65	74.00	21.58	200	196	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4237.0668	-11.99	54.69	42.70	54.00	11.30	180	355	Horizontal
2	5429.7	-6.52	46.25	39.73	54.00	14.27	200	161	Horizontal
3	15719.55	4.65	37.68	42.33	54.00	11.67	200	196	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1058.3	65.18	42.87	-22.31	74.00	31.13	100	48	Vertical
2	3019.05	56.47	41.38	-15.09	68.30	26.92	100	59	Vertical
3	5054.6	61.74	54.08	-7.66	74.00	19.92	100	70	Vertical
4	5421.45	62.52	55.61	-6.91	74.00	18.39	100	245	Vertical
5	10590.55	55.65	57.70	2.05	68.30	10.60	100	54	Vertical
6	17507.8	46.98	56.18	9.20	68.30	12.12	200	131	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	5077.788	-7.66	51.52	43.86	54.00	10.14	168	98.3	Vertical
2	5412.8978	-6.91	52.71	45.80	54.00	8.20	140	256.1	Vertical



Mode: Mode 1/ IEEE 802.11ax HE80 CDD  
 Temp. /Hum.:20.5°C/70%RH  
 Test Engineer: Zhang Zishan

Channel :5530MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1055.55	65.54	42.15	-23.39	74.00	31.85	200	0	Vertical
2	2426.15	62.59	43.41	-19.18	68.30	24.89	200	284	Vertical
3	3178	66.04	48.76	-17.28	68.30	19.54	100	38	Vertical
4	5430.25	62.81	52.89	-9.92	74.00	21.11	100	290	Vertical
5	5870.25	59.48	52.19	-7.29	68.30	16.11	100	235	Vertical
6	13950.85	43.52	52.71	9.19	68.30	15.59	200	55	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4261.7923	-14.14	56.60	42.46	54.00	11.54	200	11.3	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1057.75	65.74	40.39	-25.35	74.00	33.61	200	345	Horizontal
2	3190.1	59.63	43.06	-16.57	68.30	25.24	200	84	Horizontal
3	4263.15	67.58	53.44	-14.14	74.00	20.56	200	8	Horizontal
4	5288.35	62.39	51.98	-10.41	68.30	16.32	200	312	Horizontal
5	9338.2	48.52	51.23	2.71	74.00	22.77	100	15	Horizontal
6	13247.05	45.07	52.23	7.16	68.30	16.07	200	259	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	5410.6818	-9.92	51.47	41.55	54.00	12.45	140	324.1	Vertical
2	5430.25	-9.92	51.34	41.42	54.00	12.58	100	290	Vertical

Mode: Mode 1/ IEEE 802.11ax HE80 CDD

Channel :5610MHz

Temp. /Hum.:20.5°C/70%RH

Power supply:AC120V/60Hz

Test Engineer: Zhang Zishan

Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2663.75	65.55	46.26	-19.29	68.30	22.04	200	38	Horizontal
2	4237.85	66.94	52.72	-14.22	74.00	21.28	200	15	Horizontal
3	5288.9	62.87	52.46	-10.41	68.30	15.84	200	311	Horizontal
4	5781.7	57.23	49.74	-7.49	68.30	18.56	200	158	Horizontal
5	9278.4	48.77	51.31	2.54	68.30	16.99	100	15	Horizontal
6	13493.15	43.71	51.36	7.65	68.30	16.94	200	122	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4222.7018	-14.22	46.93	32.71	54.00	21.29	179	343.7	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1058.85	64.58	41.28	-23.30	74.00	32.72	200	53	Vertical
2	1406.45	60.63	38.61	-22.02	74.00	35.39	200	22	Vertical
3	5178.9	58.20	48.56	-9.64	68.30	19.74	100	238	Vertical
4	5764.1	61.58	53.80	-7.78	68.30	14.50	200	185	Vertical
5	9182.95	48.56	51.64	3.08	74.00	22.36	100	308	Vertical
6	16882.2	45.84	52.17	6.33	68.30	16.13	200	136	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	9182.95	3.08	38.13	41.21	54.00	12.79	100	308	Vertical

Mode: Mode 1/ IEEE 802.11ax HE80 CDD

Channel :5690MHz

Temp. /Hum.:20.5°C/70%RH

Power supply:AC120V/60Hz

Test Engineer: Zhang Zishan

Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1064.9	63.65	39.20	-24.45	74.00	34.80	200	143	Horizontal
2	3700.5	60.59	45.73	-14.86	74.00	28.27	200	294	Horizontal
3	4000.25	61.99	47.94	-14.05	74.00	26.06	200	171	Horizontal
4	4221.9	66.62	53.27	-13.35	74.00	20.73	200	181	Horizontal
5	5969.8	56.71	50.32	-6.39	68.30	17.98	200	314	Horizontal
6	15007.7	44.53	52.90	8.37	68.30	15.40	100	87	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4221.9	-13.35	46.95	33.60	54.00	20.40	200	181	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1056.1	64.79	39.73	-25.06	74.00	34.27	100	172	Vertical
2	2639.55	70.60	51.47	-19.13	68.30	16.83	100	172	Vertical
3	2921.15	62.44	44.63	-17.81	68.30	23.67	200	192	Vertical
4	3402.4	60.00	43.37	-16.63	68.30	24.93	100	294	Vertical
5	6003.35	58.74	52.42	-6.32	68.30	15.88	100	254	Vertical
6	14556.9	44.86	53.48	8.62	68.30	14.82	100	340	Vertical

----- The following blanks -----

Mode: Mode 1/ IEEE 802.11ax HE80 CDD

Temp. /Hum.:20.5°C/70%RH

Test Engineer: Zhang Zishan

Channel :5775MHz

Power supply:AC120V/60Hz

Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1059.4	63.40	38.17	-25.23	74.00	35.83	100	0	Horizontal
2	4243.9	68.24	54.16	-14.08	74.00	19.84	200	7	Horizontal
3	5686	64.28	55.77	-8.51	68.30	12.53	100	138	Horizontal
4	5880.7	61.89	54.49	-7.40	68.30	13.81	200	313	Horizontal
5	13497.75	45.61	53.39	7.78	68.30	14.91	100	309	Horizontal
6	17174.3	48.25	54.70	6.45	68.30	13.60	200	134	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4260.1755	-14.08	57.95	43.87	54.00	10.13	186	16.7	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1058.3	64.49	41.32	-23.17	74.00	32.68	100	346	Vertical
2	4337.95	61.62	48.05	-13.57	74.00	25.95	100	94	Vertical
3	5682.15	70.27	61.62	-8.65	68.30	6.68	200	180	Vertical
4	5881.25	67.25	59.84	-7.41	68.30	8.46	100	72	Vertical
5	9743	48.81	52.99	4.18	68.30	15.31	200	226	Vertical
6	17489.4	47.84	57.05	9.21	68.30	11.25	100	201	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4337.95	-13.57	52.38	38.81	54.00	15.19	100	94	Vertical

Mode: Mode 1/ IEEE 802.11ax HE160 CDD  
 Temp. /Hum.:20.5°C/70%RH  
 Test Engineer: Zhang Zishan

Channel :5250MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2653.3	63.28	45.81	-17.47	68.30	22.49	200	50	Horizontal
2	4257.65	65.57	53.77	-11.80	74.00	20.23	200	15	Horizontal
3	5101.35	67.33	60.83	-6.50	74.00	13.17	200	15	Horizontal
4	5417.6	59.96	53.39	-6.57	74.00	20.61	200	212	Horizontal
5	10516.95	50.67	53.65	2.98	68.30	14.65	100	345	Horizontal
6	17506.65	47.37	55.52	8.15	68.30	12.78	200	245	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4257.65	-11.80	53.65	41.85	54.00	12.15	200	15	Horizontal
2	5092.8602	-6.50	49.64	43.14	54.00	10.86	131	347.8	Horizontal
3	5392.119	-6.57	46.32	39.75	54.00	14.25	131	202.3	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2638.45	68.10	51.04	-17.06	68.30	17.26	100	15	Vertical
2	3187.35	62.86	47.00	-15.86	68.30	21.30	100	358	Vertical
3	5106.3	73.25	66.55	-6.70	74.00	7.45	100	72	Vertical
4	5392.85	66.10	59.07	-7.03	74.00	14.93	100	60	Vertical
5	10437.6	54.53	58.13	3.60	68.30	10.17	100	17	Vertical
6	17525.05	47.69	56.55	8.86	68.30	11.75	200	245	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	5093.5895	-6.70	52.08	45.38	54.00	8.62	163	100.9	Vertical
2	5385.9818	-7.03	54.95	47.92	54.00	6.08	120	38.7	Vertical

Mode: Mode 1/ IEEE 802.11ax HE160 CDD  
 Temp. /Hum.:20.5°C/70%RH  
 Test Engineer: Zhang Zishan

Channel :5570MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2652.2	65.05	45.89	-19.16	68.30	22.41	200	28	Horizontal
2	4177.9	67.11	52.85	-14.26	74.00	21.15	200	158	Horizontal
3	5425.3	66.88	57.26	-9.62	74.00	16.74	200	214	Horizontal
4	5773.45	61.58	54.01	-7.57	68.30	14.29	100	170	Horizontal
5	9853.4	48.12	52.76	4.64	68.30	15.54	200	221	Horizontal
6	17462.95	47.65	55.57	7.92	68.30	12.73	200	59	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4177.9	-14.26	62.24	47.98	54.00	6.02	200	158	Horizontal
2	5425.3	-9.62	55.24	45.62	54.00	8.38	200	214	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2642.3	67.60	48.95	-18.65	68.30	19.35	100	4	Vertical
2	3197.25	66.64	49.34	-17.30	68.30	18.96	100	38	Vertical
3	4177.9	67.42	52.84	-14.58	74.00	21.16	100	345	Vertical
4	5425.3	71.71	61.74	-9.97	74.00	12.26	100	135	Vertical
5	5785.55	68.08	60.45	-7.63	68.30	7.85	100	71	Vertical
6	17503.2	46.37	55.68	9.31	68.30	12.62	100	242	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4157.7055	-14.58	52.46	37.88	54.00	16.12	100	334.6	Vertical
2	5405.4365	-9.97	53.56	43.59	54.00	10.41	141	101.3	Vertical

Mode: Mode 1/ IEEE 802.11ax HE20 SDM  
 Temp. /Hum.:23.9°C/59%RH  
 Test Engineer: Zhang Zishan

Channel :5180MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-16

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1507.65	57.31	35.79	-21.52	74.00	38.21	200	15	Horizontal
2	3167	58.16	43.10	-15.06	68.30	25.20	200	60	Horizontal
3	4245	64.64	52.68	-11.96	74.00	21.32	200	15	Horizontal
4	6468.65	55.10	52.20	-2.90	68.30	16.10	200	210	Horizontal
5	10366.3	58.44	60.74	2.30	68.30	7.56	100	139	Horizontal
6	15770.15	49.12	53.99	4.87	74.00	20.01	200	323	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4242.113	-11.96	48.83	36.87	54.00	17.13	157	182	Horizontal
2	15770.15	4.87	39.56	44.43	54.00	9.57	200	323	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1405.9	60.24	39.45	-20.79	74.00	34.55	200	332	Vertical
2	2643.4	64.03	47.07	-16.96	68.30	21.23	100	27	Vertical
3	5060.65	61.47	53.94	-7.53	74.00	20.06	200	136	Vertical
4	5703.05	60.07	54.33	-5.74	68.30	13.97	100	242	Vertical
5	6474.7	57.02	53.93	-3.09	68.30	14.37	100	231	Vertical
6	10361.7	62.66	65.38	2.72	68.30	2.92	100	51	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	5060.65	-7.53	48.63	41.10	54.00	12.90	200	136	Vertical
2	10360.2015	2.72	48.43	51.15	NA	NA	100	26.1	Vertical

Mode: Mode 1/ IEEE 802.11 ax HE20 SDM  
 Temp. /Hum.:23.9°C/59%RH  
 Test Engineer: Zhang Zishan

Channel :5200MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-16

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1065.45	59.79	35.43	-24.36	74.00	38.57	200	338	Horizontal
2	1717.2	60.32	38.14	-22.18	68.30	30.16	200	17	Horizontal
3	2657.15	61.13	43.62	-17.51	68.30	24.68	200	28	Horizontal
4	4243.35	65.40	53.44	-11.96	74.00	20.56	200	17	Horizontal
5	10403.1	54.92	57.20	2.28	68.30	11.10	100	48	Horizontal
6	16193.35	47.81	53.95	6.14	74.00	20.05	200	240	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4242.4292	-11.96	48.29	36.33	54.00	17.67	170	184.8	Vertical
2	16193.35	6.14	39.26	45.40	54.00	8.60	200	240	Vertical

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1405.9	59.82	39.03	-20.79	74.00	34.97	100	26	Vertical
2	2639	61.37	44.32	-17.05	68.30	23.98	200	38	Vertical
3	3182.4	64.32	48.46	-15.86	68.30	19.84	100	38	Vertical
4	4933.05	62.15	53.78	-8.37	74.00	20.22	100	80	Vertical
5	5586.45	59.70	53.90	-5.80	68.30	14.40	100	233	Vertical
6	10396.2	60.72	63.69	2.97	68.30	4.61	100	12	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4935.3348	-8.37	52.65	44.28	54.00	9.72	159	76.9	Horizontal
2	10401.169	2.97	48.20	51.17	NA	NA	192	40.7	Horizontal



Mode: Mode 1/ IEEE 802.11 ax HE20 SDM

Channel :5240MHz

Temp. /Hum.:23.9°C/59%RH

Power supply:AC120V/60Hz

Test Engineer: Zhang Zishan

Test Date: 2023-04-16

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1714.45	68.95	46.76	-22.19	68.30	21.54	100	192	Vertical
2	4235.1	63.75	51.77	-11.98	74.00	22.23	200	6	Vertical
3	5247.1	57.99	50.98	-7.01	68.30	17.32	200	83	Vertical
4	6459.3	52.56	49.73	-2.83	68.30	18.57	100	18	Vertical
5	10480.15	55.06	58.10	3.04	68.30	10.20	100	15	Vertical
6	15769	48.71	53.60	4.89	74.00	20.40	200	268	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4245.0905	-11.98	48.09	36.11	54.00	17.89	166	185.3	Vertical
2	15769	4.89	42.36	47.25	54.00	6.75	200	268	Vertical

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1723.25	64.45	43.60	-20.85	68.30	24.70	200	268	Horizontal
2	2656.05	62.20	45.36	-16.84	68.30	22.94	100	40	Horizontal
3	4962.75	61.81	53.58	-8.23	74.00	20.42	200	81	Horizontal
4	5592.5	59.05	53.36	-5.69	68.30	14.94	100	225	Horizontal
5	10474.4	59.40	62.65	3.25	68.30	5.65	200	333	Horizontal
6	13957.75	45.45	54.27	8.82	68.30	14.03	200	225	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4971.2242	-8.23	52.29	44.06	54.00	9.94	158	78	Horizontal
2	10480.308	3.25	48.56	51.81	NA	NA	185	310.8	Horizontal

Mode: Mode 1/ IEEE 802.11 ax HE20 SDM

Channel :5260MHz

Temp. /Hum.:23.9°C/59%RH

Power supply:AC120V/60Hz

Test Engineer: Zhang Zishan

Test Date: 2023-04-16

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1406.45	59.15	38.35	-20.80	74.00	35.65	200	344	Horizontal
2	2652.75	63.41	46.57	-16.84	68.30	21.73	100	323	Horizontal
3	4938.55	62.21	53.81	-8.40	74.00	20.19	200	290	Horizontal
4	5704.15	59.71	53.96	-5.75	68.30	14.34	100	228	Horizontal
5	10523.85	60.96	63.81	2.85	68.30	4.49	200	322	Horizontal
6	14853.6	46.08	53.51	7.43	68.30	14.79	200	259	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4938.55	-8.40	48.62	40.22	54.00	13.78	200	290	Horizontal
2	10520.6508	2.85	45.10	47.95	NA	NA	199	344.6	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1713.35	63.32	41.12	-22.20	68.30	27.18	100	12	Vertical
2	1893.75	63.61	43.39	-20.22	68.30	24.91	200	301	Vertical
3	2645.05	63.75	46.28	-17.47	68.30	22.02	200	29	Vertical
4	4227.95	63.85	51.86	-11.99	74.00	22.14	200	7	Vertical
5	5281.75	58.09	51.07	-7.02	68.30	17.23	100	302	Vertical
6	10559.5	53.65	56.86	3.21	68.30	11.44	100	245	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4244.8372	-11.99	47.89	35.90	54.00	18.10	171	187.1	Vertical

Mode: Mode 1/ IEEE 802.11 ax HE20 SDM

Temp. /Hum.:23.9°C/59%RH

Test Engineer: Zhang Zishan

Channel :5280MHz

Power supply:AC120V/60Hz

Test Date: 2023-04-16

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1747.45	62.69	40.63	-22.06	68.30	27.67	100	344	Horizontal
2	2661	59.49	41.94	-17.55	68.30	26.36	100	76	Horizontal
3	4238.95	63.49	51.52	-11.97	74.00	22.48	200	14	Horizontal
4	5055.15	58.25	50.62	-7.63	74.00	23.38	100	149	Horizontal
5	10636.55	53.82	56.09	2.27	74.00	17.91	100	353	Horizontal
6	17508.95	47.43	55.53	8.10	68.30	12.77	100	15	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4246.8632	-11.97	47.16	35.19	54.00	18.81	168	204.5	Horizontal
2	5055.6622	-7.63	47.51	39.88	54.00	14.12	132	169.9	Horizontal
3	10640.3972	2.27	44.91	47.18	54.00	6.82	101	344.3	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1895.95	62.97	41.38	-21.59	68.30	26.92	100	54	Vertical
2	2648.35	62.13	45.26	-16.87	68.30	23.04	200	17	Vertical
3	3167	60.54	44.71	-15.83	68.30	23.59	200	346	Vertical
4	4936.9	60.67	52.28	-8.39	74.00	21.72	100	87	Vertical
5	5577.1	59.07	53.08	-5.99	68.30	15.22	100	292	Vertical
6	10557.2	59.22	62.08	2.86	68.30	6.22	200	323	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4958.3335	-8.39	51.59	43.20	54.00	10.80	163	78.8	Vertical

Mode: Mode 1/ IEEE 802.11 ax HE20 SDM  
 Temp. /Hum.:23.9°C/59%RH  
 Test Engineer: Zhang Zishan

Channel :5320MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-16

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2655.5	61.21	42.02	-19.19	68.30	26.28	200	60	Horizontal
2	4125.65	66.41	52.00	-14.41	74.00	22.00	200	179	Horizontal
3	4243.9	66.26	52.06	-14.20	74.00	21.94	200	312	Horizontal
4	5305.95	61.64	51.24	-10.40	68.30	17.06	200	312	Horizontal
5	11003.4	50.51	53.95	3.44	74.00	20.05	200	52	Horizontal
6	17559.55	48.06	55.29	7.23	68.30	13.01	200	198	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4125.0528	-14.41	66.43	52.02	54.00	1.98	179	158.7	Horizontal
2	4245.6815	-14.20	47.63	33.43	54.00	20.57	166	330.2	Horizontal
3	10994.163	3.44	41.30	44.74	54.00	9.26	199	17	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1059.4	62.13	39.86	-22.27	74.00	34.14	200	59	Vertical
2	2656.05	63.20	46.36	-16.84	68.30	21.94	100	0	Vertical
3	3990.35	62.23	49.25	-12.98	74.00	24.75	100	191	Vertical
4	5063.95	59.29	51.82	-7.47	74.00	22.18	200	102	Vertical
5	5593.05	58.41	52.73	-5.68	68.30	15.57	100	140	Vertical
6	10638.85	57.33	59.43	2.10	74.00	14.57	200	358	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	3990.0032	-12.98	59.20	46.22	54.00	7.78	136	180.5	Vertical
2	5050.2462	-7.47	50.63	43.16	54.00	10.84	147	83.5	Vertical
3	10640.8558	2.10	49.03	51.13	54.00	2.87	199	342.6	Vertical

Mode: Mode 1/ IEEE 802.11 ax HE20 SDM

Channel :5500MHz

Temp. /Hum.:23.9°C/59%RH

Power supply:AC120V/60Hz

Test Engineer: Zhang Zishan

Test Date: 2023-04-16

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2655.5	61.21	42.02	-19.19	68.30	26.28	200	60	Horizontal
2	4125.65	66.41	52.00	-14.41	74.00	22.00	200	179	Horizontal
3	4243.9	66.26	52.06	-14.20	74.00	21.94	200	312	Horizontal
4	5305.95	61.64	51.24	-10.40	68.30	17.06	200	312	Horizontal
5	11003.4	50.51	53.95	3.44	74.00	20.05	200	52	Horizontal
6	17559.55	48.06	55.29	7.23	68.30	13.01	200	198	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4125.0528	-14.41	66.43	52.02	54.00	1.98	179	158.7	Horizontal
2	4245.6815	-14.20	47.63	33.43	54.00	20.57	166	330.2	Horizontal
3	10994.163	3.44	41.30	44.74	54.00	9.26	199	17	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1056.65	63.90	40.55	-23.35	74.00	33.45	200	15	Vertical
2	2655.5	62.17	43.63	-18.54	68.30	24.67	200	25	Vertical
3	3198.35	61.03	43.73	-17.30	68.30	24.57	200	15	Vertical
4	4125.1	68.56	53.70	-14.86	74.00	20.30	100	192	Vertical
5	10999.95	55.49	59.79	4.30	74.00	14.21	200	51	Vertical
6	17529.65	46.71	55.48	8.77	68.30	12.82	200	226	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4125.0405	-14.86	66.59	51.73	54.00	2.27	122	163.6	Vertical
2	10999.3102	4.30	46.58	50.88	54.00	3.12	190	8.7	Vertical

Mode: Mode 1/ IEEE 802.11 ax HE20 SDM

Channel :5580MHz

Temp. /Hum.:23.9°C/59%RH

Power supply:AC120V/60Hz

Test Engineer: Zhang Zishan

Test Date: 2023-04-16

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1059.4	61.42	36.06	-25.36	74.00	37.94	200	10	Horizontal
2	3171.95	59.75	43.22	-16.53	68.30	25.08	200	31	Horizontal
3	4185.6	66.10	51.83	-14.27	74.00	22.17	200	170	Horizontal
4	9790.15	47.60	52.08	4.48	68.30	16.22	100	257	Horizontal
5	11158.65	48.15	51.99	3.84	74.00	22.01	200	38	Horizontal
6	17495.15	46.86	55.09	8.23	68.30	13.21	100	257	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4184.994	-14.27	64.68	50.41	54.00	3.59	165	167.2	Horizontal
2	11157.0368	3.84	38.16	42.00	54.00	12.00	157	32	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1056.65	64.80	41.45	-23.35	74.00	32.55	100	0	Vertical
2	2661	63.53	44.98	-18.55	68.30	23.32	100	9	Vertical
3	3195.05	63.23	45.93	-17.30	68.30	22.37	100	345	Vertical
4	4185.6	66.75	52.23	-14.52	74.00	21.77	100	345	Vertical
5	11163.25	52.08	55.58	3.50	74.00	18.42	100	350	Vertical
6	17490.55	48.33	57.57	9.24	68.30	10.73	100	329	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4184.994	-14.52	64.56	50.04	54.00	3.96	114	201.9	Vertical
2	11158.7237	3.50	42.58	46.08	54.00	7.92	100	344	Vertical

Mode: Mode 1/ IEEE 802.11 ax HE20 SDM  
 Temp. /Hum.:23.9°C/59%RH  
 Test Engineer: Zhang Zishan

Channel :5700MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-16

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1057.2	62.29	36.93	-25.36	74.00	37.07	100	49	Horizontal
2	2664.3	63.35	44.05	-19.30	68.30	24.25	200	309	Horizontal
3	4000.25	61.17	46.55	-14.62	74.00	27.45	200	298	Horizontal
4	4224.65	66.45	52.20	-14.25	74.00	21.80	200	16	Horizontal
5	9775.2	48.52	52.77	4.25	68.30	15.53	100	251	Horizontal
6	17507.8	47.14	55.26	8.12	68.30	13.04	200	324	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4224.65	-14.25	57.66	43.41	54.00	10.59	200	16	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1057.75	65.78	42.46	-23.32	74.00	31.54	100	49	Vertical
2	1405.9	60.61	38.60	-22.01	74.00	35.40	200	17	Vertical
3	2661	67.68	49.13	-18.55	68.30	19.17	100	27	Vertical
4	3195.05	61.33	44.03	-17.30	68.30	24.27	200	50	Vertical
5	5792.15	59.43	51.84	-7.59	68.30	16.46	200	138	Vertical
6	17540	47.64	56.19	8.55	68.30	12.11	100	293	Vertical

----- The following blanks -----

Mode: Mode 1/ IEEE 802.11 ax HE20 SDM

Channel :5720MHz

Temp. /Hum.:23.9°C/59%RH

Power supply:AC120V/60Hz

Test Engineer: Zhang Zishan

Test Date: 2023-04-16

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBµV/m]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1063.8	63.76	39.30	-24.46	74.00	34.70	100	138	Horizontal
2	2652.75	60.69	41.75	-18.94	68.30	26.55	200	75	Horizontal
3	3188.45	59.16	42.45	-16.71	68.30	25.85	200	150	Horizontal
4	4000.25	61.99	47.94	-14.05	74.00	26.06	200	189	Horizontal
5	4221.9	65.99	52.64	-13.35	74.00	21.36	200	127	Horizontal
6	15015.75	45.04	53.29	8.25	68.30	15.01	200	126	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBµV/m]	AV Value [dBµV/m]	AV Limit [dBµV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4221.9	-13.35	45.36	32.01	54.00	21.99	200	127	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBµV/m]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1062.15	61.16	35.99	-25.17	74.00	38.01	200	304	Vertical
2	1252.45	57.75	35.60	-22.15	68.30	32.70	200	345	Vertical
3	1873.95	60.00	37.81	-22.19	68.30	30.49	100	179	Vertical
4	2657.7	69.93	50.88	-19.05	68.30	17.42	200	170	Vertical
5	5987.95	59.17	52.84	-6.33	68.30	15.46	200	345	Vertical
6	11431.2	48.60	52.45	3.85	74.00	21.55	200	189	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBµV/m]	AV Value [dBµV/m]	AV Limit [dBµV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	11441.124	3.85	34.61	38.46	54.00	15.54	199	144.2	Vertical



Mode: Mode 1/ IEEE 802.11ax HE20 SDM  
 Temp. /Hum.:23.9°C/59%RH  
 Test Engineer: Zhang Zishan

Channel :5745MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-16

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2651.1	60.30	41.18	-19.12	68.30	27.12	200	169	Horizontal
2	4000.25	62.91	47.96	-14.95	74.00	26.04	200	16	Horizontal
3	4263.7	66.50	52.45	-14.05	74.00	21.55	200	16	Horizontal
4	5595.8	56.66	47.83	-8.83	68.30	20.47	200	335	Horizontal
5	6126	55.90	48.95	-6.95	68.30	19.35	200	213	Horizontal
6	17446.85	47.05	54.79	7.74	68.30	13.51	100	256	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4263.7	-14.05	57.36	43.31	54.00	10.69	200	16	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2416.25	63.99	45.02	-18.97	68.30	23.28	100	114	Vertical
2	2643.95	68.15	49.53	-18.62	68.30	18.77	100	15	Vertical
3	3191.2	62.80	45.18	-17.62	68.30	23.12	200	37	Vertical
4	5688.2	63.00	54.35	-8.65	68.30	13.95	100	91	Vertical
5	6001.15	60.21	53.31	-6.90	68.30	14.99	100	236	Vertical
6	17515.85	46.88	55.93	9.05	68.30	12.37	100	140	Vertical

----- The following blanks -----

Mode: Mode 1/ IEEE 802.11 ax HE20 SDM  
 Temp. /Hum.:23.9°C/59%RH  
 Test Engineer: Zhang Zishan

Channel :5785MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-16

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1064.35	62.51	37.26	-25.25	74.00	36.74	200	19	Horizontal
2	2657.15	60.17	40.97	-19.20	68.30	27.33	200	215	Horizontal
3	4000.25	63.29	48.34	-14.95	74.00	25.66	200	1	Horizontal
4	4256.55	65.59	51.54	-14.05	74.00	22.46	200	8	Horizontal
5	5312.55	60.82	50.67	-10.15	68.30	17.63	200	29	Horizontal
6	17510.1	46.30	54.39	8.09	68.30	13.91	200	222	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4000.25	-14.95	55.34	40.39	54.00	13.61	200	1	Horizontal
2	4256.55	-14.05	57.96	43.91	54.00	10.09	200	8	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1061.6	62.63	39.54	-23.09	74.00	34.46	200	6	Vertical
2	2661	61.99	43.46	-18.53	68.30	24.84	100	43	Vertical
3	5684.9	62.08	53.43	-8.65	68.30	14.87	100	142	Vertical
4	6073.75	61.00	53.55	-7.45	68.30	14.75	100	239	Vertical
5	13949.7	44.39	53.61	9.22	68.30	14.69	200	242	Vertical
6	17450.3	47.67	56.33	8.66	68.30	11.97	200	262	Vertical

----- The following blanks -----

Mode: Mode 1/ IEEE 802.11 ax HE20 SDM  
 Temp. /Hum.:23.9°C/59%RH  
 Test Engineer: Zhang Zishan

Channel :5825MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-16

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1063.8	64.97	39.72	-25.25	74.00	34.28	100	344	Horizontal
2	2662.1	59.42	40.16	-19.26	68.30	28.14	200	115	Horizontal
3	4225.75	66.27	52.14	-14.13	74.00	21.86	200	314	Horizontal
4	5314.75	59.81	49.73	-10.08	68.30	18.57	200	344	Horizontal
5	6204.1	57.26	50.53	-6.73	68.30	17.77	200	207	Horizontal
6	17606.7	48.35	54.95	6.60	68.30	13.35	200	124	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4225.75	-14.13	57.33	43.20	54.00	10.80	200	314	Vertical

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1060.5	61.95	38.83	-23.12	74.00	35.17	200	343	Vertical
2	1376.2	60.50	38.47	-22.03	74.00	35.53	100	15	Vertical
3	3173.6	63.94	46.32	-17.62	68.30	21.98	100	4	Vertical
4	5590.3	62.04	53.57	-8.47	68.30	14.73	100	236	Vertical
5	5923.05	61.90	54.69	-7.21	68.30	13.61	100	137	Vertical
6	17525.05	46.86	55.72	8.86	68.30	12.58	100	349	Vertical

----- The following blanks -----

Mode: Mode 1/ IEEE 802.11ac VHT40 SDM

Temp. /Hum.:20.5°C/70%RH

Test Engineer: Zhang Zishan

Channel :5190MHz

Power supply:AC120V/60Hz

Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1064.35	59.48	35.12	-24.36	74.00	38.88	200	313	Horizontal
2	2241.35	55.83	38.44	-17.39	74.00	35.56	200	72	Horizontal
3	4229.6	64.96	52.97	-11.99	74.00	21.03	200	18	Horizontal
4	5070.55	57.28	50.04	-7.24	74.00	23.96	200	127	Horizontal
5	10377.8	55.59	60.85	5.26	68.30	7.45	100	59	Horizontal
6	15006.55	38.75	51.12	12.37	68.30	17.18	100	329	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4229.6	-11.99	48.31	36.32	54.00	17.68	200	18	Horizontal
2	5070.55	-7.24	49.31	42.07	54.00	11.93	200	127	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1375.1	59.49	38.65	-20.84	74.00	35.35	200	9	Vertical
2	1896.5	62.52	40.94	-21.58	68.30	27.36	100	135	Vertical
3	2651.1	60.04	43.20	-16.84	68.30	25.10	200	9	Vertical
4	4929.75	60.71	52.36	-8.35	74.00	21.64	200	290	Vertical
5	5990.7	56.33	51.36	-4.97	68.30	16.94	200	322	Vertical
6	10373.2	59.77	65.58	5.81	68.30	2.72	100	69	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4929.75	-8.35	56.31	47.96	54.00	6.04	200	290	Vertical
2	10379.654	5.81	42.32	48.13	NA	NA	100	41.8	Vertical

Mode: Mode 1/ IEEE 802.11ac VHT40 SDM  
 Temp. /Hum.:20.5°C/70%RH  
 Test Engineer: Zhang Zishan

Channel :5230MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1711.7	66.39	44.19	-22.20	68.30	24.11	100	301	Horizontal
2	2343.65	58.02	39.08	-18.94	74.00	34.92	100	136	Horizontal
3	4221.9	65.09	53.08	-12.01	74.00	20.92	200	16	Horizontal
4	6433.45	52.53	49.46	-3.07	68.30	18.84	200	220	Horizontal
5	10469.8	51.69	54.88	3.19	68.30	13.42	100	33	Horizontal
6	15026.1	45.47	54.56	9.09	68.30	13.74	100	194	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1375.1	59.89	39.05	-20.84	74.00	34.95	200	334	Vertical
2	1874.5	59.16	37.23	-21.93	68.30	31.07	200	16	Vertical
3	5079.35	57.79	50.65	-7.14	74.00	23.35	100	88	Vertical
4	6446.65	53.44	50.42	-3.02	68.30	17.88	100	163	Vertical
5	10459.45	57.33	60.92	3.59	68.30	7.38	100	43	Vertical
6	15681.6	48.79	55.03	6.24	74.00	18.97	100	251	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	5079.35	-7.14	54.32	47.18	54.00	6.82	100	88	Vertical
2	15681.6	6.24	36.94	43.18	54.00	10.82	100	251	Vertical

----- The following blanks -----

Mode: Mode 1/ IEEE 802.11ac VHT40 SDM  
 Temp. /Hum.:20.5°C/70%RH  
 Test Engineer: Zhang Zishan

Channel :5270MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1724.35	60.96	38.81	-22.15	68.30	29.49	100	303	Horizontal
2	2812.25	56.14	39.92	-16.22	74.00	34.08	100	192	Horizontal
3	4248.3	65.74	53.79	-11.95	74.00	20.21	200	16	Horizontal
4	5257.55	56.38	49.35	-7.03	68.30	18.95	100	180	Horizontal
5	10525	52.56	55.64	3.08	68.30	12.66	100	25	Horizontal
6	16426.8	49.26	55.06	5.80	68.30	13.24	200	260	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4248.3	-11.95	54.56	42.61	54.00	11.39	200	16	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1406.45	59.55	38.75	-20.80	74.00	35.25	100	16	Vertical
2	1874.5	58.93	37.00	-21.93	68.30	31.30	200	17	Vertical
3	5058.45	58.53	50.95	-7.58	74.00	23.05	200	296	Vertical
4	6426.85	53.61	50.28	-3.33	68.30	18.02	100	180	Vertical
5	10538.8	56.75	59.71	2.96	68.30	8.59	100	21	Vertical
6	16716.6	48.58	54.27	5.69	68.30	14.03	100	98	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	5058.45	-7.58	54.32	46.74	54.00	7.26	200	296	Vertical

Mode: Mode 1/ IEEE 802.11ac VHT40 SDM  
 Temp. /Hum.:20.5°C/70%RH  
 Test Engineer: Zhang Zishan

Channel :5310MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1268.4	56.87	35.27	-21.60	68.30	33.03	100	321	Horizontal
2	2257.3	56.44	39.02	-17.42	74.00	34.98	100	299	Horizontal
3	4240.6	64.23	52.26	-11.97	74.00	21.74	200	15	Horizontal
4	6464.25	54.20	51.34	-2.86	68.30	16.96	100	91	Horizontal
5	11326.55	48.75	52.12	3.37	74.00	21.88	200	102	Horizontal
6	15677	48.50	52.95	4.45	74.00	21.05	100	21	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4238.207	-11.97	46.99	35.02	54.00	18.98	165	166.7	Horizontal
2	11326.55	3.37	47.56	50.93	54.00	3.07	200	102	Horizontal
3	15677	4.45	36.89	41.34	54.00	12.66	100	21	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1374.55	60.39	39.54	-20.85	74.00	34.46	200	355	Vertical
2	1727.65	61.76	40.91	-20.85	68.30	27.39	200	272	Vertical
3	3170.3	58.35	42.52	-15.83	68.30	25.78	100	15	Vertical
4	5528.7	58.07	51.51	-6.56	68.30	16.79	100	146	Vertical
5	10607.8	53.50	55.37	1.87	74.00	18.63	100	44	Vertical
6	13887.6	45.61	53.19	7.58	68.30	15.11	100	208	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	10615.321	1.87	45.22	47.09	54.00	6.91	100	41.4	Vertical

Mode: Mode 1/ IEEE 802.11ac VHT40 SDM  
 Temp. /Hum.:20.5°C/70%RH  
 Test Engineer: Zhang Zishan

Channel :5510MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1245.3	57.62	34.96	-22.66	68.30	33.34	100	322	Horizontal
2	1714.45	60.10	36.81	-23.29	68.30	31.49	200	314	Horizontal
3	2861.2	56.31	38.62	-17.69	74.00	35.38	200	14	Horizontal
4	4233.45	67.30	53.07	-14.23	74.00	20.93	200	325	Horizontal
5	9898.25	47.98	52.04	4.06	68.30	16.26	200	233	Horizontal
6	13256.25	46.19	53.25	7.06	74.00	20.75	100	16	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4233.45	-14.23	54.32	40.09	54.00	13.91	200	325	Horizontal
2	13256.25	7.06	39.12	46.18	54.00	7.82	100	16	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1058.3	59.86	36.55	-23.31	74.00	37.45	200	16	Vertical
2	1385.55	56.84	34.90	-21.94	74.00	39.10	100	32	Vertical
3	2460.8	58.00	38.25	-19.75	68.30	30.05	200	332	Vertical
4	4221.9	66.91	52.68	-14.23	74.00	21.32	200	321	Vertical
5	8051.35	49.71	49.26	-0.45	74.00	24.74	100	220	Vertical
6	9860.3	47.36	51.54	4.18	68.30	16.76	200	102	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4221.9	-14.23	51.25	37.02	54.00	16.98	200	321	Vertical
2	8051.35	-0.45	46.36	45.91	54.00	8.09	100	220	Vertical



Mode: Mode 1/ IEEE 802.11ac VHT40 SDM

Channel :5550MHz

Temp. /Hum.:20.5°C/70%RH

Power supply:AC120V/60Hz

Test Engineer: Zhang Zishan

Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1057.75	61.90	36.55	-25.35	74.00	37.45	100	0	Horizontal
2	1838.75	57.08	34.88	-22.20	68.30	33.42	100	245	Horizontal
3	2201.2	56.20	37.37	-18.83	74.00	36.63	100	54	Horizontal
4	3150.5	56.68	40.21	-16.47	68.30	28.09	100	291	Horizontal
5	4245	67.29	53.09	-14.20	74.00	20.91	200	17	Horizontal
6	9799.35	47.68	52.30	4.62	68.30	16.00	100	72	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4250.099	-14.20	46.37	32.17	54.00	21.83	198	10	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1061.6	61.41	38.20	-23.21	74.00	35.80	100	2	Vertical
2	1406.45	59.97	37.95	-22.02	74.00	36.05	200	24	Vertical
3	1893.75	65.65	42.86	-22.79	68.30	25.44	100	175	Vertical
4	4163.05	66.08	51.39	-14.69	74.00	22.61	100	152	Vertical
5	6010.5	57.10	49.55	-7.55	68.30	18.75	100	141	Vertical
6	9741.85	48.01	52.15	4.14	68.30	16.15	200	216	Vertical

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBμV/m]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4162.5678	-14.69	60.74	46.05	54.00	7.95	186	195.5	Vertical

Mode: Mode 1/ IEEE 802.11ac VHT40 SDM  
 Temp. /Hum.:20.5°C/70%RH  
 Test Engineer: Zhang Zishan

Channel :5670MHz  
 Power supply:AC120V/60Hz  
 Test Date: 2023-04-21

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBµV/m]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1219.45	57.53	34.08	-23.45	74.00	39.92	100	21	Horizontal
2	2549.35	55.99	37.28	-18.71	68.30	31.02	100	195	Horizontal
3	4263.7	68.02	53.88	-14.14	74.00	20.12	200	7	Horizontal
4	5769.05	55.87	48.27	-7.60	68.30	20.03	100	175	Horizontal
5	9810.85	47.30	51.94	4.64	68.30	16.36	100	330	Horizontal
6	14643.15	45.19	53.12	7.93	68.30	15.18	200	264	Horizontal

AV Final Data List									
NO.	Freq. [MHz]	Factor [dB]	AV Reading [dBµV/m]	AV Value [dBµV/m]	AV Limit [dBµV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	4252.4695	-14.14	50.51	36.37	54.00	17.63	169	185.3	Horizontal

Suspected Data List									
NO.	Freq. [MHz]	Reading [dBµV/m]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1056.65	62.97	39.62	-23.35	74.00	34.38	200	19	Vertical
2	1406.45	60.39	38.37	-22.02	74.00	35.63	200	324	Vertical
3	1876.15	59.72	36.65	-23.07	68.30	31.65	200	19	Vertical
4	4247.75	59.79	45.78	-14.01	74.00	28.22	100	29	Vertical
5	5923.6	59.27	51.87	-7.40	68.30	16.43	100	139	Vertical
6	9791.3	48.73	53.48	4.75	68.30	14.82	200	136	Vertical

----- The following blanks -----