

**RF EXPOSURE EVALUATION**

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

Measurement Result

**BT:**

Operation Frequency: 2402MHz~2480MHz  
 Power density limited: 1mW/ cm<sup>2</sup>

Antenna Type: External antenna

BT antenna gain: 5 dBi ;

R=20cm

mW=10^(dBm/10)

Antenna	Tune-up limit (dBm)	Gain (dBi)	EIRP (dBm)	EIRP (mW)	R(cm)	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Conclusion
BLE ANT	5.33	5	10.33	10.79	20	0.00215	1	Pass

**2.4G/5G WIFI:**

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,  
 WIFI 802.11n HT40:2422-2452MHz  
 Power density limited: 1mW/ cm<sup>2</sup>

Operation Frequency:

WIFI 802.11a/ac/n(HT20): 5180-5240MHz; 5745-5825MHz;

WIFI 802.11ac/n(HT40): 5190-5230MHz; 5755-5795MHz;

WIFI 802.11ac80:5210-5210MHz; 5775-5775MHz

Power density limited: 1mW/cm

Antenna Type: External antenna

2.4G WIFI antenna1/2/3/4 gain: 5 dBi

5G WIFI antenna1/2/3/4 gain: 5 dBi

R=20cm

mW=10^(dBm/10)

**WLAN2.4G SISO MODE**

Antenna	Tune-up limit (dBm)	Gain (dBi)	EIRP (dBm)	EIRP (mW)	R(cm)	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Conclusion
Ant 1	18.04	5	23.04	201.37	20	0.04006	1	Pass
Ant 2	18.25	5	23.25	211.35	20	0.04205	1	
Ant 3	18.20	5	23.2	208.93	20	0.04156	1	
Ant 4	18.18	5	23.18	207.97	20	0.04137	1	

**WLAN5.2G SISO MODE**

Antenna	Tune-up limit (dBm)	Gain (dBi)	EIRP (dBm)	EIRP (mW)	R(cm)	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Conclusion
Ant 1	10.03	5	15.03	31.84	20	0.00633	1	Pass
Ant 2	10.01	5	15.01	31.70	20	0.00631	1	
Ant 3	9.95	5	14.95	31.26	20	0.00622	1	
Ant 4	9.82	5	14.82	30.34	20	0.00604	1	

### WLAN5.8G SISO MODE

Antenna	Tune-up limit (dBm)	Gain (dBi)	EIRP (dBm)	EIRP (mW)	R(cm)	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Conclusion
Ant 1	8.84	5	13.84	24.21	20	0.00482	1	Pass
Ant 2	8.79	5	13.79	23.93	20	0.00476	1	
Ant 3	8.74	5	13.74	23.66	20	0.00471	1	
Ant 4	8.62	5	13.62	23.01	20	0.00458	1	

### SIMULTANEOUS TRANSMISSIONS

When a number of sources at different frequencies, and/or broadband sources, contribute to the total exposure, it becomes necessary to weigh each contribution relative to the MPE. To comply with the MPE, the fraction of the MPE in terms of E<sup>2</sup>, H<sup>2</sup> (or power density) incurred within each frequency interval should be determined and the sum of all such fractions should not exceed unity. In order to ensure compliance with the MPE for a controlled environment, the sum of the ratios of the power density to the corresponding MPE should not exceed unity. That is

$$\sum_{i=1}^n \frac{S_i}{MPE_i} \leq 1$$

### Max. SIMULTANEOUS TRANSMISSIONS for BLE Module + Wi-Fi Module

Band	Tune-up limit (dBm)	Gain (dBi)	EIRP (dBm)	EIRP (mW)	R(cm)	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Calculation result	Conclusion
BLE	5.33	3	8.33	6.81	20	0.00215	1	0.9401	Pass
5G n71						0.1989	0.2220		
WIFI 2.4	18.25	5	23.25	211.35	20	0.04205	1		

Note:

1. 5G n71 Test data reference to FCC ID: XMR2020RM502QAE.
2. NO simultaneous transmissions are possible for this device of LTE1 Module + LTE2 Module.
3. NO simultaneous transmissions are possible for this device of Wi-Fi 5G + Wi-Fi 2.4G.

Signature:

Date: 2022-8-29



**NAME AND TITLE** (Please print or type): Alex/Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.