



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V04  
Report Template Revision Date: 2018-07-06

# RF Exposure Evaluation Report

**Report No.:** CQASZ2020090939E-02

**Applicant:** Aiwa Electronics International Co., Ltd

**Address of Applicant:** 4F., No. 24, Ln. 141, Sec. 3, Beishen Rd., Shenkeng Dist., New Taipei City 222, Taiwan (R.O.C.)

**Equipment Under Test (EUT):**

**EUT Name:** Bluetooth headset

**Model No.:** AT-X80J, aiwa AT-X80J

**Test Model No.:** AT-X80J

**Brand Name:** aiwa

**FCC ID:** 2AW6XATX80J

**Standards:** 47 CFR Part 1.1307

47 CFR Part 2.1093

KDB447498D01 General RF Exposure Guidance v06

**Date of Receipt:** 2020-08-27

**Date of Test:** 2020-08-27 to 2020-09-07

**Date of Issue:** 2020-09-14

**Test Result:** PASS\*

\*In the configuration tested, the EUT complied with the standards specified above

**Tested By:**

Tiny You

( Tiny You )

**Reviewed By:**

Sheek, Luo

( Sheek Luo )

**Approved By:**

Jack Ai



## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20200800939E-02	Rev.01	Initial report	2020-09-14

## 2 Contents

	Page
1 VERSION .....	2
2 CONTENTS .....	3
3 GENERAL INFORMATION .....	4
3.1 CLIENT INFORMATION .....	4
3.2 GENERAL DESCRIPTION OF EUT .....	4
4 SAR EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 Standard Requirement.....	5
4.1.2 Limits .....	5
4.1.3 EUT RF Exposure.....	6

### 3 General Information

#### 3.1 Client Information

Applicant:	Aiwa Electronics International Co., Ltd
Address of Applicant:	4F., No. 24, Ln. 141, Sec. 3, Beishen Rd., Shenkeng Dist., New Taipei City 222, Taiwan (R.O.C.)
Manufacturer:	Shenzhen Haohua Digital Technology Co., Ltd
Address of Manufacturer:	Room 2101, building a, Bantian International Center, Longgang District, Shenzhen City, Guangdong Province
Factory:	Shenzhen Haohua Digital Technology Co., Ltd
Address of Factory:	Room 2101, building a, Bantian International Center, Longgang District, Shenzhen City, Guangdong Province

#### 3.2 General Description of EUT

Product Name:	Bluetooth headset
Model No.:	AT-X80J, aiwa AT-X80J
Test Model No.:	AT-X80J
Trade Mark:	aiwa
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V5.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, π/4DQPSK
Number of Channel:	79
Transfer Rate:	1Mbps/2Mbps
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Test Software of EUT:	FCC Assist 1.0.1.2 (manufacturer declare)
Antenna Type:	Chip Antenna
Antenna Gain:	0.5 dBi
Power Supply:	lithium battery:DC3.7V, Charge by DC5V

Note:

1. Since the RF parameters of the left and right earplugs are the same, only the right ear was tested in this report.
2. Model No.: AT-X80J, aiwa AT-X80J

Only the model AT-X80J was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

## 4 SAR Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

##### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

#### 4.1.3 EUT RF Exposure

##### Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance		Maximum tune-up Power
		(dBm)	(dBm)	(dBm)
Lowest(2402MHz)	-5.710	-6.5±1	-5.5	0.282
Middle(2441MHz)	-6.090	-7.0±1	-6.0	0.251
Highest(2480MHz)	-6.170	-7.0±1	-6.0	0.251
π/4DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance		Maximum tune-up Power
		(dBm)	(dBm)	(dBm)
Lowest(2402MHz)	-4.870	-5.5±1	-4.5	0.355
Middle(2441MHz)	-5.280	-6.0±1	-5.0	0.316
Highest(2480MHz)	-5.410	-6.0±1	-5.0	0.316

##### Worst case: π/4DQPSK

Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	-4.870	-5.5±1	-4.5	0.355	0.110	3.0
Middle (2441MHz)	-5.280	-6.0±1	-5.0	0.316	0.099	
Highest (2480MHz)	-5.410	-6.0±1	-5.0	0.316	0.100	

Conclusion: the calculated value ≤3.0, SAR is exempted.

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20200800939E-01