

RF Exposure Evaluation

FCC ID: 2AW72-K1PLUS

1. Client Information

Applicant	:	GUANGDONG AP TENON SCI.&TECH. CO., LTD.
Address	:	No.3, Zexi Street, Hanxi Business Center, Panyu, GuangZhou, China
Manufacturer	:	GUANGDONG AP TENON SCI.&TECH. CO., LTD.
Address	:	No.3, Zexi Street, Hanxi Business Center, Panyu, GuangZhou, China

2. General Description of EUT

EUT Name	:	SMART LOCK
Model(s) No.	:	K1 Plus, K Series
Model Difference	:	All PCB boards and circuit diagrams are the same, the only difference is that appearance and name.
Product Description	Operation Frequency:	Bluetooth 5.1(BLE): 2402MHz~2480MHz
	Number of Channel:	BLE:40 channels
	Antenna Gain:	2dBi Ceramic Antenna
	Modulation Type:	GFSK
	Bit Rate of Transmitter:	1/2Mbps
Power Supply	:	Input: DC 6V/1A
Li-ion Polymer Battery	:	DC 1.5V by AAA battery*4
Software Version	:	V102
Hardware Version	:	V1.0.1
Remark: The antenna gain provided by the applicant, the adapter and verified for the RF conduction test and adapter provided by TOBY test lab.		

Note: More test information about the EUT please refer the RF Test Report.

SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

(1) Clause 4.3: General SAR test reduction and exclusion guidance

Sub clause 4.31: Standalone SAR test exclusion considerations

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance ≤ 5 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f(\text{GHz})}] \leq 7.5.0$ for 10-g SAR

2. Calculation:

Test separation: 5mm						
Bluetooth LE Mode(1Mbps)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	7.043	7±1	8	6.310	1.956	3.0
2.440	7.071	7±1	8	6.310	1.971	3.0
2.480	7.174	7±1	8	6.310	1.987	3.0
Bluetooth LE Mode(2Mbps)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	6.113	6±1	7	5.012	1.554	3.0
2.440	6.322	6±1	7	5.012	1.566	3.0
2.480	6.429	6±1	7	5.012	1.579	3.0

Conclusion:

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

-----END OF REPORT-----