

# Acknowledgment

## SPECIFICATION FOR APPROVAL

CUSTOMER: ZLGD-A1-0302

PART NO. : ZLGD-Y17×39-130-FR

DESCRIPTION: coil+hard ferrite sheet

SPECIFICATION: 17x39,0.08x24P×2P, from ferrite sheet130mm

DATE: 20240326

TRX APPROVAL		
Production	Audit	Recognition date
Xiaoxian Zeng	Zhihui Qiu	20240326
CUSTOMER APPROVAL		
Project	Approved	Recognition date
Result:	<input type="checkbox"/> Qualified	<input type="checkbox"/> Disqualified <input type="checkbox"/> Other

**Dongguan city DFL Electronic Technology Co.,LTD**

107 Xinfeng West Road, Shijie, Dongguan, Guangdong,

TEL: 0769-86016320 FAX: 0769-86372427

# Dongguan city DFL Electronic Technology Co., LTD

SPECIFICATION																																				
DESC :	ZLGD-Y17×39-130-FR	version Rev:A	Customer:	ZLGD-A1-0302																																
			Description:	coil+hard ferrite sheet																																
			Date:	20240326																																
1、 DIMENSION:(mm)			<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>A</td><td>17.0±1.0</td></tr> <tr><td>B</td><td>39.0±1.5</td></tr> <tr><td>C</td><td>130.0±4.0</td></tr> <tr><td>D</td><td>3.0±2.0</td></tr> <tr><td>E</td><td>44.0±1.0</td></tr> <tr><td>F</td><td>0.8±0.2</td></tr> <tr><td>G</td><td>120.0±4.0</td></tr> <tr><td>H</td><td></td></tr> <tr><td>I</td><td></td></tr> <tr><td>J</td><td></td></tr> <tr><td>K</td><td></td></tr> <tr><td>L</td><td></td></tr> <tr><td>M</td><td></td></tr> <tr><td>N</td><td></td></tr> <tr><td>O</td><td></td></tr> <tr><td>P</td><td></td></tr> </table>		A	17.0±1.0	B	39.0±1.5	C	130.0±4.0	D	3.0±2.0	E	44.0±1.0	F	0.8±0.2	G	120.0±4.0	H		I		J		K		L		M		N		O		P	
A	17.0±1.0																																			
B	39.0±1.5																																			
C	130.0±4.0																																			
D	3.0±2.0																																			
E	44.0±1.0																																			
F	0.8±0.2																																			
G	120.0±4.0																																			
H																																				
I																																				
J																																				
K																																				
L																																				
M																																				
N																																				
O																																				
P																																				
			<p>Note:</p> <ol style="list-style-type: none"> <li>1. The coil is pasted with G44*0.8 hard ferrite</li> <li>2. Wrap 8MM high-temperature tape around the coil outlet position.</li> <li>3. Double-sided tape for ears attached to the back of the ferrite sheet</li> <li>4. Two leads and 1.5 CB * 120mm tube</li> <li>5. The coil cannot be loosened</li> </ol>																																	
2、 schematic diagram:																																				
3、 WindingSpecification:																																				
NO.	TERMINAL	WIRE	Turns	Winding Direction																																
1		0.08×24P×2P Hot Stranded wire	11TS	Counterclockwise																																
4、 ELECTRICAL CHARACTERISTICS:																																				
TEMPERATURE:25±10°C,RELATIVE HUMIDITY:65±20%																																				
NO.	ITEM	TERMINAL	SPECIFICATION	TEST FREQUENCY	TEST EQUIPMENTS																															
1	IND.		6.8UH ± 0.3 with hard ferrite added	100KHz/1.0V	SHDA 1062																															
2	IND.																																			
3	Q value																																			
4	DCR																																			
PREPARED BY/DATE		CHECKED BY/DATE		CUSTOMEU/DATE																																