## SPECIFICATION FOR APPROVAL



Specification number	HG20231018002		
Effective date			

Customer	Yitianyuan electronic Technology Co., LTD		
Product type	MG2Scoil L=35MM		
Honggui P/N	43.5*0.8 double slot with hole 12 rings back round white glue		
Customer P/N			

【☑New edition issued, □version revised】 【This specification contains 3 pages of contents】
【RoHS Compliant Parts 】

AUTHOR	СНЕСК	APPROVE
Peng Jianji		

## Anfu Honggui Electronics Co., LTD

This SPECIFICATION FOR APPROVAL must be signed and returned to the customer within one week of receipt. Overdue production shall be regarded as following the standards of this acknowledgement.

Customer approval Recognition status:	☑Full admission □Conditio □Denial	nal admission I	Date:
APPROVE	AUDIT	RECHECK	CHECK

## SPECIFICATION FOR APPROVAL

2		SPECIFICATI	ON FOR A	FFROVAL			
Customer	Yidangyuan ele	ectronic Technology Co., LTD	Customer P/N				
Honggui P/N	43.5*0.8 double slot v	with hole 12 rings back round white glue	Specification number	HG20231018002	Edition	01	
◆Boundary Dimension					(Unit: mm)	*	
				A	43.5 ±.0.5		
	The Part of the Pa			В	40.0 ±1.5		
	, č	H www		С	15.0 ±0.5		
	D_	- MAX		D	5.3		
		H /		E			
			X		37.0 ±2		
	WWW LAND	\       /	0	F	35.0 ±2		
		)    \	0	G 	3.0 ±1		
			/	Н	2.5 ±0.2		
		, ,	The state of the s	1	0.8 ±0.1		
		1-11			Ј 8		
P	Fi			1.Wire diameter: 0.08*105P silk-covered self-adhesive copper wire			
				2.Number of coils wound: 12TS			
	•	- J		3.Whether the start and end lines cross: Yes     4.Wrap coil with 8mm wide high temperature tape			
				5.The coil and magnetic disk must be centered			
(front view) (side view)			(bottom view)	6.Disc back round 42 white glue			
-	101001111110000000	Parameter					
LO	Specificati		ndition	Test instrument			
LO	6.8±0.3	100 (0.00)	Hz/1V	■TH1816B			
Q DCR	>30		Hz/1V 5°C	■TH1816B			
DCR	X00		ating temperature	■CH-502BC			
		966	-40°C ~125°C				
8		<b>A</b> I	Bill of materials				
Serials			on or materials				
1	Materials	Specification	Suppliers	Notes			
2	Magnetic sheet	43.5 *0.8 Double slots with hole	s	PC95Mn-Zn			
3	Copper wire	0.08*105P		Silk-covered self-adhesive copper wire			
4 H	igh-temperature tape	8MM		Ed	co-friendly adhesive tape		
5	Tin	High temperature tin bar		Thous	Thousand island environmental tin		
6	Glue	White glues		Eco-friendly adhesive			
7	Adhesive backing	42 rounds of white glue					
AUTHOR CHECK		<	APPROVE				
	Peng Jianji						