



RF EXPOSURE REPORT

Report No: STS2201129H02

Issued for

Litum bilgi teknolojileri san. Ve dis tic. A.S

Sevket Ozcelik sok. No29 Alsancak izmir Turkey

Product Name:	430 Collision Warning System
Brand Name:	Litum
Model Name:	430
Series Model:	4300000001, 4300000002, 4300000003
FCC ID:	2AW7W430
Test Standard:	FCC 47CFR §2.1093

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, all test data presented in this report is only applicable to presented test sample.

Shenzhen STS Test Services Co., Ltd.
A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ,
Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China
TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail:sts@stsapp.com





Test Report Certification

Applicant's Name..... : Litum bilgi teknolojileri san. Ve dis tic. A.S
Address : Sevket Ozcelik sok. No29 Alsancak izmir Turkey
Manufacturer's Name : Litum bilgi teknolojileri san. Ve dis tic. A.S
Address : Sevket Ozcelik sok. No29 Alsancak izmir Turkey

Product Description

Product Name..... : 430 Collision Warning System
Brand Name : Litum
Model Name : 430
Series Model..... : 4300000001, 4300000002, 4300000003

Standards..... : FCC 47CFR §2.1093

This report shall not be reproduced except in full, without the written approval of STS, this document only be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test..... :

Date of receipt of test item : 22 Feb. 2022

Date (s) of performance of tests..... : 22 Feb. 2022 ~ 03 Mar. 2022

Date of Issue..... : 03 Mar. 2022

Test Result..... : **Pass**

Testing Engineer :

(Chris Chen)

Technical Manager :

(Sean she)

Authorized Signatory :

(Vita Li)





TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST FACTORY	5
2. FCC 47CFR §2.1093 REQUIREMENT	6
2.1 DETERMINATION OF EXEMPTION	6
2.2 TEST RESULT	8





Revision History

Rev.	Issue Date	Report No.	Effect Page	Contents
00	03 Mar. 2022	STS2201129H02	ALL	Initial Issue





1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF THE EUT

Product Name	430 Collision Warning System	
Brand Name	Litum	
Model Name	430	
Series Model	4300000001, 4300000002, 4300000003	
Model Difference	Only difference in model name.	
Product Description	The EUT is 430 Collision Warning System	
	Operation Frequency:	6489.6MHz
	Modulation Type:	BPM with BPSK
	Antenna gain:	Ceramic Antenna
	Antenna Designation:	3.3dBi
Rating	Input: 9-30V	
Hardware version number	AFA01-01-02	
Software version number	1.15.15.0	

1.2 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01



2. FCC 47CFR §2.1093 REQUIREMENT

2.1 DETERMINATION OF EXEMPTION

For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if:

(A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of Part 1.1307. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);



(C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

RF Source frequency (MHz)	Threshold ERP(watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2f$.
1,500-100,000	$19.2R^2$.



2.2 TEST RESULT

TURN UP POWER

Mode	Field Strength	EIRP
UWB	60.05dBuV/m	-35.15dBm (+/- 1dBm)
2.4G SRD	94.26dBuV/m	-0.94dBm(+/- 1dBm)

Remark: dBm= dBuV/m-95.2

ANT Gain (G)

Antenna Gain: 3.3dBi (gain of antenna in linear scale=2.14)

Mode	Frequency (GHz)	Separation distance (cm)	Max EIRP (dBm)	Max EIRP (mW)	Limit (mW)
UWB	6.4896	20	-34.15	0.00004	1
2.4G SRD	2.432	20	0.06	1.01	3060

Simultaneous Transmission:

UWB/1 mW +2.4G SRD/3060 mW

= $0.00029/1+1.01/3060=0.00062<1$

Conclusion: the maximum power is less than the limit, complies with the exemption requirements.

※※※※※END OF THE REPORT※※※※※