CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China
Tel: +86-755- 27521059 Fax: +86-755- 27521011 Http://www.sz-ctc.org.cn

TEST REPORT

Report No. ·····:	**CTC20231811E03**
FCC ID·····:	**2AWAA-T12M**
Applicant·····:	**ZHEJIANG DALI TECHNOLOGY CO., LTD**
Address·····:	NO639 Binkang Road, Hangzhou, P.R.CHINA, 310053
Manufacturer·····:	ZHEJIANG DALI TECHNOLOGY CO., LTD
Address·····:	NO639 Binkang Road, Hangzhou, P.R.CHINA, 310053
Product Name·····:	**Thermal Imaging Camera**
Trade Mark·····:	/
Model/Type reference·····:	T12-M
Listed Model(s) ·····:	T12, IR12, IR12-M
Standard·····:	**FCC CFR Title 47 Part 15 Subpart C Section 15.247**
Date of receipt of test sample…:	Sept. 06, 2023
Date of testing……..:	Sept. 07, 2023 ~ Oct. 31, 2023
Date of issue……....:	Nov. 01, 2023
Result……:	**PASS**

Compiled by: (Printed name+signature)	Terry Su	
Supervised by: (Printed name+signature)	Eric Zhang	
Approved by: (Printed name+signature)	Totti Zhao	

Testing Laboratory Name……:	**CTC Laboratories, Inc.**
Address……..:	1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

This test report may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CTC. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CTC within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit. The test report merely correspond to the test sample.

Table of Contents **Page**

1. TEST SUMMARY 3

1.1. TEST STANDARDS 3
1.2. REPORT VERSION 3
1.3. TEST DESCRIPTION 4
1.4. TEST FACILITY 5
1.5. MEASUREMENT UNCERTAINTY 5
1.6. ENVIRONMENTAL CONDITIONS 6

2. GENERAL INFORMATION 7

2.1. CLIENT INFORMATION 7
2.2. GENERAL DESCRIPTION OF EUT 8
2.3. ACCESSORY EQUIPMENT INFORMATION 9
2.4. OPERATION STATE 10
2.5. MEASUREMENT INSTRUMENTS LIST 11

3. TEST ITEM AND RESULTS 13

3.1. CONDUCTED EMISSION 13
3.2. RADIATED EMISSION 16
3.3. BAND EDGE EMISSIONS (RADIATED) 45
3.4. BAND EDGE AND SPURIOUS EMISSIONS (CONDUCTED) 62
3.5. DTS BANDWIDTH 97
3.6. MAXIMUM CONDUCTED OUTPUT POWER 107
3.7. POWER SPECTRAL DENSITY 109
3.8. DUTY CYCLE 119
3.9. ANTENNA REQUIREMENT 129

1. TEST SUMMARY

1.1. Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Operation within the bands of 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz.
RSS 247 Issue 2: Standard Specifications for Frequency Hopping Systems (FHSs) and Digital Transmission Systems (DTSs) Operating in the Bands 902-928MHz, 2400-2483.5MHz and 5725-5850MHz.
ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

1.2. Report version

Revised No.	Date of issue	Description
01	Nov. 01, 2023	Original

1.3. Test Description

FCC Part 15 Subpart C (15.247) / RSS 247 Issue 2				
Test Item	Standard Section		Result	Test Engineer
	FCC	IC		
Antenna Requirement	15.203	/	Pass	Alicia Liu
Conducted Emission	15.207	RSS-Gen 8.8	Pass	Cecilia Luo
Radiated Band Edge and Spurious Emissions	15.205&15.209& 15.247(d)	RSS 247 5.5	Pass	Alicia Liu
Conducted Band Edge and Spurious Emissions	15.247(d)	RSS 247 5.5	Pass	Alicia Liu
6dB Bandwidth	15.247(a)(2)	RSS 247 5.2 (a)	Pass	Alicia Liu
Conducted Max Output Power	15.247(b)(3)	RSS 247 5.4 (d)	Pass	Alicia Liu
Power Spectral Density	15.247(e)	RSS 247 5.2 (b)	Pass	Alicia Liu
Transmitter Radiated Spurious	15.209&15.247(d)	RSS 247 5.5& RSS-Gen 8.9	Pass	Alicia Liu

Note: The measurement uncertainty is not included in the test result.

1.4. Test Facility

CTC Laboratories, Inc.

Add: 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

A2LA-Lab Cert. No.: 4340.01

CTC Laboratories, Inc. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

Industry Canada (Registration No.: 9783A, CAB Identifier: CN0029)

CTC Laboratories, Inc. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 9783A on Jan, 2016.

FCC (Registration No.: 951311, Designation Number CN1208)

CTC Laboratories, Inc. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained inour files. Registration 951311, Aug 26, 2017.

1.5. Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01" Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the CTC Laboratories, Inc. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Below is the best measurement capability for CTC Laboratories, Inc.

Test Items	Measurement Uncertainty	Notes
DTS Bandwidth	±0.0196%	(1)
Maximum Conducted Output Power	±0.686 dB	(1)
Maximum Power Spectral Density Level	±0.743 dB	(1)
Band-edge Compliance	±1.328 dB	(1)
Unwanted Emissions In Non-restricted Freq Bands	9kHz-1GHz: ±0.746dB 1GHz-26GHz: ±1.328dB	(1)
Conducted Emissions 9kHz~30MHz	±3.08 dB	(1)
Radiated Emissions 30~1000MHz	±4.51 dB	(1)
Radiated Emissions 1~18GHz	±5.84 dB	(1)
Radiated Emissions 18~40GHz	±6.12 dB	(1)

Note (1): This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.6. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	21°C ~ 27°C
Relative Humidity:	40% ~ 60%
Air Pressure:	101kPa

2. GENERAL INFORMATION

2.1. Client Information

Applicant:	ZHEJIANG DALI TECHNOLOGY CO., LTD
Address:	NO639 Binkang Road, Hangzhou, P.R.CHINA, 310053
Manufacturer:	ZHEJIANG DALI TECHNOLOGY CO., LTD
Address:	NO639 Binkang Road, Hangzhou, P.R.CHINA, 310053

2.2. General Description of EUT

Product Name:	Thermal Imaging Camera
Trade Mark:	/
Model/Type reference:	T12-M
Listed Model(s):	T12, IR12, IR12-M
Model Different:	All these models are identical in the same PCB, layout and electrical circuit, The only difference is sales channels
Power supply:	5Vdc from USB Cable 3.6Vdc from 6200mAh Li-ion Battery
Adapter Model:	CD104 Input: 100-240V~ 50/60Hz 0.6A Output: 5Vdc/3.4A
Hardware version:	/
Software version:	/
WIFI 802.11b/ g/ n(HT20)/ n(HT40)	
Modulation:	802.11b: DSSS(CCK, DQPSK, DBPSK) 802.11g/n: OFDM(BPSK, QPSK, 16QAM, 64QAM)
Operation frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz 802.11n(HT40): 2422MHz~2452MHz
Channel number:	802.11b/g/n(HT20):11channels 802.11n(HT40):7channels
Channel separation:	5MHz
Antenna type:	FPC Antenna
Antenna 1 gain:	2.8dBi Max
Antenna 2 gain:	0.5dBi Max
Antenna 1 and 2 Directional gain:	4.74dBi

2.3. Accessory Equipment information

Equipment Information			
Name	Model	S/N	Manufacturer
Notebook	ThinkBook 14G3 ACL	MP246QDR	Lenovo
/	/	/	/
Cable Information			
Name	Shielded Type	Ferrite Core	Length
/	/	/	/
Test Software Information			
Name	Versions	/	/
Qualcomm Radio Control Tool	2.5.0	/	/

2.4. Operation state

Operation Frequency List: The EUT has been tested under typical operating condition. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing.

Operation Frequency List:

Channel	Frequency (MHz)
01	2412
02	2417
03	2422
04	2427
05	2432
06	2437
07	2442
08	2447
09	2452
10	2457
11	2462

Note: CH 01~CH 11 for 802.11b/g/n(HT20), CH 03~CH 09 for 802.11n(HT40)

Data Rated

Preliminary tests were performed in different data rate, and found which the below bit rate is worst case mode, so only show data which it is a worst case mode.

Mode	Data rate (worst mode)
802.11b	1Mbps
802.11g	6Mbps
802.11n(HT20)	HT-MCS0
802.11n(HT40)	HT-MCS0

Test mode

For RF test items:
The engineering test program was provided and enabled to make EUT continuous transmit.
For AC power line conducted emissions:
The EUT was set to connect with the WLAN AP under large package sizes transmission.
For Radiated spurious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data Recorded in the report.

2.5. Measurement Instruments List

RF Test System					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated Until
1	Spectrum Analyzer	R&S	FSV40-N	101331	Mar. 14, 2024
2	Spectrum Analyzer	R&S	FSV40-N	101654	Aug. 07, 2024
3	Spectrum Analyzer	R&S	FSU26	100105	Dec. 16, 2023
4	MXA Signal Analyzer	Keysight	N9020A	MY46471737	Dec. 16, 2023
5	MXA Signal Analyzer	Keysight	N9020A	MY52091402	Aug. 22, 2024
6	MXG Vector Signal Generator	Agilent	N5182A	MY47420864	Dec. 16, 2023
7	PSG Analog Signal Generator	Agilent	E8257D	MY46521908	Dec. 16, 2023
8	EXG Analog Signal Generator	Keysight	N5173B	MY59100842	Dec. 16, 2023
9	MXG Vector Signal Generator	Keysight	N5182B	MY59100212	Dec. 16, 2023
10	Wideband Radio Communication Tester	R&S	CMW500	102257	May 25, 2024
11	Wideband Radio Communication Tester	R&S	CMW500	102414	Dec. 16, 2023
12	High and low temperature test chamber	ESPEC	MT3035	/	Mar. 24, 2024
13	RF Control Unit	Tonscend	JS0806-2	/	Aug. 22, 2024
14	Test Software	Tonscend	JS1120-3	V3.3.38	/

Radiated Emission (3m chamber 2)					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated Until
1	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	9168-1013	Dec. 07, 2024
2	Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-648	Dec. 07, 2024
3	Spectrum Analyzer	R&S	FSU26	100105	Dec. 16, 2023
4	Spectrum Analyzer	R&S	FSV40-N	101331	Mar. 14 2024
5	Pre-Amplifier	SONOMA	310	186194	Dec. 16, 2023
6	Low Noise Pre-Amplifier	EMCI	EMC051835	980075	Dec. 16, 2023
7	Test Receiver	R&S	ESCI7	100967	Dec. 16, 2023
8	3m chamber 2	Frankonia	EE025	/	Oct. 23, 2024
9	Test Software	FARA	EZ-EMC	FA-03A2	/

Radiated Emission (3m chamber 3)					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated Until
1	Trilog-Broadband Antenna	Schwarzbeck	VULB 9163	01026	Dec. 18, 2024
2	Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-647	Dec. 01, 2024
3	Test Receiver	Keysight	N9038A	MY56400071	Dec. 16, 2023
4	Broadband Amplifier	SCHWARZBECK	BBV9743B	259	Dec. 16, 2023
5	Mirowave Broadband	SCHWARZBECK	BBV9718C	111	Dec. 16, 2023

	Amplifier				
6	3m chamber 3	YIHENG	EE106	/	Aug. 28, 2026
7	Test Software	FARA	EZ-EMC	FA-03A2	/

Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated Until
1	LISN	R&S	ENV216	101112	Dec. 16, 2023
2	LISN	R&S	ENV216	101113	Dec. 16, 2023
3	EMI Test Receiver	R&S	ESCS30	100353	Dec. 16, 2023
4	ISN CAT6	Schwarzbeck	NTFM 8158	CAT6-8158-0046	Dec. 16, 2023
5	ISN CAT5	Schwarzbeck	NTFM 8158	CAT5-8158-0046	Dec. 16, 2023
6	Test Software	R&S	EMC32	6.10.10	/

Note: 1. The Cal. Interval was one year.
2. The Cal. Interval was three year of the chamber
3. The cable loss has calculated in test result which connection between each test instruments.

3. TEST ITEM AND RESULTS

3.1. Conducted Emission

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.207/ RSS - Gen 8.8:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

Test Configuration



Test Procedure

1. The EUT was setup according to ANSI C63.10:2013 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
4. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
5. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
6. Conducted Emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
7. During the above scans, the emissions were maximized by cable manipulation.

Test Mode:

Please refer to the clause 2.4.

Test Results

Test Voltage:	AC 120V/60 Hz
Terminal:	Line



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBµ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµ V)	Comment
0.494850	37.2	1000.00	9.000	On	L1	9.5	18.9	56.1	
0.504820	38.6	1000.00	9.000	On	L1	9.5	17.4	56.0	
11.452590	48.1	1000.00	9.000	On	L1	9.7	11.9	60.0	

Final Measurement Detector 2

Frequency (MHz)	Average (dBµ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµ V)	Comment
0.504820	25.4	1000.00	9.000	On	L1	9.5	20.6	46.0	
10.039020	34.8	1000.00	9.000	On	L1	9.7	15.2	50.0	
11.452590	40.8	1000.00	9.000	On	L1	9.7	9.2	50.0	

Emission Level= Read Level+ Correct Factor

Test Voltage:	AC 120V/60 Hz
Terminal:	Neutral



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBµ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµ V)	Comment
10.039020	47.4	1000.00	9.000	On	N	9.6	12.6	60.0	
11.406960	53.7	1000.00	9.000	On	N	9.6	6.3	60.0	
18.788150	44.8	1000.00	9.000	On	N	9.5	15.2	60.0	

Final Measurement Detector 2

Frequency (MHz)	Average (dBµ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµ V)	Comment
10.079170	41.2	1000.00	9.000	On	N	9.6	8.8	50.0	
11.498400	47.0	1000.00	9.000	On	N	9.6	3.0	50.0	
18.713300	33.8	1000.00	9.000	On	N	9.5	16.2	50.0	

Emission Level= Read Level+ Correct Factor

3.2. Radiated Emission

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.209/ RSS – Gen 8.9:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F (kHz)	300
0.490~1.705	24000/F (kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Frequency Range (MHz)	dBμV/m (at 3 meters)	
	Peak	Average
Above 1000	74	54

Note:

(1) The tighter limit applies at the band edges.

(2) Emission Level (dBuV/m)=20log Emission Level (uV/m).

Test Configuration



Below 30MHz Test Setup



Below 1000MHz Test Setup



Above 1GHz Test Setup

Test Procedure

1. The EUT was setup and tested according to ANSI C63.10:2013
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Below 30 MHz:
   9kHz – 150kHz, RBW=200Hz, VBW≥RBW, Sweep=auto, Detector function=peak, Trace=max hold;
   150kHz – 30MHz, RBW=9kHz, VBW≥RBW, Sweep=auto, Detector function=peak, Trace=max hold; If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
   (3) 30 MHz - 1 GHz:

RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

(4) From 1 GHz to 10th harmonic:

RBW=1MHz, VBW=3MHz Peak detector for Peak value.

RBW=1MHz, VBW≥1/T Peak detector for Average value.

Note 1: For the 1/T& Duty Cycle please refer to clause 3.8 Duty Cycle.

Test Mode

Please refer to the clause 2.4.

Test Result

9 KHz~30 MHz

From 9 KHz to 30 MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Pre-scan all antenna, only show the test data for worse case antenna on the test report.

30MHz-1GHz

Ant. Pol.	Horizontal
Test Mode:	Ant 1 802.11b Mode 2412MHz
Remark:	Only worse case is reported



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 !	232.5318	55.83	-15.01	40.82	46.00	-5.18	QP
2 !	299.3158	54.80	-13.48	41.32	46.00	-4.68	QP
3 !	354.1831	52.91	-11.79	41.12	46.00	-4.88	QP
4 !	779.6067	46.33	-4.53	41.80	46.00	-4.20	QP
5 *	872.1832	45.26	-3.37	41.89	46.00	-4.11	QP
6	993.0114	47.03	-2.06	44.97	54.00	-9.03	QP

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant. Pol.	Vertical
Test Mode:	Ant 1 802.11b Mode 2412MHz
Remark:	Only worse case is reported



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	60.0691	38.56	-15.39	23.17	40.00	-16.83	QP
2	69.6004	43.33	-17.81	25.52	40.00	-14.48	QP
3	233.3486	47.16	-14.99	32.17	46.00	-13.83	QP
4	298.2681	45.60	-13.51	32.09	46.00	-13.91	QP
5 *	446.4140	49.35	-10.36	38.99	46.00	-7.01	QP
6	552.8832	45.89	-8.35	37.54	46.00	-8.46	QP

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Adobe 1GHz

Ant No.:	Ant 2
Ant. Pol.	Horizontal
Test Mode:	TX 802.11b Mode 2412MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	4824.335	25.83	2.11	27.94	54.00	-26.06	AVG
2	4824.861	37.05	2.11	39.16	74.00	-34.84	peak

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 2
Ant. Pol.	Vertical
Test Mode:	TX 802.11b Mode 2412MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	4823.096	25.78	2.10	27.88	54.00	-26.12	AVG
2	4823.295	36.47	2.10	38.57	74.00	-35.43	peak

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 2
Ant. Pol.	Horizontal
Test Mode:	TX 802.11b Mode 2437MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	4874.581	26.37	2.18	28.55	54.00	-25.45	AVG
2	4874.660	37.76	2.18	39.94	74.00	-34.06	peak

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 2
Ant. Pol.	Vertical
Test Mode:	TX 802.11b Mode 2437MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4874.370	37.64	2.18	39.82	74.00	-34.18	peak
2 *	4874.817	26.41	2.18	28.59	54.00	-25.41	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 2
Ant. Pol.	Horizontal
Test Mode:	TX 802.11b Mode 2462MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4923.437	37.26	2.26	39.52	74.00	-34.48	peak
2 *	4924.900	25.10	2.26	27.36	54.00	-26.64	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 2
Ant. Pol.	Vertical
Test Mode:	TX 802.11b Mode 2462MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	4924.539	25.27	2.26	27.53	54.00	-26.47	AVG
2	4924.809	37.04	2.26	39.30	74.00	-34.70	peak

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 2
Ant. Pol.	Horizontal
Test Mode:	TX 802.11g Mode 2412MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	4823.509	25.65	2.11	27.76	54.00	-26.24	AVG
2	4823.598	38.23	2.11	40.34	74.00	-33.66	peak

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 2
Ant. Pol.	Vertical
Test Mode:	TX 802.11g Mode 2412MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	4823.055	25.75	2.10	27.85	54.00	-26.15	AVG
2	4824.304	37.34	2.11	39.45	74.00	-34.55	peak

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 2
Ant. Pol.	Horizontal
Test Mode:	TX 802.11g Mode 2437MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	4873.968	26.67	2.18	28.85	54.00	-25.15	AVG
2	4874.883	38.23	2.18	40.41	74.00	-33.59	peak

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 2
Ant. Pol.	Vertical
Test Mode:	TX 802.11g Mode 2437MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4873.153	38.35	2.18	40.53	74.00	-33.47	peak
2 *	4874.363	26.33	2.18	28.51	54.00	-25.49	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 2
Ant. Pol.	Horizontal
Test Mode:	TX 802.11g Mode 2462MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4923.379	37.18	2.26	39.44	74.00	-34.56	peak
2 *	4924.795	25.20	2.26	27.46	54.00	-26.54	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 2
Ant. Pol.	Vertical
Test Mode:	TX 802.11g Mode 2462MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4924.129	36.84	2.26	39.10	74.00	-34.90	peak
2 *	4924.397	25.17	2.26	27.43	54.00	-26.57	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 1 + Ant 2
Ant. Pol.	Horizontal
Test Mode:	TX 802.11n(HT20) Mode 2412MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	4824.196	25.84	2.11	27.95	54.00	-26.05	AVG
2	4824.498	37.53	2.11	39.64	74.00	-34.36	peak

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 1 + Ant 2
Ant. Pol.	Vertical
Test Mode:	TX 802.11n(HT20) Mode 2412MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	4823.067	25.70	2.10	27.80	54.00	-26.20	AVG
2	4824.631	37.13	2.11	39.24	74.00	-34.76	peak

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 1 + Ant 2
Ant. Pol.	Horizontal
Test Mode:	TX 802.11n(HT20) Mode 2437MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4873.807	37.04	2.18	39.22	74.00	-34.78	peak
2 *	4874.749	26.46	2.18	28.64	54.00	-25.36	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 1 + Ant 2
Ant. Pol.	Vertical
Test Mode:	TX 802.11n(HT20) Mode 2437MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	4874.632	26.37	2.18	28.55	54.00	-25.45	AVG
2	4874.931	38.32	2.18	40.50	74.00	-33.50	peak

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 1 + Ant 2
Ant. Pol.	Horizontal
Test Mode:	TX 802.11n(HT20) Mode 2462MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4923.320	37.49	2.25	39.74	74.00	-34.26	peak
2 *	4923.765	25.19	2.26	27.45	54.00	-26.55	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 1 + Ant 2
Ant. Pol.	Vertical
Test Mode:	TX 802.11n(HT20) Mode 2462MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4923.670	36.43	2.26	38.69	74.00	-35.31	peak
2 *	4924.709	25.35	2.26	27.61	54.00	-26.39	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 1 + Ant 2
Ant. Pol.	Horizontal
Test Mode:	TX 802.11n(HT40) Mode 2422MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4843.677	37.20	2.13	39.33	74.00	-34.67	peak
2 *	4844.911	26.54	2.13	28.67	54.00	-25.33	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 1 + Ant 2
Ant. Pol.	Vertical
Test Mode:	TX 802.11n(HT40) Mode 2422MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	4843.905	27.02	2.13	29.15	54.00	-24.85	AVG
2	4844.660	37.31	2.13	39.44	74.00	-34.56	peak

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 1 + Ant 2
Ant. Pol.	Horizontal
Test Mode:	TX 802.11n(HT40) Mode 2437MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	4873.927	26.50	2.18	28.68	54.00	-25.32	AVG
2	4874.249	37.78	2.18	39.96	74.00	-34.04	peak

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 1 + Ant 2
Ant. Pol.	Vertical
Test Mode:	TX 802.11n(HT40) Mode 2437MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4874.021	37.37	2.18	39.55	74.00	-34.45	peak
2 *	4874.295	27.06	2.18	29.24	54.00	-24.76	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 1 + Ant 2
Ant. Pol.	Horizontal
Test Mode:	TX 802.11n(HT40) Mode 2452MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	4904.537	26.10	2.22	28.32	54.00	-25.68	AVG
2	4904.861	37.48	2.22	39.70	74.00	-34.30	peak

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 1 + Ant 2
Ant. Pol.	Vertical
Test Mode:	TX 802.11n(HT40) Mode 2452MHz
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	4903.029	26.61	2.21	28.82	54.00	-25.18	AVG
2	4903.719	37.36	2.22	39.58	74.00	-34.42	peak

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

3.3. Band Edge Emissions (Radiated)

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d)/ RSS 247 5.5:

Restricted Frequency Band (MHz)	(dBuV/m)(at 3m)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54

Test Configuration



Test Procedure

1. The EUT was setup and tested according to ANSI C63.10:2013 requirements.
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
5. The receiver set as follow:
   RBW=1MHz, VBW=3MHz Peak detector for Peak value.
   RBW=1MHz, VBW see note 1 with Peak Detector for Average Value.

   Note 1: For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 3.8 Duty Cycle.

Test Mode

Please refer to the clause 2.4.

Test Results

Pre-scan all antenna, only show the test data for worse case antenna on the test report.

Ant No.:	Ant 2
Ant. Pol.	Horizontal
Test Mode:	802.11b Mode 2412MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2390.000	22.87	31.31	54.18	74.00	-19.82	peak
2 *	2390.000	6.15	31.31	37.46	54.00	-16.54	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 2
Ant. Pol.	Vertical
Test Mode:	802.11b Mode 2412MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2390.000	22.81	31.31	54.12	74.00	-19.88	peak
2 *	2390.000	6.01	31.31	37.32	54.00	-16.68	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 2
Ant. Pol.	Horizontal
Test Mode:	802.11b Mode 2462 MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2483.500	20.93	31.48	52.41	74.00	-21.59	peak
2 *	2483.500	5.67	31.48	37.15	54.00	-16.85	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 2
Ant. Pol.	Vertical
Test Mode:	802.11b Mode 2462 MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2483.500	22.85	31.48	54.33	74.00	-19.67	peak
2 *	2483.500	5.68	31.48	37.16	54.00	-16.84	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 2
Ant. Pol.	Horizontal
Test Mode:	802.11g Mode 2412MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2390.000	30.10	31.31	61.41	74.00	-12.59	peak
2 *	2390.000	14.54	31.31	45.85	54.00	-8.15	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 2
Ant. Pol.	Vertical
Test Mode:	802.11g Mode 2412MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2390.000	34.78	31.31	66.09	74.00	-7.91	peak
2 *	2390.000	19.83	31.31	51.14	54.00	-2.86	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 2
Ant. Pol.	Horizontal
Test Mode:	802.11g Mode 2462MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2483.500	27.51	31.48	58.99	74.00	-15.01	peak
2 *	2483.500	16.29	31.48	47.77	54.00	-6.23	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 2
Ant. Pol.	Vertical
Test Mode:	802.11g Mode 2462MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2483.500	29.57	31.48	61.05	74.00	-12.95	peak
2 *	2483.500	20.81	31.48	52.29	54.00	-1.71	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 1 + Ant 2
Ant. Pol.	Horizontal
Test Mode:	802.11n(HT20) Mode 2412MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2390.000	20.83	31.31	52.14	74.00	-21.86	peak
2 *	2390.000	6.78	31.31	38.09	54.00	-15.91	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 1 + Ant 2
Ant. Pol.	Vertical
Test Mode:	802.11n(HT20) Mode 2412MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2390.000	23.72	31.31	55.03	74.00	-18.97	peak
2 *	2390.000	7.38	31.31	38.69	54.00	-15.31	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 1 + Ant 2
Ant. Pol.	Horizontal
Test Mode:	802.11n(HT20) Mode 2462MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2483.500	23.46	31.48	54.94	74.00	-19.06	peak
2 *	2483.500	8.49	31.48	39.97	54.00	-14.03	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 1 + Ant 2
Ant. Pol.	Vertical
Test Mode:	802.11n(HT20) Mode 2462MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2483.500	23.28	31.48	54.76	74.00	-19.24	peak
2 *	2483.500	8.73	31.48	40.21	54.00	-13.79	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 1 + Ant 2
Ant. Pol.	Horizontal
Test Mode:	802.11n(HT40) Mode 2422MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2390.000	23.38	31.31	54.69	74.00	-19.31	peak
2 *	2390.000	10.00	31.31	41.31	54.00	-12.69	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 1 + Ant 2
Ant. Pol.	Vertical
Test Mode:	802.11n(HT40) Mode 2422MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2390.000	23.65	31.31	54.96	74.00	-19.04	peak
2 *	2390.000	11.21	31.31	42.52	54.00	-11.48	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 1 + Ant 2
Ant. Pol.	Horizontal
Test Mode:	802.11n(HT40) Mode 2452MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2483.500	23.15	31.48	54.63	74.00	-19.37	peak
2 *	2483.500	8.48	31.48	39.96	54.00	-14.04	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

Ant No.:	Ant 1 + Ant 2
Ant. Pol.	Vertical
Test Mode:	802.11n(HT40) Mode 2452MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2483.500	20.46	31.48	51.94	74.00	-22.06	peak
2 *	2483.500	9.06	31.48	40.54	54.00	-13.46	AVG

Remarks:
1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2.Margin value = Level -Limit value

3.4. Band edge and Spurious Emissions (Conducted)

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

Test Configuration



Test Procedure

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
   RBW = 100 kHz, VBW ≥ RBW, scan up through 10th harmonic.
   Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

Test Mode

Please refer to the clause 2.4.

Test Results

(1) Band edge Conducted Test

Test Mode	Antenna	Frequency[MHz]	Ref Level[dBm]	Result[dBm]	Limit[dBm]	Verdict
802.11b	Ant1	2412	6.91	-46.13	≤-23.09	PASS
	Ant2	2412	7.50	-41.99	≤-22.50	PASS
	Ant1	2462	7.93	-56.84	≤-22.07	PASS
	Ant2	2462	7.22	-56.52	≤-22.78	PASS
802.11g	Ant1	2412	3.30	-28.35	≤-26.70	PASS
	Ant2	2412	3.60	-40.55	≤-26.40	PASS
	Ant1	2462	2.42	-37.96	≤-27.58	PASS
	Ant2	2462	1.76	-52.31	≤-28.24	PASS
802.11n(HT20)	Ant1	2412	0.69	-43.15	≤-29.31	PASS
	Ant2	2412	-0.94	-35.10	≤-30.94	PASS
	Ant1	2462	-1.02	-54.06	≤-31.02	PASS
	Ant2	2462	-1.16	-56.93	≤-31.16	PASS
802.11n(HT40)	Ant1	2422	-2.42	-44.98	≤-32.42	PASS
	Ant2	2422	-4.17	-48.25	≤-34.17	PASS
	Ant1	2452	-4.60	-54.93	≤-34.60	PASS
	Ant2	2452	-5.16	-54.71	≤-35.16	PASS

802.11b_Ant1_Low_2412



802.11b_Ant2_Low_2412



802.11b_Ant1_High_2462



802.11b_Ant2_High_2462



802.11g_Ant1_Low_2412



802.11g_Ant2_Low_2412



802.11g_Ant1_High_2462



802.11g_Ant2_High_2462



802.11n(HT20)_Ant1_Low_2412



802.11n(HT20)_Ant2_Low_2412



802.11n(HT20)_Ant1_High_2462



802.11n(HT20)_Ant2_High_2462



802.11n(HT40)_Ant1_Low_2422



802.11n(HT40)_Ant2_Low_2422



802.11n(HT40)_Ant1_High_2452



802.11n(HT40)_Ant2_High_2452



(2) Conducted Spurious Emissions Test

Test Mode	Antenna	Frequency [MHz]	Freq Range [Mhz]	Ref Level [dBm]	Result [dBm]	Limit [dBm]	Verdict
802.11b	Ant1	2412	Reference	6.42	6.42	---	PASS
			30~1000	6.42	-67.85	≤-23.58	PASS
			1000~26500	6.42	-42.36	≤-23.58	PASS
	Ant2	2412	Reference	8.02	8.02	---	PASS
			30~1000	8.02	-58.17	≤-21.98	PASS
			1000~26500	8.02	-47.92	≤-21.98	PASS
	Ant1	2437	Reference	7.25	7.25	---	PASS
			30~1000	7.25	-67.58	≤-22.75	PASS
			1000~26500	7.25	-40.58	≤-22.75	PASS
	Ant2	2437	Reference	7.45	7.45	---	PASS
			30~1000	7.45	-57.94	≤-22.55	PASS
			1000~6000	6.94	-48.96	≤-13.06	PASS
			1000~26500	7.45	-48.73	≤-22.55	PASS
			6000~26500	6.94	-51.52	≤-13.06	PASS
	Ant1	2462	Reference	8.36	8.36	---	PASS
			30~1000	8.36	-61.17	≤-21.64	PASS
			1000~26500	8.36	-40.78	≤-21.64	PASS
	Ant2	2462	Reference	7.32	7.32	---	PASS
			30~1000	7.32	-57.03	≤-22.68	PASS
			1000~26500	7.32	-48.1	≤-22.68	PASS
			1000~6000	6.97	-48.68	≤-13.03	PASS
			6000~26500	6.97	-50.01	≤-13.03	PASS
802.11g	Ant1	2412	Reference	5.06	5.06	---	PASS
			30~1000	5.06	-57.05	≤-24.94	PASS
			1000~26500	5.06	-51.66	≤-24.94	PASS
	Ant2	2412	Reference	4.56	4.56	---	PASS
			30~1000	4.56	-57.92	≤-25.44	PASS
			1000~26500	4.56	-51.01	≤-25.44	PASS
	Ant1	2437	Reference	4.24	4.24	---	PASS
			30~1000	4.24	-58.49	≤-25.76	PASS
			1000~26500	4.24	-51.45	≤-25.76	PASS
			1000~6000	4.32	-51.19	≤-15.68	PASS
			6000~26500	4.32	-51.51	≤-15.68	PASS
	Ant2	2437	Reference	4.62	4.62	---	PASS
			30~1000	4.62	-58.33	≤-25.38	PASS
			1000~26500	4.62	-50.87	≤-25.38	PASS
	Ant1	2462	Reference	5.00	5.00	---	PASS
			30~1000	5.00	-58.24	≤-25	PASS
			1000~26500	5.00	-50.94	≤-25	PASS
	Ant2	2462	Reference	4.35	4.35	---	PASS
			30~1000	4.35	-58.39	≤-25.65	PASS

			1000~26500	4.35	-51.51	≤-25.65	PASS
802.11n(HT20)	Ant1	2412	Reference	1.17	1.17	---	PASS
			30~1000	1.17	-58.24	≤-28.83	PASS
			1000~26500	1.17	-51.4	≤-28.83	PASS
	Ant2	2412	Reference	-1.47	-1.47	---	PASS
			30~1000	-1.47	-57.83	≤-31.47	PASS
			1000~26500	-1.47	-44.57	≤-31.47	PASS
	Ant1	2437	Reference	-1.39	-1.39	---	PASS
			30~1000	-1.39	-58.28	≤-31.39	PASS
			1000~26500	-1.39	-51.53	≤-31.39	PASS
	Ant2	2437	Reference	0.29	0.29	---	PASS
			30~1000	0.29	-58.56	≤-29.71	PASS
			1000~26500	0.29	-50.65	≤-29.71	PASS
	Ant1	2462	Reference	2.25	2.25	---	PASS
			30~1000	2.25	-58.01	≤-27.75	PASS
			1000~26500	2.25	-51.53	≤-27.75	PASS
	Ant2	2462	Reference	1.40	1.40	---	PASS
			30~1000	1.40	-57.49	≤-28.6	PASS
			1000~6000	1.39	-50.77	≤-18.61	PASS
			1000~26500	1.40	-51.28	≤-28.60	PASS
			6000~26500	1.39	-50.56	≤-18.61	PASS
802.11n(HT40)	Ant1	2422	Reference	-1.85	-1.85	---	PASS
			30~1000	-1.85	-58.13	≤-31.85	PASS
			1000~26500	-1.85	-51.72	≤-31.85	PASS
	Ant2	2422	Reference	-2.07	-2.07	---	PASS
			30~1000	-2.07	-58.61	≤-32.07	PASS
			1000~26500	-2.07	-50.1	≤-32.07	PASS
	Ant1	2437	Reference	-2.84	-2.84	---	PASS
			30~1000	-2.84	-58.85	≤-32.84	PASS
			1000~26500	-2.84	-51.53	≤-32.84	PASS
	Ant2	2437	Reference	-3.02	-3.02	---	PASS
			30~1000	-3.02	-57.54	≤-33.02	PASS
			1000~26500	-3.02	-50.88	≤-33.02	PASS
	Ant1	2452	Reference	-2.82	-2.82	---	PASS
			30~1000	-2.82	-58.52	≤-32.82	PASS
			1000~26500	-2.82	-51.58	≤-32.82	PASS
	Ant2	2452	Reference	-5.22	-5.22	---	PASS
			30~1000	-5.22	-57.91	≤-35.22	PASS
			1000~26500	-5.22	-50.86	≤-35.22	PASS

802.11b_Ant1_2412_0~Reference



802.11b_Ant1_2412_30~1000



802.11b_Ant1_2412_1000~26500



802.11b_Ant2_2412_0~Reference



802.11b_Ant2_2412_30~1000



802.11b_Ant2_2412_1000~26500



802.11b_Ant1_2437_0~Reference



802.11b_Ant1_2437_30~1000



802.11b_Ant1_2437_1000~26500



802.11b_Ant2_2437_0~Reference



802.11b_Ant2_2437_30~1000



802.11b_Ant2_2437_1000~26500



802.11b_Ant1_2462_0~Reference



802.11b_Ant1_2462_30~1000



802.11b_Ant1_2462_1000~26500



802.11b_Ant2_2462_0~Reference



802.11b_Ant2_2462_30~1000



802.11b_Ant2_2462_1000~26500



802.11g_Ant1_2412_0~Reference



802.11g_Ant1_2412_30~1000



802.11g_Ant1_2412_1000~26500



802.11g_Ant2_2412_0~Reference



802.11g_Ant2_2412_30~1000



802.11g_Ant2_2412_1000~26500



802.11g_Ant1_2437_0~Reference



802.11g_Ant1_2437_30~1000



802.11g_Ant1_2437_1000~26500



802.11g_Ant2_2437_0~Reference



802.11g_Ant2_2437_30~1000



802.11g_Ant2_2437_1000~26500