

MPE ESTIMATION

FCC ID: 2AWB4-DP-108B

1, Limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)	
300MHz1.5GHz	F/1500	30	
1.5GHz100GHz	1.0	30	

Note: F= Frequency in MHz

2, Estimation Result

WIFI

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (numerical)	MPE (mW/cm²)
2.4G WIFI	14.46	14±1(15)	31.623	1	1.2589	0.00792
5.2G WIFI	12.20	12±1(13)	19.953	1	1.2589	0.00500

$$Pd = \frac{Pout * G}{4\pi r^2}$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report HK2004170688-1E/2E, antenna gain=1dBi

simultaneously MPE

2.4G WIFI MPE (max)= 0.00792 (mW/cm²)

5G WIFI MPE $_{(max)}$ = 0.00500 (mW/cm²)

simultaneously MPE=0.00792+0.00500=0.01292(mW/cm²)

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.01292 mW/cm² which is< 1.0mW/cm², RF Exposure testing is not required.

