FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure							
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)			
0.3-1.34	614	1.63	*(100)	30			
1.34-30	824/f	2.19/f	*(180/f²)	30			
30-300	27.5	0.073	0.2	30			
300-1500	/	/	f/1500	30			
1500-100,000	/	/	1.0	30			

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

 $S = PG/4\pi R^2 = power density (in appropriate units, e.g. mW/cm^2);$

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Report No.: RSHE210118001-00B

Calculated Data:

2.4G WI-FI

Mode	Frequency Range (MHz)	Antenna Gain		Tune-up Output Power		Evaluation Distance	Power Density	MPE Limit
		(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm ²)	(mW/cm ²)
802.11b	2412~2462	2.47	1.77	23.00	199.53	20	0.0701	1.0
802.11g		2.47	1.77	22.50	177.83	20	0.0625	1.0
802.11 n-HT20		2.47	1.77	23.00	199.53	20	0.0701	1.0
802.11 n-HT40	2422~2452	2.47	1.77	22.00	158.49	20	0.0557	1.0

WCDMA/LTE

Mode	Frequency Range		enna Gain	Tune-up Conducted Power		Evaluation Distance	Power Density	MPE Limit
	(MHz)	(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm^2)	(mW/cm ²)
WCDMA Band II	1850-1910	2.71	1.87	22.5	177.83	20	0.0661	1.0
WCDMA Band IV	1710-1755	1.85	1.53	22.5	177.83	20	0.0541	1.0
WCDMA Band V	824-849	-1.61	0.69	22.5	177.83	20	0.0244	0.55
LTE Band 2	1850-1910	2.71	1.87	22.5	177.83	20	0.0661	1.0
LTE Band 4	1710-1755	1.85	1.53	22.5	177.83	20	0.0541	1.0
LTE Band 12	699-716	0.50	1.12	22.5	177.83	20	0.0396	0.47

1. For the above tune up power were declared by the manufacturer.2. 2.4G Wi-Fi, WCDMA / LTE can transmit simultaneously, The worst condition is as below:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} = 0.0701/1.00 + 0.0396/0.47 = 0.1544 < 1.0$$

Result: The device meet FCC MPE at 20 cm distance.

Report No.: RSHE210118001-00B