

RF Exposure Evaluation Report

Applicant: Likk Technologies Inc.

Address of Applicant: 16112 NW 13 Ave. Suite A Miami, Florida 33169 USA.

Equipment Under Test (EUT)

Product Name: Water leak alarm

Model No.: S5

FCC ID: 2AWC7S5

Applicable standards: FCC CFR Title 47 Part 2 Subpart J Section 2.1091

Date of sample receipt: 25 May, 2020

Date of Test: 26 May, to 28 Jul., 2020

Date of report issue: 29 Jul., 2020

Test Result: PASS*

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	29 Jul., 2020	Original

Tested by: YT Yang

Test Engineer

Date: 29 Jul., 2020

Reviewed by: Winner Zhang

Project Engineer

Date: 29 Jul., 2020

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 GENERAL INFORMATION	4
4.1 CLIENT INFORMATION	4
4.2 GENERAL DESCRIPTION OF E.U.T	4
4.3 OPERATING MODES	4
4.4 LABORATORY FACILITY	5
4.5 LABORATORY LOCATION	5
5 TECHNICAL REQUIREMENTS SPECIFICATION IN FCC CFR TITLE 47 PART 2.1091	6
5.1 LIMITS	6
5.2 TEST PROCEDURE	6
5.3 RESULT	7
5.4 CONCLUSION	7

4 General Information

4.1 Client Information

Applicant:	Likk Technologies Inc.
Address:	16112 NW 13 Ave. Suite A Miami, Florida 33169 USA.
Manufacturer:	Shenzhen Hengxin Wulian Technology Co., Ltd.
Address:	2nd Floor, Building 2, Longfeng Industrial Park, Guanlantian, Longhua District, Shenzhen

4.2 General Description of E.U.T.

Product Name:	Water leak alarm
Model No.:	S5
Operation Frequency:	WCDMA Band V: 826.4MHz-846.6MHz WCDMA Band II: 1852.4 MHz-1907.6 MHz LTE Band 2: TX: 1850MHz-1910MHz, RX: 1930MHz-1990MHz LTE Band 4: TX: 1710MHz-1755MHz, RX: 2110MHz-2155MHz LTE Band 12: TX: 699MHz-716MHz, RX: 729MHz-746MHz
Modulation technology:	UMTS: QPSK LTE: QPSK, 16QAM
Antenna Type:	Internal Antenna
Antenna gain:	WCDMA Band V: -0.6 dBi WCDMA Band II: 0.65 dBi LTE Band 2: 0.8dBi LTE Band 4: -0.6dBi LTE Band 12: -0.6dBi
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

4.3 Operating Modes

Operating mode	Detail description
WCDMA mode	Keep the EUT in continuously transmitting in WCDMA mode
LTE mode	Keep the EUT in continuously transmitting in LTE mode

4.4 Additions to, deviations, or exclusions from the method

No

4.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Designation No.: CN1211**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

- **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

4.6 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.

Address: No.110~116, Building B, Jinyuan Business Building, Xixiang Road,
Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info@ccis-cb.com, Website: <http://www.ccis-cb.com>

5 Technical Requirements Specification in FCC CFR Title 47 Part 2.1091

5.1 Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

5.2 Test Procedure

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

5.3 Result

Frequency (MHz)	Maximum Output power (dBm)	Maximum Output power (mW)	Antenna Gain (dBi)	Antenna Gain (numeric)	Distance (cm)	Result (mW/cm ²)	Limits for General Population/ Uncontrolled Exposure (mW/cm ²)
WCDMA 850							
826.4	24.92	310.46	-0.60	0.87	20.00	0.054	0.55
WCDMA 1900							
1907.6	22.78	189.67	0.65	1.16	20.00	0.044	1.00
LTE band 2							
1880.0	21.77	150.31	0.80	1.20	20.00	0.036	1.00
LTE band 4							
1754.3	22.42	174.58	-0.60	0.87	20.00	0.030	1.00
LTE band 12							
715.3	23.44	220.80	-0.60	0.87	20.00	0.038	0.48

Note: Just the worst case mode was shown in report.

5.4 Conclusion

The device is exempt from the RF exposure evaluation.

-----End of report-----