

TEST REPORT

Report No.: BCTC2202042633E

Applicant: ASK Technology CO., LTD


Product Name: Wireless HDMI Extender

Model/Type Ref.: JTD-611V3

Tested Date: 2022-02-25 to 2022-04-28

Issued Date: 2022-04-28


Shenzhen BCTC Testing Co., Ltd.



FCC ID: 2AWCKJTD-611V3


Product Name: Wireless HDMI Extender
Trademark: N/A
Model/Type Ref.: JTD-611V3
JTD-628V3, JTD-1651, JTD-228, JTD-351, JTD-352
Prepared For: ASK Technology CO., LTD
Address: 6th Floor, Block 1, High-Tech Industry Park, ShiLongzi Community, Shiyao Town,
BaoAn, Shenzhen, China
Manufacturer: ASK Technology CO., LTD
Address: 6th Floor, Block 1, High-Tech Industry Park, ShiLongzi Community, Shiyao Town,
BaoAn, Shenzhen, China
Prepared By: Shenzhen BCTC Testing Co., Ltd.
Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Tangwei,
Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Sample Received Date: 2022-02-25
Sample tested Date: 2022-02-25 to 2022-04-28
Issue Date: 2022-04-28
Report No.: BCTC2202042633E
FCC Part15 15.407
ANSI C63.10-2013
Test Standards: KDB 662911 D01 v02r01
KDB 789033 D02 v02r01
Test Results: PASS

Tested by:



Brave Zeng/ Project Handler

Approved by:



Zero Zhou/Reviewer


The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.

Table Of Content

Test Report Declaration	Page
1. Version	5
2. Test Summary	6
3. Measurement Uncertainty	7
4. Product Information And Test Setup	8
4.1 Product Information.....	8
4.2 Test Setup Configuration	8
4.3 Support Equipment	9
4.4 Channel List	9
4.5 Test Mode	10
4.6 Table Of Parameters Of Text Software Setting.....	10
4.7 Antenna.....	10
5. Test Facility And Test Instrument Used.....	11
5.1 Test Facility.....	11
5.2 Test Instrument Used.....	11
6. Conducted Emissions.....	13
6.1 Block Diagram Of Test Setup.....	13
6.2 Limit	13
6.3 Test Procedure	13
6.4 EUT Operating Conditions	14
6.5 Test Result.....	15
7. Radiated Emissions.....	17
7.1 Block Diagram Of Test Setup.....	17
7.2 Limit	18
7.3 Test Procedure	19
7.4 EUT Operating Conditions	20
7.5 Test Result.....	20
8. Power Spectral Density Test	26
8.1 Block Diagram Of Test Setup.....	26
8.2 Limit	26
8.3 Test Procedure	27
8.4 EUT Operating Conditions	27
8.5 Test Result.....	28
9. 6dB & 99% Emission Bandwidth	33
9.1 Block Diagram Of Test Setup.....	33
9.2 Limit	33
9.3 Test Procedure	33
9.4 EUT Operating Conditions	33
9.5 Test Result.....	34
10. Maximum Conducted Output Power.....	43
10.1 Block Diagram Of Test Setup.....	43
10.2 Limit	43
10.3 Test Procedure	43
10.4 EUT Operating Conditions	44


10.5	Test Result.....	45
11.	Out Of Band Emissions	46
11.1	Block Diagram Of Test Setup.....	46
11.2	Limit	46
11.3	Test Procedure	46
11.4	EUT Operating Conditions	46
11.5	Test Result.....	46
12.	Spurious RF Conducted Emissions.....	50
12.1	Block Diagram Of Test Setup.....	50
12.2	Limit	50
12.3	Test Procedure	50
12.4	Test Result.....	50
13.	Frequency Stability Measurement	55
13.1	Block Diagram Of Test Setup.....	55
13.2	Limit	55
13.3	Test Procedure	55
14.	Antenna Requirement	59
14.1	Limit	59
14.2	Test Result.....	59
15.	EUT Photographs.....	60
16.	EUT Test Setup Photographs.....	61

(Note: N/A Means Not Applicable)



1. Version


Report No.	Issue Date	Description	Approved
BCTC2202042633E	2022-04-28	Original	Valid



2. Test Summary

The Product has been tested according to the following specifications:


No.	Test Parameter	Clause No	Results
1	Spurious Radiated Emissions	15.209(a), 15.407 (b)(1) 15.407 (b)(4) 15.407 (b)(8)	PASS
2	Conducted Emission	15.207	PASS
3	26 dB and 99% Emission Bandwidth	15.407 (a)(12) 15.1049	PASS
4	Minimum 6 dB bandwidth	15.407(e)	PASS
5	Maximum Conducted Output Power	15.407 (a)(1) 15.407 (a)(3)	PASS
6	Band Edge	2.1051, 15.407(b)(1) 15.407(b)(4)	PASS
7	Power Spectral Density	15.407 (a)(1) 15.407 (a)(3)	PASS
8	Spurious Emissions at Antenna Terminals	2.1051, 15.407(b)	PASS
9	Antenna Requirement	15.203	PASS



3. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(9kHz-30MHz)	U=3.7dB
2	3m chamber Radiated spurious emission(30MHz-1GHz)	U=4.3dB
3	3m chamber Radiated spurious emission(1GHz-18GHz)	U=4.5dB
4	3m chamber Radiated spurious emission(18GHz-40GHz)	U=3.34dB
5	Conducted Emission(150kHz-30MHz)	U=3.20dB
6	Conducted Adjacent channel power	U=1.38dB
7	Conducted output power uncertainty Above 1G	U=1.576dB
8	Conducted output power uncertainty below 1G	U=1.28dB
9	humidity uncertainty	U=5.3%
10	Temperature uncertainty	U=0.59°C



4. Product Information And Test Setup


4.1 Product Information

Model/Type Ref.:	JTD-611V3 JTD-628V3, JTD-1651, JTD-228, JTD-351, JTD-352
Model differences:	All the model are the same circuit and RF module, except model names.
Hardware Version:	N/A
Software Version:	N/A
IEEE 802.11 Mode Supported	WLAN 802.11a/n(20MHz channel bandwidth) 802.11n(40MHz channel bandwidth)
Operation Frequency:	5745-5825 MHz for 802.11a/n(HT20); 5755-5795 MHz for 802.11n(HT40);
Data Rate	802.11a: 6,9,12,18,24,36,48,54Mbps; 802.11n(HT20/HT40):MCS0-MCS15;
Type of Modulation:	OFDM with BPSK/QPSK/16QAM/64QAM/256QAM for 802.11a/n;
Number Of Channel	5 channels for 802.11a/n20 in the 5745-5825MHz band ; 2 channels for 802.11 n40 in the 5755-5795MHz band ;
Antenna installation:	External antenna
Antenna Gain:	Antenna A: 3dBi Antenna B: 3dBi
Ratings:	AC 120V/60Hz
Adapter:	MODEL: SR-B21201000U2 INPUT: 100-240VAC 50/60Hz 0.35A OUTPUT: DC 12V 1A 12W



4.2 Test Setup Configuration

See test photographs attached in *EUT TEST SETUP PHOTOGRAPHS* for the actual connections between Product and support equipment.

Conducted Emission:



Radiated Spurious Emission



4.3 Support Equipment

No.	Device Type	Brand	Model	Series No.	Note
E-1	Wireless HDMI Extender	N/A	JTD-611V3	N/A	EUT
E-2	Adapter	N/A	SR-B21201000U 2	N/A	Auxiliary

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	0.8M	DC cable unshielded


Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4 Channel List

802.11a/n(20MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	153	5765	157	5785	161	5805
165	5825	-	-	-	-	-	-

802.11n (40MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	5755	159	5795	-	-	-	-



4.5 Test Mode

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	802.11a /n 20 CH149/ CH157/ CH 165
Mode 2	802.11n40 CH 151 / CH 159
Mode 3	Link Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11a /n 20 CH149/ CH157/ CH 165
Mode 2	802.11n40 CH 151 / CH 159
Mode 3	Link Mode

Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

4.6 Table Of Parameters Of Text Software Setting

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters

Test software Version	CMD		
Parameters	DEF	DEF	DEF

4.7 Antenna

Antenna	Brand	Model Name	Antenna Type	Gain (dBi)	NOTE
A	N/A	N/A	External antenna	3	
B	N/A	N/A	External antenna	3	

For power spectral density(PSD) measurements,
 $\text{Array Gain} = 10 \log(\text{NANT}/\text{NSS}) \text{dB} = 10 \log(2/1) = 3.01 \text{dB}$,
 So the directional gain for PSD is 6.01dB

2) For power measurements,
 The Array gain = 0 dB for $\text{NANT} \leq 4$,
 So the directional gain for Power measurements is 3dBi

5. Test Facility And Test Instrument Used

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing Co., Ltd. Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Tangwei, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards. FCC Test Firm Registration Number: 712850 IC Registered No.: 23583

5.2 Test Instrument Used

Conducted Emissions Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Receiver	R&S	ESR3	102075	May 28, 2021	May 27, 2022
LISN	R&S	ENV216	101375	May 28, 2021	May 27, 2022
Software	Frad	EZ-EMC	EMC-CON 3A1	\	\
Attenuator	\	10dB DC-6GHz	1650	May 28, 2021	May 27, 2022

RF Conducted Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Power Metter	Keysight	E4419	\	May 28, 2021	May 27, 2022
Power Sensor (AV)	Keysight	E9300A	\	May 28, 2021	May 27, 2022
Signal Analyzer20kHz-26.5GHz	Keysight	N9020A	MY49100060	May 28, 2021	May 27, 2022
Spectrum Analyzer9kHz-40GHz	R&S	FSP40	\	May 28, 2021	May 27, 2022

Radiated Emissions Test (966 Chamber)					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
966 chamber	ChengYu	966 Room	966	Jun. 06. 2020	Jun. 05, 2023
Receiver	R&S	ESR3	102075	May 28, 2021	May 27, 2022
Receiver	R&S	ESRP	101154	May 28, 2021	May 27, 2022
Amplifier	SKET	LAPA_01G18 G-45dB	\	May 28, 2021	May 27, 2022
Amplifier	Schwarzbeck	BBV9744	9744-0037	May 28, 2021	May 27, 2022
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	942	Jun. 01, 2021	May 31, 2022
Horn Antenna	Schwarzbeck	BBHA9120D	1541	Jun. 02, 2021	Jun. 01, 2022
Horn Antenn(18GH z-40GHz)	Schwarzbeck	BBHA9170	00822	Jun. 15, 2021	Jun. 14, 2022
Amplifier(18G Hz-40GHz)	MITEQ	TTA1840-35- HG	2034381	May 28, 2021	May 27, 2022
Loop Antenna(9kHz -30MHz)	Schwarzbeck	FMZB1519B	00014	Jun. 02, 2021	Jun. 01, 2022
RF cables1(9kHz- 30MHz)	Huber+Suhnar	9kHz-30MHz	B1702988-000 8	May 28, 2021	May 27, 2022
RF cables2(30MH z-1GHz)	Huber+Suhnar	30MHz-1GHz	1486150	May 28, 2021	May 27, 2022
RF cables3(1GHz -40GHz)	Huber+Suhnar	1GHz-40GHz	1607106	May 28, 2021	May 27, 2022
Power Metter	Keysight	E4419	\	May 28, 2021	May 27, 2022
Power Sensor (AV)	Keysight	E9300A	\	May 28, 2021	May 27, 2022
Signal Analyzer20kH z-26.5GHz	Keysight	N9020A	MY49100060	May 28, 2021	May 27, 2022
Spectrum Analyzer9kHz- 40GHz	R&S	FSP40	\	May 28, 2021	May 27, 2022
Software	Frad	EZ-EMC	FA-03A2 RE	\	\

6. Conducted Emissions

6.1 Block Diagram Of Test Setup



6.2 Limit

FREQUENCY (MHz)	Limit (dBuV)	
	Quas-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Notes:
 1. *Decreasing linearly with logarithm of frequency.
 2. The lower limit shall apply at the transition frequencies.


6.3 Test Procedure

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

- The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
- The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
- For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.


6.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



6.5 Test Result

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test Mode :	Mode 3




Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. Measurement=Reading Level+ Correct Factor
4. Over=Measurement-Limit

No.	Mk.	Freq. MHz	Reading Level	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1796	33.50	19.60	53.10	64.50	-11.40	QP
2		0.1796	21.38	19.60	40.98	54.50	-13.52	AVG
3		0.4993	29.94	19.61	49.55	56.01	-6.46	QP
4	*	0.4993	22.16	19.61	41.77	46.01	-4.24	AVG
5		1.4795	26.93	19.62	46.55	56.00	-9.45	QP
6		1.4795	15.52	19.62	35.14	46.00	-10.86	AVG
7		1.9801	29.85	19.62	49.47	56.00	-6.53	QP
8		1.9801	18.91	19.62	38.53	46.00	-7.47	AVG
9		7.4464	22.19	19.74	41.93	60.00	-18.07	QP
10		7.4464	7.99	19.74	27.73	50.00	-22.27	AVG
11		16.3984	20.58	19.76	40.34	60.00	-19.66	QP
12		16.3984	5.30	19.76	25.06	50.00	-24.94	AVG

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Mode :	Mode 3


Remark:


1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. Measurement=Reading Level+ Correct Factor
4. Over=Measurement-Limit

No. Mk.	Freq. MHz	Reading Level	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1	0.1768	34.23	19.60	53.83	64.63	-10.80	QP
2	0.1768	18.52	19.60	38.12	54.63	-16.51	AVG
3 *	0.5010	30.02	19.61	49.63	56.00	-6.37	QP
4	0.5010	19.89	19.61	39.50	46.00	-6.50	AVG
5	1.4862	23.40	19.62	43.02	56.00	-12.98	QP
6	1.4862	11.01	19.62	30.63	46.00	-15.37	AVG
7	1.9814	28.02	19.62	47.64	56.00	-8.36	QP
8	1.9814	18.48	19.62	38.10	46.00	-7.90	AVG
9	7.6289	17.90	19.74	37.64	60.00	-22.36	QP
10	7.6289	3.26	19.74	23.00	50.00	-27.00	AVG
11	16.4444	18.74	19.76	38.50	60.00	-21.50	QP
12	16.4444	3.87	19.76	23.63	50.00	-26.37	AVG


7. Radiated Emissions

7.1 Block Diagram Of Test Setup


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



7.2 Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Field Strength uV/m	Distance (m)	Field Strength Limit at 3m Distance	
			uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log(2400/F(\text{kHz})) + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log(24000/F(\text{kHz})) + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log(30) + 40$
30 ~ 88	100	3	100	$20\log(100)$
88 ~ 216	150	3	150	$20\log(150)$
216 ~ 960	200	3	200	$20\log(200)$
Above 960	500	3	500	$20\log(500)$

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1)The limit for radiated test was performed according to FCC PART 15C.
- (2)The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

7.3 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205.

It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested

and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW [kHz]})$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

7.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

7.5 Test Result

Below 30MHz

Temperature:	26°C	Relative Humidity:	24%
Pressure:	101 kPa	Test Voltage :	AC120V/60Hz
Test Mode :	Mode 1	Polarization :	--

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State P/F
--	--	--	--	PASS
--	--	--	--	PASS

Note:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

Between 30MHz – 1GHz


Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Test Voltage :	AC120V/60Hz
Test Mode :	Mode 3	Polarization :	Horizontal



- Remark:
1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
 2. Measurement=Reading Level+ Correct Factor
 3. Over=Measurement-Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	85.5976	43.19	-16.36	26.83	40.00	-13.17	QP
2 *	222.9502	55.23	-13.28	41.95	46.00	-4.05	QP
3 !	297.2240	51.35	-10.29	41.06	46.00	-4.94	QP
4	372.0045	47.58	-8.44	39.14	46.00	-6.86	QP
5	446.4140	44.24	-5.62	38.62	46.00	-7.38	QP
6 !	744.8660	42.23	-1.06	41.17	46.00	-4.83	QP

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kpa	Test Voltage :	AC120V/60Hz
Test Mode :	Mode 3	Polarization :	Vertical


Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement=Reading Level+ Correct Factor
3. Over=Measurement-Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	87.1116	48.44	-16.31	32.13	40.00	-7.87	QP
2 *	222.9502	54.42	-13.28	41.14	46.00	-4.86	QP
3	297.2241	49.62	-10.29	39.33	46.00	-6.67	QP
4	440.1962	42.53	-5.91	36.62	46.00	-9.38	QP
5 !	550.9480	43.87	-3.02	40.85	46.00	-5.15	QP
6	900.1474	35.47	1.31	36.78	46.00	-9.22	QP

Test Mode :	TX (5.8G) -- 802.11a
-------------	----------------------

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Cable loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/ m)	Margin (dB)	Detector Type
Low Channel (5745 MHz)-Above 1G									
V	4679.063	57.37	5.94	35.40	44.00	54.71	74	-19.29	PK
V	4679.063	43.66	5.94	35.40	44.00	41.00	54	-13.00	AV
V	11490.147	56.81	8.46	39.75	44.50	60.52	68.2	-7.68	PK
V	11490.147	43.06	8.46	39.75	44.50	46.77	54	-7.23	AV
V	17235.135	60.13	10.12	38.80	44.10	64.95	68.2	-3.25	PK
V	17235.135	43.84	10.12	38.80	42.70	50.06	54	-3.94	AV
H	4679.115	54.36	5.94	35.18	44.00	51.48	74	-22.52	PK
H	4679.115	43.05	5.94	35.18	44.00	40.17	54	-13.83	AV
H	11490.003	50.51	8.46	38.71	44.50	53.18	68.2	-15.02	PK
H	11490.003	43.28	8.46	38.71	44.50	45.95	54	-8.05	AV
H	17235.136	50.63	10.12	38.38	44.10	55.03	68.2	-13.17	PK
H	17235.136	41.33	10.12	38.38	44.10	45.73	54	-8.27	AV
middle Channel (5785 MHz)-Above 1G									
V	4592.108	56.47	6.48	36.35	44.05	55.25	74	-18.75	PK
V	4592.108	43.79	6.48	36.35	44.05	42.57	54	-11.43	AV
V	11570.040	58.09	8.47	37.88	44.51	59.93	68.2	-8.27	PK
V	11570.040	43.28	8.47	37.88	44.51	45.12	54	-8.88	AV
V	17355.004	57.23	10.12	38.80	44.10	62.05	68.2	-6.15	PK
V	17355.004	39.83	10.12	38.80	42.70	46.05	54	-7.95	AV
H	4592.012	55.21	6.48	36.37	44.05	54.01	74	-19.99	PK
H	4592.012	43.63	6.48	36.37	44.05	42.43	54	-11.57	AV
H	11570.059	51.12	8.47	38.64	44.50	53.73	68.2	-14.47	PK
H	11570.059	40.17	8.47	38.64	44.50	42.78	54	-11.22	AV
H	17355.027	52.86	10.12	38.38	44.10	57.26	68.2	-10.94	PK
H	17355.027	43.30	10.12	38.38	44.10	47.70	54	-6.30	AV
High Channel (5825 MHz)-Above 1G									
V	6039.177	59.33	7.10	37.24	43.50	60.17	68.2	-8.03	PK
V	6039.177	43.97	7.10	37.24	43.50	44.81	54	-9.19	AV
V	11650.081	62.06	8.46	37.68	44.50	63.70	74	-10.30	PK
V	11650.081	43.48	8.46	37.68	44.50	45.12	54	-8.88	AV
V	17475.014	56.72	10.12	38.80	44.10	61.54	68.2	-6.66	PK
V	17475.014	43.66	10.12	38.80	42.70	49.88	54	-4.12	AV
H	6039.084	55.44	7.10	37.24	43.50	56.28	68.2	-11.92	PK
H	6039.084	43.62	7.10	37.24	43.50	44.46	54	-9.54	AV
H	11650.053	54.06	8.46	38.57	44.50	56.59	74	-17.41	PK
H	11650.053	40.52	8.46	38.57	44.50	43.05	54	-10.95	AV
H	17475.116	52.56	10.12	38.38	44.10	56.96	68.2	-11.24	PK
H	17475.116	42.33	10.12	38.38	44.10	46.73	54	-7.27	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

The Worst mode is Antenna A.

Test Mode :	TX (5.8G) --802.11n-HT20
-------------	--------------------------

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Cable loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/ m)	Margin (dB)	Detector Type
Low Channel (5745 MHz)-Above 1G									
V	4679.067	58.62	5.94	35.40	44.00	55.96	74	-18.04	PK
V	4679.067	43.52	5.94	35.40	44.00	40.86	54	-13.14	AV
V	11490.170	56.92	8.46	39.75	44.50	60.63	68.2	-7.57	PK
V	11490.170	43.37	8.46	39.75	44.50	47.08	54	-6.92	AV
V	17235.149	57.27	10.12	38.80	44.10	62.09	68.2	-6.11	PK
V	17235.149	43.24	10.12	38.80	42.70	49.46	54	-4.54	AV
H	4679.023	59.30	5.94	35.18	44.00	56.42	74	-17.58	PK
H	4679.023	43.29	5.94	35.18	44.00	40.41	54	-13.59	AV
H	11490.152	49.06	8.46	38.71	44.50	51.73	68.2	-16.47	PK
H	11490.152	41.22	8.46	38.71	44.50	43.89	54	-10.11	AV
H	17235.122	51.35	10.12	38.38	44.10	55.75	68.2	-12.45	PK
H	17235.122	41.00	10.12	38.38	44.10	45.40	54	-8.60	AV
middle Channel (5785 MHz)-Above 1G									
V	4592.135	58.73	6.48	36.35	44.05	57.51	74	-16.49	PK
V	4592.135	43.36	6.48	36.35	44.05	42.14	54	-11.86	AV
V	11570.001	57.84	8.47	37.88	44.51	59.68	68.2	-8.52	PK
V	11570.001	43.12	8.47	37.88	44.51	44.96	54	-9.04	AV
V	17355.075	58.59	10.12	38.80	44.10	63.41	68.2	-4.79	PK
V	17355.075	43.49	10.12	38.80	42.70	49.71	54	-4.29	AV
H	4592.182	58.00	6.48	36.37	44.05	56.80	74	-17.20	PK
H	4592.182	43.11	6.48	36.37	44.05	41.91	54	-12.09	AV
H	11570.182	53.71	8.47	38.64	44.50	56.32	68.2	-11.88	PK
H	11570.182	41.38	8.47	38.64	44.50	43.99	54	-10.01	AV
H	17355.049	51.67	10.12	38.38	44.10	56.07	68.2	-12.13	PK
H	17355.049	44.17	10.12	38.38	44.10	48.57	54	-5.43	AV
High Channel (5825 MHz)-Above 1G									
V	6039.075	58.96	7.10	37.24	43.50	59.80	68.2	-8.40	PK
V	6039.075	43.59	7.10	37.24	43.50	44.43	54	-9.57	AV
V	11650.027	59.73	8.46	37.68	44.50	61.37	74	-12.63	PK
V	11650.027	43.81	8.46	37.68	44.50	45.45	54	-8.55	AV
V	17475.056	57.67	10.12	38.80	44.10	62.49	68.2	-5.71	PK
V	17475.056	43.98	10.12	38.80	42.70	50.20	54	-3.80	AV
H	6039.184	59.57	7.10	37.24	43.50	60.41	68.2	-7.79	PK
H	6039.184	43.01	7.10	37.24	43.50	43.85	54	-10.15	AV
H	11650.079	52.76	8.46	38.57	44.50	55.29	74	-18.71	PK
H	11650.079	44.89	8.46	38.57	44.50	47.42	54	-6.58	AV
H	17475.196	52.66	10.12	38.38	44.10	57.06	68.2	-11.14	PK
H	17475.196	43.78	10.12	38.38	44.10	48.18	54	-5.82	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode :	TX (5.8G) -- 802.11n-HT40
-------------	---------------------------

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Cable loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/ m)	Margin (dB)	Detector Type
Low Channel (5755 MHz)-Above 1G									
V	4679.185	57.16	5.94	35.40	44.00	54.50	74	-19.50	PK
V	4679.185	43.08	5.94	35.40	44.00	40.42	54	-13.58	AV
V	11510.159	55.57	8.46	39.75	44.50	59.28	74	-14.72	PK
V	11510.159	43.40	8.46	39.75	44.50	47.11	54	-6.89	AV
V	17265.178	57.22	10.12	38.80	44.10	62.04	68.2	-6.16	PK
V	17265.178	2.00	10.12	38.80	42.70	8.22	54	-45.78	AV
H	4679.152	60.16	5.94	35.18	44.00	57.28	74	-16.72	PK
H	4679.152	43.13	5.94	35.18	44.00	40.25	54	-13.75	AV
H	11510.102	52.54	8.46	38.71	44.50	55.21	74	-18.79	PK
H	11510.102	41.35	8.46	38.71	44.50	44.02	54	-9.98	AV
H	17265.126	50.76	10.12	38.38	44.10	55.16	68.2	-13.04	PK
H	17265.126	42.00	10.12	38.38	44.10	46.40	54	-7.60	AV
middle Channel (5795 MHz)-Above 1G									
V	6039.169	60.52	6.48	36.35	44.05	59.30	68.2	-8.90	PK
V	6039.169	43.50	6.48	36.35	44.05	42.28	54	-11.72	AV
V	11590.020	57.59	8.47	37.88	44.51	59.43	74	-14.57	PK
V	11590.020	43.95	8.47	37.88	44.51	45.79	54	-8.21	AV
V	17385.034	55.03	10.12	38.80	44.10	59.85	68.2	-8.35	PK
V	17385.034	41.80	10.12	38.80	42.70	48.02	54	-5.98	AV
H	6039.013	56.09	6.48	36.37	44.05	54.89	68.2	-13.31	PK
H	6039.013	43.62	6.48	36.37	44.05	42.42	54	-11.58	AV
H	11590.178	50.65	8.47	38.64	44.50	53.26	74	-20.74	PK
H	11590.178	43.42	8.47	38.64	44.50	46.03	54	-7.97	AV
H	17385.090	51.38	10.12	38.38	44.10	55.78	68.2	-12.42	PK
H	17385.090	40.27	10.12	38.38	44.10	44.67	54	-9.33	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

8. Power Spectral Density Test

8.1 Block Diagram Of Test Setup



8.2 Limit

For the band 5.15-5.25 GHz,

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz

(3) For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

8.3 Test Procedure


For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:

- a) Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $VBW \geq 3 RBW$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/RBW)$ to the measured result, whereas RBW (< 500 KHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/RBW)$ to the measured result, whereas RBW (< 1 MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since RBW=100 KHZ is available on nearly all spectrum analyzers.

8.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.





8.5 Test Result



Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX Frequency U-NII-3 (5745-5825MHz)		



Note: A(B) Represent the value of antenna A and B, The worst data is Antenna A, only shown Antenna A Plot.



Note: Antenna A gain: 3dBi, Antenna B gain: 3dBi, Directional gain=[10log(GA+ G B)] dbi=6.01
 limit=30-(6.01-6)=29.99

Mode	Frequency	Measured Power Spectral			Limit (dBm/500kHz)	Result
		Density				
		(dBm/500KHz)				
ANT A	ANT B	Total				
802.11 a	5745 MHz	3.45	3.07	/	30	PASS
	5785 MHz	1.52	0.88	/	30	PASS
	5825 MHz	0.12	-0.15	/	30	PASS
802.11 n20	5745 MHz	2.88	1.53	5.27	29.99	PASS
	5785 MHz	0.04	-0.71	2.69	29.99	PASS
	5825 MHz	-0.45	-0.99	2.30	29.99	PASS
802.11 n40	5755 MHz	-0.56	-1.99	1.79	29.99	PASS
	5795 MHz	-3.13	-4.07	-0.56	29.99	PASS










9. 6dB & 99% Emission Bandwidth

9.1 Block Diagram Of Test Setup



9.2 Limit

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

9.3 Test Procedure

- a) Set RBW = approximately 1% of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

9.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



9.5 Test Result



Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX Frequency U-NII-3(5745-5825MHz)		



Note: A(B) Represent the value of antenna A and B, The worst data is Antenna A, only shown Antenna A Plot.



Mode	Channel	Frequency (MHz)	99% bandwidth(MHz)	6dB bandwidth (MHz)	Limit MHz	Result
			ANT A	ANT A		
802.11a	CH149	5745	16.534	16.341	≥500	Pass
	CH157	5785	16.555	16.305	≥500	Pass
	CH165	5825	16.531	16.29	≥500	Pass
802.11 n20	CH149	5745	17.68	17.558	≥500	Pass
	CH157	5785	17.677	17.146	≥500	Pass
	CH165	5825	17.666	17.322	≥500	Pass
802.11 n40	CH151	5755	36.316	35.508	≥500	Pass
	CH159	5795	36.317	35.9	≥500	Pass



Mode	Channel	Frequency (MHz)	99% bandwidth(MHz)	6dB bandwidth (MHz)	Limit MHz	Result
			ANT B	ANT B		
802.11a	CH149	5745	16.559	16.309	≥500	Pass
	CH157	5785	16.552	16.32	≥500	Pass
	CH165	5825	16.527	16.275	≥500	Pass
802.11 n20	CH149	5745	17.701	17.298	≥500	Pass
	CH157	5785	17.701	17.261	≥500	Pass
	CH165	5825	17.643	17.04	≥500	Pass
802.11 n40	CH151	5755	36.152	35.35	≥500	Pass
	CH159	5795	36.207	35.148	≥500	Pass



-6dB Bandwidth
Test Graphs
-6dB Bandwidth NVNT a 5745MHz AntA

-6dB Bandwidth NVNT a 5785MHz AntA












99% OBW
Test Graphs
OBW NVNT a 5745MHz AntA

OBW NVNT a 5785MHz AntA









10. Maximum Conducted Output Power

10.1 Block Diagram Of Test Setup



10.2 Limit

According to FCC §15.407

The maximum conducted output power should not exceed:

Frequency Band(MHz)	Limit
5150~5250	1W
5725~5850	1W

10.3 Test Procedure

Maximum conducted output power may be measured using a spectrum analyzer/EMI receiver or an RF power meter.

1. Device Configuration

If possible, configure or modify the operation of the EUT so that it transmits continuously at its maximum power control level (see section II.B.).

a) The intent is to test at 100 percent duty cycle; however a small reduction in duty cycle (to no lower than 98 percent) is permitted if required by the EUT for amplitude control purposes. Manufacturers are expected to provide software to the test lab to permit such continuous operation.

b) If continuous transmission (or at least 98 percent duty cycle) cannot be achieved due to hardware limitations (e.g., overheating), the EUT shall be operated at its maximum power control level with the transmit duration as long as possible and the duty cycle as high as possible.

2. Measurement using a Spectrum Analyzer or EMI Receiver (SA)

Measurement of maximum conducted output power using a spectrum analyzer requires integrating the spectrum across a frequency span that encompasses, at a minimum, either the EBW or the 99-percent occupied bandwidth of the signal. However, the EBW must be used to determine bandwidth dependent limits on maximum conducted output power in accordance with § 15.407(a).

a) The test method shall be selected as follows: (i) Method SA-1 or SA-1 Alternative (averaging with the EUT transmitting at full power throughout each sweep) shall be applied if either of the following conditions can be satisfied:

- The EUT transmits continuously (or with a duty cycle ≥ 98 percent).

- Sweep triggering or gating can be implemented in a way that the device transmits at the maximum power control level throughout the duration of each of the instrument sweeps to be averaged. This condition can generally be achieved by triggering the instrument's sweep if the duration of the sweep (with the analyzer configured as in Method SA-1, below) is equal to or shorter than the duration T of each transmission from the EUT and if those transmissions exhibit full power throughout their durations.

(ii) Method SA-2 or SA-2 Alternative (averaging across on and off times of the EUT transmissions, followed by duty cycle correction) shall be applied if the conditions of (i) cannot be achieved and the transmissions exhibit a constant duty cycle during the measurement duration. Duty cycle will be considered to be constant if variations are less than ± 2 percent.

(iii) Method SA-3 (RMS detection with max hold) or SA-3 Alternative (reduced VBW with max hold) shall be applied if the conditions of (i) and (ii) cannot be achieved.

b) Method SA-1 (trace averaging with the EUT transmitting at full power throughout each sweep): (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.

(ii) Set RBW = 1 MHz.

(iii) Set VBW \geq 3 MHz.

(iv) Number of points in sweep \geq 2 Span / RBW. (This ensures that bin-to-bin spacing is \leq RBW/2, so that narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.


(vii) If transmit duty cycle < 98 percent, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle \geq 98 percent, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".

(viii) Trace average at least 100 traces in power averaging (i.e., RMS) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum

10.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.




10.5 Test Result

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX (5G) Mode Frequency U-NII-3 (5745-5825MHz)		

Mode	Test Channel	Frequency (MHz)	Maximum output power. Antenna port (AV)			LIMIT dBm	Result
			ANT A(dBm)	ANT B(dBm)	Total(dBm)		
TX 802.11a	CH 149	5745	10.16	9.4	/	30	Pass
	CH 157	5785	7.82	7.19	/	30	Pass
	CH 165	5825	6.89	6.36	/	30	Pass
TX 802.11 n20M	CH 149	5745	9.63	8.57	12.14	29.99	Pass
	CH 157	5785	7.03	6.3	9.69	29.99	Pass
	CH 165	5825	6.15	5.51	8.85	29.99	Pass
TX 802.11 n40M	CH 151	5755	9.26	7.81	11.61	29.99	Pass
	CH 159	5795	6.42	5.35	8.93	29.99	Pass

Note:
 $\text{limit} = 30 - (6.01 - 6) = 29.99$



11. Out Of Band Emissions

11.1 Block Diagram Of Test Setup



11.2 Limit

According to FCC §15.407(b)

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

11.3 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



11.4 EUT Operating Conditions



The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data



11.5 Test Result

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz

Note: A(B) Represent the value of antenna A and B, The worst data is Antenna A, only shown Antenna A Plot.








12. Spurious RF Conducted Emissions

12.1 Block Diagram Of Test Setup



12.2 Limit

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.725-5.85 GHz band(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge..

12.3 Test Procedure



1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



12.4 Test Result



Remark: The measurement frequency range is from 9KHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandedge measurement data.



About: 26.5GHz-40GHz, The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Note: A(B) Represent the value of antenna A and B, The worst data is Antenna A, only shown Antenna A Plot.










13. Frequency Stability Measurement

13.1 Block Diagram Of Test Setup



13.2 Limit

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

The transmitter center frequency tolerance shall be ± 20 ppm maximum for the 5 GHz band (IEEE 802.11n specification)..

13.3 Test Procedure

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f) / f_c \times 10^6$ ppm and he limit is less than ± 20 ppm (IEEE 802.11n specification).
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature is $-20^\circ\text{C} \sim 70^\circ\text{C}$.

13.4 Test Result

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz
Hzst Mode :	TX Frequency(5745-5825MHz)		

Voltage vs. Frequency Stabilit

TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	120.00	5745.00577	5745	0.00577	1.0046
		V max (V)	138.00	5745.00189	5745	0.00189	0.3291
		V min (V)	102.00	5745.00873	5745	0.00873	1.5193
Limits				5725-5850 MHz			
Result				Complies			

Temperature vs. Frequency Stability


TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	120	T (°C)	-20	5745.00179	5745	0.00179	0.3119
		T (°C)	-10	5745.00613	5745	0.00613	1.0677
		T (°C)	0	5745.00606	5745	0.00606	1.0551
		T (°C)	10	5745.00685	5745	0.00685	1.1919
		T (°C)	20	5745.01032	5745	0.01032	1.7956
		T (°C)	30	5745.00739	5745	0.00739	1.2866
		T (°C)	40	5745.00481	5745	0.00481	0.8380
		T (°C)	50	5745.00940	5745	0.00940	1.6356
		T (°C)	60	5745.00031	5745	0.00031	0.0547
		T (°C)	70	5745.01120	5745	0.01120	1.9499
Limits				5725-5850 MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	120.00	5785.00580	5785	0.00580	1.0032
		V max (V)	138.00	5785.00883	5785	0.00883	1.5267
		V min (V)	102.00	5785.00199	5785	0.00199	0.3438
Limits				5725-5850 MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	120	T (°C)	-20	5785.00819	5785	0.00819	1.4164
		T (°C)	-10	5785.00876	5785	0.00876	1.5140
		T (°C)	0	5785.00810	5785	0.00810	1.3997
		T (°C)	10	5785.00839	5785	0.00839	1.4511
		T (°C)	20	5785.00606	5785	0.00606	1.0470
		T (°C)	30	5785.00294	5785	0.00294	0.5083
		T (°C)	40	5785.00932	5785	0.00932	1.6116
		T (°C)	50	5785.00951	5785	0.00951	1.6446
		T (°C)	60	5785.00725	5785	0.00725	1.2529
		T (°C)	70	5785.00248	5785	0.00248	0.4291
Limits				5725-5850 MHz			
Result				Complies			




Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	120.00	5825.01305	5825	0.01305	2.2412
		V max (V)	138.00	5825.01258	5825	0.01258	2.1591
		V min (V)	102.00	5825.00488	5825	0.00488	0.8371
Limits				5725-5850 MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	120	T (°C)	-20	5825.00051	5825	0.00051	0.0871
		T (°C)	-10	5825.00110	5825	0.00110	0.1887
		T (°C)	0	5825.00673	5825	0.00673	1.1556
		T (°C)	10	5825.00004	5825	0.00004	0.0073
		T (°C)	20	5825.01035	5825	0.01035	1.7771
		T (°C)	30	5825.00626	5825	0.00626	1.0741
		T (°C)	40	5825.00141	5825	0.00141	0.2416
		T (°C)	50	5825.00759	5825	0.00759	1.3025
		T (°C)	60	5825.01130	5825	0.01130	1.9403
		T (°C)	70	5825.01102	5825	0.01102	1.8920
Limits				5725-5850 MHz			
Result				Complies			




14. Antenna Requirement

14.1 Limit

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

14.2 Test Result

The EUT antenna is External antenna (antenna gain (A): 3dBi; antenna gain (B) : 3dBi). It comply with the standard requirement.




15. EUT Photographs

EUT Photo 1




EUT Photo 2





16. EUT Test Setup Photographs

Conducted Measurement Photo



Radiated Measurement Photos





STATEMENT

- 1.The equipment lists are traceable to the national reference standards.
- 2.The test report can not be partially copied unless prior written approval is issued from our lab.
- 3.The test report is invalid without stamp of laboratory.
- 4.The test report is invalid without signature of person(s) testing and authorizing.
- 5.The test process and test result is only related to the Unit Under Test.
- 6.The quality system of our laboratory is in accordance with ISO/IEC17025.
- 7.If there is any objection to report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Tangwei, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL: 400-788-9558

P.C.: 518103

FAX: 0755-33229357

Website: <http://www.chnbctc.com>

E-Mail: bctc@bctc-lab.com.cn

***** END *****

