

RF EXPOSURE REPORT

CERTIFICATE OF CONFORMITY

FCC Rule Part: FCC Part 2 (Section 2.1091)

Report No.: MFBEDV-WTW-P24090203

FCC ID: 2AWD3ESRM2G3

Product: ESR-M

Brand: AOS ESR-M

Model No.: ESRM2G3

Series Model: ESRD3C4X (X =A-Z)

ESRE3C4X (X =A-Z)

Received Date: 2024/9/10

Test Date: 2024/10/15

Issued Date: 2024/11/5

Applicant: Aetheros Inc

Address: 80 Liberty Ship Way, Suites 6, Sausalito, CA 94965 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kewi Shan Dist., Taoyuan City 33383, Taiwan

FCC Registration / 788550 / TW0003

Designation Number:

Approved by:	Jeremy Lin	, Date:	2024/11/5	
	Jeremy Lin / Project Engineer			

This test report consists of 8 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.





Prepared by: Vera Huang / Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at https://www.bureauveritas.com/home/about-us/terms-conditions/ and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



Table of Contents

Relea	ase Control Record	3
1	Certificate	4
2	Applicable RF Exposure Limit	5
3	Test Results	7
4	Conclusion	7
5	Information of the Testing Laboratories	8



Release Control Record

Issue No.	Description	Date Issued
MFBEDV-WTW-P24090203	Original Release	2024/11/5

Report No.: MFBEDV-WTW-P24090203 Page No. 3 / 8 Report Format Version: 7.1.0



1 Certificate

Product: ESR-M

Brand: AOS ESR-M

Test Model: ESRM2G3

Series Model: ESRD3C4X (X =A-Z)

ESRE3C4X (X = A-Z)

Sample Status: Production Unit

Applicant: Aetheros Inc

Test Date: 2024/10/15

FCC Rule Part: FCC Part 2 (Section 2.1091)

Standard: KDB 447498 D04 Interim General RF Exposure Guidance v01

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.



2 Applicable RF Exposure Limit

- § 1.1310 Radiofrequency radiation exposure limits.
- (a) Specific absorption rate (SAR) shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in § 1.1307(b) of this part within the frequency range of 100 kHz to 6 GHz (inclusive).
- (b) The SAR limits for occupational/controlled exposure are 0.4 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 8 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit for occupational/controlled exposure is 20 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 6 minutes to determine compliance with occupational/controlled SAR limits.
- (c) The SAR limits for general population/uncontrolled exposure are 0.08 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 1.6 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit is 4 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 30 minutes to determine compliance with general population/uncontrolled SAR limits.

(e) Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields

Limits for General Population/Uncontrolled Exposure

Elithis for General i opulation/oricontrolled Exposure							
Frequency Range (MHz)	nge Electric Field Strength (V/m) Magnetic Field Strength Power Density (M/m) (mW/cm²)		9	Average Time (minutes)			
	Limits For General Population / Uncontrolled Exposure						
0.3-1.34	614	1.63	(100)*	<30			
1.34-30	824/f	2.19/f	(180/f ²)*	<30			
30-300	27.5	0.073	0.2	<30			
300-1,500			f/1500	<30			
1,500-100,000			1.0	<30			

f = frequency in MHz. * = Plane-wave equivalent power density.

Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time (minutes)			
	Limits For General Population / Uncontrolled Exposure						
0.3-3.0	614	1.63	*(100)	⊴6			
3.0-30	1842/f	4.89/f	*(900/f²)	<6			
30-300	61.4	0.163	1.0	<6			
300-1,500			f/300	<6			
1,500-100,000			5	<6			

f = frequency in MHz. * = Plane-wave equivalent power density.

Report No.: MFBEDV-WTW-P24090203 Page No. 5 / 8 Report Format Version: 7.1.0



MPE-based Exemption - §1.1307(b)(3)(i)(C)

> The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power.

Table applies to any RF source (i.e. single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits.

DE Source frequency (MUz)	Minimum	Distance	Threshold EDD (wette)			
RF Source frequency (MHz)	λ∟/ 2π	λн/ 2π	Threshold ERP (watts)			
0.3-1.34	159 m-	35.6 m	1,920 R².			
1.34-30	35.6 m–1.6 m		3,450 R ² /f ² .			
30-300	1.6 m–159 mm		3.83 R ² .			
300-1,500	159 mm-31.8 mm		0.0128 R ² f.			
1,500-100,000	31.8 mm–0.5 mm		19.2 R ^{2.}			
R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters.						

MPE-based Exemption - §1.1307(b)(3)(i)(B)

For mobile devices that are not exempt per Table 1 of §1.1307(b)(1)(i)(C) and device at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power.

$$P_{\text{th}} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \le f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \le f \le 6 \text{ GHz} \end{cases}$$



3 Test Results

Environmental Conditions:	25°C, 64% RH	Tested By:	Tim Chen
---------------------------	--------------	------------	----------

MPE-based Exemption §1.1307(b)(3)(i)(C)							
Operation Mode	Frequency Band (MHz)	Average Power (mW)	Antenna Gain (dBi)	Maximum ERP (mW)	Distance (cm)	Limit Threshold (mW)	Test Result
WLAN 2.4 GHz	2412-2462	51.168	1.9	48.306	20	768	Pass

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

MPE-based Exemption §1.1307(b)(3)(i)(B)							
Operation Mode Frequency Band (MHz) Average Power (mW) Antenna Gain (dBi) Maximum ERP (cm) Distance (cm) Test (mW) Test (mW)					Test Result		
Wi-Sun	915.2-927.8	389.045	3.54	535.796	20	1867.008	Pass

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

4 Conclusion

Source-base time average power is below Exemption Criteria and/or Routine Evaluation MPE thresholds, therefore the device is compliant FCC RF exposure requirement.

Report No.: MFBEDV-WTW-P24090203 Page No. 7 / 8 Report Format Version: 7.1.0



5 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180 Fax: 886-2-26051924

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: service.adt@bureauveritas.com
Web Site: http://ee.bureauveritas.com.tw

The address and road map of all our labs can be found in our web site also.

--- END ---

et us at the following:

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565 Fax: 886-3-6668323