

FCC ID: 2AWDBHTV213FRF

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1091, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

## Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b) Limits for Maximum Permissible Exposure (MPE)

	*20								
Frequency	Electric field	Magnetic field	Power density	Averaging time (minutes)					
range	strength	strength	(mW/cm <sup>2</sup> )						
(MHz)	(V/m)	(A/m)	(111117)						
(A) Limits for Occupational/Controlled Exposures									
0.3–3.0	614	1.63	*(100)	6					
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6					
30–300	61.4	0.163	1.0	6					
300–1500		41%	f/300	6					
1500-100,000			5	6					
(B) Limits for General Population/Uncontrolled Exposure									
0.3–1.34	614	1.63	*(100)	30					
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30					
30–300	27.5	0.073	0.2	30					
300–1500			f/1500	30					
1500-100,000			1.0	30					

f = frequency in MHz

Friis transmission formula:  $Pd = (Pout*G)/(4*pi*r^2)$ 

## Where

**Pd** = power density in mW/cm<sup>2</sup>, **Pout** = output power to antenna in mW;

**G** = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.









## **Test Procedure**

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

Mode	Max Power (dBm)	Tune-up power (dBm)	Max Power (mW)	Min. Distance (cm)	Calc. thresholds	limit
433.70MHz	-16.47	-16±1	0.0316	20	0.0000003	1.0

EIRP=78.69+20log(3)-104.7= -16.47dBm

So a SAR test is not required

Remark: Antenna gain=-13.66dBi

