

MPE REPORT

FCC ID:2AWEE-8762-01

Date of issue: May 27, 2020

Report number:	MTi20042002-1E2
Sample description:	BLE Bluetooth Module
Model(s):	8762-01
Applicant:	Shenzhen jingxun software communication technology Co. LTD
Address:	3/F, A5 Building Zhiyuan Community No.1001, Xueyuan Road Nanshan District, Shenzhen City
Date of test:	Apr. 29, 2020 to May 27, 2020

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>



TEST RESULT CERTIFICATION	
Applicant's name:	Shenzhen jingxun software communication technology Co. LTD
Address:	3/F, A5 Building Zhiyuan Community No.1001, Xueyuan Road Nanshan District, Shenzhen City
Manufacture's name:	Shenzhen jingxun software communication technology Co. LTD. Baoan branch
Address:	2nd floor, building A, no. 47, futang road, songgang tang xia chung, baoan district, shenzhen
Product name:	BLE Bluetooth Module
Trademark:	JINGXUNSOFT
Model and/or type reference:	8762-01
Serial model:	N/A
RF exposure procedures:	KDB 447498 D01 v06

This device described above has been tested by Shenzhen Microtest Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Tested by:

Danny Xu

May 27, 2020

Reviewed by:

Leo Su

May 27, 2020

Approved by:

Tom Xue

May 27, 2020

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*300/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π = 3.1415926

R = distance between observation point and center of the radiator in cm (20cm)

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

BLE:

Operation Frequency: 2402-2480MHz

Power density limited: 1mW/ cm²

Antenna Type: PCB Antenna;

WIFI antenna gain: 0dBi

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(0/10)}=1.00$

	Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
					tune-up power		Gain			
					(dBm)	(mW)	(dBi)	Numeric		
LE 1M	2402	GFSK	6.426	6±1	7	5.012	0.00	1.00	0.0010	1
	2440		6.737	6±1	7	5.012	0.00	1.00	0.0010	1
	2480		6.43	6±1	7	5.012	0.00	1.00	0.0010	1
LE 2M	2402	GFSK	3.178	3±1	4	2.512	0.00	1.00	0.0005	1
	2440		3.380	3±1	4	2.512	0.00	1.00	0.0005	1
	2480		3.740	3±1	4	2.512	0.00	1.00	0.0005	1

Conclusion:

For the max result: $0.0010 \leq 1.0$ for 1g SAR, No SAR is required.

----END OF REPORT----