


FCC PART 22/24/27 TEST REPORT

FCC Part 22H/Part 24E/Part 27

Report Reference No.....	LCS201214172AEC
FCC ID.....	2AWF3ES-AST-P100
Date of Issue.....	January 07, 2021
Testing Laboratory Name	Shenzhen LCS Compliance Testing Laboratory Ltd. 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Address Yabianxuezizhong, Shajing Street, Baoan District, Shenzhen, 518000, China
Applicant's name	SHENZHEN EVERSMART TECHNOLOGY CO., LTD. Address Floor 3, Building C, Seven Star Creative Workshop, BaoTian Road 1, Xixiang, Bao'an District, Shenzhen, GuangDong, China
Test specification.....	FCC CFR Title 47 Part 2, Part 22H, Part 24E, Part 27 Standard TIA-603-E: 2016 KDB971168 D01 Power Meas License Digital Systems v03r01
Test Report Form No	LCSEMC-1.0
TRF Originator	Shenzhen LCS Compliance Testing Laboratory Ltd.
Master TRF	Dated 2011-03
Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved. This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
Test item description.....	4G Car DVR
Trade Mark.....	AddSecure
Test Model	AddSecure FFC LTE NA
Modulation Type	QPSK, 16QAM
Rating.....	Input: DC 12/24V
Hardware version.....	P100_Vx
Software version	P100.NO.ES.RTL_D8_YE22.V1.2021xxxx.xxxxxx
Result.....	PASS

Compiled by:



Supervised by:



Approved by:



Ray Yang/ Administrators

Jin Wang/ Technique principal

Gavin Liang/ Manager

TEST REPORT

Test Report No. :	LCS201214172AEC	January 07, 2021
		Date of issue

Equipment under Test : 4G Car DVR

Test Model : AddSecure FFC LTE NA

Applicant : SHENZHEN EVERSMART TECHNOLOGY CO., LTD.

Address : Floor 3, Building C, Seven Star Creative Workshop, BaoTian Road 1, Xixiang, Bao'an District, Shenzhen, GuangDong, China

Manufacturer : Shenzhen Turui Digital Tech Co., Ltd

Address : Floor 2.4.5, Building 4, Workshopt of HongXiang Industrial Park, Hezhou Development Zone, Xixiang Residential District, Bao'an, Shenzhen City, Guangdong Province, P.R.China

Factory : /

Address : /

Test Result:	PASS
--------------	------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Revision	Issue Date	Revisions	Revised By
000	January 07, 2021	Initial Issue	Gavin Liang

Contents

<u>1</u>	<u>TEST STANDARDS</u>	5
<u>2</u>	<u>SUMMARY</u>	6
2.1	General Remarks	6
2.2	Product Description	6
2.3	Equipment under Test	8
2.4	Short description of the Equipment under Test (EUT)	8
2.5	Normal Accessory setting	8
2.6	EUT configuration	8
2.7	Related Submittal(s) / Grant (s)	8
2.8	Modifications	8
2.9	General Test Conditions/Configurations	9
<u>3</u>	<u>TEST ENVIRONMENT</u>	10
3.1	Address of the test laboratory	10
3.2	Test Facility	10
3.3	Environmental conditions	10
3.4	Test Description	10
3.5	Equipments Used during the Test	13
3.6	Measurement uncertainty	14
<u>4</u>	<u>TEST CONDITIONS AND RESULTS</u>	15
4.1	Output Power	15
4.2	Peak-to-Average Ratio (PAR)	25
4.3	Occupied Bandwidth and Emission Bandwidth	26
4.4	Band Edge compliance	27
1.1	Spurious Emssion on Antenna Port	29
4.5	Radiated Spurious Emssion	31
4.6	Frequency Stability under Temperature & Voltage Variations	40
<u>5</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	49
<u>6</u>	<u>EXTERNAL PHOTOS OF THE EUT</u>	49
<u>7</u>	<u>INTERNAL PHOTOS OF THE EUT</u>	49

1 TEST STANDARDS

The tests were performed according to following standards:

[FCC Part 22H](#): Cellular Radiotelephone Service

[FCC Part 24E](#): Broadband PCS

[FCC Part 27](#): MISCELLANEOUS WIRELESS COMMUNICATIONS SERVICES

[TIA-603-E March 2016](#): Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

[47 CFR FCC Part 15 Subpart B](#): Unintentional Radiators

[FCC Part 2](#): FREQUENCY ALLOCATION AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS

[ANSI C63.4:2014](#): Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

[FCC KDB971168 D01](#) Power Meas License Digital Systems v03r01

2 SUMMARY

2.1 General Remarks

Date of receipt of test sample	:	December 16, 2020
Testing commenced on	:	December 16, 2020 ~ December 31, 2020
Date of Report	:	January 07, 2021

2.2 Product Description

The **SHENZHEN EVERSMART TECHNOLOGY CO., LTD.**’s Model: AddSecure FFC LTE NA or the “EUT” as referred to in this report; more general information as follows, for more details, refer to the user’s manual of the EUT.

EUT	:	4G Car DVR
Test Model	:	AddSecure FFC LTE NA
Additional Models No.	:	ES-D6, ES-D6 Plus, ES-D5, ES-D5 Plus, AddSecure FFC LTE EU/AU
Models Declaration	:	PCB board, structure and internal of these model(s) are the same, So no additional models were tested
Power Supply	:	Input: DC 12/24V
Hardware Version	:	P100_Vx
Software Version	:	P100.NO.ES.RTL_D8_YE22.V1.2021xxxx.xxxxxx
WIFI(2.4G Band)	:	
Frequency Range	:	2412MHz ~ 2462MHz
Channel Spacing	:	5MHz
Channel Number	:	11 Channel for 20MHz bandwidth(2412~2462MHz) 7 Channel for 20MHz bandwidth(2422~2452MHz)
Modulation Type	:	802.11b: DSSS; 802.11g/n: OFDM
Antenna Description	:	PIFA Antenna, -1.2dBi(Max.)

3G

Support Band	:	<input checked="" type="checkbox"/> WCDMA Band II (U.S.-Band) <input checked="" type="checkbox"/> WCDMA Band V (U.S.-Band) <input checked="" type="checkbox"/> WCDMA Band IV (U.S.-Band) <input type="checkbox"/> WCDMA Band I (EU-Band) <input type="checkbox"/> WCDMA Band VIII (EU-Band)
Release Version	:	R7
Type Of Modulation	:	WCDMA: QPSK; HSDPA/HSUPA: QPSK
Antenna Description	:	PIFA Antenna; -1.78dBi (max.) For WCDMA Band II -1.78dBi (max.) For WCDMA Band IV -1.78dBi (max.) For WCDMA Band V

LTE

Support Band	:	<input checked="" type="checkbox"/> E-UTRA Band 2(U.S.-Band) <input checked="" type="checkbox"/> E-UTRA Band 4(U.S.-Band)
--------------	---	--

	<input checked="" type="checkbox"/> E-UTRA Band 5(U.S.-Band)
	<input checked="" type="checkbox"/> E-UTRA Band 12(U.S.-Band)
	<input checked="" type="checkbox"/> E-UTRA Band 17(U.S.-Band)
LTE Release Version	: R10
Type Of Modulation	: QPSK/16QAM
Antenna Description	: PIFA Antenna; 1.1dBi (max.) For E-UTRA Band 2 1.1dBi (max.) For E-UTRA Band 4 1.1dBi (max.) For E-UTRA Band 5 1.1dBi (max.) For E-UTRA Band 12 1.1dBi (max.) For E-UTRA Band 17
Power Class	: Class 3
GPS function	: Support and only RX
Extreme temp. Tolerance	: -20°C to +70°C
Extreme vol. Limits	: 10.2VDC to 13.8VDC (nominal: 12VDC)

2.3 Equipment under Test

Power supply system utilised

Power supply voltage	:	<input type="radio"/>	120V / 60 Hz	<input type="radio"/>	115V / 60Hz
		<input checked="" type="radio"/>	12 V DC	<input checked="" type="radio"/>	24 V DC
		<input type="radio"/>	Other (specified in blank below)	3.7 V DC	

2.4 Short description of the Equipment under Test (EUT)

2.4.1 General Description

4G Car DVR is subscriber equipment in the 2.4WIFI/ WCDMA/ LTE system. LTE frequency bands are band 2/4/5/12/17. The LTE frequency band 2/4/5/12/17 test data included in this report. The 4G Car DVR implements such functions as RF signal receiving/transmitting, GSM/GPRS/EGPRS/ HSPA/UMTS/LTE protocol processing, video MMS service and etc. Externally it provides SIM card interface.

2.5 Normal Accessory setting

Fully charged battery was used during the test.

2.6 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

<input type="radio"/>	Power Cable	Length (m) :	/
		Shield :	/
		Detachable :	/
<input type="radio"/>	Multimeter	Manufacturer :	/
		Model No. :	/

2.7 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: 2AWF3ES-AST-P100 filing to comply with FCC Part 22, Part 24 , Part 27 Rules

2.8 Modifications

No modifications were implemented to meet testing criteria.

2.9 General Test Conditions/Configurations

2.10.1 Test Environment

Environment Parameter	Selected Values During Tests	
Relative Humidity	Ambient	
Temperature	TN	Ambient
Voltage	VL	DC 10.2V
	VN	DC 12V
	VH	DC 13.8V

Environment Parameter	Selected Values During Tests	
Relative Humidity	Ambient	
Temperature	TN	Ambient
Voltage	VL	DC 20.4V
	VN	DC 24V
	VH	DC 27.6V

NOTE: VL=lower extreme test voltage VN=nominal voltage

VH=upper extreme test voltage TN=normal temperature

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen LCS Compliance Testing Laboratory Ltd

101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

The sites are constructed in conformance with the requirements of ANSI C63.4 (2014) and CISPR Publication 22.

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4 Test Description

Band 2 (1850-1910MHz paired with 1930-1990MHz)

Test Item	FCC Rule No.	Requirements	Verdict
Effective(Isotropic) Radiated Output Power	§2.1046, §24.232	EIRP ≤ 2W	PASS
Peak-Average Ratio	§2.1046, §24.232	FCC: Limit ≤ 13dB	PASS
Modulation Characteristics	§2.1047	Digital modulation	N/A
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	PASS
Band Edges Compliance	§2.1051, §24.238	≤ -13dBm/1%*EBW, In 1MHz bands immediately outside and adjacent to the frequency block.	PASS
Spurious Emission at Antenna Terminals	§2.1051, §24.238	≤ -13dBm/1MHz, from 9kHz to 10 th harmonics but outside authorized Operating frequency ranges.	PASS
Field Strength of Spurious Radiation	§2.1053, §24.238	≤ -13dBm/1MHz.	PASS
Frequency Stability	§2.1055, §24.235	FCC: within authorized frequency block.	PASS

NOTE 1: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".

Band 4 (1710-1755MHz paired with 2110-2155MHz)

Test Item	FCC Rule No.	Requirements	Verdict
Effective(Isotropic) Radiated Power Output Data	§2.1046, §27.50(d)	EIRP ≤ 1W;	PASS
Peak-Average Ratio	§2.1046, §27.50(d)	Limit ≤ 13dB	Pass
Modulation Characteristics	§2.1047	Digital modulation	N/A
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	PASS
Band Edges Compliance	§2.1051, §27.53(h)	≤ -13dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	PASS
Spurious Emission at Antenna Terminals	§2.1051, §27.53(h)	≤ -13dBm/1MHz, from 9kHz to 10 th harmonics but outside authorized operating frequency ranges.	PASS
Frequency Stability	§2.1055, §27.54	Within authorized bands of operation/frequency block.	PASS
Radiated spurious emission	§2.1053, §27.53(h)	≤ -13dBm/1MHz.	PASS

NOTE 1: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested"

Band 5 (824-849MHz paired with 869-894MHz)

Test Item	FCC Rule No.	Requirements	Verdict
Effective(Isotropic) Radiated Output Power	§2.1046, §22.913	FCC: ERP ≤ 7W.	Pass
Modulation Characteristics	§2.1047	Digital modulation	N/A
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Pass
Band Edges Compliance	§2.1051, §22.917	≤ -13dBm/1%*EBW, In 1MHz bands immediately outside and adjacent to the frequency block.	Pass
Spurious Emission at Antenna Terminals	§2.1051, §22.917	FCC: ≤ -13dBm/100kHz, from 9kHz to 10 th harmonics but outside authorized operating frequency ranges.	Pass
Field Strength of Spurious Radiation	§2.1053, §22.917	FCC: ≤ -13dBm/100kHz.	Pass
Frequency Stability	§2.1055, §22.355	≤ ±2.5ppm.	Pass

NOTE 1: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".

Band 12 (699-716MHz paired with 729-746MHz)

Test Item	FCC Rule No.	Requirements	Verdict
Effective(Isotropic) Radiated Power Output Data	§2.1046, §27.50(c)	ERP ≤ 3W;	PASS
Peak-Average Ratio	§2.1046, §27.50(c)	Limit≤13dB	PASS
Modulation Characteristics	§2.1047	Digitalmodulation	N/A
Bandwidth	§2.1049	OBW: Nolimit. EBW: Nolimit.	PASS
BandEdges Compliance	§2.1051, §27.53(g)	≤ -13dBm/1%*EBW,in1 MHz bands immediately outside and adjacent to The frequency block.	PASS
Spurious Emission at Antenna Terminals	§2.1051, §27.53(g)	≤ -13dBm/100KHz, from 9kHz to10th harmonics but outside authorized Operating frequency ranges.	PASS
Frequency Stability	§2.1055, §27.54	Within authorized bands of operation/frequency block.	PASS
Radiatedspurious emission	§2.1053, §27.53(g)	≤ -13dBm/100KHz.	PASS

NOTE 1:For the verdict, the "N/A"denotes"not applicable",the "N/T"de notes "not tested".

Band 17(704-716MHz pairedwith 734-746MHz)

Test Item	FCC Rule No.	Requirements	Verdict
Effective(Isotropic) Radiated Power Output Data	§2.1046, §27.50(b)	ERP ≤ 3W;	PASS
Peak-Average Ratio	§2.1046, §27.50(b)	Limit≤13dB	PASS
Modulation Characteristics	§2.1047	Digitalmodulation	N/A
Bandwidth	§2.1049	OBW: Nolimit. EBW: Nolimit.	PASS
BandEdges Compliance	§2.1051, §27.53(c)	≤ -13dBm/1%*EBW,in1 MHz bands immediately outside and adjacent to The frequency block.	PASS
Spurious Emission at Antenna Terminals	§2.1051, §27.53(c)	≤ -13dBm/100KHz, from 9kHz to10th harmonics but outside authorized Operating frequency ranges.	PASS
Frequency Stability	§2.1055, §27.54	Within authorized bands of operation/frequency block.	PASS
Radiated spurious emission	§2.1053, §27.53(c)	≤ -13dBm/100KHz.	PASS

NOTE 1:For the verdict, the "N/A"denotes"not applicable",the "N/T"de notes "not tested".

3.5 Equipments Used during the Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	LTE Test Software	Tonscend	JS1120-1	N/A	N/A	N/A
2	RF Control Unit	Tonscend	JS0806	158060009	2020-06-22	2021-06-21
3	MXA Signal Analyzer	Agilent	N9020A	MY51250905	2020-11-21	2021-11-20
4	DC Power Supply	Agilent	E3642A	N/A	2020-11-13	2021-11-12
5	MXG Vector Signal Generator	Agilent	N5182A	MY47071151	2020-06-22	2021-06-21
6	PSG Analog Signal Generator	Agilent	E8257D	MY4520521	2020-06-22	2021-06-21
7	Temperature & Humidity Chamber	GUANGZHOU GOGNWEN	GDS-100	70932	2020-10-08	2021-10-07
8	EMI Test Software	AUDIX	E3	/	N/A	N/A
9	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2020-06-22	2021-06-21
10	Positioning Controller	MF	MF7082	MF78020803	2020-06-22	2021-06-21
11	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00005	2018-07-26	2021-07-25
12	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2018-07-26	2021-07-25
13	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2018-07-02	2021-07-01
14	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	791	2020-09-20	2023-09-19
15	Broadband Preamplifier	SCHWARZBECK	BBV9745	9719-025	2020-06-22	2021-06-21
16	EMI Test Receiver	R&S	ESR 7	101181	2020-06-22	2021-06-21
17	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2020-11-21	2021-11-20
18	Broadband Preamplifier	/	BP-01M18G	P190501	2020-06-22	2021-06-21
19	RF Cable-R03m	Jye Bao	RG142	CB021	2020-06-22	2021-06-21
20	RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	2020-06-22	2021-06-21
21	WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW 500	103818	2020-06-22	2021-06-21
22	RF Filter	Micro-Tronics	BR50718	S/N-017	2020-11-21	2021-11-20
23	RF Filter	Micro-Tronics	BR50719	S/N-011	2020-11-21	2021-11-20
24	RF Filter	Micro-Tronics	BR50720	S/N-011	2020-11-21	2021-11-20
25	RF Filter	Micro-Tronics	BR50721	S/N-013	2020-11-21	2021-11-20
26	RF Filter	Micro-Tronics	BRM50702	S/N-195	2020-06-22	2021-06-21
27	6dB Attenuator	/	100W/6dB	1172040	2020-06-22	2021-06-21
28	3dB Attenuator	/	2N-3dB	/	2020-06-22	2021-06-21
29	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2020-11-21	2021-11-20

Note: All equipment is calibrated through CHINA CEPREI LABORATORY and GUANGZHOU LISAI CALIBRATION AND TEST CO., LTD.

3.6 Measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to ETSI TR 100 028 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics" and is documented in the Shenzhen LCS Compliance Testing Laboratory Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen LCS Compliance Testing Laboratory Ltd. is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	3.10 dB	(1)
Radiated Emission	1~18GHz	3.80 dB	(1)
Radiated Emission	18~40GHz	3.90 dB	(1)
Conducted Disturbance	0.15~30MHz	1.63 dB	(1)
Conducted Power	9KHz~18GHz	0.61 dB	(1)
Spurious RF Conducted Emission	9KHz~40GHz	1.22 dB	(1)
Band Edge Compliance of RF Emission	9KHz~40GHz	1.22 dB	(1)
Occupied Bandwidth	9KHz~40GHz	-	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

4 TEST CONDITIONS AND RESULTS


4.1 Output Power

TEST APPLICABLE

During the process of testing, the EUT was controlled via R&S Digital Radio Communication tester (CMW 500) to ensure max power transmission and proper modulation. This result contains output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

4.1.1. Conducted Output Power

TEST CONFIGURATION



TEST PROCEDURE

Conducted Power Measurement:

- a) Place the EUT on a bench and set it in transmitting mode.
- b) Connect a low loss RF cable from the antenna port to a CMW 500 by an Att.
- c) EUT Communicate with CMW 500 then selects a channel for testing.
- d) Add a correction factor to the display CMW 500, and then test.

TEST RESULTS

Remark:

1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 2, LTE FDD Band 4, LTE FDD Band 5, LTE FDD Band 12, LTE FDD Band 17; recorded worst case for each Channel Bandwidth of LTE FDD Band 2, LTE FDD Band 4, LTE FDD Band 5, LTE FDD Band 12, LTE FDD Band 17
2. For E-UTRA Band 2, please refer to Appendix B: Section B.1
3. For E-UTRA Band 4, please refer to Appendix C: Section C.1
4. For E-UTRA Band 5, please refer to Appendix D: Section D.1
5. For E-UTRA Band 12, please refer to Appendix E: Section E.1
6. For E-UTRA Band 17, please refer to Appendix F: Section H.1

4.1.2. Radiated Output Power

LIMIT

This is the test for the maximum radiated power from the EUT.

Per §22.913(2) Extend coverage on a secondary basis into cellular unserved areas, as those areas are defined in §22.949, the ERP of base transmitters and cellular repeaters of such systems must not exceed 1000 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.


Rule Part 24.232(c) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(e) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Per Part 27.50(d) (4) specifies, Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755MHz band are limited to 1W EIRP. Fixed stations operating in this band are limited to a maximum antenna height of 10 meters above ground. Mobile and portable stations operating in this band must employ a means for limiting power to the minimum necessary for successful communications.

Per Part 27.50(c) (10) specifies, Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

Per Part 27.50(h) (2) specifies Mobile and other user stations. Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

TEST CONFIGURATION



TEST PROCEDURE

1. EUT was placed on a 1.50 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.50m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz, And the maximum value of the receiver should be recorded as (P_r).
4. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
5. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (P_{cl}), the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.
The measurement results are obtained as described below:
$$\text{Power(EIRP)} = P_{Mea} + P_{Ag} - P_{cl} + G_a$$
6. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
7. ERP can be calculated from EIRP by subtracting the gain of the dipole, $\text{ERP} = \text{EIRP} - 2.15\text{dBi}$.

TEST RESULTS

Radiated Measurement:

Remark:

1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 2, LTE FDD Band 4, LTE FDD Band 5, LTE FDD Band 12, LTE FDD Band 17; recorded worst case for each Channel Bandwidth of LTE FDD Band 2, LTE FDD Band 4, LTE FDD Band 5, LTE FDD Band 12, LTE FDD Band 17
2. $\text{EIRP} = P_{Mea}(\text{dBm}) - P_{cl}(\text{dB}) + P_{Ag}(\text{dB}) + G_a(\text{dBi})$
3. $\text{ERP} = \text{EIRP} - 2.15\text{dBi}$ as EIRP by subtracting the gain of the dipole.
4. Margin = Emission Level - Limit
5. We test the H direction and V direction recorded worst case

LTE FDD Band 2_Channel Bandwidth 1.4MHz_QPSK

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	G_a Antenna Gain(dB)	P_{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.7	-19.31	4.03	8.38	35.51	20.55	33.01	-12.46	V
1880.0	-19.25	4.08	8.33	35.56	20.56	33.01	-12.45	V
1909.3	-19.79	4.14	8.26	35.63	19.96	33.01	-13.05	V

LTE FDD Band 2_Channel Bandwidth 3MHz_QPSK

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	G_a Antenna Gain(dB)	P_{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1851.5	-20.01	4.03	8.38	35.51	19.85	33.01	-13.16	V
1880.0	-20.41	4.08	8.33	35.56	19.40	33.01	-13.61	V
1908.5	-20.16	4.14	8.26	35.63	19.59	33.01	-13.42	V

LTE FDD Band 2_Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	G_a Antenna Gain(dB)	P_{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1852.5	-20.24	4.03	8.38	35.51	19.62	33.01	-13.39	V
1880.0	-20.13	4.08	8.33	35.56	19.68	33.01	-13.33	V
1907.5	-20.98	4.14	8.26	35.63	18.77	33.01	-14.24	V

LTE FDD Band 2_Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1855.0	-20.53	4.03	8.38	35.51	19.33	33.01	-13.68	V
1880.0	-20.75	4.08	8.33	35.56	19.06	33.01	-13.95	V
1905.0	-21.50	4.14	8.26	35.63	18.25	33.01	-14.76	V

LTE FDD Band 2_Channel Bandwidth 15MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1857.5	-21.60	4.03	8.38	35.51	18.26	33.01	-14.75	V
1880.0	-21.37	4.08	8.33	35.56	18.44	33.01	-14.57	V
1902.5	-21.79	4.14	8.26	35.63	17.96	33.01	-15.05	V

LTE FDD Band 2_Channel Bandwidth 20MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1860.0	-21.87	4.03	8.38	35.51	17.99	33.01	-15.02	V
1880.0	-21.64	4.08	8.33	35.56	18.17	33.01	-14.84	V
1900.0	-21.76	4.14	8.26	35.63	17.99	33.01	-15.02	V

LTE FDD Band 2_Channel Bandwidth 1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.7	-20.47	4.03	8.38	35.51	19.39	33.01	-13.62	V
1880.0	-19.94	4.08	8.33	35.56	19.87	33.01	-13.14	V
1909.3	-19.66	4.14	8.26	35.63	20.09	33.01	-12.92	V

LTE FDD Band 2_Channel Bandwidth 3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1851.5	-20.47	4.03	8.38	35.51	19.39	33.01	-13.62	V
1880.0	-20.96	4.08	8.33	35.56	18.85	33.01	-14.16	V
1908.5	-20.84	4.14	8.26	35.63	18.91	33.01	-14.10	V

LTE FDD Band 2_Channel Bandwidth 5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1852.5	-21.28	4.03	8.38	35.51	18.58	33.01	-14.43	V
1880.0	-21.37	4.08	8.33	35.56	18.44	33.01	-14.57	V
1907.5	-21.11	4.14	8.26	35.63	18.64	33.01	-14.37	V

LTE FDD Band 2_Channel Bandwidth 10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1855.0	-21.49	4.03	8.38	35.51	18.37	33.01	-14.64	V
1880.0	-21.35	4.08	8.33	35.56	18.46	33.01	-14.55	V
1905.0	-21.01	4.14	8.26	35.63	18.74	33.01	-14.27	V

LTE FDD Band 2_Channel Bandwidth 15MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1857.5	-22.14	4.03	8.38	35.51	17.72	33.01	-15.29	V
1880.0	-21.61	4.08	8.33	35.56	18.20	33.01	-14.81	V
1902.5	-21.54	4.14	8.26	35.63	18.21	33.01	-14.80	V

LTE FDD Band 2_Channel Bandwidth 20MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1860.0	-22.83	4.03	8.38	35.51	17.03	33.01	-15.98	V
1880.0	-22.60	4.08	8.33	35.56	17.21	33.01	-15.80	V
1900.0	-22.73	4.14	8.26	35.63	17.02	33.01	-15.99	V

LTE FDD Band 4_Channel Bandwidth 1.4MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1710.7	-18.71	3.93	9.05	34.96	21.37	30.00	-8.63	V
1732.5	-19.04	3.93	8.89	35.01	20.93	30.00	-9.07	V
1754.3	-18.89	3.94	8.76	35.08	21.01	30.00	-8.99	V

LTE FDD Band 4_Channel Bandwidth 3MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1711.5	-18.92	3.93	9.05	34.96	21.16	30.00	-8.84	V
1732.5	-19.62	3.93	8.89	35.01	20.35	30.00	-9.65	V
1753.5	-19.08	3.94	8.76	35.08	20.82	30.00	-9.18	V

LTE FDD Band 4_Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1712.5	-18.64	3.93	9.05	34.96	21.44	30.00	-8.56	V
1732.5	-19.17	3.93	8.89	35.01	20.80	30.00	-9.20	V
1752.5	-18.59	3.94	8.76	35.08	21.31	30.00	-8.69	V

LTE FDD Band 4_Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1715.0	-19.58	3.93	9.05	34.96	20.50	30.00	-9.50	V
1732.5	-18.92	3.93	8.89	35.01	21.05	30.00	-8.95	V
1750.0	-19.62	3.94	8.76	35.08	20.28	30.00	-9.72	V

LTE FDD Band 4_Channel Bandwidth 15MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1717.5	-19.11	3.93	9.05	34.96	20.97	30.00	-9.03	V
1732.5	-18.66	3.93	8.89	35.01	21.31	30.00	-8.69	V
1747.5	-18.54	3.94	8.76	35.08	21.36	30.00	-8.64	V

LTE FDD Band 4_Channel Bandwidth 20MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1720.0	-19.81	3.93	9.05	34.96	20.27	30.00	-9.73	V
1732.5	-19.85	3.93	8.89	35.01	20.12	30.00	-9.88	V
1745.0	-19.56	3.94	8.76	35.08	20.34	30.00	-9.66	V

LTE FDD Band 4_Channel Bandwidth 1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1710.7	-19.76	3.93	9.05	34.96	20.32	30.00	-9.68	V
1732.5	-19.53	3.93	8.89	35.01	20.44	30.00	-9.56	V
1754.3	-19.11	3.94	8.76	35.08	20.79	30.00	-9.21	V

LTE FDD Band 4_Channel Bandwidth 3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1711.5	-18.60	3.93	9.05	34.96	21.48	30.00	-8.52	V
1732.5	-19.27	3.93	8.89	35.01	20.70	30.00	-9.30	V
1753.5	-19.47	3.94	8.76	35.08	20.43	30.00	-9.57	V

LTE FDD Band 4_Channel Bandwidth 5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1712.5	-19.05	3.93	9.05	34.96	21.03	30.00	-8.97	V
1732.5	-19.06	3.93	8.89	35.01	20.91	30.00	-9.09	V
1752.5	-19.41	3.94	8.76	35.08	20.49	30.00	-9.51	V

LTE FDD Band 4_Channel Bandwidth 10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1715.0	-19.34	3.93	9.05	34.96	20.74	30.00	-9.26	V
1732.5	-19.11	3.93	8.89	35.01	20.86	30.00	-9.14	V
1750.0	-19.45	3.94	8.76	35.08	20.45	30.00	-9.55	V

LTE FDD Band 4_Channel Bandwidth 15MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1717.5	-19.71	3.93	9.05	34.96	20.37	30.00	-9.63	V
1732.5	-19.41	3.93	8.89	35.01	20.56	30.00	-9.44	V
1747.5	-19.39	3.94	8.76	35.08	20.51	30.00	-9.49	V

LTE FDD Band 4_Channel Bandwidth 20MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Aq} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1720.0	-19.04	3.93	9.05	34.96	21.04	30.00	-8.96	V
1732.5	-19.31	3.93	8.89	35.01	20.66	30.00	-9.34	V
1745.0	-18.92	3.94	8.76	35.08	20.98	30.00	-9.02	V

LTE FDD Band 5_Channel Bandwidth 1.4MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Aq} (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
824.70	-16.48	3.45	8.45	2.15	33.79	20.16	38.45	-18.29	V
836.50	-16.40	3.49	8.45	2.15	33.85	20.26	38.45	-18.19	V
848.30	-16.02	3.55	8.36	2.15	33.88	20.52	38.45	-17.93	V

LTE FDD Band 5_Channel Bandwidth 3MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Aq} (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
825.50	-15.57	3.45	8.45	2.15	33.79	21.07	38.45	-17.38	V
836.50	-16.03	3.49	8.45	2.15	33.85	20.63	38.45	-17.82	V
847.50	-15.82	3.55	8.36	2.15	33.88	20.72	38.45	-17.73	V

LTE FDD Band 5_Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Aq} (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
826.50	-15.54	3.45	8.45	2.15	33.79	21.10	38.45	-17.35	V
836.50	-16.22	3.49	8.45	2.15	33.85	20.44	38.45	-18.01	V
846.50	-16.37	3.55	8.36	2.15	33.88	20.17	38.45	-18.28	V

LTE FDD Band 5_Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Aq} (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
829.00	-15.94	3.45	8.45	2.15	33.79	20.70	38.45	-17.75	V
836.50	-15.95	3.49	8.45	2.15	33.85	20.71	38.45	-17.74	V
844.00	-15.59	3.55	8.36	2.15	33.88	20.95	38.45	-17.50	V

LTE FDD Band 5_Channel Bandwidth 1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Aq} (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
824.70	-16.90	3.45	8.45	2.15	33.79	19.74	38.45	-18.71	V
836.50	-17.31	3.49	8.45	2.15	33.85	19.35	38.45	-19.10	V
848.30	-17.11	3.55	8.36	2.15	33.88	19.43	38.45	-19.02	V

LTE FDD Band 5_Channel Bandwidth 3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Aq} (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
825.50	-16.70	3.45	8.45	2.15	33.79	19.94	38.45	-18.51	V
836.50	-16.65	3.49	8.45	2.15	33.85	20.01	38.45	-18.44	V
847.50	-16.90	3.55	8.36	2.15	33.88	19.64	38.45	-18.81	V

LTE FDD Band 5_Channel Bandwidth 5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Aq} (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
826.50	-17.50	3.45	8.45	2.15	33.79	19.14	38.45	-19.31	V
836.50	-17.11	3.49	8.45	2.15	33.85	19.55	38.45	-18.90	V
846.50	-17.37	3.55	8.36	2.15	33.88	19.17	38.45	-19.28	V

LTE FDD Band 5_Channel Bandwidth 10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Aq} (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
829.00	-16.72	3.45	8.45	2.15	33.79	19.92	38.45	-18.53	V
836.50	-17.37	3.49	8.45	2.15	33.85	19.29	38.45	-19.16	V
844.00	-16.81	3.55	8.36	2.15	33.88	19.73	38.45	-18.72	V

LTE FDD Band 12_Channel Bandwidth 1.4MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain (dB)	P _{Aq} (dB)	Correction (dB)	Burst Avergae ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
699.70	-14.49	3.01	8.29	33.52	2.15	22.16	34.77	-12.61	V
707.50	-14.05	3.02	8.29	33.52	2.15	22.59	34.77	-12.18	V
715.30	-14.57	3.06	8.29	33.52	2.15	22.03	34.77	-12.74	V

LTE FDD Band 12_Channel Bandwidth 3MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain (dB)	P _{Aq} (dB)	Correction (dB)	Burst Avergae ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
700.50	-15.24	3.01	8.29	33.52	2.15	21.41	34.77	-13.36	V
707.50	-15.27	3.02	8.29	33.52	2.15	21.37	34.77	-13.40	V
714.50	-14.56	3.06	8.29	33.52	2.15	22.04	34.77	-12.73	V

LTE FDD Band 12_Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain (dB)	P _{Aq} (dB)	Correction (dB)	Burst Avergae ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
701.50	-15.68	3.01	8.29	33.52	2.15	20.97	34.77	-13.80	V
707.50	-15.45	3.02	8.29	33.52	2.15	21.19	34.77	-13.58	V
713.50	-15.23	3.06	8.29	33.52	2.15	21.37	34.77	-13.40	V

LTE FDD Band 12_Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain (dB)	P _{Aq} (dB)	Correction (dB)	Burst Avergae ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
704.00	-16.20	3.01	8.29	33.52	2.15	20.45	34.77	-14.32	V
707.50	-15.69	3.02	8.29	33.52	2.15	20.95	34.77	-13.82	V
711.00	-16.45	3.06	8.29	33.52	2.15	20.15	34.77	-14.62	V

LTE FDD Band 12_Channel Bandwidth 1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain (dB)	P _{Aq} (dB)	Correction (dB)	Burst Avergae ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
699.70	-14.89	3.01	8.29	33.52	2.15	21.76	34.77	-13.01	V
707.50	-15.45	3.02	8.29	33.52	2.15	21.19	34.77	-13.58	V
715.30	-14.78	3.06	8.29	33.52	2.15	21.82	34.77	-12.95	V

LTE FDD Band 12_Channel Bandwidth 3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain (dB)	P _{Aq} (dB)	Correction (dB)	Burst Avergae ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
700.50	-15.06	3.01	8.29	33.52	2.15	21.59	34.77	-13.18	V
707.50	-15.11	3.02	8.29	33.52	2.15	21.53	34.77	-13.24	V
714.50	-15.35	3.06	8.29	33.52	2.15	21.25	34.77	-13.52	V

LTE FDD Band 12_Channel Bandwidth 5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain (dB)	P _{Aq} (dB)	Correction (dB)	Burst Avergae ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
701.50	-15.69	3.01	8.29	33.52	2.15	20.96	34.77	-13.81	V
707.50	-15.86	3.02	8.29	33.52	2.15	20.78	34.77	-13.99	V
713.50	-15.72	3.06	8.29	33.52	2.15	20.88	34.77	-13.89	V

LTE FDD Band 12_Channel Bandwidth 10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain (dB)	P _{Aq} (dB)	Correction (dB)	Burst Avergae ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
704.00	-16.84	3.01	8.29	33.52	2.15	19.81	34.77	-14.96	V
707.50	-16.55	3.02	8.29	33.52	2.15	20.09	34.77	-14.68	V
711.00	-16.14	3.06	8.29	33.52	2.15	20.46	34.77	-14.31	V

LTE FDD Band 17_Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Ag} (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
706.5	-16.04	3.02	8.29	2.15	33.52	20.60	34.77	-14.17	V
710.0	-15.59	3.06	8.29	2.15	33.52	21.01	34.77	-13.76	V
713.5	-15.90	3.06	8.29	2.15	33.52	20.70	34.77	-14.07	V

LTE FDD Band 17_Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Ag} (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
709.0	-15.94	3.06	8.29	2.15	33.52	20.66	34.77	-14.11	V
710.0	-15.86	3.06	8.29	2.15	33.52	20.74	34.77	-14.03	V
711.0	-15.93	3.06	8.29	2.15	33.52	20.67	34.77	-14.10	V

LTE FDD Band 17_Channel Bandwidth 5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Ag} (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
706.5	-16.94	3.02	8.29	2.15	33.52	19.70	34.77	-15.07	V
710.0	-16.60	3.06	8.29	2.15	33.52	20.00	34.77	-14.77	V
713.5	-16.66	3.06	8.29	2.15	33.52	19.94	34.77	-14.83	V

LTE FDD Band 17_Channel Bandwidth 10MHz_16QAM


Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Ag} (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
709.0	-17.10	3.06	8.29	2.15	33.52	19.50	34.77	-15.27	V
710.0	-17.18	3.06	8.29	2.15	33.52	19.42	34.77	-15.35	V
711.0	-16.85	3.06	8.29	2.15	33.52	19.75	34.77	-15.02	V

4.2 Peak-to-Average Ratio (PAR)

LIMIT

The Peak-to-Average Ratio (PAR) of the transmission may not exceed 13 dB.

TEST CONFIGURATION



TEST PROCEDURE

1. Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
2. Set resolution/measurement bandwidth \geq signal's occupied bandwidth;
3. Set the number of counts to a value that stabilizes the measured CCDF curve;
4. Set the measurement interval as follows:
 - 1). for continuous transmissions, set to 1 ms,
 - 2). for burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
5. Record the maximum PAPR level associated with a probability of 0.1%.

TEST RESULTS

Remark:


1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 2, LTE FDD Band 4, LTE FDD Band 5, LTE FDD Band 12, LTE FDD Band 17; recorded worst case for each Channel Bandwidth of LTE FDD Band 2, LTE FDD Band 4, LTE FDD Band 5, LTE FDD Band 12, LTE FDD Band 17.
2. *For E-UTRA Band 2, please refer to Appendix B: Section B.2*
3. *For E-UTRA Band 4, please refer to Appendix C: Section C.2*
4. *For E-UTRA Band 5, please refer to Appendix D: Section D.2*
5. *For E-UTRA Band 12, please refer to Appendix E: Section E.2*
6. *For E-UTRA Band 17, please refer to Appendix F: Section H.2*

4.3 Occupied Bandwidth and Emission Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The occupied bandwidth was measured with the spectrum analyzer at low, middle and high channel in each band. The -26dBc Emission bandwidth was also measured and recorded. Set RBW was set to about 1% of emission BW, $VBW \geq 3$ times RBW.

-26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

TEST RESULTS

Remark:

1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 2, LTE FDD Band 4, LTE FDD Band 5, LTE FDD Band 12, LTE FDD Band 17; recorded worst case for each Channel Bandwidth of LTE FDD Band 2, LTE FDD Band 4, LTE FDD Band 5, LTE FDD Band 12, LTE FDD Band 17.
2. For E-UTRA Band 2, please refer to Appendix B: Section B.3
3. For E-UTRA Band 4, please refer to Appendix C: Section C.3
4. For E-UTRA Band 5, please refer to Appendix D: Section D.3
5. For E-UTRA Band 12, please refer to Appendix E: Section E.3
6. For E-UTRA Band 17, please refer to Appendix F: Section H.3

4.4 Band Edge compliance

LIMIT

For LTE FDD Band 2: Per FCC § 24.238 the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log(P)$ dB.


For LTE FDD Band 4: Per § 27.53(h): For operations in the 1710 – 1755 MHz and 2110 – 2155 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB.

For LTE FDD Band 5: Per FCC § 22.917 the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log(P)$ dB.

For LTE FDD Band 12: Per §27.53 (g): For operations in the 698–746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB.

For LTE FDD Band 17: Per §27.53(g): (g) For operations in the 600 MHz band and the 698–746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output port was connected to base station.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator, the path loss was compensated to the results for each measurement.
3. Set EUT at maximum power through base station.
4. Select lowest and highest channels for each band and different modulation.
5. Measure Band edge using RMS (Average) detector by spectrum

TEST RESULTS

Remark:

1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 2, LTE FDD Band 4, LTE FDD Band 5, LTE FDD Band 12, LTE FDD Band 17; recorded worst case for each Channel Bandwidth of LTE FDD Band 2, LTE FDD Band 4, LTE FDD Band 5, LTE FDD Band 12, LTE FDD Band 17.
2. *For E-UTRA Band 2, please refer to Appendix B: Section B.4*
3. *For E-UTRA Band 4, please refer to Appendix C: Section C.4*
4. *For E-UTRA Band 5, please refer to Appendix D: Section D.4*
5. *For E-UTRA Band 12, please refer to Appendix E: Section E.4*
6. *For E-UTRA Band 17, please refer to Appendix F: Section H.4*

1.1 Spurious Emission on Antenna Port

LIMIT

For LTE FDD Band 2: Per FCC § 24.238 the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log(P)$ dB.


For LTE FDD Band 4: Per § 27.53(h): For operations in the 1710 – 1755 MHz and 2110 – 2155 MHz bands, the power of any emission outside a licensee’s frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB.

For LTE FDD Band 5: Per FCC § 22.917 the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log(P)$ dB.

For LTE FDD Band 12: Per §27.53 (g): For operations in the 698–746 MHz band, the power of any emission outside a licensee’s frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB.

For LTE FDD Band 17: Per §27.53(g): (g) For operations in the 600 MHz band and the 698–746 MHz band, the power of any emission outside a licensee’s frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee’s frequency block, a resolution bandwidth of at least 30 kHz may be employed.

TEST CONFIGURATION



TEST PROCEDURE

The EUT was setup according to TIA-603-E

- a. Place the EUT on a bench and set it in transmitting mode.
- b. Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMW 500 by a Directional Couple.
- c. EUT Communicate with CMW 500, then select a channel for testing.
- d. Add a correction factor to the display of spectrum, and then test.
- e. The resolution bandwidth of the spectrum analyzer was set sufficient scans were taken to show the out of band Emission if any up to 10th harmonic.
- f. Please refer to following tables for test antenna conducted emissions.

Working Frequency	Sub range (GHz)	RBW	VBW	Sweep time (s)
LTE FDD Band 2	0.000009~0.000015	1KHz	3KHz	Auto
	0.000015~0.03	10KHz	30KHz	Auto
	0.03~26	1 MHz	3 MHz	Auto
LTE FDD Band 4	0.000009~0.000015	1KHz	3KHz	Auto
	0.000015~0.03	10KHz	30KHz	Auto
	0.03~26	1 MHz	3 MHz	Auto
LTE FDD Band 5	0.000009~0.000015	1KHz	3KHz	Auto
	0.000015~0.03	10KHz	30KHz	Auto
	0.03~26	1 MHz	3 MHz	Auto
LTE FDD Band 12	0.000009~0.000015	1KHz	3KHz	Auto
	0.000015~0.03	10KHz	30KHz	Auto
	0.03~26	1 MHz	3 MHz	Auto
LTE FDD Band 17	0.000009~0.000015	1KHz	3KHz	Auto
	0.000015~0.03	10KHz	30KHz	Auto
	0.03~26	1 MHz	3 MHz	Auto

TEST RESULTS

Remark:

1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 2, LTE FDD Band 4, LTE FDD Band 5, LTE FDD Band 12, LTE FDD Band 17; recorded worst case for each Channel Bandwidth of LTE FDD Band 2, LTE FDD Band 4, LTE FDD Band 5, LTE FDD Band 12, LTE FDD Band 17.
2. For E-UTRA Band 2, please refer to Appendix B: Section B.5
3. For E-UTRA Band 4, please refer to Appendix C: Section C.5
4. For E-UTRA Band 5, please refer to Appendix D: Section D.5
5. For E-UTRA Band 12, please refer to Appendix E: Section E.5
6. For E-UTRA Band 17, please refer to Appendix F: Section H.5

4.5 Radiated Spurious Emission

LIMIT

For LTE FDD Band 2: Per FCC § 24.238 the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log(P)$ dB.


For LTE FDD Band 4: Per § 27.53(h): For operations in the 1710 – 1755 MHz and 2110 – 2155 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB.

For LTE FDD Band 5: Per FCC § 22.917 the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10\log(P)$ dB.

For LTE FDD Band 12: Per §27.53 (g): For operations in the 698–746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB.

For LTE FDD Band 17: Per §27.53(g): (g) For operations in the 600 MHz band and the 698–746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

TEST CONFIGURATION



TEST PROCEDURE

1. EUT was placed on a 1.50 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.50m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz, And the maximum value of the receiver should be recorded as (P_r).
4. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
5. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (P_{cl}), the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.
The measurement results are obtained as described below:
$$\text{Power(EIRP)} = P_{Mea} + P_{Ag} - P_{cl} + G_a$$
6. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
7. ERP can be calculated from EIRP by subtracting the gain of the dipole, $\text{ERP} = \text{EIRP} - 2.15\text{dBi}$.
8. In order to make sure test results more clearly, we set frequency range and sweep time for difference frequency range as follows table:

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
LTE FDD Band 2	0.00009~0.15	1KHz	3KHz	30
	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2
LTE FDD Band 4	0.00009~0.15	1KHz	3KHz	30
	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	0.00009~0.15	1KHz	3KHz	30
LTE FDD Band 5	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~9	1 MHz	3 MHz	3
	0.00009~0.15	1KHz	3KHz	30
LTE FDD Band 12	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	0.00009~0.15	1KHz	3KHz	30
	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
LTE FDD Band 17	5~8	1 MHz	3 MHz	3
	0.00009~0.15	1KHz	3KHz	30
	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3

Frequency	Channel	Frequency Range	Verdict
LTE FDD Band 2	Low	9KHz -20GHz	PASS
	Middle	9KHz -20GHz	PASS
	High	9KHz -20GHz	PASS
LTE FDD Band 4	Low	9KHz -18GHz	PASS
	Middle	9KHz -18GHz	PASS
	High	9KHz -18GHz	PASS
LTE FDD Band 5	Low	9KHz -9GHz	PASS
	Middle	9KHz -9GHz	PASS
	High	9KHz -26GHz	PASS
LTE FDD Band 12	Low	9KHz -8GHz	PASS
	Middle	9KHz -8GHz	PASS
	High	9KHz -8GHz	PASS
LTE FDD Band 17	Low	9KHz -8GHz	PASS
	Middle	9KHz -8GHz	PASS
	High	9KHz -8GHz	PASS

TEST RESULTS

Remark:

1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 2, LTE FDD Band 4, LTE FDD Band 5, LTE FDD Band 12, LTE FDD Band 17; recorded worst case for each Channel Bandwidth of LTE FDD Band 2, LTE FDD Band 4, LTE FDD Band 5, LTE FDD Band 12, LTE FDD Band 17.
3. We were not recorded other points as values lower than limits.
4. Power(EIRP)= $P_{Mea} + P_{Ag} - P_{cl} + G_a$
5. Margin = EIRP - Limit

LTE FDD Band 2_Channel Bandwidth 20MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3715.0	-40.85	5.26	3.00	9.88	-36.23	-13.00	-23.23	H
5572.5	-45.66	6.11	3.00	11.36	-40.41	-13.00	-27.41	H
3715.0	-30.24	5.26	3.00	9.88	-25.62	-13.00	-12.62	V
5572.5	-33.98	6.11	3.00	11.36	-28.73	-13.00	-15.73	V

LTE FDD Band 2_Channel Bandwidth 20MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3720.0	-37.54	5.32	3.00	10.03	-32.83	-13.00	-19.83	H
5580.0	-43.50	6.19	3.00	11.41	-38.28	-13.00	-25.28	H
3720.0	-29.30	5.32	3.00	10.03	-24.59	-13.00	-11.59	V
5580.0	-35.23	6.19	3.00	11.41	-30.01	-13.00	-17.01	V

LTE FDD Band 2_Channel Bandwidth 20MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3800.0	-39.29	5.36	3.00	9.62	-35.03	-13.00	-22.03	H
5700.0	-45.68	6.24	3.00	11.46	-40.46	-13.00	-27.46	H
3800.0	-30.33	5.36	3.00	9.62	-26.07	-13.00	-13.07	V
5700.0	-33.01	6.24	3.00	11.46	-27.79	-13.00	-14.79	V

LTE FDD Band 2_Channel Bandwidth 20MHz_16QAM_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3715.0	-41.43	5.26	3.00	9.88	-36.81	-13.00	-23.81	H
5572.5	-46.49	6.11	3.00	11.36	-41.24	-13.00	-28.24	H
3715.0	-33.54	5.26	3.00	9.88	-28.92	-13.00	-15.92	V
5572.5	-39.45	6.11	3.00	11.36	-34.20	-13.00	-21.20	V

LTE FDD Band 2_Channel Bandwidth 20MHz_16QAM_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3720.0	-40.25	5.32	3.00	10.03	-35.54	-13.00	-22.54	H
5580.0	-47.65	6.19	3.00	11.41	-42.43	-13.00	-29.43	H
3720.0	-31.30	5.32	3.00	10.03	-26.59	-13.00	-13.59	V
5580.0	-41.35	6.19	3.00	11.41	-36.13	-13.00	-23.13	V

LTE FDD Band 2_Channel Bandwidth 20MHz_16QAM_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3800.0	-43.24	5.36	3.00	9.62	-38.98	-13.00	-25.98	H
5700.0	-46.68	6.24	3.00	11.46	-41.46	-13.00	-28.46	H
3800.0	-33.48	5.36	3.00	9.62	-29.22	-13.00	-16.22	V
5700.0	-39.00	6.24	3.00	11.46	-33.78	-13.00	-20.78	V

LTE FDD Band 4_Channel Bandwidth 20MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3440.0	-41.91	4.62	3.00	9.81	-36.72	-13.00	-23.72	H
5160.0	-47.20	5.94	3.00	10.86	-42.28	-13.00	-29.28	H
3440.0	-36.04	4.62	3.00	9.81	-30.85	-13.00	-17.85	V
5160.0	-39.77	5.94	3.00	10.86	-34.85	-13.00	-21.85	V

LTE FDD Band 4_Channel Bandwidth 20MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.0	-40.33	4.63	3.00	9.84	-35.12	-13.00	-22.12	H
5197.5	-46.98	5.94	3.00	10.86	-42.06	-13.00	-29.06	H
3465.0	-34.41	4.63	3.00	9.84	-29.20	-13.00	-16.20	V
5197.5	-39.73	5.94	3.00	10.86	-34.81	-13.00	-21.81	V

LTE FDD Band 4_Channel Bandwidth 20MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490.0	-40.51	4.65	3.00	9.90	-35.26	-13.00	-22.26	H
5235.0	-47.21	5.95	3.00	10.91	-42.25	-13.00	-29.25	H
3490.0	-34.25	4.65	3.00	9.90	-29.00	-13.00	-16.00	V
5235.0	-40.41	5.95	3.00	10.91	-35.45	-13.00	-22.45	V

LTE FDD Band 4_Channel Bandwidth 20MHz_16QAM_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3440.0	-45.71	4.62	3.00	9.81	-40.52	-13.00	-27.52	H
5160.0	-49.65	5.94	3.00	10.86	-44.73	-13.00	-31.73	H
3440.0	-39.77	4.62	3.00	9.81	-34.58	-13.00	-21.58	V
5160.0	-41.60	5.94	3.00	10.86	-36.68	-13.00	-23.68	V

LTE FDD Band 4_Channel Bandwidth 20MHz_16QAM_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.0	-46.10	4.63	3.00	9.84	-40.89	-13.00	-27.89	H
5197.5	-48.17	5.94	3.00	10.86	-43.25	-13.00	-30.25	H
3465.0	-36.67	4.63	3.00	9.84	-31.46	-13.00	-18.46	V
5197.5	-43.59	5.94	3.00	10.86	-38.67	-13.00	-25.67	V

LTE FDD Band 4_Channel Bandwidth 20MHz_16QAM_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3490.0	-46.01	4.65	3.00	9.90	-40.76	-13.00	-27.76	H
5235.0	-50.14	5.95	3.00	10.91	-45.18	-13.00	-32.18	H
3490.0	-36.58	4.65	3.00	9.90	-31.33	-13.00	-18.33	V
5235.0	-41.58	5.95	3.00	10.91	-36.62	-13.00	-23.62	V

LTE FDD Band 5_Channel Bandwidth 10MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1658.00	-41.60	3.86	3.00	8.56	-36.90	-13.00	-23.90	H
2487.00	-46.76	4.29	3.00	6.98	-44.07	-13.00	-31.07	H
1658.00	-35.02	3.86	3.00	8.56	-30.32	-13.00	-17.32	V
2487.00	-39.99	4.29	3.00	6.98	-37.30	-13.00	-24.30	V

LTE FDD Band 5_Channel Bandwidth 10MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.00	-40.01	3.90	3.00	8.58	-35.33	-13.00	-22.33	H
2509.50	-44.30	4.32	3.00	6.80	-41.82	-13.00	-28.82	H
1673.00	-33.23	3.90	3.00	8.58	-28.55	-13.00	-15.55	V
2509.50	-36.75	4.32	3.00	6.80	-34.27	-13.00	-21.27	V

LTE FDD Band 5_Channel Bandwidth 10MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1688.00	-38.24	3.91	3.00	9.06	-33.09	-13.00	-20.09	H
2532.00	-44.45	4.32	3.00	6.65	-42.12	-13.00	-29.12	H
1688.00	-33.13	3.91	3.00	9.06	-27.98	-13.00	-14.98	V
2532.00	-36.33	4.32	3.00	6.65	-34.00	-13.00	-21.00	V

LTE FDD Band 5_Channel Bandwidth 10MHz_16QAM_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1658.00	-41.47	3.86	3.00	8.56	-36.77	-13.00	-23.77	H
2487.00	-48.11	4.29	3.00	6.98	-45.42	-13.00	-32.42	H
1658.00	-36.42	3.86	3.00	8.56	-31.72	-13.00	-18.72	V
2487.00	-40.67	4.29	3.00	6.98	-37.98	-13.00	-24.98	V

LTE FDD Band 5_Channel Bandwidth 10MHz_16QAM_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.00	-42.20	3.90	3.00	8.58	-37.52	-13.00	-24.52	H
2509.50	-46.97	4.32	3.00	6.80	-44.49	-13.00	-31.49	H
1673.00	-38.78	3.90	3.00	8.58	-34.10	-13.00	-21.10	V
2509.50	-39.83	4.32	3.00	6.80	-37.35	-13.00	-24.35	V

LTE FDD Band 5_Channel Bandwidth 10MHz_16QAM_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1688.00	-41.30	3.91	3.00	9.06	-36.15	-13.00	-23.15	H
2532.00	-48.86	4.32	3.00	6.65	-46.53	-13.00	-33.53	H
1688.00	-37.03	3.91	3.00	9.06	-31.88	-13.00	-18.88	V
2532.00	-41.51	4.32	3.00	6.65	-39.18	-13.00	-26.18	V

LTE FDD Band 12_Channel Bandwidth 10MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1408.00	-39.35	3.71	3.00	9.02	-34.04	-13.00	-21.04	H
2112.00	-45.70	4.22	3.00	8.64	-41.28	-13.00	-28.28	H
1408.00	-33.74	3.71	3.00	9.02	-28.43	-13.00	-15.43	V
2112.00	-39.01	4.22	3.00	8.64	-34.59	-13.00	-21.59	V

LTE FDD Band 12_Channel Bandwidth 10MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1415.00	-39.46	3.72	3.00	9.04	-34.14	-13.00	-21.14	H
2122.50	-45.20	4.23	3.00	8.60	-40.83	-13.00	-27.83	H
1415.00	-35.72	3.72	3.00	9.04	-30.40	-13.00	-17.40	V
2122.50	-39.53	4.23	3.00	8.60	-35.16	-13.00	-22.16	V

LTE FDD Band 12_Channel Bandwidth 10MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1422.00	-41.81	4.78	3.00	8.91	-37.68	-13.00	-24.68	H
2133.00	-47.35	4.25	3.00	8.26	-43.34	-13.00	-30.34	H
1422.00	-35.78	4.78	3.00	8.91	-31.65	-13.00	-18.65	V
2133.00	-37.06	4.25	3.00	8.26	-33.05	-13.00	-20.05	V

LTE FDD Band 12_Channel Bandwidth 10MHz_16QAM_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1408.00	-41.45	3.71	3.00	9.02	-36.14	-13.00	-23.14	H
2112.00	-47.71	4.22	3.00	8.64	-43.29	-13.00	-30.29	H
1408.00	-36.51	3.71	3.00	9.02	-31.20	-13.00	-18.20	V
2112.00	-39.26	4.22	3.00	8.64	-34.84	-13.00	-21.84	V

LTE FDD Band 12_Channel Bandwidth 10MHz_16QAM_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1415.00	-40.09	3.72	3.00	9.04	-34.77	-13.00	-21.77	H
2122.50	-44.99	4.23	3.00	8.60	-40.62	-13.00	-27.62	H
1415.00	-33.77	3.72	3.00	9.04	-28.45	-13.00	-15.45	V
2122.50	-38.30	4.23	3.00	8.60	-33.93	-13.00	-20.93	V

LTE FDD Band 12_Channel Bandwidth 10MHz_16QAM_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1422.00	-40.73	4.78	3.00	8.91	-36.60	-13.00	-23.60	H
2133.00	-47.82	4.25	3.00	8.26	-43.81	-13.00	-30.81	H
1422.00	-33.06	4.78	3.00	8.91	-28.93	-13.00	-15.93	V
2133.00	-39.13	4.25	3.00	8.26	-35.12	-13.00	-22.12	V

LTE FDD Band 17_Channel Bandwidth 10MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1418.0	-41.72	3.72	3.00	9.04	-36.40	-13.00	-23.40	H
2127.0	-47.15	4.23	3.00	8.60	-42.78	-13.00	-29.78	H
1418.0	-33.45	3.72	3.00	9.04	-28.13	-13.00	-15.13	V
2127.0	-37.08	4.23	3.00	8.60	-32.71	-13.00	-19.71	V

LTE FDD Band 17_Channel Bandwidth 10MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1420.0	-40.03	4.78	3.00	8.91	-35.90	-13.00	-22.90	H
2130.0	-44.95	4.25	3.00	8.26	-40.94	-13.00	-27.94	H
1420.0	-36.39	4.78	3.00	8.91	-32.26	-13.00	-19.26	V
2130.0	-37.18	4.25	3.00	8.26	-33.17	-13.00	-20.17	V

LTE FDD Band 17_Channel Bandwidth 10MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1422.0	-39.89	4.78	3.00	8.91	-35.76	-13.00	-22.76	H
2133.0	-45.56	4.25	3.00	8.26	-41.55	-13.00	-28.55	H
1422.0	-34.23	4.78	3.00	8.91	-30.10	-13.00	-17.10	V
2133.0	-39.61	4.25	3.00	8.26	-35.60	-13.00	-22.60	V

LTE FDD Band 17_Channel Bandwidth 10MHz_16QAM_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1418.0	-39.32	3.72	3.00	9.04	-34.00	-13.00	-21.00	H
2127.0	-45.50	4.23	3.00	8.60	-41.13	-13.00	-28.13	H
1418.0	-35.55	3.72	3.00	9.04	-30.23	-13.00	-17.23	V
2127.0	-36.62	4.23	3.00	8.60	-32.25	-13.00	-19.25	V

LTE FDD Band 17_Channel Bandwidth 10MHz_16QAM_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1420.0	-39.61	4.78	3.00	8.91	-35.48	-13.00	-22.48	H
2130.0	-45.04	4.25	3.00	8.26	-41.03	-13.00	-28.03	H
1420.0	-33.75	4.78	3.00	8.91	-29.62	-13.00	-16.62	V
2130.0	-38.85	4.25	3.00	8.26	-34.84	-13.00	-21.84	V

LTE FDD Band 17_Channel Bandwidth 10MHz_16QAM_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1422.0	-39.14	4.78	3.00	8.91	-35.01	-13.00	-22.01	H
2133.0	-45.84	4.25	3.00	8.26	-41.83	-13.00	-28.83	H
1422.0	-33.84	4.78	3.00	8.91	-29.71	-13.00	-16.71	V
2133.0	-37.90	4.25	3.00	8.26	-33.89	-13.00	-20.89	V


Notes: All channel bandwidth were tested, the report recorded the worst data.

4.6 Frequency Stability under Temperature & Voltage Variations

LIMIT

According to FCC §2.1055, §22.355, §24.235, §27.54 requirement, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation and should not exceed 2.5ppm.

TEST CONFIGURATION



TEST PROCEDURE

The EUT was setup according to TIA-603-E

Frequency Stability Under Temperature Variations:

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMW 500 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMW 500 and in a simulated call on middle channel for LTE - LTE band 4; measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1.5 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMW 500 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 °C increments from +50°C to -30°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

Frequency Stability Under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change.

TEST RESULTS**Remark:**

We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 2, LTE FDD Band 4, LTE FDD Band 5, LTE FDD Band 12, LTE FDD Band 17; recorded worst case for each Channel Bandwidth of LTE FDD Band 2, LTE FDD Band 4, LTE FDD Band 5, LTE FDD Band 12, LTE FDD Band 17.

LTE Band 2, QPSK, 1.4MHz bandwidth (worst case of all bandwidths)

LTE FDD Band 2					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
10.2	20	-14	-0.007	±2.50	PASS
12	20	2	0.001	±2.50	PASS
13.8	20	12	0.006	±2.50	PASS
12	-30	6	0.003	±2.50	PASS
12	-20	-6	-0.003	±2.50	PASS
12	-10	16	0.009	±2.50	PASS
12	0	6	0.003	±2.50	PASS
12	10	-6	-0.003	±2.50	PASS
12	20	16	0.009	±2.50	PASS
12	30	14	0.007	±2.50	PASS
12	40	-13	-0.007	±2.50	PASS
12	50	-5	-0.003	±2.50	PASS

LTE Band 2, 16QAM, 1.4MHz bandwidth (worst case of all bandwidths)

LTE FDD Band 2					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
10.2	20	3	0.002	±2.50	PASS
12	20	-16	-0.009	±2.50	PASS
13.8	20	-8	-0.004	±2.50	PASS
12	-30	18	0.010	±2.50	PASS
12	-20	-9	-0.005	±2.50	PASS
12	-10	16	0.009	±2.50	PASS
12	0	18	0.010	±2.50	PASS
12	10	-9	-0.005	±2.50	PASS
12	20	16	0.009	±2.50	PASS
12	30	13	0.007	±2.50	PASS
12	40	-10	-0.005	±2.50	PASS
12	50	13	0.007	±2.50	PASS

LTE Band 4, QPSK, 1.4MHz bandwidth (worst case of all bandwidths)

LTE FDD Band 4					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
10.2	20	4	0.002	±2.50	PASS
12	20	25	0.014	±2.50	PASS
13.8	20	14	0.008	±2.50	PASS
12	-30	-23	-0.013	±2.50	PASS
12	-20	-11	-0.006	±2.50	PASS
12	-10	-22	-0.013	±2.50	PASS
12	0	-23	-0.013	±2.50	PASS
12	10	-11	-0.006	±2.50	PASS
12	20	-22	-0.013	±2.50	PASS
12	30	-1	-0.001	±2.50	PASS
12	40	34	0.019	±2.50	PASS
12	50	13	0.007	±2.50	PASS

LTE Band 4, 16QAM, 1.4MHz bandwidth (worst case of all bandwidths)

LTE FDD Band 4					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
10.2	20	38	0.022	±2.50	PASS
12	20	31	0.018	±2.50	PASS
13.8	20	41	0.023	±2.50	PASS
12	-30	31	0.018	±2.50	PASS
12	-20	3	0.002	±2.50	PASS
12	-10	-1	-0.001	±2.50	PASS
12	0	31	0.018	±2.50	PASS
12	10	3	0.002	±2.50	PASS
12	20	-1	-0.001	±2.50	PASS
12	30	-1	-0.001	±2.50	PASS
12	40	12	0.007	±2.50	PASS
12	50	-21	-0.012	±2.50	PASS

LTE Band 5, QPSK, 1.4MHz bandwidth(worst case of all bandwidths)

LTE FDD Band 5					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
10.2	20	-43	-0.052	±2.50	PASS
12	20	-12	-0.015	±2.50	PASS
13.8	20	12	0.015	±2.50	PASS
12	-30	14	0.017	±2.50	PASS
12	-20	16	0.019	±2.50	PASS
12	-10	9	0.011	±2.50	PASS
12	0	14	0.017	±2.50	PASS
12	10	16	0.019	±2.50	PASS
12	20	9	0.011	±2.50	PASS
12	30	-38	-0.046	±2.50	PASS
12	40	-23	-0.028	±2.50	PASS
12	50	15	0.018	±2.50	PASS

LTE Band 5, 16QAM, 1.4MHz bandwidth(worst case of all bandwidths)

LTE FDD Band 5					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
10.2	20	4	0.005	±2.50	PASS
12	20	-21	-0.025	±2.50	PASS
13.8	20	32	0.039	±2.50	PASS
12	-30	27	0.033	±2.50	PASS
12	-20	-39	-0.047	±2.50	PASS
12	-10	-19	-0.023	±2.50	PASS
12	0	27	0.033	±2.50	PASS
12	10	-39	-0.047	±2.50	PASS
12	20	-19	-0.023	±2.50	PASS
12	30	43	0.052	±2.50	PASS
12	40	46	0.056	±2.50	PASS
12	50	-31	-0.038	±2.50	PASS

LTE Band 12, QPSK, 1.4MHz bandwidth (worst case of all bandwidths and modulation type)

LTE FDD Band 12					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
10.2	20	-5	-0.007	±2.50	PASS
12	20	-18	-0.025	±2.50	PASS
13.8	20	31	0.044	±2.50	PASS
12	-30	-22	-0.031	±2.50	PASS
12	-20	26	0.037	±2.50	PASS
12	-10	-3	-0.004	±2.50	PASS
12	0	-22	-0.031	±2.50	PASS
12	10	26	0.037	±2.50	PASS
12	20	-3	-0.004	±2.50	PASS
12	30	-37	-0.052	±2.50	PASS
12	40	5	0.007	±2.50	PASS
12	50	-15	-0.021	±2.50	PASS

LTE Band 12, 16QAM, 1.4MHz bandwidth (worst case of all bandwidths and modulation type)

LTE FDD Band 12					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
10.2	20	23	0.033	±2.50	PASS
12	20	0	0.000	±2.50	PASS
13.8	20	-14	-0.020	±2.50	PASS
12	-30	-4	-0.006	±2.50	PASS
12	-20	-5	-0.007	±2.50	PASS
12	-10	-6	-0.008	±2.50	PASS
12	0	-4	-0.006	±2.50	PASS
12	10	-5	-0.007	±2.50	PASS
12	20	-6	-0.008	±2.50	PASS
12	30	-26	-0.037	±2.50	PASS
12	40	-13	-0.018	±2.50	PASS
12	50	9	0.013	±2.50	PASS

LTE Band 17, QPSK, 5MHz bandwidth (worst case of all bandwidths and modulation type)

LTE FDD Band 17					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
10.2	20	12	0.017	±2.50	PASS
12	20	-47	-0.066	±2.50	PASS
13.8	20	-45	-0.063	±2.50	PASS
12	-30	-37	-0.052	±2.50	PASS
12	-20	49	0.069	±2.50	PASS
12	-10	-33	-0.046	±2.50	PASS
12	0	-37	-0.052	±2.50	PASS
12	10	49	0.069	±2.50	PASS
12	20	-33	-0.046	±2.50	PASS
12	30	-22	-0.031	±2.50	PASS
12	40	7	0.010	±2.50	PASS
12	50	42	0.059	±2.50	PASS

LTE Band 17, 16QAM, 5MHz bandwidth (worst case of all bandwidths and modulation type)

LTE FDD Band 17					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
10.2	20	-49	-0.069	±2.50	PASS
12	20	30	0.042	±2.50	PASS
13.8	20	-23	-0.032	±2.50	PASS
12	0	-19	-0.027	±2.50	PASS
12	-30	-49	-0.069	±2.50	PASS
12	-20	-41	-0.058	±2.50	PASS
12	-10	-34	-0.048	±2.50	PASS
12	10	-49	-0.069	±2.50	PASS
12	20	-41	-0.058	±2.50	PASS
12	30	-34	-0.048	±2.50	PASS
12	40	35	0.049	±2.50	PASS
12	50	-36	-0.051	±2.50	PASS

LTE Band 2, QPSK, 1.4MHz bandwidth (worst case of all bandwidths)

LTE FDD Band 2					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
20.4	20	4	0.002	±2.50	PASS
24	20	-10	-0.005	±2.50	PASS
27.6	20	5	0.003	±2.50	PASS
24	-30	8	0.004	±2.50	PASS
24	-20	19	0.010	±2.50	PASS
24	-10	-5	-0.003	±2.50	PASS
24	0	9	0.005	±2.50	PASS
24	10	-18	-0.010	±2.50	PASS
24	20	-11	-0.006	±2.50	PASS
24	30	8	0.004	±2.50	PASS
24	40	-17	-0.009	±2.50	PASS
24	50	11	0.006	±2.50	PASS

LTE Band 2, 16QAM, 1.4MHz bandwidth (worst case of all bandwidths)

LTE FDD Band 2					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
20.4	20	16	0.009	±2.50	PASS
24	20	18	0.010	±2.50	PASS
27.6	20	7	0.004	±2.50	PASS
24	-30	-7	-0.004	±2.50	PASS
24	-20	-13	-0.007	±2.50	PASS
24	-10	2	0.001	±2.50	PASS
24	0	7	0.004	±2.50	PASS
24	10	18	0.010	±2.50	PASS
24	20	-9	-0.005	±2.50	PASS
24	30	-4	-0.002	±2.50	PASS
24	40	6	0.003	±2.50	PASS
24	50	-16	-0.009	±2.50	PASS

LTE Band 4, QPSK, 1.4MHz bandwidth (worst case of all bandwidths)

LTE FDD Band 4					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
20.4	20	-10	-0.006	±2.50	PASS
24	20	40	0.023	±2.50	PASS
27.6	20	18	0.010	±2.50	PASS
24	-30	-48	-0.027	±2.50	PASS
24	-20	44	0.025	±2.50	PASS
24	-10	16	0.009	±2.50	PASS
24	0	44	0.025	±2.50	PASS
24	10	12	0.007	±2.50	PASS
24	20	-49	-0.028	±2.50	PASS
24	30	4	0.002	±2.50	PASS
24	40	1	0.001	±2.50	PASS
24	50	2	0.001	±2.50	PASS

LTE Band 4, 16QAM, 1.4MHz bandwidth (worst case of all bandwidths)

LTE FDD Band 4					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
20.4	20	-18	-0.010	±2.50	PASS
24	20	-32	-0.018	±2.50	PASS
27.6	20	-33	-0.019	±2.50	PASS
24	-30	22	0.013	±2.50	PASS
24	-20	-6	-0.003	±2.50	PASS
24	-10	5	0.003	±2.50	PASS
24	0	38	0.022	±2.50	PASS
24	10	-38	-0.022	±2.50	PASS
24	20	-23	-0.013	±2.50	PASS
24	30	-22	-0.013	±2.50	PASS
24	40	5	0.003	±2.50	PASS
24	50	30	0.017	±2.50	PASS

LTE Band 5, QPSK, 1.4MHz bandwidth(worst case of all bandwidths)

LTE FDD Band 5					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
20.4	20	4	0.005	±2.50	PASS
24	20	-32	-0.039	±2.50	PASS
27.6	20	-35	-0.042	±2.50	PASS
24	-30	-46	-0.056	±2.50	PASS
24	-20	-9	-0.011	±2.50	PASS
24	-10	17	0.021	±2.50	PASS
24	0	10	0.012	±2.50	PASS
24	10	1	0.001	±2.50	PASS
24	20	-1	-0.001	±2.50	PASS
24	30	-12	-0.015	±2.50	PASS
24	40	50	0.061	±2.50	PASS
24	50	32	0.039	±2.50	PASS

LTE Band 5, 16QAM, 1.4MHz bandwidth(worst case of all bandwidths)

LTE FDD Band 5					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
20.4	20	31	0.038	±2.50	PASS
24	20	-4	-0.005	±2.50	PASS
27.6	20	18	0.022	±2.50	PASS
24	-30	20	0.024	±2.50	PASS
24	-20	-31	-0.038	±2.50	PASS
24	-10	41	0.050	±2.50	PASS
24	0	40	0.049	±2.50	PASS
24	10	15	0.018	±2.50	PASS
24	20	39	0.047	±2.50	PASS
24	30	16	0.019	±2.50	PASS
24	40	36	0.044	±2.50	PASS
24	50	-7	-0.008	±2.50	PASS

LTE Band 12, QPSK, 1.4MHz bandwidth (worst case of all bandwidths and modulation type)

LTE FDD Band 12					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
20.4	20	-47	-0.066	±2.50	PASS
24	20	16	0.023	±2.50	PASS
27.6	20	49	0.069	±2.50	PASS
24	-30	44	0.062	±2.50	PASS
24	-20	4	0.006	±2.50	PASS
24	-10	19	0.027	±2.50	PASS
24	0	3	0.004	±2.50	PASS
24	10	49	0.069	±2.50	PASS
24	20	-48	-0.068	±2.50	PASS
24	30	-30	-0.042	±2.50	PASS
24	40	-35	-0.049	±2.50	PASS
24	50	22	0.031	±2.50	PASS

LTE Band 12, 16QAM, 1.4MHz bandwidth (worst case of all bandwidths and modulation type)

LTE FDD Band 12					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
20.4	20	-26	-0.037	±2.50	PASS
24	20	22	0.031	±2.50	PASS
27.6	20	-33	-0.047	±2.50	PASS
24	-30	-42	-0.059	±2.50	PASS
24	-20	24	0.034	±2.50	PASS
24	-10	49	0.069	±2.50	PASS
24	0	27	0.038	±2.50	PASS
24	10	45	0.064	±2.50	PASS
24	20	15	0.021	±2.50	PASS
24	30	16	0.023	±2.50	PASS
24	40	9	0.013	±2.50	PASS
24	50	-47	-0.066	±2.50	PASS

LTE Band 17, QPSK, 5MHz bandwidth (worst case of all bandwidths and modulation type)

LTE FDD Band 17					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
20.4	20	38	0.054	±2.50	PASS
24	20	43	0.061	±2.50	PASS
27.6	20	21	0.030	±2.50	PASS
24	-30	18	0.025	±2.50	PASS
24	-20	-15	-0.021	±2.50	PASS
24	-10	-40	-0.056	±2.50	PASS
24	0	-2	-0.003	±2.50	PASS
24	10	16	0.023	±2.50	PASS
24	20	-48	-0.068	±2.50	PASS
24	30	-50	-0.070	±2.50	PASS
24	40	30	0.042	±2.50	PASS
24	50	-46	-0.065	±2.50	PASS

LTE Band 17, 16QAM, 5MHz bandwidth (worst case of all bandwidths and modulation type)

LTE FDD Band 17					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
20.4	20	30	0.042	±2.50	PASS
24	20	18	0.025	±2.50	PASS
27.6	20	4	0.006	±2.50	PASS
24	0	-34	-0.048	±2.50	PASS
24	-30	10	0.014	±2.50	PASS
24	-20	28	0.039	±2.50	PASS
24	-10	-13	-0.018	±2.50	PASS
24	10	-46	-0.065	±2.50	PASS
24	20	-40	-0.056	±2.50	PASS
24	30	-2	-0.003	±2.50	PASS
24	40	40	0.056	±2.50	PASS
24	50	45	0.063	±2.50	PASS

5 Test Setup Photos of the EUT

Please refer to separated files for Test Setup Photos of the EUT.

6 External Photos of the EUT

Please refer to separated files for External Photos of the EUT.

7 Internal Photos of the EUT

Please refer to separated files for Internal Photos of the EUT.

*****End of Report*****