

# **RF Exposure Report**

#### For

Applicant Name: Shenzhen Sunchip Technology Co.,Ltd

Address: 2nd-3rd Floor, Building 4, Fuan Industry Area Phase 2, Dayang

Development Zone, Fuyong, Baoan, Shenzhen, China

EUT Name: RK3588 Edge Computing Device

Brand Name: SUNCHIP

Model Number: AD-0160

Series Model Number: Refer to Section 2

### **Issued By**

Company Name: BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park,

Address: Tantou Community, Songgang Street, Bao'an District, Shenzhen,

China

Report Number: BTF230317R01206

Test Standards: 47 CFR Part 2 Subpart J Section 2.1091

FCC ID: 2AWFG-AD0160

Test Conclusion: Pass

Test Date: 2023-03-19 to 2023-03-31

Date of Issue: 2023-04-10

Prepared By:

Gavin Cui / Project Enginee

Gavin Cui


Date: 2023-04-10

Approved By:

Ryan.CJ / EMC Manager


Date: 2023-04-10

Note: All the test results in this report only related to the testing samples. Which can be duplicated completely for the legal use with approval of applicant; it shall not be reproduced except in full without the written approval of BTF Testing Lab (Shenzhen) Co., Ltd., All the objections should be raised within thirty days from the date of issue. To validate the report, you can contact us.





Revision History				
Version	Issue Date	Revisions Content		
R_V0	2023-04-10	Original		
Note:	Once the revision has	Once the revision has been made, then previous versions reports are invalid.		





#### **Table of Contents**

1.	Introdu	uction
	1.1	Identification of Testing Laboratory
		Identification of the Responsible Testing Location4
		Laboratory Condition
		Announcement
2.	Produ	ct Information
	2.1	Application Information
	2.2	Manufacturer Information
	2.3	Factory Information
	2.4	General Description of Equipment under Test (EUT)
3.		IREMENT
	3.1	Assessment Result



Test Report Number: BTF230317R01206

### 1. Introduction

### 1.1 Identification of Testing Laboratory

Company Name:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address: F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tommunity, Songgang Street, Bao'an District, Shenzhen, China	
Phone Number:	+86-0755-23146130
Fax Number:	+86-0755-23146130

#### 1.2 Identification of the Responsible Testing Location

Test Location:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
Description:	All measurement facilities used to collect the measurement data are located at F101,201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
FCC Registration Number:	518915
Designation Number:	CN1330

### 1.3 Laboratory Condition

Ambient Temperature:	20℃ to 25℃
Ambient Relative Humidity:	45% to 55%
Ambient Pressure:	100 kPa to 102 kPa

#### 1.4 Announcement

- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by BTF and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.



Test Report Number: BTF230317R01206

# 2. Product Information

# 2.1 Application Information

Company Name:	Shenzhen Sunchip Technology Co.,Ltd
Address:	2nd-3rd Floor, Building 4, Fuan Industry Area Phase 2, Dayang Development Zone, Fuyong, Baoan, Shenzhen, China

### 2.2 Manufacturer Information

Company Name: Shenzhen Sunchip Technology Co.,Ltd	
Address:	2nd-3rd Floor, Building 4, Fuan Industry Area Phase 2, Dayang Development Zone, Fuyong, Baoan, Shenzhen, China

# 2.3 Factory Information

Company Name:	Shenzhen Sunchip Technology Co.,Ltd	
Address:	2nd-3rd Floor, Building 4, Fuan Industry Area Phase 2, Dayang Development Zone, Fuyong, Baoan, Shenzhen, China	

# 2.4 General Description of Equipment under Test (EUT)

EUT Name RK3588 Edge Computing Device		
Under Test Model Name	AD-0160	
Series Model Name AD-0160A, AD-0160B, AD-0160C, AD-0160D		
Description of Model name differentiation	The model name is different from the exterior color of the case, others are the same.	
Hardware Version	PCB AD-0160-V1.2 20230201	
Software and Firmware Version	AD_0160-V1.0-12-PAPPER-8K+DP-SW0.1-20230222	



Test Report Number: BTF230317R01206

# 3. Test Requirement

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b), Limits for Maximum Permissible Exposure (MPE),

Frequency range Electric field		Magnetic field strength	Power density	Averaging time
(MHz)	strength(V/m)	(A/m)	(mW/cm <sup>2</sup> )	(minutes)
	(A) Limits f	or Occupational/Controlled	l Exposures	
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300	61.4	0.163	1.0	6
300-1500	- 1_3	-	f/300	6
1500-100,000	-	-	5	6
	(B) Limits for G	General Population/Unconti	rolled Exposure	
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz

#### **EVALUATION METHOD**

Transmission formula:  $Pd = (Pout*G)/(4*pi*r^2)$ 

Where

Pd = power density in mW/cm<sup>2</sup>, Pout = output power to antenna in mW, G = gain of antenna in linear scale;


Pi = 3.1416, R = distance between observation point and center of the radiator in cm

#### 3.1 Assessment Result

⊠ Passed	■ Not Applicable
----------	------------------

Frequency (MHz)	Туре	Conducted Power (dBm)	Maximum Tune- up (dBm)	Power Density (mW/cm2)	Limit (mW/cm2)	Result
2402	BT-EDR	4.63	5	0.0011	1.0000	Pass
2402	BT-BLE	4.64	5	0.0011	1.0000	Pass
2412	802.11n	22.77	23	0.1251	1.0000	Pass
5785	802.11ac	16.28	17	0.0235	1.0000	Pass

Note: The exposure evaluation safety distance is 20cm.







BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

www.btf-lab.com

-- END OF REPORT--