
SAR Test Report

Report No.: AGC09966200404FH01

FCC ID : 2AWFM-MARAPHONES-Z1

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION : Smart Phone

BRAND NAME : Mara Phones

MODEL NAME : Mara Phones Z1

APPLICANT : Mara Phones Limited

DATE OF ISSUE : May 19,2020

STANDARD(S) : IEEE Std. 1528:2013
FCC 47 CFR Part 2§2.1093:2013
IEEE Std C95.1™-2005
IEC 62209-1: 2016

REPORT VERSION : V1.0

Attestation of Global Compliance(Shenzhen) Co., Ltd.

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	May 19,2020	Valid	Initial Release

Test Report

Applicant Name	Mara Phones Limited
Applicant Address	C/O SAFYR UTILIS LTD, 7th Floor, Tower 1, Nexteracom, Cybercity Ebene, 72201, Mauritius
Manufacturer Name	Mara Phones Rwanda Limited
Manufacturer Address	Plot No 2166, Kigali Special Economic Zone, Masoro, Ndera, Gasabo District, Kigali, Rwanda
Factory Name	Mara Phones Rwanda Limited
Factory Address	Plot no 2166, Kigali Special Economic Zone, Masoro Ndera, Gasabo District, Kigali, Rwanda
Factory Name	Mara Phones South Africa (PTY) Limited
Factory Address	Dube Trade Port, No.5 Umkhomazi Drive, ERF 618 La Mercy Durban, KwaZulu-Natal, 4399, South Africa
Product Designation	Smart Phone
Brand Name	Mara Phones
Model Name	Mara Phones Z1
EUT Voltage	DC3.85V by battery
Applicable Standard	IEEE Std. 1528:2013 FCC 47 CFR Part 2§2.1093:2013 IEEE Std C95.1™-2005 IEC 62209-1: 2016
Test Date	Apr. 13,2020 to Apr. 30,2020
Report Template	AGCRT-US-4G/SAR (2018-01-01)

Note: The results of testing in this report apply to the product/system which was tested only.

Jack Gui

Prepared By _____

Jack Gui (Project Engineer) Apr. 30,2020

Angela Li

Reviewed By _____

Angela Li (Reviewer) May 19,2020

Forrest Lei

Approved By _____

Forrest Lei
(Authorized Officer) May 19,2020

TABLE OF CONTENTS

1. SUMMARY OF MAXIMUM SAR VALUE 5

2. GENERAL INFORMATION..... 6

 2.1. EUT DESCRIPTION..... 6

3. SAR MEASUREMENT SYSTEM 8

 3.1. THE SATIMO SYSTEM USED FOR PERFORMING COMPLIANCE TESTS CONSISTS OF FOLLOWING ITEMS..... 8

 3.2. COMOSAR E-FIELD PROBE 9

 3.3. ROBOT..... 9

 3.4. VIDEO POSITIONING SYSTEM 10

 3.5. DEVICE HOLDER 10

 3.6. SAM TWIN PHANTOM..... 11

 3.7. ELLI39 PHANTOM..... 11

4. SAR MEASUREMENT PROCEDURE 12

 4.1. SPECIFIC ABSORPTION RATE (SAR) 12

 4.2. SAR MEASUREMENT PROCEDURE 13

 4.3. RF EXPOSURE CONDITIONS..... 15

5. TISSUE SIMULATING LIQUID 17

 5.1. THE COMPOSITION OF THE TISSUE SIMULATING LIQUID..... 17

 5.2. TISSUE DIELECTRIC PARAMETERS FOR HEAD AND BODY PHANTOMS 18

 5.3. TISSUE CALIBRATION RESULT..... 19

6. SAR SYSTEM CHECK PROCEDURE 21

 6.1. SAR SYSTEM CHECK PROCEDURES..... 21

 6.2. SAR SYSTEM CHECK 22

7. EUT TEST POSITION 24

 7.1. DEFINE TWO IMAGINARY LINES ON THE HANDSET..... 24

 7.2. CHEEK POSITION 25

 7.3. TILT POSITION..... 25

 7.4. BODY WORN POSITION..... 26

8. SAR EXPOSURE LIMITS 27

9. TEST FACILITY 28

10. TEST EQUIPMENT LIST 29

11. MEASUREMENT UNCERTAINTY 30

12. CONDUCTED POWER MEASUREMENT 33

13. TEST RESULTS 55

 13.1. SAR TEST RESULTS SUMMARY 55

APPENDIX A. SAR SYSTEM CHECK DATA 76

APPENDIX B. SAR MEASUREMENT DATA..... 96

APPENDIX C. TEST SETUP PHOTOGRAPHS 136

APPENDIX D. CALIBRATION DATA..... 143

1. SUMMARY OF MAXIMUM SAR VALUE

The maximum results of Specific Absorption Rate (SAR) found during testing for EUT are as follows:

Frequency Band	Highest Reported 1g-SAR(W/Kg)		SAR Test Limit (W/Kg)
	Head	Body-worn10mm	
GSM 850	0.322	0.760	1.6
PCS 1900	0.155	0.399	
UMTS Band II	0.222	0.423	
UMTS Band V	0.166	0.326	
LTE Band 7	0.104	0.265	
LTE Band 38	0.071	0.134	
LTE Band 40	0.057	0.130	
LTE Band 41	0.097	0.212	
WIFI 2.4G	0.307	0.251	
Simultaneous Reported SAR	1.011		
SAR Test Result	PASS		

This device is compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6W/Kg) specified in IEEE Std. 1528:2013; FCC 47CFR § 2.1093; IEEE/ANSI C95.1:2005 and the following specific FCC Test Procedures:

- KDB 447498 D01 General RF Exposure Guidance v06
- KDB 648474 D04 Handset SAR v01r03
- KDB 865664 D01 SAR Measurement 100MHz to 6GHz v01r04
- KDB 941225 D01 3G SAR Procedures v03r01
- KDB 941225 D06 Hotspot Mode v02r01
- KDB 248227 D01 802 11 Wi-Fi SAR v02r02
- KDB 941225 D05 SAR for LTE Devices v02r05

2. GENERAL INFORMATION

2.1. EUT Description

General Information	
Product Designation	Smart Phone
Test Model	Mara Phones Z1
Hardware Version	K6503N_01
Software Version	Mara_Z1_d_V1.0_20200609
Device Category	Portable
RF Exposure Environment	Uncontrolled
Antenna Type	Internal
GSM and GPRS& EGPRS	
Support Band	<input checked="" type="checkbox"/> GSM 850 <input checked="" type="checkbox"/> PCS 1900 (U.S. Bands) <input checked="" type="checkbox"/> GSM 900 <input checked="" type="checkbox"/> DCS 1800 (Non-U.S. Bands)
GPRS & EGPRS Type	Class B
GPRS & EGPRS Class	Class 12(1Tx+4Rx, 2Tx+3Rx, 3Tx+2Rx, 4Tx+1Rx)
TX Frequency Range	GSM 850 : 820-850MHz; PCS 1900: 1850-1910MHz;
RX Frequency Range	GSM 850 : 869~894MHz; PCS 1900: 1930~1990MHz
Release Version	R99
Type of modulation	GMSK for GSM/GPRS; GMSK & 8-PSK for EGPRS
Antenna Gain	GSM850: 2.3dBi; PCS1900: 1.85dBi
Max. Average Power	GSM850: 32.52dBm; PCS1900: 27.97dBm
WCDMA	
Support Band	<input checked="" type="checkbox"/> UMTS FDD Band II <input checked="" type="checkbox"/> UMTS FDD Band V (U.S. Bands) <input checked="" type="checkbox"/> UMTS FDD Band I <input checked="" type="checkbox"/> UMTS FDD Band VIII(Non-U.S. Bands)
HS Type	HSPA(HSUPA/HSDPA)
TX Frequency Range	FDD Band II: 1850-1910MHz; FDD Band V: 820-850MHz
RX Frequency Range	FDD Band II: 1930-1990MHz; FDD Band V: 869-894MHz
Release Version	Rel-6
Type of modulation	HSDPA:QPSK/16QAM; HSUPA:BPSK; WCDMA:QPSK
Antenna Gain	Band II: 1.85dBii; Band V: 2.3dBi
Max. Average Power	Band II: 20.70dBm; Band V: 22.29dBm

EUT Description (Continue)


LTE	
Support Band	<input checked="" type="checkbox"/> FDD Band 7 <input checked="" type="checkbox"/> TDD Band 38 <input checked="" type="checkbox"/> TDD Band 40 <input checked="" type="checkbox"/> TDD Band 41 (U.S. Bands)
TX Frequency Range	Band 7:2500-2570MHz; Band 38: 2570-2620MHz; Band 40:2300-2400MHz ; Band 41:2496-2690MHz
RX Frequency Range	Band 7:2620-2690MHz; Band 38: 2570-2620MHz; Band 40:2300-2400MHz ; Band 41:2496-2690MHz
Release Version	Rel-8
Type of modulation	QPSK, 16QAM
Antenna Gain	Band 7: 1.25dBi; Band 38: 1.32dBi; Band 40: -0.75dBi; Band 41: 1.24dBi;
Diversity Antenna Gain	Band 7: 1.23dBi; Band 38: 1.30dBi; Band 40: -0.79dBi; Band 41: 1.20dBi;
Max. Average Power	Band 7: 24.37dBm; Band 38: 24.40dBm; Band 40:24.38dBm; Band 41: 23.84dBm
Bluetooth	
Bluetooth Version	<input type="checkbox"/> V2.0 <input type="checkbox"/> V2.1 <input type="checkbox"/> V2.1+EDR <input type="checkbox"/> V3.0 <input type="checkbox"/> V3.0+HS <input type="checkbox"/> V4.0 <input checked="" type="checkbox"/> V5.0
Operation Frequency	2402~2480MHz
Type of modulation	<input checked="" type="checkbox"/> GFSK <input checked="" type="checkbox"/> II/4-DQPSK <input checked="" type="checkbox"/> 8-DPSK
Peak Power	2.302dBm
Antenna Gain	0dBi
WIFI	
WIFI Specification	<input type="checkbox"/> 802.11a <input checked="" type="checkbox"/> 802.11b <input checked="" type="checkbox"/> 802.11g <input checked="" type="checkbox"/> 802.11n(20) <input checked="" type="checkbox"/> 802.11n(40)
Operation Frequency	2412~2462MHz
Avg. Burst Power	11b: 12.05dBm,11g:9.86dBm,11n(20):8.70dBm,11n(40):8.74dBm
Antenna Gain	0dBi
Accessories	
Battery	Brand name: Mara Phones Model No. : MPX1Z1 Voltage and Capacitance: 3.85V & 3900mAh
Earphone	Brand name: N/A Model No. : N/A

- Note:1. CMU200 can measure the average power and Peak power at the same time
2. The sample used for testing is end product.
3. The test sample has no any deviation to the test method of standard mentioned in page 1.

Product	Type
	<input checked="" type="checkbox"/> Production unit <input type="checkbox"/> Identical Prototype

3. SAR MEASUREMENT SYSTEM

3.1. The SATIMO system used for performing compliance tests consists of following items




The COMOSAR system for performing compliance tests consists of the following items:

- The PC. It controls most of the bench devices and stores measurement data. A computer running WinXP and the Opensar software.
- The E-Field probe. The probe is a 3-axis system made of 3 distinct dipoles. Each dipole returns a voltage in function of the ambient electric field.
- The Keithley multimeter measures each probe dipole voltages.
- The SAM phantom simulates a human head. The measurement of the electric field is made inside the phantom.
- The liquids simulate the dielectric properties of the human head tissues.
- The network emulator controls the mobile phone under test.
- The validation dipoles are used to measure a reference SAR. They are used to periodically check the bench to make sure that there is no drift of the system characteristics over time.
- The phantom, the device holder and other accessories according to the targeted measurement.

3.2. COMOSAR E-Field Probe

The SAR measurement is conducted with the dosimetric probe manufactured by SATIMO. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. SATIMO conducts the probe calibration in compliance with international and national standards (e.g. IEEE 1528 and relevant KDB files.) The calibration data are in Appendix D.

Isotropic E-Field Probe Specification

Model	SSE5	
Manufacture	MVG	
Identification No.	SN 22/16 EP315	
Frequency	0.7GHz-3GHz Linearity:±0.06dB(0.7GHz-3GHz)	
Dynamic Range	0.01W/Kg-100W/Kg Linearity:±0.06dB	
Dimensions	Overall length:330mm Length of individual dipoles:4.5mm Maximum external diameter:8mm Probe Tip external diameter:5mm Distance between dipoles/ probe extremity:2.7mm	
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 3 GHz with precision of better 30%.	

3.3. Robot

The COMOSAR system uses the KUKA robot from SATIMO SA (France).For the 6-axis controller COMOSAR system, the KUKA robot controller version from SATIMO is used.


The XL robot series have many features that are important for our application:

- High precision (repeatability 0.02 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)
- 6-axis controller




3.4. Video Positioning System

The video positioning system is used in OpenSAR to check the probe. Which is composed of a camera, LED, mirror and mechanical parts. The camera is piloted by the main computer with firewire link. During the process, the actual position of the probe tip with respect to the robot arm is measured, as well as the probe length and the horizontal probe offset. The software then corrects all movements, such that the robot coordinates are valid for the probe tip. The repeatability of this process is better than 0.1 mm. If a position has been taught with an aligned probe, the same position will be reached with another aligned probe within 0.1 mm, even if the other probe has different dimensions. During probe rotations, the probe tip will keep its actual position.



3.5. Device Holder

The COMOSAR device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (EPR). Thus the device needs no repositioning when changing the angles. The COMOSAR device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon_r = 3$ and loss tangent $\delta = 0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



3.6. SAM Twin Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region where shell thickness increases to 6mm). It has three measurement areas:

- Left head
- Right head
- Flat phantom



The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

3.7. ELLI39 Phantom

The Flat phantom is a fiberglass shell phantom with 2mm \pm 0.2 mm shell thickness. It has only one measurement area for Flat phantom



4. SAR MEASUREMENT PROCEDURE

4.1. Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and occupational/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element(dv) of given mass density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dV} \right)$$

SAR is expressed in units of Watts per kilogram (W/Kg)

SAR can be obtained using either of the following equations:

$$SAR = \frac{\sigma E^2}{\rho}$$

$$SAR = c_h \left. \frac{dT}{dt} \right|_{t=0}$$

Where

SAR	is the specific absorption rate in watts per kilogram;
E	is the r.m.s. value of the electric field strength in the tissue in volts per meter;
σ	is the conductivity of the tissue in siemens per metre;
ρ	is the density of the tissue in kilograms per cubic metre;
c _h	is the heat capacity of the tissue in joules per kilogram and Kelvin;

$\left. \frac{dT}{dt} \right|_{t=0}$ is the initial time derivative of temperature in the tissue in kelvins per second

4.2. SAR Measurement Procedure

Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurement are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface is 2.7mm This distance cannot be smaller than the distance os sensor calibration points to probe tip as `defined in the probe properties,

Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in SATIMO software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in db) is specified in the standards for compliance testing. For example, a 2db range is required in IEEE Standard 1528 and IEC62209 standards, whereby 3db is a requirement when compliance is assessed in accordance with the ARIB standard (Japan) If one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximum are detected, the number of Zoom Scan has to be increased accordingly.

Area Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100MHz to 6GHz

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

Step 3: Zoom Scan

Zoom Scan are used to assess the peak spatial SAR value within a cubic average volume containing 1g abd 10g of simulated tissue. The Zoom Scan measures points(refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1g and 10g and displays these values next to the job's label.

Zoom Scan Parameters extracted from KDB865664 d01 SAR Measurement 100MHz to 6GHz

Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}		≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$	≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$
Minimum zoom scan volume	x, y, z	≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
<p>Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.</p> <p>* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based I-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.</p>			

Step 4: Power Drift Measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the same settings. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

4.3. RF Exposure Conditions


Test Configuration and setting:

The EUT is a model of GSM Portable Mobile Station (MS). It supports GSM/GPRS/EGPRS, WCDMA/HSPA, LTE, BT, WIFI, and support hot spot mode.

For WWAN SAR testing, the device was controlled by using a base station emulator. Communication between the device and the emulator were established by air link. The distance between the EUT and the antenna is larger than 50cm, and the output power radiated from the emulator antenna is at least 30db smaller than the output power of EUT.

For WLAN testing, the EUT is configured with the WLAN continuous TX tool through engineering command.

Antenna Location: (the back view)



For WWAN mode:

Test Configurations	Antenna to edges/surface	SAR required	Note
Head			
Left Touch		Yes	--
Left Tilt		Yes	--
Right Touch		Yes	--
Right Tilt		Yes	--
Body			
Back	<25mm	Yes	--
Front	<25mm	Yes	--
Hotspot			
Back	<25mm	Yes	--
Front	<25mm	Yes	--
Edge 1 (Top)	156mm	No	SAR is not required for the distance between the antenna and the edge is >25mm as per KDB 941225 D06 Hotspot SAR
Edge 2 (Right)	1mm	Yes	--
Edge 3 (Bottom)	1mm	Yes	--
Edge 4 (Left)	1mm	Yes	--

For WLAN mode:

Test Configurations	Antenna to edges/surface	SAR required	Note
Head			
Left Touch		Yes	--
Left Tilt		Yes	--
Right Touch		Yes	--
Right Tilt		Yes	--
Body			
Back	<25mm	Yes	--
Front	<25mm	Yes	--
Hotspot			
Back	<25mm	Yes	--
Front	<25mm	Yes	--
Edge 1 (Top)	1mm	Yes	--
Edge 2 (Right)	1mm	Yes	--
Edge 3 (Bottom)	157mm	No	SAR is not required for the distance between the antenna and the edge is >25mm as per KDB 941225 D06 Hotspot SAR
Edge 4 (Left)	54mm	No	SAR is not required for the distance between the antenna and the edge is >25mm as per KDB 941225 D06 Hotspot SAR

5. TISSUE SIMULATING LIQUID

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15cm. For head SAR testing the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15cm For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 10% are listed in 6.2

5.1. The composition of the tissue simulating liquid

Ingredient (% Weight) Frequency (MHz)	Water	Nacl	Polysorbate 20	DGBE	1,2 Propanediol	Triton X-100
835 Head	50.36	1.25	48.39	0.0	0.0	0.0
1900 Head	54.9	0.18	0.0	44.92	0.0	0.0
2300 Head	62.82	0.51	0.0	36.67	0.0	0.0
2450 Head	71.88	0.16	0.0	7.99	0.0	19.97
2600 Head	55.242	0.306	0	44.452	0	0

5.2. Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEC 62209-1 have been incorporated in the following table. The body tissue dielectric parameters recommended by the IEC 62209-2 have been incorporated in the following table.

Target Frequency (MHz)	head		body	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
300	45.3	0.87	45.3	0.87
450	43.5	0.87	43.5	0.87
750	41.9	0.89	41.9	0.89
835	41.5	0.90	41.5	0.90
900	41.5	0.97	41.5	0.97
915	41.5	1.01	41.5	1.01
1450	40.5	1.20	40.5	1.20
1610	40.3	1.29	40.3	1.29
1750	40.1	1.37	40.1	1.37
1800 – 2000	40.0	1.40	40.0	1.40
2300	39.5	1.67	39.5	1.67
2450	39.2	1.80	39.2	1.80
2600	39.0	1.96	39.0	1.96
3000	38.5	2.40	38.5	2.40

(ϵ_r = relative permittivity, σ = conductivity and $\rho = 1000 \text{ kg/m}^3$)

5.3. Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using SATIMO Dielectric Probe Kit and R&S Network Analyzer ZVL6.

Tissue Stimulant Measurement for 835MHz					
	Fr. (MHz)	Dielectric Parameters ($\pm 10\%$)		Tissue Temp [°C]	Test time
		ϵ_r 41.5 (37.35-45.65)	δ [s/m] 0.90(0.81-0.99)		
Head	824.2	41.56	0.87	21.3	Apr. 23,2020
	826.4	41.23	0.88		
	835	40.92	0.89		
	836.6	40.79	0.90		
	846.6	40.55	0.91		
	848.8	40.34	0.92		

Tissue Stimulant Measurement for 1900MHz					
	Fr. (MHz)	Dielectric Parameters ($\pm 10\%$)		Tissue Temp [°C]	Test time
		ϵ_r 40.00(36.00-44.00)	δ [s/m]1.40(1.26-1.54)		
Head	1850.2	39.46	1.34	21.0	Apr. 15,2020
	1852.4	39.17	1.35		
	1880	38.82	1.36		
	1900	38.61	1.37		
	1907.6	38.43	1.38		
	1909.8	38.29	1.39		

Tissue Stimulant Measurement for 2300MHz					
	Fr. (MHz)	Dielectric Parameters ($\pm 10\%$)		Tissue Temp [°C]	Test time
		ϵ_r 39.5(35.55-43.45)	δ [s/m] 1.67 (1.503-1.837)		
Head	2310	39.75	1.62	21.2	Apr. 13,2020
	2300	39.58	1.63		
	2350	39.34	1.64		
	2390	39.19	1.65		

Tissue Stimulant Measurement for 2450MHz					
	Fr. (MHz)	Dielectric Parameters ($\pm 10\%$)		Tissue Temp [°C]	Test time
		ϵ_r 39.2(35.28-43.12)	δ [s/m]1.80(1.62-1.98)		
Head	2412	41.98	1.80	21.3	Apr. 26,2020
	2437	41.82	1.81		
	2450	41.61	1.82		
	2462	41.43	1.83		

Tissue Stimulant Measurement for 2600MHz					
	Fr. (MHz)	Dielectric Parameters ($\pm 10\%$)		Tissue Temp [°C]	Test time
		ϵ_r 39(35.1-42.9)	δ [s/m]1.96(1.764-2.156)		
Head	2510	38.64	1.86	21.2	Apr. 17,2020
	2535	38.45	1.87		
	2560	38.23	1.88		
	2595	38.15	1.88		
	2605	38.01	1.89		


6. SAR SYSTEM CHECK PROCEDURE

6.1. SAR System Check Procedures

SAR system check is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device. The same SAR probe(s) and tissue-equivalent media combinations used with each specific SAR system for system verification must be used for device testing. When multiple probe calibration points are required to cover substantially large transmission bands, independent system verifications are required for each probe calibration point. A system verification must be performed before each series of SAR measurements using the same probe calibration point and tissue-equivalent medium. Additional system verification should be considered according to the conditions of the tissue-equivalent medium and measured tissue dielectric parameters, typically every three to four days when the liquid parameters are remeasured or sooner when marginal liquid parameters are used at the beginning of a series of measurements.


Each SATIMO system is equipped with one or more system check kits. These units, together with the predefined measurement procedures within the SATIMO software, enable the user to conduct the system check and system validation. System kit includes a dipole, and dipole device holder.

The system check verifies that the system operates within its specifications. It's performed daily or before every SAR measurement. The system check uses normal SAR measurement in the flat section of the phantom with a matched dipole at a specified distance. The system check setup is shown as below.



6.2. SAR System Check

6.2.1. Dipoles



Frequency	L (mm)	h (mm)	d (mm)
835MHz	161.0	89.8	3.6
1900MHz	68	39.5	3.6
2300MHz	55.5	32.6	3.6
2450MHz	51.5	30.4	3.6
2600MHz	48.5	28.8	3.6

6.2.2. System Check Result

System Performance Check at 835MHz &1900MHz &2300MHz &2450MHz&2600MHz for Head								
Validation Kit: SN29/15 DIP 0G835-383& SN 46/11 DIP 1G900-187& SN 47/14 DIP 2G300-341&SN46/11 DIP 2G450-189& SN 47/14 DIP 2G600-342								
Frequency [MHz]	Target Value(W/Kg)		Reference Result ($\pm 10\%$)		Tested Value(W/Kg)		Tissue Temp. [°C]	Test time
	1g	10g	1g	10g	1g	10g		
835	9.85	6.27	8.865-10.835	5.643-6.897	9.41	6.09	21.3	Apr. 23,2020
1900	40.25	20.50	36.225-44.275	18.45-22.55	43.72	21.90	21.0	Apr. 15,2020
2300	50.97	23.39	45.873-56.067	21.051-25.729	51.09	23.66	21.2	Apr. 13,2020
2450	53.97	24.01	48.573-59.367	21.609-26.411	49.74	22.54	21.3	Apr. 26,2020
2600	56.86	24.84	51.174-62.546	22.356-27.324	52.61	23.17	21.2	Apr. 17,2020
835	9.85	6.27	8.865-10.835	5.643-6.897	10.06	6.28	21.3	Apr. 23,2020
1900	40.25	20.50	36.225-44.275	18.45-22.55	42.04	19.26	21.0	Apr. 15,2020
2300	50.97	23.39	45.873-56.067	21.051-25.729	51.71	21.21	21.2	Apr. 13,2020
2450	53.97	24.01	48.573-59.367	21.609-26.411	52.21	24.03	21.3	Apr. 26,2020
2600	56.86	24.84	51.174-62.546	22.356-27.324	55.01	22.81	21.2	Apr. 17,2020

Note:



(1) We use a CW signal of 18dBm for system check, and then all SAR value are normalized to 1W forward power. The result must be within $\pm 10\%$ of target value.

7. EUT TEST POSITION

This EUT was tested in **Right Cheek, Right Tilted, Left Cheek, Left Tilted, Body back, Body front and 4 edges.**

7.1. Define Two Imaginary Lines on the Handset

- (1) The vertical centerline passes through two points on the front side of the handset: the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the handset.
- (2) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- (3) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.



7.2. Cheek Position

- (1) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- (2) To move the device towards the phantom with the ear piece aligned with the the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost





7.3. Tilt Position

- (1) To position the device in the “cheek” position described above.
- (2) While maintaining the device in the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until with the ear is lost.



7.4. Body Worn Position

- (1) To position the EUT parallel to the phantom surface.
- (2) To adjust the EUT parallel to the flat phantom.
- (3) To adjust the distance between the EUT surface and the flat phantom to **10mm**.



8. SAR EXPOSURE LIMITS

Limits for General Population/Uncontrolled Exposure (W/kg)

Type Exposure	Uncontrolled Environment Limit (W/kg)
Spatial Peak SAR (1g cube tissue for brain or body)	1.60
Spatial Average SAR (Whole body)	0.08
Spatial Peak SAR (Limbs)	4.0

9. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Designation Number	CN1259
FCC Test Firm Registration Number	975832
A2LA Cert. No.	5054.02
Description	Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by A2LA

10. TEST EQUIPMENT LIST

Equipment description	Manufacturer/ Model	Identification No.	Current calibration date	Next calibration date
SAR Probe	MVG	SN 22/16 EP315	Jun. 04,2019	Jun. 03,2020
Phantom	SATIMO	SN_4511_SAM90	Validated. No cal required.	Validated. No cal required.
Phantom	SATIMO	ELLI39	Validated. No cal required.	Validated. No cal required.
Liquid	SATIMO	-	Validated. No cal required.	Validated. No cal required.
Comm Tester	Agilent-8960	GB46310822	Oct. 08,2019	Oct. 07,2020
Comm Tester	R&S- CMW500	S/N120909	Jul. 02,2019	Jul. 01,2020
Multimeter	Keithley 2000	4114939	Sep. 09,2019	Sep. 08,2020
Dipole	SATIMO SID835	SN29/15 DIP 0G835-383	Apr. 26,2019	Apr. 25,2022
Dipole	SATIMO SID1900	SN 46/11 DIP 1G900-187	Apr. 26,2019	Apr. 25,2022
Dipole	SATIMO SID2300	SN 47/14 DIP 2G300-341	Apr. 26,2019	Apr. 25,2022
Dipole	SATIMO SID2450	SN46/11 DIP 2G450-189	Apr. 26,2019	Apr. 25,2022
Dipole	SATIMO SID2600	SN 47/14 DIP 2G600-342	Apr. 26,2019	Apr. 25,2022
Signal Generator	Agilent-E4438C	US41461365	Oct. 08,2019	Oct. 07,2020
Vector Analyzer	Agilent / E4440A	US41421290	Sep. 09,2019	Sep. 08,2020
Network Analyzer	Rhode & Schwarz ZVL6	SN101443	Oct. 08,2019	Oct. 07,2020
Attenuator	Warison /WATT-6SR1211	S/N:WRJ34AYM2F1	June 11,2019	June 10, 2020
Attenuator	Mini-circuits / VAT-10+	31405	June 11,2019	June 10, 2020
Amplifier	AS0104-55_55	1004793	June 12,2019	June 11,2020
Directional Couple	Werlatone/ C5571-10	SN99463	June 12,2019	June 11,2020
Directional Couple	Werlatone/ C6026-10	SN99482	June 12,2019	June 11,2020
Power Sensor	NRP-Z21	1137.6000.02	Sep. 09,2019	Sep. 08,2020
Power Sensor	NRP-Z23	US38261498	Feb. 18,2020	Feb. 17,2021
Power Viewer	R&S	V2.3.1.0	N/A	N/A

Note: Per KDB 865664 Dipole SAR Validation, AGC Lab has adopted 3 years calibration intervals. On annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

1. There is no physical damage on the dipole;
2. System validation with specific dipole is within 10% of calibrated value;
3. Return-loss is within 20% of calibrated measurement;
4. Impedance is within 5Ω of calibrated measurement.

11. MEASUREMENT UNCERTAINTY

Measurement uncertainty for Dipole averaged over 1 gram / 10 gram									
a	b	c	d	^e f(d,k)	f	g	^h c×f/e	ⁱ c×g/e	k
Uncertainty Component	Sec.	Tol (+-%)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (±%)	10g Ui (±%)	vi
Measurement System									
Probe calibration	E.2.1	5.831	N	1	1	1	5.83	5.83	∞
Axial Isotropy	E.2.2	0.57	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	0.23	0.23	∞
Hemispherical Isotropy	E.2.2	0.915	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	0.37	0.37	∞
Boundary effect	E.2.3	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	E.2.4	0.675	R	$\sqrt{3}$	1	1	0.39	0.39	∞
System detection limits	E.2.4	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	E.2.5	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Readout Electronics	E.2.6	0.021	N	1	1	1	0.021	0.021	∞
Response Time	E.2.7	0	R	$\sqrt{3}$	1	1	0	0	∞
Integration Time	E.2.8	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
RF ambient conditions-Noise	E.6.1	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient conditions-reflections	E.6.1	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner mechanical tolerance	E.6.2	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to phantom shell	E.6.3	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	E.5	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Test sample Related									
Test sample positioning	E.4.2	2.6	N	1	1	1	2.6	2.6	∞
Device holder uncertainty	E.4.1	3	N	1	1	1	3	3	∞
Output power variation—SAR drift measurement	E.2.9	5	R	$\sqrt{3}$	1	1	2.89	2.89	∞
SAR scaling	E.6.5	5	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Phantom and tissue parameters									
Phantom shell uncertainty—shape, thickness, and permittivity	E.3.1	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	1.9	N	1	1	0.84	1.90	1.60	∞
Liquid conductivity measurement	E.3.3	4	N	1	0.78	0.71	3.12	2.84	M
Liquid permittivity measurement	E.3.3	5	N	1	0.23	0.26	1.15	1.30	M
Liquid conductivity—temperature uncertainty	E.3.4	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid permittivity—temperature uncertainty	E.3.4	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty			RSS				9.787	9.587	
Expanded Uncertainty (95% Confidence interval)			K=2				19.573	19.175	

System Validation uncertainty for Dipole averaged over 1 gram / 10 gram.									
a	b	c	d	^e f(d,k)	f	g	^h cxf/e	ⁱ cxg/e	k
Uncertainty Component	Sec.	Tol (±%)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (±%)	10g Ui (±%)	vi
Measurement System									
Probe calibration	E.2.1	5.831	N	1	1	1	5.83	5.83	∞
Axial Isotropy	E.2.2	0.57	R	$\sqrt{3}$	1	1	0.33	0.33	∞
Hemispherical Isotropy	E.2.2	0.915	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Boundary effect	E.2.3	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	E.2.4	0.675	R	$\sqrt{3}$	1	1	0.39	0.39	∞
System detection limits	E.2.4	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	E.2.5	3.0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Readout Electronics	E.2.6	0.021	N	1	1	1	0.021	0.021	∞
Response Time	E.2.7	0.0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Integration Time	E.2.8	1.4	R	$\sqrt{3}$	0	0	0.00	0.00	∞
RF ambient conditions-Noise	E.6.1	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient conditions-reflections	E.6.1	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner mechanical tolerance	E.6.2	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to phantom shell	E.6.3	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	E.5	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
System check source (dipole)									
Deviation of experimental dipole from numerical dipole	E.6.4	5.0	N	1	1	1	5.00	5.00	∞
Input power and SAR drift measurement	8,6.6.4	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Dipole axis to liquid distance	8,E.6.6	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and tissue parameters									
Phantom shell uncertainty—shape, thickness, and permittivity	E.3.1	4.0	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	1.9	N	1	1	0.84	1.90	1.60	∞
Liquid conductivity measurement	E.3.3	4.0	N	1	0.78	0.71	3.12	2.84	M
Liquid permittivity measurement	E.3.3	5.0	N	1	0.23	0.26	1.15	1.30	M
Liquid conductivity—temperature uncertainty	E.3.4	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid permittivity—temperature uncertainty	E.3.4	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty			RSS				9.735	9.534	
Expanded Uncertainty (95% Confidence interval)			K=2				19.470	19.069	

System check uncertainty for Dipole averaged over 1 gram / 10 gram.									
a	b	c	d	^e f(d,k)	f	g	^h c×f/e	ⁱ c×g/e	k
Uncertainty Component	Sec.	Tol (+-%)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	vi
Measurement System									
Probe calibration drift	E.2.1.3	0.5	N	1	1	1	0.50	0.50	∞
Axial Isotropy	E.2.2	0.57	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Hemispherical Isotropy	E.2.2	0.915	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Boundary effect	E.2.3	1.0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Linearity	E.2.4	0.675	R	$\sqrt{3}$	0	0	0.00	0.00	∞
System detection limits	E.2.4	1.0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Modulation response	E.2.5	3.0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Readout Electronics	E.2.6	0.021	N	1	0	0	0.00	0.00	∞
Response Time	E.2.7	0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Integration Time	E.2.8	1.4	R	$\sqrt{3}$	0	0	0.00	0.00	∞
RF ambient conditions-Noise	E.6.1	3.0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
RF ambient conditions-reflections	E.6.1	3.0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Probe positioner mechanical tolerance	E.6.2	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to phantom shell	E.6.3	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	E.5	2.3	R	$\sqrt{3}$	0	0	0.00	0.00	∞
System check source (dipole)									
Deviation of experimental dipoles	E.6.4	2	N	1	1	1	2	2	∞
Input power and SAR drift measurement	8,6.6.4	5	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Dipole axis to liquid distance	8,E.6.6	2	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and tissue parameters									
Phantom shell uncertainty—shape, thickness, and permittivity	E.3.1	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	1.9	N	1	1	0.84	1.90	1.60	∞
Liquid conductivity measurement	E.3.3	4	N	1	0.78	0.71	3.12	2.84	M
Liquid permittivity measurement	E.3.3	5	N	1	0.23	0.26	1.15	1.30	M
Liquid conductivity—temperature uncertainty	E.3.4	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid permittivity—temperature uncertainty	E.3.4	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty			RSS				5.564	5.205	
Expanded Uncertainty (95% Confidence interval)			K=2				11.128	10.410	

12. CONDUCTED POWER MEASUREMENT GSM BAND

Mode	Frequency(MHz)	Avg. Burst Power(dBm)	Duty cycle Factor(dBm)	Frame Power(dBm)
Maximum Power <1>				
GSM 850	824.2	32.52	-9	23.52
	836.6	31.99	-9	22.99
	848.8	31.97	-9	22.97
GPRS 850 (1 Slot)	824.2	32.50	-9	23.50
	836.6	30.92	-9	21.92
	848.8	30.93	-9	21.93
GPRS 850 (2 Slot)	824.2	28.46	-6	22.46
	836.6	28.58	-6	22.58
	848.8	28.55	-6	22.55
GPRS 850 (3 Slot)	824.2	27.25	-4.26	22.99
	836.6	27.21	-4.26	22.95
	848.8	27.20	-4.26	22.94
GPRS 850 (4 Slot)	824.2	25.35	-3	22.35
	836.6	25.31	-3	22.31
	848.8	25.27	-3	22.27
EGPRS 850 (1 Slot)	824.2	26.37	-9	17.37
	836.6	25.62	-9	16.62
	848.8	25.33	-9	16.33
EGPRS 850 (2 Slot)	824.2	23.71	-6	17.71
	836.6	23.64	-6	17.64
	848.8	23.51	-6	17.51
EGPRS 850 (3 Slot)	824.2	21.79	-4.26	17.53
	836.6	21.80	-4.26	17.54
	848.8	21.87	-4.26	17.61
EGPRS 850 (4 Slot)	824.2	19.71	-3	16.71
	836.6	19.80	-3	16.80
	848.8	19.70	-3	16.70

Mode	Frequency(MHz)	Avg. Burst Power(dBm)	Duty cycle Factor(dBm)	Frame Power(dBm)
Maximum Power <2>				
GSM 850	824.2	32.42	-9	23.42
	836.6	31.87	-9	22.87
	848.8	31.84	-9	22.84
GPRS 850 (1 Slot)	824.2	32.39	-9	23.39
	836.6	30.80	-9	21.80
	848.8	30.81	-9	21.81
GPRS 850 (2 Slot)	824.2	28.35	-6	22.35
	836.6	28.48	-6	22.48
	848.8	28.42	-6	22.42
GPRS 850 (3 Slot)	824.2	27.13	-4.26	22.87
	836.6	27.07	-4.26	22.81
	848.8	27.06	-4.26	22.80
GPRS 850 (4 Slot)	824.2	25.23	-3	22.23
	836.6	25.19	-3	22.19
	848.8	25.15	-3	22.15

GSM BAND CONTINUE

Mode	Frequency(MHz)	Avg. Burst Power(dBm)	Duty cycle Factor(dBm)	Frame Power(dBm)
Maximum Power <1>				
PCS1900	1850.2	27.21	-9	18.21
	1880	27.82	-9	18.82
	1909.8	27.97	-9	18.97
GPRS1900 (1 Slot)	1850.2	27.25	-9	18.25
	1880	27.83	-9	18.83
	1909.8	27.93	-9	18.93
GPRS1900 (2 Slot)	1850.2	25.62	-6	19.62
	1880	25.64	-6	19.64
	1909.8	25.84	-6	19.84
GPRS1900 (3 Slot)	1850.2	23.64	-4.26	19.38
	1880	23.57	-4.26	19.31
	1909.8	23.43	-4.26	19.17
GPRS1900 (4 Slot)	1850.2	21.14	-3	18.14
	1880	21.11	-3	18.11
	1909.8	21.18	-3	18.18
EGPRS1900 (1 Slot)	1850.2	22.20	-9	13.20
	1880	22.64	-9	13.64
	1909.8	22.84	-9	13.84
EGPRS1900 (2 Slot)	1850.2	21.87	-6	15.87
	1880	21.72	-6	15.72
	1909.8	21.68	-6	15.68
EGPRS1900 (3 Slot)	1850.2	20.37	-4.26	16.11
	1880	20.38	-4.26	16.12
	1909.8	20.54	-4.26	16.28
EGPRS1900 (4 Slot)	1850.2	19.68	-3	16.68
	1880	19.74	-3	16.74
	1909.8	19.66	-3	16.66

Mode	Frequency(MHz)	Avg. Burst Power(dBm)	Duty cycle Factor(dBm)	Frame Power(dBm)
Maximum Power <2>				
PCS1900	1850.2	27.09	-9	18.09
	1880	27.72	-9	18.72
	1909.8	27.86	-9	18.86
GPRS1900 (1 Slot)	1850.2	27.14	-9	18.14
	1880	27.70	-9	18.70
	1909.8	27.81	-9	18.81
GPRS1900 (2 Slot)	1850.2	25.53	-6	19.53
	1880	25.54	-6	19.54
	1909.8	25.75	-6	19.75
GPRS1900 (3 Slot)	1850.2	23.56	-4.26	19.30
	1880	23.47	-4.26	19.21
	1909.8	23.30	-4.26	19.04
GPRS1900 (4 Slot)	1850.2	21.02	-3	18.02
	1880	20.98	-3	17.98
	1909.8	21.07	-3	18.07

Note 1:

The Frame Power (Source-based time-averaged Power) is scaled the maximum burst average power based on time slots. The calculated methods are show as following:

Frame Power = Max burst power (1 Up Slot) – 9 dB

Frame Power = Max burst power (2 Up Slot) – 6 dB

Frame Power = Max burst power (3 Up Slot) – 4.26 dB

Frame Power = Max burst power (4 Up Slot) – 3 dB

Note 2:

SAR is not required for GPRS (1 Slot) Mode because its output power is less than of Voice Mode

UMTS BAND

HSDPA Setup Configuration:

- The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- The RF path losses were compensated into the measurements.
- A call was established between EUT and Based Station with following setting:
 - (1) Set Gain Factors(β_c and β_d) parameters set according to each
 - (2) Set RMC 12.2Kbps+HSDPA mode.
 - (3) Set Cell Power=-86dBm
 - (4) Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - (5) Select HSDPA Uplink Parameters
 - (6) Set Delta ACK, Delta NACK and Delta CQI=8
 - (7) Set Ack - Nack Repetition Factor to 3
 - (8) Set CQI Feedback Cycle (k) to 4ms
 - (9) Set CQI Repetition Factor to 2
 - (10) Power Ctrl Mode=All Up bits
- The transmitted maximum output power was recorded.

Table C.10.2.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c (Note5)	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15(Note 4)	15/15(Note 4)	64	12/15(Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: $\Delta ACK, \Delta NACK$ and $\Delta CQI = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, ΔACK and $\Delta NACK = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$, and $\Delta CQI = 24/15$ with $\beta_{hs} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d = 12/15, \beta_c/\beta_d = 24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

HSUPA Setup Configuration:

- The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- The RF path losses were compensated into the measurements.
- A call was established between EUT and Base Station with following setting * :
 - (1) Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - (2) Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - (3) Set Cell Power = -86 dBm
 - (4) Set Channel Type = 12.2k + HSPA
 - (5) Set UE Target Power
 - (6) Power Ctrl Mode= Alternating bits
 - (7) Set and observe the E-TFCI
 - (8) Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (Note 4) (Note 5)	β_{ed} (SF)	β_{ed} (Code s)	CM (dB) (Note 2)	MPR (dB) (Note 2) (Note 6)	AG Index (Note 5)	E-TF CI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/225	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} : 47/15 β_{ed2} : 47/15	4 4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4, ΔACK , $\Delta NACK$ and $\Delta CQI = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. For sub-test 5, ΔACK , $\Delta NACK$ and $\Delta CQI = 5/15$ with $\beta_{hs} = 5/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $hs/c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the c/d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $c = 10/15$ and $d = 15/15$.

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5: β_{ed} cannot be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

UMTS BAND II

Mode	Frequency (MHz)	Avg. Burst Power (dBm)
WCDMA 1900 RMC	1852.4	20.18
	1880	20.61
	1907.6	20.70
WCDMA 1900 AMR	1852.4	20.16
	1880	20.41
	1907.6	20.64
HSDPA Subtest 1	1852.4	19.21
	1880	19.66
	1907.6	19.81
HSDPA Subtest 2	1852.4	18.52
	1880	18.88
	1907.6	18.99
HSDPA Subtest 3	1852.4	18.45
	1880	18.80
	1907.6	18.94
HSDPA Subtest 4	1852.4	18.34
	1880	18.78
	1907.6	18.98
HSUPA Subtest 1	1852.4	16.55
	1880	16.82
	1907.6	16.77
HSUPA Subtest 2	1852.4	17.66
	1880	17.92
	1907.6	17.84
HSUPA Subtest 3	1852.4	18.53
	1880	18.82
	1907.6	18.74
HSUPA Subtest 4	1852.4	17.24
	1880	17.54
	1907.6	17.42
HSUPA Subtest 5	1852.4	16.69
	1880	16.69
	1907.6	16.94

UMTS BAND V

Mode	Frequency (MHz)	Avg. Burst Power (dBm)
WCDMA 850 RMC	826.4	22.11
	836.6	22.25
	846.6	22.29
WCDMA 850 AMR	826.4	21.68
	836.6	21.75
	846.6	21.64
HSDPA Subtest 1	826.4	21.18
	836.6	21.60
	846.6	21.65
HSDPA Subtest 2	826.4	20.78
	836.6	20.90
	846.6	20.86
HSDPA Subtest 3	826.4	20.69
	836.6	20.81
	846.6	20.82
HSDPA Subtest 4	826.4	20.63
	836.6	20.87
	846.6	20.81
HSUPA Subtest 1	826.4	20.17
	836.6	20.41
	846.6	20.79
HSUPA Subtest 2	826.4	20.16
	836.6	20.43
	846.6	20.78
HSUPA Subtest 3	826.4	21.15
	836.6	21.40
	846.6	21.79
HSUPA Subtest 4	826.4	19.73
	836.6	20.05
	846.6	20.42
HSUPA Subtest 5	826.4	19.05
	836.6	19.60
	846.6	19.99

According to 3GPP 25.101 sub-clause 6.2.2 , the maximum output power is allowed to be reduced by following the table.

Table 6.1aA: UE maximum output power with HS-DPCCH and E-DCH

UE Transmit Channel Configuration	CM(db)	MPR(db)
For all combinations of ,DPDCH,DPCCH HS-DPDCH,E-DPDCH and E-DPCCH	$0 \leq CM \leq 3.5$	$MAX(CM-1,0)$
Note: CM=1 for $\beta_d/\beta_{d'}=12/15$, $\beta_{hs}/\beta_c=24/15$.For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.		

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present the beta gains on those channels are reduced firsts to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced. The cubic metric will likely get lower each time this is done .However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a compensation for the power back-off by increasing the gain of TX_AGC in the transceiver (PA) device.

The end effect is that the DUT output power is identical to the case where there is no MPR in the device.

LTE Band

LTE (TDD) Considerations

For Time-Division Duplex (TDD) systems, SAR must be tested using a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by the defined 3GPP LTE TDD configurations.

SAR was tested with the highest transmission duty factor (63.33%) using Uplink-downlink configuration 0 and Special subframe configuration 7.

LTE TDD Band 40 supports 3GPP TS 36.211 section 4.2 for Type 2 Frame Structure and Table 4.2-2 for uplink-downlink configurations and Table 4.2-1 for Special subframe configurations.

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS)

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	$6592 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$	$7680 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$
1	$19760 \cdot T_s$			$20480 \cdot T_s$		
2	$21952 \cdot T_s$			$23040 \cdot T_s$		
3	$24144 \cdot T_s$			$25600 \cdot T_s$		
4	$26336 \cdot T_s$			$7680 \cdot T_s$		
5	$6592 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$	$20480 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$
6	$19760 \cdot T_s$			$23040 \cdot T_s$		
7	$21952 \cdot T_s$			$12800 \cdot T_s$		
8	$24144 \cdot T_s$			-		
9	$13168 \cdot T_s$			-	-	-

Table 4.2-2: Uplink-downlink configurations

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number										
		0	1	2	3	4	5	6	7	8	9	
0	5 ms	D	S	U	U	U	D	S	U	U	U	
1	5 ms	D	S	U	U	D	D	S	U	U	D	
2	5 ms	D	S	U	D	D	D	S	U	D	D	
3	10 ms	D	S	U	U	U	D	D	D	D	D	
4	10 ms	D	S	U	U	D	D	D	D	D	D	
5	10 ms	D	S	U	D	D	D	D	D	D	D	
6	5 ms	D	S	U	U	U	D	S	U	U	D	

Calculated Duty Cycle

Uplink-Downlink Configuration	Downlink-to-Uplink Switch-point Periodicity	Subframe Number										Calculated Duty Cycle(%)
		0	1	2	3	4	5	6	7	8	9	
0	5ms	D	S	U	U	U	D	S	U	U	U	63.33
1	5ms	D	S	U	U	D	D	S	U	U	D	43.33
2	5ms	D	S	U	D	D	D	S	U	D	D	23.33
3	10ms	D	S	U	U	U	D	D	D	D	D	31.67
4	10ms	D	S	U	U	D	D	D	D	D	D	21.67
5	10ms	D	S	U	D	D	D	D	D	D	D	11.67
6	5ms	D	S	U	U	U	D	S	U	U	D	53.33

Note: Calculated Duty Cycle = Extended cyclic prefix in uplink x (Ts) x # of S + # of U

Example for Calculated Duty Cycle for Uplink-Downlink Configuration 0:

Calculated Duty Cycle = $5120 \times [1/(15000 \times 2048)] \times 2 + 6 \text{ ms} = 63.33\%$

where

$T_s = 1/(15000 \times 2048)$ seconds

LTE Band

Conducted Power of LTE Band 7 (dBm)							
Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel
					20775	21100	21425
5MHz	QPSK	1	0	0	23.20	23.97	22.98
			12	0	23.44	24.10	23.24
			24	0	23.24	23.96	23.12
		12	0	1	22.40	23.04	22.06
			6	1	22.41	23.04	22.03
			13	1	22.46	23.05	22.06
	25	0	1	20.54	23.04	21.99	
	16QAM	1	0	1	22.17	23.02	21.75
			12	1	22.50	23.21	22.00
			24	1	22.36	23.14	21.89
		12	0	2	21.52	22.09	20.97
			6	2	21.55	22.10	20.97
			13	2	21.50	22.14	20.99
		25	0	2	21.70	22.10	20.96
Bandwidth		Modulation	RB size	RB offset	Target MPR	Channel	Channel
					20800	21100	21400
10MHz	QPSK	1	0	0	23.45	24.06	22.96
			24	0	23.58	24.17	23.16
			49	0	23.44	24.10	23.14
		25	0	1	22.66	23.11	21.96
			12	1	22.66	23.09	21.94
			25	1	22.66	23.19	22.02
	50	0	1	22.69	23.10	21.94	
	16QAM	1	0	1	22.67	22.97	21.90
			24	1	22.87	23.18	22.07
			49	1	22.75	23.26	22.11
		25	0	2	21.67	22.13	20.85
			12	2	21.69	22.16	20.87
			25	2	21.73	22.24	20.95
		50	0	2	21.72	22.16	20.85

Conducted Power of LTE Band 7 (dBm)

Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel	
					20825	21100	21375	
15MHz	QPSK	1	0	0	23.39	24.05	22.79	
			37	0	23.54	24.23	23.05	
			74	0	23.46	24.02	23.03	
		37	0	1	22.69	23.32	22.19	
			16	1	22.70	23.32	22.18	
			35	1	22.68	23.31	22.19	
	75	0	1	22.68	23.33	22.19		
	16QAM	1	0	1	22.70	23.03	21.84	
			37	1	22.79	23.29	21.99	
			74	1	22.66	23.33	22.04	
		37	0	2	21.58	22.28	22.16	
			16	2	21.54	22.15	22.18	
			35	2	21.62	22.29	22.17	
		75	0	2	21.61	22.24	21.03	
Bandwidth		Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel
						20850	21100	21350
20MHz	QPSK	1	0	0	23.25	23.77	22.79	
			49	0	23.65	24.37	23.33	
			99	0	23.50	23.95	23.06	
		50	0	1	22.50	23.04	21.89	
			25	1	22.46	23.06	21.89	
			49	1	22.87	23.18	21.91	
	100	0	1	22.62	23.12	21.90		
	16QAM	1	0	1	22.42	22.72	21.84	
			49	1	22.74	23.25	22.10	
			99	1	22.51	23.12	21.89	
		50	0	2	21.54	22.09	20.92	
			25	2	21.53	22.07	20.90	
			49	2	21.89	22.28	20.86	
		100	0	2	21.73	22.11	20.83	

Conducted Power of LTE Band 38(dBm)								
Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel	
					37775	38000	38225	
5MHz	QPSK	1	0	0	22.75	22.77	22.74	
			12	0	23.31	23.26	23.35	
			24	0	23.05	23.01	22.92	
		12	0	1	22.79	22.77	22.77	
			6	1	22.78	22.61	22.65	
			13	1	22.99	22.85	22.71	
	25	0	1	21.80	21.82	21.82		
	16QAM	1	0	1	21.79	21.82	21.69	
			12	1	22.04	22.01	22.03	
			24	1	21.87	21.87	21.86	
		12	0	2	21.84	21.86	21.80	
			6	2	21.87	21.72	21.82	
			13	2	21.79	21.83	21.81	
		25	0	2	20.94	20.90	20.94	
Bandwidth		Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel
						37800	38000	38200
10MHz	QPSK	1	0	0	22.77	22.77	22.75	
			24	0	23.26	23.28	23.29	
			49	0	22.86	23.01	22.87	
		25	0	1	21.81	21.80	21.81	
			12	1	21.80	21.82	21.83	
			25	1	21.94	21.91	22.03	
	50	0	1	21.84	21.88	21.64		
	16QAM	1	0	1	21.81	21.73	21.69	
			24	1	22.03	22.12	22.13	
			49	1	21.92	21.89	21.90	
		25	0	2	20.95	20.93	20.60	
			12	2	20.96	20.91	20.59	
			25	2	20.92	20.92	21.02	
		50	0	2	20.91	20.90	20.69	

Conducted Power of LTE Band 38(dBm)								
Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel	
					37825	38000	38175	
15MHz	QPSK	1	0	0	22.02	21.85	22.31	
			37	0	22.70	22.75	22.97	
			74	0	22.67	22.77	22.92	
		36	0	1	21.55	21.78	21.80	
			16	1	21.69	21.80	21.78	
			35	1	21.70	21.79	20.75	
		75	0	1	21.70	21.91	21.87	
		16QAM	1	0	1	20.93	20.95	21.34
				37	1	21.50	21.67	21.94
	74			1	21.59	22.01	22.05	
	36		0	2	21.57	21.77	21.75	
			16	2	21.58	21.75	21.71	
			35	2	21.61	21.78	21.71	
	75	0	2	20.87	20.86	20.80		
	Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel
					37850	38000	38150	
20MHz	QPSK	1	0	0	22.97	23.97	23.42	
			49	0	23.86	24.40	23.31	
			99	0	24.00	23.21	22.55	
		50	0	1	22.62	23.15	22.29	
			25	1	22.64	23.18	22.30	
			49	1	23.18	22.68	21.85	
		100	0	1	22.93	22.99	22.10	
		16QAM	1	0	1	22.14	23.22	22.39
				49	1	23.27	23.12	22.26
	99			1	23.02	22.37	21.50	
	50		0	2	21.71	22.19	21.40	
			25	2	21.72	22.18	21.37	
			49	2	22.19	21.76	20.94	
	100	0	2	21.98	22.00	21.19		

Avg. Output Power of LTE Band 40(dBm)								
Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel	
					38675	39150	39625	
5MHz	QPSK	1	0	0	23.81	22.56	23.78	
			12	0	23.85	22.64	23.83	
			24	0	22.94	22.28	23.57	
		12	0	1	22.31	21.57	22.69	
			6	1	22.33	21.59	22.69	
			11	1	22.21	21.48	22.52	
		25	0	1	22.22	21.49	22.55	
		16QAM	1	0	1	22.25	21.45	22.74
				12	1	22.26	21.47	22.76
	24			1	22.00	21.20	22.52	
	12		0	2	21.30	20.50	21.58	
			6	2	21.29	20.52	21.58	
			11	2	21.16	20.37	21.42	
	25	0	2	21.28	20.51	21.56		
	Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel
					38700	39150	39600	
10MHz	QPSK	1	0	0	23.31	22.82	24.18	
			24	0	23.25	22.81	24.23	
			49	0	22.70	22.31	23.75	
		25	0	1	22.28	21.65	22.91	
			12	1	22.25	21.66	22.91	
			25	1	21.97	21.45	22.60	
		50	0	1	22.15	21.54	22.71	
		16QAM	1	0	1	22.50	21.83	22.94
				24	1	22.46	21.83	22.93
	49			1	21.92	21.41	22.46	
	25		0	2	21.27	20.60	21.83	
			12	2	21.27	20.61	21.84	
			25	2	21.00	20.47	21.51	
	50	0	2	21.15	20.57	21.66		

Avg. Output Power of LTE Band 40(dBm)								
Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel	
					38725	39150	39575	
15MHz	QPSK	1	0	0	24.01	22.98	24.16	
			37	0	23.68	22.72	24.05	
			74	0	22.97	22.33	23.61	
		36	0	1	22.83	21.77	23.13	
			16	1	22.78	21.78	23.11	
			35	1	22.81	21.77	23.12	
	75	0	1	22.78	21.75	23.13		
	16QAM	1	0	1	23.18	21.91	22.98	
			37	1	22.83	21.66	22.76	
			74	1	22.15	21.42	22.29	
		36	0	2	22.79	21.77	23.13	
			16	2	22.81	21.76	23.08	
			35	2	22.82	21.77	23.12	
		75	0	2	21.71	20.66	21.94	
Bandwidth		Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel
						38750	39150	39550
20MHz	QPSK	1	0	0	23.85	22.76	24.04	
			49	0	23.71	22.93	24.38	
			99	0	22.41	22.38	23.41	
		50	0	1	22.80	21.68	23.13	
			25	1	22.78	21.68	23.12	
			49	1	22.09	21.41	22.66	
	100	0	1	22.46	21.55	22.94		
	16QAM	1	0	1	22.88	21.81	23.00	
			49	1	22.76	21.96	23.13	
			99	1	21.44	21.59	22.23	
		50	0	2	21.86	20.69	22.14	
			25	2	21.84	20.70	22.15	
			49	2	21.14	20.47	21.62	
		100	0	2	21.49	20.54	21.87	

Conducted Power of LTE Band 41(dBm)									
Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel		
					40315	40740	41166		
5MHz	QPSK	1	0	0	23.45	23.03	22.53		
			12	0	23.61	23.17	22.68		
			24	0	23.49	23.12	22.55		
		12	0	1	22.55	22.15	21.67		
			6	1	22.54	22.13	21.65		
			11	1	22.54	22.12	21.64		
		25	0	1	22.55	22.15	21.66		
		16QAM	1	0	1	22.51	21.82	21.58	
				12	1	22.66	21.96	21.70	
	24			1	22.55	21.88	21.61		
	12		0	2	21.38	21.28	21.65		
			6	2	21.45	21.35	21.67		
			11	2	21.39	21.24	21.65		
	25		0	2	21.59	21.19	20.71		
	Bandwidth		Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel
							40340	40740	41141
	10MHz	QPSK	1	0	0	23.49	23.08	22.67	
				24	0	23.84	23.40	22.95	
49				0	23.47	23.10	22.67		
25			0	1	22.58	22.11	21.71		
			12	1	22.57	22.14	21.69		
			25	1	22.60	22.25	21.71		
50			0	1	22.62	22.17	21.70		
16QAM			1	0	1	22.66	22.29	21.76	
				24	1	22.00	22.62	22.00	
		49		1	22.71	22.32	21.77		
		25	0	2	21.35	21.35	21.69		
			12	2	21.58	21.28	21.71		
			25	2	21.47	21.22	21.70		
		50	0	2	21.66	21.21	20.72		

Conducted Power of LTE Band 41(dBm)							
Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel
					40365	40740	41116
15MHz	QPSK	1	0	0	23.39	22.90	22.63
			37	0	23.53	23.13	22.69
			74	0	23.25	23.03	22.56
		36	0	1	22.62	22.15	21.77
			16	1	22.60	22.16	21.72
			35	1	22.59	22.16	21.71
	75	0	1	22.60	22.16	21.73	
	16QAM	1	0	1	22.57	22.12	21.89
			37	1	22.71	22.37	21.88
			74	1	22.51	22.22	21.73
		36	0	2	21.07	21.55	21.73
			16	2	21.12	21.36	21.75
			35	2	21.03	21.46	21.74
	75	0	2	21.52	21.09	20.71	
Bandwidth	Modulation	RB size	RB offset	Target MPR	Channel	Channel	Channel
					40390	40740	41091
20MHz	QPSK	1	0	0	23.20	22.74	22.62
			49	0	23.74	23.37	22.97
			99	0	22.96	22.86	22.44
		50	0	1	22.51	22.00	21.68
			25	1	22.51	22.01	21.70
			49	1	22.39	22.15	21.61
	100	0	1	22.43	22.08	21.63	
	16QAM	1	0	1	22.25	21.82	21.85
			49	1	22.80	22.44	22.20
			99	1	22.04	21.95	21.65
		50	0	2	21.52	21.03	20.75
			25	2	21.54	21.02	20.77
			49	2	21.44	21.19	20.67
	100	0	2	21.45	21.13	20.68	

The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

UE Power Class: 3 (23 +/- 2dBm). The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3.3-1 of the 3GPP TS36.101.

Table 6.2.3.3-1 Maximum Power Reduction (MPR) for Power class3

Modulation	Maximum Power Reduction (MPR) for Power[RB]						MPR(dB)
	1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz	
QPSK	>5	>4	>8	>12	>16	>18	≤1
16QAM	≤5	≤4	≤8	≤12	≤16	≤18	≤1
16QAM	>5	>4	>8	>12	>16	>18	≤2

The allowed A-MPR values specified below in Table 6.2.4.3-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signaling Value of "NS_01".3

Table 6.2.4.3-1: Additional Maximum Power Reduction (A-MPR) / Spectrum Emission requirements

Network Signaling value	Requirements (sub-clause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.2-1	1.4,3,5,10,15,20	Table 5.4.2-1	N/A
NS_03	6.6.2.2.3.1	2,4,10, 23, 25,35,36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.3.2	41	5	>6	≤ 1
			10, 15, 20	Table 6.2.4.3-4	
NS_05	6.6.3.3.3.1	1	10,15,20	≥ 50	≤ 1
NS_06	6.6.2.2.3.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.4.2-1	N/A
NS_07	6.6.2.2.3.3 6.6.3.3.3.2	13	10	Table 6.2.4.3-2	Table 6.2.4.3-2
NS_08	6.6.3.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4.3-3	Table 6.2.4.3-3
NS_11	6.6.2.2.1 6.6.3.3.13	231	1.4, 3, 5, 10,15,20	Table 6.2.4.3-5	Table 6.2.4.3-5
NS_12	6.6.3.3.5	26	1.4, 3, 5	Table 6.2.4.3-6	Table 6.2.4.3-6
NS_13	6.6.3.3.6	26	5	Table 6.2.4.3-7	Table 6.2.4.3-7
NS_14	6.6.3.3.7	26	10, 15	Table 6.2.4.3-8	Table 6.2.4.3-8
NS_15	6.6.3.3.8	26	1.4, 3, 5, 10, 15	Table 6.2.4.3-9 Table 6.2.4.3-10	Table 6.2.4.3-9, Table 6.2.4.3-10
NS_16	6.6.3.3.9	27	3, 5, 10	Table 6.2.4.3-11, Table 6.2.4.3-12, Table 6.2.4.3-13	
NS_17	6.6.3.3.10	28	5, 10	Table 5.4.2-1	N/A
	6.6.3.3.11	28	5	≥ 2	≤ 1
NS_18			10, 15, 20	≥ 1	≤ 4
NS_19			10, 15, 20	Table 6.2.4.3-15	Table 6.2.4.3-15
NS_20			5, 10, 15, 20	Table 6.2.4.3-14	Table 6.2.4.3-14
...					
NS_20	-	-	-	-	-

WIFI

Mode	Data Rate (Mbps)	Channel	Frequency(MHz)	Avg. Burst Power(dBm)
802.11b	1	01	2412	11.84
		06	2437	11.96
		11	2462	12.05
802.11g	6	01	2412	9.45
		06	2437	9.86
		11	2462	9.64
802.11n(20)	6.5	01	2412	8.29
		06	2437	8.70
		11	2462	8.30
802.11n(40)	13.5	03	2422	8.06
		06	2437	8.74
		09	2452	7.12

Bluetooth_V4.0 (BR/EDR)

Modulation	Channel	Frequency(MHz)	Peak Power (dBm)
GFSK	0	2402	2.302
	39	2441	2.167
	78	2480	1.307
$\pi/4$ -DQPSK	0	2402	1.533
	39	2441	1.512
	78	2480	0.697
8-DPSK	0	2402	1.504
	39	2441	1.503
	78	2480	0.696

Bluetooth_V4.0 (BLE)

Modulation	Channel	Frequency(MHz)	Peak Power (dBm)
GFSK	0	2402	-6.442
	19	2440	-5.919
	39	2480	-6.814

13. TEST RESULTS

13.1. SAR Test Results Summary

13.1.1. Test position and configuration

Head SAR was performed with the device configured in the positions according to IEEE 1528-2013, Body-worn and 4 Edges SAR was performed with the device 10mm from the phantom.

13.1.2. Operation Mode

1. Per KDB 447498 D01 v06 ,for each exposure position, if the highest 1-g SAR is ≤ 0.8 W/kg, testing for low and high channel is optional.
2. Per KDB 865664 D01 v01r04,for each frequency band, if the measured SAR is ≥ 0.8 W/Kg, testing for repeated SAR measurement is required , that the highest measured SAR is only to be tested. When the SAR results are near the limit, the following procedures are required for each device to verify these types of SAR measurement related variation concerns by repeating the highest measured SAR configuration in each frequency band.
 - (1) When the original highest measured SAR is ≥ 0.8 W/Kg, repeat that measurement once.
 - (2) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is >1.20 or when the original or repeated measurement is ≥ 1.45 W/Kg.
 - (3) Perform a third repeated measurement only if the original, first and second repeated measurement is ≥ 1.5 W/Kg and ratio of largest to smallest SAR for the original, first and second measurement is ≥ 1.20 .
3. Body-worn exposure conditions are intended to voice call operations, therefore GSM voice call mode is selected to be test.
4. Per KDB 648474 D04 v01r03,when the reported SAR for a body-worn accessory measured without a headset connected to the handset is ≤ 1.2 W/Kg, SAR testing with a headset connected is not required.
5. Per KDB 248227 D01v02r02,for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
6. Per KDB 941225 D06 V02r01, When the same wireless mode transmission configurations for voice and data are required for SAR measurements, the more conservative configuration with a smaller separation distance should be tested for the overlapping SAR configurations.
7. Maximum Scaling SAR in order to calculate the Maximum SAR values to test under the standard Peak Power, Calculation method is as follows:
Maximum Scaling SAR =tested SAR (Max.) \times [maximum turn-up power (mw)/ maximum measurement output power(mw)]
8. Proximity sensor, just for avoiding the wrong operation in the phone screen when call, and has no influence on output power or SAR result
9. Per KDB 941225 D05v02r03, start with the largest channel bandwidth and measure SAR for QPSK with 1RB allocation using the RB offset and required test channel combination with highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
10. Per KDB 941125 D05v02r03, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
11. Per KDB 941125 D05v02r03. For QPSK with 100% RB allocation. SAR is not required when the highest maximum output power for 100% RB allocation is less than the highest maximum output power in 50% and

1RB allocation and the highest reported SAR is >1.45 W/Kg, the remaining required test channels must also be tested.

12. Per KDB 941125 D05v02r03. 16QAM output power for each RB allocation configuration is not 1/2 dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/Kg, Per KDB 941225 D05v02r02, 16QAM SAR testing is not required.
13. Per KDB 941125 D05v02r03. Smaller bandwidth output power for each RB allocation configuration is $>$ not 1/2 dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/Kg. Per KDB 941125 D05v02r03, smaller bandwidth SAR testing is not required.

13.1.3. Test Result

SAR MEASUREMENT									
Depth of Liquid (cm):>15					Relative Humidity (%): 48.8				
Product: Smart Phone									
Test Mode: GSM850 with GMSK modulation									
Position	Mode	Ch.	Fr. (MHz)	Power Drift ($\pm 5\%$)	SAR (1g) (W/kg)	Max. Tune-up Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)
SIM 1 Card									
Left Cheek	voice	190	836.6	0.35	0.219	32.60	31.99	0.252	1.6
Left Tilt	voice	190	836.6	-0.48	0.141	32.60	31.99	0.162	1.6
Right Cheek	voice	190	836.6	-0.52	0.280	32.60	31.99	0.322	1.6
Right Tilt	voice	190	836.6	0.39	0.154	32.60	31.99	0.177	1.6
Body back	voice	190	836.6	0.36	0.384	32.60	31.99	0.442	1.6
Body front	voice	190	836.6	-0.32	0.367	32.60	31.99	0.422	1.6
Body back	GPRS-1 slot	190	836.6	-0.28	0.528	32.50	30.92	0.760	1.6
Body front	GPRS-1 slot	190	836.6	0.16	0.483	32.50	30.92	0.695	1.6
Edge 2(Right)	GPRS-1 slot	190	836.6	-0.35	0.459	32.50	30.92	0.660	1.6
Edge 3(Bottom)	GPRS-1 slot	190	836.6	-0.33	0.440	32.50	30.92	0.633	1.6
Edge 4(Left)	GPRS-1 slot	190	836.6	0.29	0.195	32.50	30.92	0.281	1.6

Note:

- When the 1-g Reported SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back, body front and 4 Edges is 10mm of all above table.

SAR MEASUREMENT									
Depth of Liquid (cm):>15					Relative Humidity (%): 61.2				
Product: Smart Phone									
Test Mode: PCS1900 with GMSK modulation									
Position	Mode	Ch.	Fr. (MHz)	Power Drift (<±5%)	SAR (1g) (W/kg)	Max. Tune-up Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)
SIM 1 Card									
Left Cheek	voice	661	1880.0	-0.12	0.149	28.00	27.82	0.155	1.6
Left Tilt	voice	661	1880.0	0.28	0.057	28.00	27.82	0.059	1.6
Right Cheek	voice	661	1880.0	-0.16	0.057	28.00	27.82	0.059	1.6
Right Tilt	voice	661	1880.0	0.23	0.061	28.00	27.82	0.064	1.6
Body back	voice	661	1880.0	0.25	0.181	28.00	27.82	0.189	1.6
Body front	voice	661	1880.0	-0.37	0.173	28.00	27.82	0.180	1.6
Body back	GPRS-2 slot	661	1880	-0.52	0.282	25.90	25.64	0.299	1.6
Body front	GPRS-2 slot	661	1880.0	0.46	0.257	25.90	25.64	0.273	1.6
Edge 2(Right)	GPRS-2 slot	661	1880.0	-0.27	0.019	25.90	25.64	0.020	1.6
Edge 3(Bottom)	GPRS-2 slot	661	1880.0	-0.29	0.376	25.90	25.64	0.399	1.6
Edge 4(Left)	GPRS-2 slot	661	1880.0	0.36	0.187	25.90	25.64	0.199	1.6

Note:

- When the 1-g Reported SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back, body front and 4 Edges is 10mm of all above table.

SAR MEASUREMENT									
Depth of Liquid (cm):>15					Relative Humidity (%): 61.2				
Product: Smart Phone									
Test Mode: WCDMA Band II with QPSK modulation									
Position	Mode	Ch.	Fr. (MHz)	Power Drift (<±5%)	SAR (1g) (W/kg)	Max. Tune-up Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)
Left Cheek	RMC 12.2kbps	9400	1880	-0.85	0.217	20.70	20.61	0.222	1.6
Left Tilt	RMC 12.2kbps	9400	1880	0.96	0.102	20.70	20.61	0.104	1.6
Right Cheek	RMC 12.2kbps	9400	1880	-0.54	0.116	20.70	20.61	0.118	1.6
Right Tilt	RMC 12.2kbps	9400	1880	0.52	0.092	20.70	20.61	0.094	1.6
Body back	RMC 12.2kbps	9400	1880	-0.56	0.293	20.70	20.61	0.299	1.6
Body front	RMC 12.2kbps	9400	1880	0.74	0.279	20.70	20.61	0.285	1.6
Edge 2(Right)	RMC 12.2kbps	9400	1880	-0.85	0.023	20.70	20.61	0.023	1.6
Edge 3(Bottom)	RMC 12.2kbps	9400	1880	0.35	0.414	20.70	20.61	0.423	1.6
Edge 4(Left)	RMC 12.2kbps	9400	1880	-0.56	0.190	20.70	20.61	0.194	1.6

Note:

- When the 1-g Reported SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back, body front and 4 Edges is 10mm of all above table.

SAR MEASUREMENT									
Depth of Liquid (cm):>15					Relative Humidity (%): 48.8				
Product: Smart Phone									
Test Mode: WCDMA Band V with QPSK modulation									
Position	Mode	Ch.	Fr. (MHz)	Power Drift (<±5%)	SAR (1g) (W/kg)	Max. Tune-up Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)
Left Cheek	RMC 12.2kbps	4183	836.6	0.28	0.160	22.30	22.25	0.162	1.6
Left Tilt	RMC 12.2kbps	4183	836.6	-0.62	0.088	22.30	22.25	0.089	1.6
Right Cheek	RMC 12.2kbps	4183	836.6	0.51	0.164	22.30	22.25	0.166	1.6
Right Tilt	RMC 12.2kbps	4183	836.6	-0.42	0.080	22.30	22.25	0.081	1.6
Body back	RMC 12.2kbps	4183	836.6	0.23	0.322	22.30	22.25	0.326	1.6
Body front	RMC 12.2kbps	4183	836.6	-0.35	0.308	22.30	22.25	0.312	1.6
Edge 2(Right)	RMC 12.2kbps	4183	836.6	0.62	0.243	22.30	22.25	0.246	1.6
Edge 3(Bottom)	RMC 12.2kbps	4183	836.6	-0.67	0.300	22.30	22.25	0.303	1.6
Edge 4(Left)	RMC 12.2kbps	4183	836.6	-0.59	0.098	22.30	22.25	0.099	1.6

Note:

- When the 1-g Reported SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back, body front and 4 Edges is 10mm of all above table.

SAR MEASUREMENT												
Depth of Liquid (cm):>15						Relative Humidity (%): 56.2						
Product: Smart Phone												
Test Mode: LTE Band 7												
BM MHz	MOD	Position	Test Mode		Ch.	Freq. (MHz)	Power Drift (<±5%)	SAR (1g) (W/kg)	Max. Tuneup Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)
			UL RB Allocation	UL RB START								
20	QPSK	Left Cheek	1	0	21100	2535	0.48	0.088	24.40	23.77	0.102	1.6
		Left Tilt	1	0	21100	2535	-0.62	0.059	24.40	23.77	0.068	1.6
		Right Cheek	1	0	21100	2535	0.36	0.051	24.40	23.77	0.059	1.6
		Right Tilt	1	0	21100	2535	-0.65	0.090	24.40	23.77	0.104	1.6
		Body back	1	0	21100	2535	0.69	0.178	24.40	23.77	0.206	1.6
		Body front	1	0	21100	2535	-0.57	0.161	24.40	23.77	0.186	1.6
		Edge 2(Right)	1	0	21100	2535	0.52	0.019	24.40	23.77	0.022	1.6
		Edge 3(Bottom)	1	0	21100	2535	-0.38	0.229	24.40	23.77	0.265	1.6
		Edge 4(Left)	1	0	21100	2535	-0.34	0.200	24.40	23.77	0.231	1.6

Note:

- When the 1-g Reported SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back, body front and 4 Edges is 10mm of all above table.

SAR MEASUREMENT												
Depth of Liquid (cm):>15						Relative Humidity (%): 56.2						
Product: Smart Phone												
Test Mode: LTE Band 38												
BM MHz	MOD	Position	Test Mode		Ch.	Freq. (MHz)	Power Drift (<±5%)	SAR (1g) (W/kg)	Max. Tuneup Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)
			UL RB Allocation	UL RB START								
20	QPSK	Left Cheek	1	0	38000	2595	-0.36	0.055	24.40	23.97	0.061	1.6
		Left Tilt	1	0	38000	2595	0.28	0.043	24.40	23.97	0.047	1.6
		Right Cheek	1	0	38000	2595	-0.35	0.033	24.40	23.97	0.036	1.6
		Right Tilt	1	0	38000	2595	0.42	0.064	24.40	23.97	0.071	1.6
		Body back	1	0	38000	2595	-0.54	0.091	24.40	23.97	0.100	1.6
		Body front	1	0	38000	2595	0.23	0.098	24.40	23.97	0.108	1.6
		Edge 2(Right)	1	0	38000	2595	-0.39	0.017	24.40	23.97	0.019	1.6
		Edge 3(Bottom)	1	0	38000	2595	0.51	0.120	24.40	23.97	0.132	1.6
		Edge 4(Left)	1	0	38000	2595	-0.23	0.121	24.40	23.97	0.134	1.6

Note:

- When the 1-g Reported SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back, body front and 4 Edges is 10mm of all above table.

SAR MEASUREMENT												
Depth of Liquid (cm):>15						Relative Humidity (%): 45.3						
Product: Smart Phone												
Test Mode: LTE Band 40												
BW MHz	MOD	Position	Test Mode		Ch.	Freq. (MHz)	Power Drift (<±5%)	SAR (1g) (W/kg)	Max. Tuneup Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)
			UL RB Allocation	UL RB START								
20	QPSK	Left Cheek	1	0	39150	2350	0.15	0.039	24.40	22.76	0.057	1.6
		Left Tilt	1	0	39150	2350	-0.32	0.023	24.40	22.76	0.034	1.6
		Right Cheek	1	0	39150	2350	-0.26	0.023	24.40	22.76	0.034	1.6
		Right Tilt	1	0	39150	2350	-0.38	0.029	24.40	22.76	0.042	1.6
		Body back	1	0	39150	2350	0.52	0.053	24.40	22.76	0.077	1.6
		Body front	1	0	39150	2350	-0.47	0.064	24.40	22.76	0.093	1.6
		Edge 2(Right)	1	0	39150	2350	0.26	0.007	24.40	22.76	0.010	1.6
		Edge 3(Bottom)	1	0	39150	2350	-0.39	0.082	24.40	22.76	0.120	1.6
		Edge 4(Left)	1	0	39150	2350	0.33	0.089	24.40	22.76	0.130	1.6

Note:

- When the 1-g Reported SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back, body front and 4 Edges is 10mm of all above table

SAR MEASUREMENT												
Depth of Liquid (cm):>15						Relative Humidity (%):56.2						
Product: Smart Phone												
Test Mode: LTE Band 41												
BW MHz	MOD	Position	Test Mode		Ch.	Freq. (MHz)	Power Drift (<±5%)	SAR (1g) (W/kg)	Max. Tuneup Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)
			UL RB Allocation	UL RB START								
20	QPSK	Left Cheek	1	0	40740	2605	-0.54	0.060	23.90	22.74	0.078	1.6
		Left Tilt	1	0	40740	2605	0.52	0.047	23.90	22.74	0.061	1.6
		Right Cheek	1	0	40740	2605	-0.46	0.046	23.90	22.74	0.060	1.6
		Right Tilt	1	0	40740	2605	-0.39	0.074	23.90	22.74	0.097	1.6
		Body back	1	0	40740	2605	0.62	0.090	23.90	22.74	0.118	1.6
		Body front	1	0	40740	2605	-0.52	0.084	23.90	22.74	0.110	1.6
		Edge 2(Right)	1	0	40740	2605	-0.58	0.022	23.90	22.74	0.029	1.6
		Edge 3(Bottom)	1	0	40740	2605	0.67	0.162	23.90	22.74	0.212	1.6
		Edge 4(Left)	1	0	40740	2605	-0.51	0.137	23.90	22.74	0.179	1.6

Note:

- When the 1-g Reported SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. Refer to KDB 447498.
- The test separation for body back, body front and 4 Edges is 10mm of all above table

SAR MEASUREMENT									
Depth of Liquid (cm):>15					Relative Humidity (%): 51.7				
Product: Smart Phone									
Test Mode:802.11b									
Position	Mode	Ch.	Fr. (MHz)	Power Drift (<±5%)	SAR (1g) (W/kg)	Max. Tune-up Power (dBm)	Meas. output Power (dBm)	Scaled SAR (W/Kg)	Limit (W/kg)
Left Cheek	DTS	6	2437	-0.86	0.297	12.10	11.96	0.307	1.6
Left Tilt	DTS	6	2437	0.65	0.269	12.10	11.96	0.278	1.6
Right Cheek	DTS	6	2437	-0.74	0.154	12.10	11.96	0.159	1.6
Right Tilt	DTS	6	2437	0.59	0.145	12.10	11.96	0.150	1.6
Body back	DTS	6	2437	-0.62	0.243	12.10	11.96	0.251	1.6
Body front	DTS	6	2437	0.66	0.203	12.10	11.96	0.210	1.6
Edge 1 (Top)	DTS	6	2437	-0.84	0.183	12.10	11.96	0.189	1.6
Edge 2(Right)	DTS	6	2437	-0.75	0.214	12.10	11.96	0.221	1.6
Edge 4(Left)	DTS	6	2437	0.83	0.037	12.10	11.96	0.038	1.6

Note:

- According to KDB248227, SAR is not required for 802.11n HT20/HT40 channels when the maximum average output power is less than 1/4 dB higher than that measured on the corresponding 802.11a/b channels.
- All of above "DTS" means data transmitters.
- The test separation for body back, body front and 4 Edges is 10mm of all above table.

Simultaneous Multi-band Transmission Evaluation:
Application Simultaneous Transmission information:

NO	Simultaneous state	Portable Handset		
		Head	Body-worn	Hotspot
1	GSM(voice)+ WLAN 2.4GHz (data)	Yes	Yes	-
2	GSM(voice)+ Bluetooth(data)	-	Yes	-
3	GSM (Data) + WLAN 2.4GHz (data)	-	Yes	Yes
4	GSM (Data) + Bluetooth(data)	-	Yes	Yes
5	WCDMA+ WLAN 2.4GHz (data)	Yes	Yes	Yes
6	WCDMA+ Bluetooth(data)	-	Yes	Yes
7	LTE + WLAN 2.4GHz (data)	Yes	Yes	Yes
8	LTE + Bluetooth(data)	--	Yes	Yes

NOTE:

1. WIFI and BT share the same antenna, and cannot transmit simultaneously.
2. Simultaneous with every transmitter must be the same test position.
3. KDB 447498 D01, BT SAR is excluded as below table.
4. KDB 447498 D01, for handsets the test separation distance is determined by the smallest distance between the outer surface of the device and the user; which is 0mm for head SAR and 10mm for body-worn SAR.
5. According to KDB 447498 D01 4.3.1, Standalone SAR test exclusion is as follow:
For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR³⁰, where
 - f(GHz) is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation³¹
 - The result is rounded to one decimal place for comparison
 - The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below
The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.
6. If the test separation distance is < 5 mm, 5mm is used for excluded SAR calculation.
7. According to KDB 447498 D01 4.3.2, simultaneous transmission SAR test exclusion is as follow:
 - (1) Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna.
 - (2) Any transmitters and antennas should be considered when calculating simultaneous mode.
 - (3) For mobile phone and PC, it's the sum of all transmitters and antennas at the same mode with same position in each applicable exposure condition
 - (4) When the standalone SAR test exclusion of section 4.3.2 is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to the following to det
$$(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})/x}] \text{ W/kg}$$
for test separation distances ≤ 50 mm;
where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.

8. When the sum of SAR is larger than the limit, SAR test exclusion is determined by the SAR to peak location separation ratio. The simultaneous transmitting antennas in each operating mode and exposure condition combination must be considered one pair at a time to determine the SAR to peak location separation ratio to qualify for test exclusion. The ratio is determined by $(SAR1 + SAR2)1.5/R_i$, rounded to two decimal digits, and must be ≤ 0.04 for all antenna pairs in the configuration to qualify for 1-g SAR test exclusion.

Estimated SAR		Max Power including Tune-up Tolerance		Separation Distance (mm)	Estimated SAR (W/kg)
		dBm	mW		
BT	Head	3	1.995	0	0.082
	Body	3	1.995	10	0.041

Sum of the SAR for GSM 850 & Wi-Fi & BT:

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario			Σ1-g SAR (W/Kg)	SPLSR (Yes/No)
		GSM 850	Wi-Fi DTS Band	Bluetooth		
Head (voice)	Left Touch	0.252	0.307		0.559	No
	Left Tilt	0.162	0.278		0.440	No
	Right Touch	0.322	0.159		0.481	No
	Right Tilt	0.177	0.150		0.327	No
Body-worn (voice)	Rear	0.442	0.251		0.693	No
		0.442		0.041	0.483	No
	Front	0.422	0.210		0.632	No
		0.422		0.041	0.463	No
Body-worn (Data)	Rear	0.760		0.041	0.801	No
		0.760	0.251		1.011	No
	Front	0.695		0.041	0.736	No
		0.695	0.210		0.905	No
Body-worn (Hotspot)	Edge 1	/	0.189		0.189	No
	Edge 2	0.660	0.221		0.881	No
	Edge 3	0.633	/		0.633	No
	Edge 4	0.281	0.038		0.319	No
	Edge 1	/		0.041	0.041	No
	Edge 2	0.660		0.041	0.701	No
	Edge 3	0.633		0.041	0.674	No
	Edge 4	0.281		0.041	0.322	No

Note:

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is “The SAR to Peak Location Separation Ratio “

Sum of the SAR for GSM 1900 & Wi-Fi & BT:

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario			Σ1-g SAR (W/Kg)	SPLSR (Yes/No)
		PCS 1900	Wi-Fi DTS Band	Bluetooth		
Head (voice)	Left Touch	0.155	0.307		0.462	No
	Left Tilt	0.059	0.278		0.337	No
	Right Touch	0.059	0.159		0.218	No
	Right Tilt	0.064	0.150		0.214	No
Body-worn (voice)	Rear	0.189	0.251		0.440	No
		0.189		0.041	0.230	No
	Front	0.180	0.210		0.390	No
		0.180		0.041	0.221	No
Body-worn (Data)	Rear	0.299		0.041	0.340	No
		0.299	0.251		0.550	No
	Front	0.273		0.041	0.314	No
		0.273	0.210		0.483	No
Body-worn (Hotspot)	Edge 1	/	0.189		0.189	No
	Edge 2	0.020	0.221		0.241	No
	Edge 3	0.399	/		0.399	No
	Edge 4	0.199	0.038		0.237	No
	Edge 1	/		0.041	0.041	No
	Edge 2	0.020		0.041	0.061	No
	Edge 3	0.399		0.041	0.440	No
	Edge 4	0.199		0.041	0.240	No

Note:

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is "The SAR to Peak Location Separation Ratio "

Sum of the SAR for WCDMA Band II & Wi-Fi & BT:

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario			Σ1-g SAR (W/Kg)	SPLSR (Yes/No)
		WCDMA Band II	Wi-Fi DTS Band	Bluetooth		
Head	Left Touch	0.222	0.307		0.529	No
	Left Tilt	0.104	0.278		0.382	No
	Right Touch	0.118	0.159		0.277	No
	Right Tilt	0.094	0.150		0.244	No
Body-worn	Rear	0.299	0.251		0.550	No
	Front	0.285	0.210		0.495	No
	Edge 1	/	0.189		0.189	No
	Edge 2	0.023	0.221		0.244	No
	Edge 3	0.423	/		0.423	No
	Edge 4	0.194	0.038		0.232	No
	Rear	0.299		0.041	0.340	No
	Front	0.285		0.041	0.326	No
	Edge 1	/		0.041	0.041	No
	Edge 2	0.023		0.041	0.064	No
	Edge 3	0.423		0.041	0.464	No
	Edge 4	0.194		0.041	0.235	No

Note:

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is "The SAR to Peak Location Separation Ratio "

Sum of the SAR for WCDMA Band V & Wi-Fi & BT:

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario			Σ1-g SAR (W/Kg)	SPLSR (Yes/No)
		WCDMA Band V	Wi-Fi DTS Band	Bluetooth		
Head	Left Touch	0.162	0.307		0.469	No
	Left Tilt	0.089	0.278		0.367	No
	Right Touch	0.166	0.159		0.325	No
	Right Tilt	0.081	0.150		0.231	No
Body-worn	Rear	0.326	0.251		0.577	No
	Front	0.312	0.210		0.522	No
	Edge 1	/	0.189		0.189	No
	Edge 2	0.246	0.221		0.467	No
	Edge 3	0.303	/		0.303	No
	Edge 4	0.099	0.038		0.137	No
	Rear	0.326		0.041	0.367	No
	Front	0.312		0.041	0.353	No
	Edge 1	/		0.041	0.041	No
	Edge 2	0.246		0.041	0.287	No
	Edge 3	0.303		0.041	0.344	No
	Edge 4	0.099		0.041	0.140	No

Note:

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is "The SAR to Peak Location Separation Ratio "

Sum of the SAR for LTE Band 7 & Wi-Fi & BT:

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario			Σ1-g SAR (W/Kg)	SPLSR (Yes/No)
		LTE Band 2	Wi-Fi DTS Band	Bluetooth		
Head	Left Touch	0.102	0.307		0.409	No
	Left Tilt	0.068	0.278		0.346	No
	Right Touch	0.059	0.159		0.218	No
	Right Tilt	0.104	0.150		0.254	No
Body-worn	Rear	0.206	0.251		0.457	No
	Front	0.186	0.210		0.396	No
	Edge 1	/	0.189		0.189	No
	Edge 2	0.022	0.221		0.243	No
	Edge 3	0.265	/		0.265	No
	Edge 4	0.231	0.038		0.269	No
	Rear	0.206		0.041	0.247	No
	Front	0.186		0.041	0.227	No
	Edge 1	/		0.041	0.041	No
	Edge 2	0.022		0.041	0.063	No
	Edge 3	0.265		0.041	0.306	No
	Edge 4	0.231		0.041	0.272	No

Note:

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is "The SAR to Peak Location Separation Ratio "

Sum of the SAR for LTE Band 38 & Wi-Fi & BT:

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario			Σ1-g SAR (W/Kg)	SPLSR (Yes/No)
		LTE Band 5	Wi-Fi DTS Band	Bluetooth		
Head	Left Touch	0.061	0.307		0.368	No
	Left Tilt	0.047	0.278		0.325	No
	Right Touch	0.036	0.159		0.195	No
	Right Tilt	0.071	0.150		0.221	No
Body-worn	Rear	0.100	0.251		0.351	No
	Front	0.108	0.210		0.318	No
	Edge 1	/	0.189		0.189	No
	Edge 2	0.019	0.221		0.240	No
	Edge 3	0.132	/		0.132	No
	Edge 4	0.134	0.038		0.172	No
	Rear	0.100		0.041	0.141	No
	Front	0.108		0.041	0.149	No
	Edge 1	/		0.041	0.041	No
	Edge 2	0.019		0.041	0.060	No
	Edge 3	0.132		0.041	0.173	No
	Edge 4	0.134		0.041	0.175	No

Note:

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is "The SAR to Peak Location Separation Ratio "

Sum of the SAR for LTE Band 40 & Wi-Fi & BT:

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario			Σ1-g SAR (W/Kg)	SPLSR (Yes/No)
		LTE Band 7	Wi-Fi DTS Band	Bluetooth		
Head	Left Touch	0.057	0.307		0.364	No
	Left Tilt	0.034	0.278		0.312	No
	Right Touch	0.034	0.159		0.193	No
	Right Tilt	0.042	0.150		0.192	No
Body-worn	Rear	0.077	0.251		0.328	No
	Front	0.093	0.210		0.303	No
	Edge 1	/	0.189		0.189	No
	Edge 2	0.010	0.221		0.231	No
	Edge 3	0.120	/		0.120	No
	Edge 4	0.130	0.038		0.168	No
	Rear	0.077		0.041	0.118	No
	Front	0.093		0.041	0.134	No
	Edge 1	/		0.041	0.041	No
	Edge 2	0.010		0.041	0.051	No
	Edge 3	0.120		0.041	0.161	No
	Edge 4	0.130		0.041	0.171	No

Note:

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is "The SAR to Peak Location Separation Ratio "

Sum of the SAR for LTE Band 41 &Wi-Fi & BT:

RF Exposure Conditions	Test Position	Simultaneous Transmission Scenario			Σ1-g SAR (W/Kg)	SPLSR (Yes/No)
		LTE Band 41	Wi-Fi DTS Band	Bluetooth		
Head	Left Touch	0.078	0.307		0.385	No
	Left Tilt	0.061	0.278		0.339	No
	Right Touch	0.060	0.159		0.219	No
	Right Tilt	0.097	0.150		0.247	No
Body-worn	Rear	0.118	0.251		0.369	No
	Front	0.110	0.210		0.320	No
	Edge 1	/	0.189		0.189	No
	Edge 2	0.029	0.221		0.250	No
	Edge 3	0.212	/		0.212	No
	Edge 4	0.179	0.038		0.217	No
	Rear	0.118		0.041	0.159	No
	Front	0.110		0.041	0.151	No
	Edge 1	/		0.041	0.041	No
	Edge 2	0.029		0.041	0.070	No
	Edge 3	0.212		0.041	0.253	No
	Edge 4	0.179		0.041	0.220	No

Note:

- According to KDB 447498 D01 General RF Exposure Guidance, when the simultaneous transmission SAR is less than 1.6 W/Kg, SPLSR assessment is not required.
- SPLSR mean is “The SAR to Peak Location Separation Ratio “

APPENDIX A. SAR SYSTEM CHECK DATA

Test Laboratory: AGC Lab

Date: Apr. 23,2020

System Check Head 835 MHz

DUT: Dipole 835 MHz Type: SID 835

Communication System CW; Communication System Band: D835 (835.0 MHz); Duty Cycle: 1:1; Conv.F=5.05

Frequency: 835 MHz; Medium parameters used: $f = 835$ MHz; $\sigma = 0.89$ mho/m; $\epsilon_r = 40.92$; $\rho = 1000$ kg/m³ ;

Phantom section: Flat Section; Input Power=18dBm


Ambient temperature (°C):21.6, Liquid temperature (°C): 21.3

SATIMO Configuration:

- Probe: SSE5; Calibrated: Jun. 04,2019; Serial No.: SN 22/16 EP315
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: SAM twin phantom
- Measurement SW: OpenSAR V4_02_35

Configuration/System Check 835MHz Head/Area Scan: Measurement grid: dx=10mm, dy=10mm



Configuration/System Check 835MHz Head/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm



Maximum location: X=8.00, Y=-1.00

SAR Peak: 0.86 W/kg

SAR 10g (W/Kg)	0.383954
SAR 1g (W/Kg)	0.593985



Test Laboratory: AGC Lab
System Check Head 1900MHz

Date: Apr. 15,2020

DUT: Dipole 1900 MHz; Type: SID 1900

Communication System: CW; Communication System Band: D1900 (1900.0 MHz); Duty Cycle:1:1; Conv.F=4.48
Frequency: 1900 MHz; Medium parameters used: $f = 1850$ MHz; $\sigma = 1.37$ mho/m; $\epsilon_r = 38.61$; $\rho = 1000$ kg/m³ ;
Phantom section: Flat Section; Input Power=18dBm
Ambient temperature (°C):21.3, Liquid temperature (°C): 21.0


SATIMO Configuration:

Probe: SSE5; Calibrated: Jun. 04,2019; Serial No.: SN 22/16 EP315

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: SAM twin phantom
- Measurement SW: OpenSAR V4_02_35



Configuration/System Check 1900MHz Head/Area Scan: Measurement grid: dx=8mm, dy=8mm

Configuration/System Check 1900MHz Head/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm



Maximum location: X=7.00, Y=0.00
SAR Peak: 4.68 W/kg

SAR 10g (W/Kg)	1.381844
SAR 1g (W/Kg)	2.758321



Test Laboratory: AGC Lab
System Check Head 2300 MHz

Date: Apr. 13,2020

DUT: Dipole 2300 MHz Type: SID 2300


Communication System CW; Communication System Band: D2300 (2300.0 MHz); Duty Cycle: 1:1; Conv.F=4.58
Frequency: 2300 MHz; Medium parameters used: $f = 2300$ MHz; $\sigma = 1.63$ mho/m; $\epsilon r = 39.58$; $\rho = 1000$ kg/m³ ;
Phantom section: Flat Section; Input Power=18dBm
Ambient temperature (°C):21.4, Liquid temperature (°C): 21.2

SATIMO Configuration

- Probe: SSE5; Calibrated: Jun. 04,2019; Serial No.: SN 22/16 EP315
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: SAM twin phantom
- Measurement SW: OpenSAR V4_02_35

Configuration/System Check 2300MHz Head/Area Scan: Measurement grid: dx=8mm, dy=8mm



Configuration/System Check 2300MHz Head/Zoom Scan: Measurement grid: dx=5mm,dy=5mm, dz=5mm



Maximum location: X=0.00, Y=0.00

SAR Peak: 5.93 W/kg

SAR 10g (W/Kg)	1.492645
SAR 1g (W/Kg)	3.223674



Test Laboratory: AGC Lab
System Check Head 2450 MHz

Date: Apr. 26,2020

DUT: Dipole 2450 MHz Type: SID 2450


Communication System CW; Communication System Band: D2450 (2450.0 MHz); Duty Cycle: 1:1; Conv.F=4.12
Frequency: 2450 MHz; Medium parameters used: $f = 2450$ MHz; $\sigma = 1.82$ mho/m; $\epsilon_r = 41.61$; $\rho = 1000$ kg/m³ ;
Phantom section: Flat Section; Input Power=18dBm
Ambient temperature (°C):21.5, Liquid temperature (°C): 21.3

SATIMO Configuration

- Probe: SSE5; Calibrated: Jun. 04,2019; Serial No.: SN 22/16 EP315
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: SAM twin phantom
- Measurement SW: OpenSAR V4_02_35



Configuration/System Check 2450MHz Head/Area Scan: Measurement grid: dx=8mm, dy=8mm

Configuration/System Check 2450MHz Head/Zoom Scan: Measurement grid: dx=5mm,dy=5mm, dz=5mm



Maximum location: X=0.00, Y=0.00
SAR Peak: 5.74 W/kg

SAR 10g (W/Kg)	1.421965
SAR 1g (W/Kg)	3.138234



Test Laboratory: AGC Lab
System Check Head 2600MHz

Date: Apr. 17,2020

DUT: Dipole 2600 MHz; Type: SID 2600


Communication System: CW; Communication System Band: D2600 (2600.0 MHz); Duty Cycle: 1:1; Conv.F=3.77
Frequency:2600 MHz; Medium parameters used: $f = 2600$ MHz; $\sigma = 1.89$ mho/m; $\epsilon_r = 38.15$; $\rho = 1000$ kg/m³ ;
Phantom section: Flat Section; Input Power=18dBm
Ambient temperature (°C): 21.4, Liquid temperature (°C): 21.2

SATIMO Configuration:

- Probe: SSE5; Calibrated: Jun. 04,2019; Serial No.: SN 22/16 EP315
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: SAM twin phantom
- Measurement SW: OpenSAR V4_02_35

Configuration/System Check 2600 Head/Area Scan: Measurement grid: dx=8mm,dy=8mm



Configuration/System Check 2600 Head/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm



Maximum location: X=0.00, Y=0.00

SAR Peak: 5.81 W/kg

SAR 10g (W/Kg)	1.461816
SAR 1g (W/Kg)	3.319752



Test Laboratory: AGC Lab
System Check Head 835 MHz

Date: Apr. 23,2020

DUT: Dipole 835 MHz Type: SID 835


Communication System CW; Communication System Band: D835 (835.0 MHz); Duty Cycle: 1:1; Conv.F=5.05
Frequency: 835 MHz; Medium parameters used: $f = 835$ MHz; $\sigma = 0.89$ mho/m; $\epsilon_r = 40.92$; $\rho = 1000$ kg/m³ ;
Phantom section: Flat Section; Input Power=18dBm
Ambient temperature (°C):21.6, Liquid temperature (°C): 21.3

SATIMO Configuration:

- Probe: SSE5; Calibrated: Jun. 04,2019; Serial No.: SN 22/16 EP315
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: ELLI39 Phantom
- Measurement SW: OpenSAR V4_02_35

Configuration/System Check 835MHz Head/Area Scan: Measurement grid: dx=8mm, dy=8mm



Configuration/System Check 835MHz Head/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm



Maximum location: X=-3.00, Y=5.00

SAR Peak: 0.93 W/kg

SAR 10g (W/Kg)	0.395974
SAR 1g (W/Kg)	0.634952



Test Laboratory: AGC Lab
System Check Head 1900MHz

Date: Apr. 15,2020

DUT: Dipole 1900 MHz; Type: SID 1900

Communication System: CW; Communication System Band: D1900 (1900.0 MHz); Duty Cycle:1:1; Conv.F=4.48
Frequency: 1900 MHz; Medium parameters used: $f = 1850$ MHz; $\sigma = 1.37$ mho/m; $\epsilon_r = 38.61$; $\rho = 1000$ kg/m³ ;
Phantom section: Flat Section; Input Power=18dBm
Ambient temperature (°C):21.3, Liquid temperature (°C): 21.0


SATIMO Configuration:

Probe: SSE5; Calibrated: Jun. 04,2019; Serial No.: SN 22/16 EP315

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Phantom: ELLI39 Phantom
- Measurement SW: OpenSAR V4_02_35

Configuration/System Check 1900MHz Head/Area Scan: Measurement grid: dx=8mm, dy=8mm

Configuration/System Check 1900MHz Head/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm



Maximum location: X=0.00, Y=0.00
SAR Peak: 5.05 W/kg

SAR 10g (W/Kg)	1.215421
SAR 1g (W/Kg)	2.652345

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	5.1128	2.7823	1.1745	0.5164	0.2238	0.1084	0.0436

