



## FCC CERTIFICATION TEST REPORT

<b>Applicant</b>	:	Guangdong ERSE Acoustics Inc.
<b>Address of Applicant</b>	:	No.6 LIUHUA XIHENGSA N STREET, XIAKOU, DONGCHENG DISTRICT, DONGGUAN CITY, GUANGDONG, CHINA
<b>Manufacturer</b>	:	Guangdong ERSE Acoustics Inc.
<b>Address of Manufacturer</b>	:	No.6 LIUHUA XIHENGSA N STREET, XIAKOU, DONGCHENG DISTRICT, DONGGUAN CITY, GUANGDONG, CHINA
<b>Equipment under Test</b>	:	Rock Speaker
<b>Model No.</b>	:	ERS-1002, SPR501C02-SL-PR, RS400T01-SL-PR, ERS-1001, ERS-1003-XX, ERS-1004-XX, ERS-1005-XX, ERS-1006-XX, ERS-1007-XX, ERS-1008-XX, ERS-1009-XX, ERS-1010-XX, NRS-1011-XX, NRS-1012-XX, NRS-1013-XX, NRS-1014-XX, NRS-1015-XX, NRS-1016-XX, NRS-1017-XX, NRS-1018-XX, NRS-1019-XX, NRS-1020-XX, VRS-1021-XX, VRS-1022-XX, VRS-1023-XX, VRS-1024-XX, VRS-1025-XX, VRS-1026-XX, VRS-1027-XX, VRS-1028-XX, VRS-1029-XX, VRS-1030-XX, ERS-2000, ERS-2001-XX, ERS-2002-XX, ERS-2003-XX, ERS-2004-XX, ERS-2005-XX, ERS-2006-XX, ERS-2007-XX, ERS-2008-XX, ERS-2009-XX, ERS-2010-XX, NRS-2011-XX, NRS-2012-XX, NRS-2013-XX, NRS-2014-XX, NRS-2015-XX, NRS-2016-XX, NRS-2017-XX, NRS-2018-XX, NRS-2019-XX, NRS-2020-XX, VRS-1031-XX, VRS-1032-XX, VRS-1033-XX, VRS-1034-XX, VRS-1035-XX, VRS-1036-XX, VRS-1037-XX, VRS-1038-XX, VRS-1039-XX, VRS-1040-XX
<b>Trade Mark</b>		Emerson, NAXA, VICTOR
<b>FCC ID</b>	:	2AWFXSPR506
<b>Test Standard(s)</b>	:	FCC Rules and Regulations Part 15 Subpart C, ANSI C63.10:2013
<b>Report No.</b>	:	DDT-RE23122113-2E01
<b>Issue Date</b>	:	2024/01/30
<b>Issue By</b>	:	Guangdong Dongdian Testing Service Co., Ltd.
<b>Address of Laboratory</b>	:	Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

# REPORT

## Table of Contents

	Test report declares.....	4
1.	Summary of Test Results.....	8
2.	General Test Information .....	9
2.1.	Description of EUT.....	9
2.2.	Accessories of EUT .....	11
2.3.	Assistant equipment used for test.....	11
2.4.	Block diagram of EUT configuration for test.....	11
2.5.	Deviations of test standard .....	12
2.6.	Test environment conditions .....	12
2.7.	Test laboratory.....	12
2.8.	Measurement uncertainty .....	13
3.	Equipment Used During Conductive Test.....	14
4.	20 dB Bandwidth.....	15
4.1.	Block diagram of test setup.....	15
4.2.	Limits .....	15
4.3.	Test procedure.....	15
4.4.	Test result .....	16
4.5.	Test graphs.....	17
5.	99% Bandwidth.....	20
5.1.	Block diagram of test setup.....	20
5.2.	Limits .....	20
5.3.	Test procedure.....	20
5.4.	Test result .....	21
5.5.	Test graphs.....	22
6.	Maximum Peak Output Power .....	25
6.1.	Block diagram of test setup.....	25
6.2.	Limits .....	25
6.3.	Test procedure.....	25
6.4.	Test result .....	26
6.5.	Test graphs.....	27
7.	Carrier Frequency Separation.....	30
7.1.	Block diagram of test setup.....	30
7.2.	Limits .....	30
7.3.	Test procedure.....	30
7.4.	Test result .....	31
7.5.	Test graphs.....	32
8.	Dwell Time .....	33

8.1.	Block diagram of test setup.....	33
8.2.	Limits .....	33
8.3.	Test procedure.....	33
8.4.	Test result.....	34
8.5.	Test graphs.....	35
9.	Number of Hopping Channel .....	41
9.1.	Block diagram of test setup.....	41
9.2.	Limits .....	41
9.3.	Test procedure.....	41
9.4.	Test result.....	42
9.5.	Test graphs.....	43
10.	Band Edge Compliance (Conducted Method).....	44
10.1.	Block diagram of test setup.....	44
10.2.	Limit .....	44
10.3.	Test procedure.....	44
10.4.	Test result.....	45
10.5.	Test graphs.....	46
11.	RF Conducted Spurious Emissions .....	50
11.1.	Block diagram of test setup.....	50
11.2.	Limits .....	50
11.3.	Test procedure.....	50
11.4.	Test result.....	51
11.5.	Test graphs.....	52
12.	Duty cycle .....	61
12.1.	Block diagram of test setup.....	61
12.2.	Limit .....	61
12.3.	Test procedure.....	61
12.4.	Test result.....	62
12.5.	Test graphs.....	63
13.	Radiated Emission.....	66
13.1.	Test equipment.....	66
13.2.	Block diagram of test setup.....	67
13.3.	Limit.....	69
13.4.	Test procedure.....	70
13.5.	Test result.....	71
14.	Band Edge Compliance (Radiated Method) .....	80
14.1.	Test equipment.....	80
14.2.	Block diagram of test setup.....	80

14.3.	Limit.....	80
14.4.	Test procedure.....	80
14.5.	Test result.....	80
15.	Power Line Conducted Emission.....	94
15.1.	Test equipment.....	94
15.2.	Block diagram of test setup.....	94
15.3.	Power line conducted emission limits.....	94
15.4.	Test procedure.....	94
15.5.	Test result.....	95
16.	Antenna Requirements.....	98
16.1.	Limit.....	98
16.2.	Result.....	98
17.	Test Setup Photograph.....	99
18.	Photos of the EUT.....	102

## Test Report Declare

<b>Applicant</b>	:	Guangdong ERSE Acoustics Inc.
<b>Address of Applicant</b>	:	No.6 LIUHUA XIHENGSA N STREET, XIAKOU, DONGCHENG DISTRICT, DONGGUAN CITY, GUANGDONG, CHINA
<b>Equipment under Test</b>	:	Rock Speaker
<b>Model No.</b>	:	ERS-1002, SPR501C02-SL-PR,RS400T01-SL-PR, ERS-1001, ERS-1003-XX, ERS-1004-XX, ERS-1005-XX, ERS-1006-XX, ERS-1007-XX, ERS-1008-XX, ERS-1009-XX, ERS-1010-XX, NRS-1011-XX, NRS-1012-XX, NRS-1013-XX, NRS-1014-XX, NRS-1015-XX, NRS-1016-XX, NRS-1017-XX, NRS-1018-XX, NRS-1019-XX, NRS-1020-XX, VRS-1021-XX, VRS-1022-XX, VRS-1023-XX, VRS-1024-XX, VRS-1025-XX, VRS-1026-XX, VRS-1027-XX, VRS-1028-XX, VRS-1029-XX, VRS-1030-XX, ERS-2000, ERS-2001-XX, ERS-2002-XX, ERS-2003-XX, ERS-2004-XX, ERS-2005-XX, ERS-2006-XX, ERS-2007-XX, ERS-2008-XX, ERS-2009-XX, ERS-2010-XX, NRS-2011-XX, NRS-2012-XX, NRS-2013-XX, NRS-2014-XX, NRS-2015-XX, NRS-2016-XX, NRS-2017-XX, NRS-2018-XX, NRS-2019-XX, NRS-2020-XX, VRS-1031-XX, VRS-1032-XX, VRS-1033-XX, VRS-1034-XX, VRS-1035-XX, VRS-1036-XX, VRS-1037-XX, VRS-1038-XX, VRS-1039-XX, VRS-1040-XX
<b>Trade Mark</b>		Emerson, NAXA, VICTOR
<b>Manufacturer</b>	:	Guangdong ERSE Acoustics Inc.
<b>Address of Manufacturer</b>	:	No.6 LIUHUA XIHENGSA N STREET, XIAKOU, DONGCHENG DISTRICT, DONGGUAN CITY, GUANGDONG, CHINA

### Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C

### Test Procedure Used:

ANSI C63.10:2013

### We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

**After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above standards.**

<b>Report No.:</b>	DDT-RE23122113-2E01		
<b>Date of Receipt:</b>	2024/01/08	<b>Date of Test:</b>	2024/01/08~2024/01/30

**Prepared By:**

**Approved By:**

*Ziqin Chen*

**Ziqin Chen/Engineer**



**Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

### Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2024/01/30	

## 1. Summary of Test Results

Description of Test Item	Standard	Result
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1)	Pass
20 dB Bandwidth	FCC Part 15: 15.247(a)(1)	Pass
99% Bandwidth	ANSI C63.10:2013	Pass
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1)	Pass
Number of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii)	Pass
Dwell Time	FCC Part 15: 15.247(a)(1)(iii)	Pass
RF Conducted Spurious Emissions	FCC Part 15: 15.247(d)	Pass
Radiated Emission	FCC Part 15: 15.205 FCC Part 15: 15.209 FCC Part 15: 15.247(d)	Pass
Band Edge Compliance	FCC Part 15: 15.205 FCC Part 15: 15.209 FCC Part 15: 15.247(d)	Pass
Power Line Conducted Emissions	FCC Part 15: 15.207(a)	Pass
Antenna Requirement	FCC Part 15: 15.203	Pass



## 2. General Test Information

### 2.1. Description of EUT

EUT Name	: Rock Speaker
Model Number	: ERS-1002, SPR501C02-SL-PR,RS400T01-SL-PR, ERS-1001, ERS-1003-XX, ERS-1004-XX, ERS-1005-XX, ERS-1006-XX, ERS-1007-XX, ERS-1008-XX, ERS-1009-XX, ERS-1010-XX, NRS-1011-XX, NRS-1012-XX, NRS-1013-XX, NRS-1014-XX, NRS-1015-XX, NRS-1016-XX, NRS-1017-XX, NRS-1018-XX, NRS-1019-XX, NRS-1020-XX, VRS-1021-XX, VRS-1022-XX, VRS-1023-XX, VRS-1024-XX, VRS-1025-XX, VRS-1026-XX, VRS-1027-XX, VRS-1028-XX, VRS-1029-XX, VRS-1030-XX, ERS-2000, ERS-2001-XX, ERS-2002-XX, ERS-2003-XX, ERS-2004-XX, ERS-2005-XX, ERS-2006-XX, ERS-2007-XX, ERS-2008-XX, ERS-2009-XX, ERS-2010-XX, NRS-2011-XX, NRS-2012-XX, NRS-2013-XX, NRS-2014-XX, NRS-2015-XX, NRS-2016-XX, NRS-2017-XX, NRS-2018-XX, NRS-2019-XX, NRS-2020-XX, VRS-1031-XX, VRS-1032-XX, VRS-1033-XX, VRS-1034-XX, VRS-1035-XX, VRS-1036-XX, VRS-1037-XX, VRS-1038-XX, VRS-1039-XX, VRS-1040-XX
Difference of models	: Above models are identical in schematic and structure, only the model number are different, therefore the test performed on the model ERS-1002
EUT Function Description	: Please reference user manual of this device
Power Supply	: DC 5V from external AC Adapter or DC 3.7 V Polymer Li-ion built-in battery
Radio Specification	: Bluetooth V5.0 (BR/EDR)
Operation Frequency	: Bluetooth (BR/EDR): 2402 MHz-2480 MHz
Modulation	: Bluetooth BR/EDR: GFSK, $\pi/4$ -DQPSK, 8DPSK

Note 1: “☑” means to be chosen or applicable; “☐” means don't to be chosen or not applicable; This note applies to entire report.

Note 2: This report only for Bluetooth BR/EDR.

Note 3: Antenna information:

Bluetooth Antenna information	
Antenna Type	: FPC
Antenna Gain(dBi)	: 1.9

Note 4: Channel information:

Bluetooth BR/EDR Channel information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	27	2429	54	2456
1	2403	28	2430	55	2457
2	2404	29	2431	56	2458
3	2405	30	2432	57	2459
4	2406	31	2433	58	2460

5	2407	32	2434	59	2461
6	2408	33	2435	60	2462
7	2409	34	2436	61	2463
8	2410	35	2437	62	2464
9	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

Note 5: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.


## 2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number	Description	Remark
POWER SUPPLY	SHENZHEN PUSHIDA ELECTRONIC TECHNOLOGY CO., LTD	PSD0502000US	INPUT: 100-240V~ 50/60Hz 0.5A Max OUTPUT: DC5.0/2.0A 10.0W	POWER SUPPLY
USB Cable	/	/	/	USB Cable

## 2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	EMC Compliance	SN
Notebook	Lenovo	Ryzen 5 PRO 3500U	N/A	00425-00000-00002-AA135
POWER SUPPLY	SHENZHEN PUSHIDA ELECTRONIC TECHNOLOGY CO., LTD	PSD0502000US	INPUT: 100-240V~ 50/60Hz 0.5A Max OUTPUT: DC5.0/2.0A 10.0W	POWER SUPPLY

## 2.4. Block diagram of EUT configuration for test



Test software: BT\_Tool.exe

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table.

The pathloss of external cable: 0.5 dB (According to the manufacturer's claims)

Tested mode, channel, information			
Mode	Setting Tx Power	Channel	Frequency (MHz)
GFSK hopping on Tx mode	5	CH0 to CH78	2402 to 2480
$\pi/4$ -DQPSK hopping on Tx mode	5	CH0 to CH78	2402 to 2480
8DPSK hopping on Tx mode	5	CH0 to CH78	2402 to 2480
GFSK hopping off Tx mode	5	CH0	2402
	5	CH39	2441
	5	CH78	2480
$\pi/4$ -DQPSK hopping off Tx mode	5	CH0	2402
	5	CH39	2441
	5	CH78	2480

8DPSK hopping off Tx mode	5	CH0	2402
	5	CH39	2441
	5	CH78	2480
Worst-case data rates were: GFSK mode: DH5, $\pi/4$ -DQPSK mode: 2DH5, 8DPSK mode: 3DH5			

## 2.5. Deviations of test standard

No deviation.

## 2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15°C to +35 °C
Humidity range:	20% to 75%
Pressure range:	86 kPa to 106 kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

## 2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: [ddt@dgddt.com](mailto:ddt@dgddt.com).

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

## 2.8. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86 dB (10 MHz ≤ f < 3.6 GHz);
	1.38 dB (3.6 GHz ≤ f < 8 GHz)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB (10 MHz ≤ f < 3.6 GHz);
	1.38 dB (3.6 GHz ≤ f < 8 GHz)
Frequencies Stability	6.7 x 10 <sup>-8</sup> (Antenna couple method)
	5.5 x 10 <sup>-8</sup> (Conducted method)
Conducted spurious emissions	0.86 dB (10 MHz ≤ f < 3.6 GHz);
	1.40 dB (3.6 GHz ≤ f < 8 GHz)
	1.66 dB (8 GHz ≤ f < 26.5 GHz)
Uncertainty for radio frequency (RBW < 20 kHz)	3x10 <sup>-8</sup>
Temperature	0.4 °C
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.70 dB (Antenna Polarize: V)
	4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.10 dB (1 - 6 GHz)
	4.40 dB (6 GHz - 18 GHz)
	3.54 dB (18 GHz - 26 GHz)
	4.30 dB (26 GHz - 40 GHz)
Uncertainty for Power line conduction emission test	3.34dB (150KHz-30MHz)
	3.72dB (9KHz-150KHz)


Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

### 3. Equipment Used During Conductive Test

Equipment	Manufacturer	Model No.	Serial Number	Due Date
☑RF Connected Test (RF Measurement System 3#)				
SIGNAL ANALYZER	R&S	FSV40	101407	2024/07/11
Wideband Radio Communication Tester	R&S	CMW500	117491	2024/04/26
EXG Analog Signal Generator	KEYSIGHT	N5173B	MY62153058	2024/07/11
MXG Vector Signal Generator	Agilent	N5182A	MY48180912	2024/04/22
RF Control Unit	Tonscend	JS0806-2	20C8060230	2024/04/26
TEMP&HUMI Programmable Chamber	ZHIXIANG	ZXGDJS-150L	ZX170110-A	2024/05/14
Test Software	Tonscend	JS1120-3	Ver.3.2.22	N/A

## 4. 20 dB Bandwidth

### 4.1. Block diagram of test setup



### 4.2. Limits

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

### 4.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 6.9.2.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for the 20 dB bandwidth measurement:

RBW:	1% to 5% of the OBW
VBW:	approximately three times RBW
Span:	between 2 times and 5 times the OBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold

- (5) Measure and record the results in the report.


**4.4. Test result**




Test Engineer:	Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	22.9°C,49.0%RH	Test Date:	2024.01.12
Test Power Supply:	DC 3.3V	EUT:	Rock Speaker
Sample Number:	S23122113-03	Model No.:	ERS-1002

Test Mode	Antenna	Frequency [MHz]	20dB EBW[MHz]
DH5	Ant1	2402	0.95
		2441	0.95
		2480	0.95
2DH5	Ant1	2402	1.32
		2441	1.32
		2480	1.32
3DH5	Ant1	2402	1.31
		2441	1.32
		2480	1.31




4.5. Test graphs







### 3DH5\_Ant1\_2402



3DH5 Ant1 2441




3DH5 Ant1 2480



## 5. 99% Bandwidth

### 5.1. Block diagram of test setup



### 5.2. Limits

Just for Report.

### 5.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 6.9.3.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for the 99% bandwidth measurement:
 

RBW:	1% to 5% of the OBW
VBW:	approximately three times RBW
Span:	between 1.5 times and 5.0 times the OBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold
- (5) Measure and record the results in the report.




#### 5.4. Test result

Test Engineer:	Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	22.9°C, 49.0%RH	Test Date:	2024.01.12
Test Power Supply:	DC 3.3V	EUT:	Rock Speaker
Sample Number:	S23122113-03	Model No.:	ERS-1002




Test Mode	Antenna	Frequency [MHz]	OCB [MHz]	FL[MHz]	FH[MHz]
DH5	Ant1	2402	0.836	2401.5624	2402.3986
		2441	0.839	2440.5594	2441.3986
		2480	0.839	2479.5594	2480.3986
2DH5	Ant1	2402	1.169	2401.3976	2402.5664
		2441	1.166	2440.3976	2441.5634
		2480	1.169	2479.3976	2480.5664
3DH5	Ant1	2402	1.187	2401.3856	2402.5724
		2441	1.187	2440.3856	2441.5724
		2480	1.187	2479.3856	2480.5724

5.5. Test graphs






### 3DH5\_Ant1\_2402





## 6. Maximum Peak Output Power

### 6.1. Block diagram of test setup



### 6.2. Limits

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W.

### 6.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 7.8.5.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:
 




RBW:	> 20 dB bandwidth of the emission being measured.
VBW:	VBW $\geq$ RBW.
Span:	Approximately five times the 20 dB bandwidth, centered on a hopping channel.
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold
- (5) Use the marker-to-peak function to set the marker to the peak of the emission and record the results in the report.




#### 6.4. Test result

Test Engineer:	Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	22.9°C, 49.0%RH	Test Date:	2024.01.12
Test Power Supply:	DC 3.3V	EUT:	Rock Speaker
Sample Number:	S23122113-03	Model No.:	ERS-1002


Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power[dBm]	Conducted Limit[dBm]	EIRP[dBm]	EIRP Limit[dBm]	Verdict
DH5	Ant1	2402	-12.91	≤20.97	-12.91	≤36	PASS
		2441	-13.29	≤20.97	-13.29	≤36	PASS
		2480	-13.14	≤20.97	-13.14	≤36	PASS
2DH5	Ant1	2402	-10.48	≤20.97	-10.48	≤36	PASS
		2441	-10.86	≤20.97	-10.86	≤36	PASS
		2480	-10.67	≤20.97	-10.67	≤36	PASS
3DH5	Ant1	2402	-9.80	≤20.97	-9.80	≤36	PASS
		2441	-10.17	≤20.97	-10.17	≤36	PASS
		2480	-10.09	≤20.97	-10.09	≤36	PASS

### 6.5. Test graphs







### 3DH5\_Ant1\_2402



3DH5 Ant1 2441




3DH5 Ant1 2480



## 7. Carrier Frequency Separation

### 7.1. Block diagram of test setup



### 7.2. Limits

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### 7.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 7.8.2.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:
 




RBW:	approximately 30% of the channel spacing
VBW:	VBW $\geq$ RBW.
Span:	Wide enough to capture the peaks of two adjacent channels.
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold
- (5) Use the marker-delta function to determine the separation between the peaks of the adjacent channels and record the results in the report.

**7.4. Test result**

Test Engineer:	Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	22.9°C, 49.0%RH	Test Date:	2024.01.12
Test Power Supply:	DC 3.3V	EUT:	Rock Speaker
Sample Number:	S23122113-03	Model No.:	ERS-1002

Test Mode	Antenna	Frequency [MHz]	Result [MHz]	Limit [MHz]	Verdict
DH5	Ant1	Hop	1.009	≥0.950	PASS
2DH5	Ant1	Hop	0.986	≥0.880	PASS
3DH5	Ant1	Hop	1.006	≥0.880	PASS


7.5. Test graphs





## 8. Dwell Time

### 8.1. Block diagram of test setup



### 8.2. Limits

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### 8.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 7.8.4.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:
 


RBW:	≤ channel spacing and where possible RBW should be set $\gg 1 / T$
VBW:	$VBW \geq RBW$ .
Span:	Zero span, centered on a hopping channel.
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Clear Write.
- (5) The test period:  $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$
- (6) Measure the hopping number and on time of each pulse with spectrum analyzer in zero span set, and calculate dwell time with formula  $\text{Dwell time} = \text{total hops} \times \text{pulse's on time}$ .
- (7) Measure and record the results in the report.


**8.4. Test result**

Test Engineer:	Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	22.9°C, 49.0%RH	Test Date:	2024.01.12
Test Power Supply:	DC 3.3V	EUT:	Rock Speaker
Sample Number:	S23122113-03	Model No.:	ERS-1002



Test Mode	Antenna	Frequency [MHz]	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.370	321	0.119	≤0.4	PASS
DH3	Ant1	Hop	1.640	156	0.256	≤0.4	PASS
DH5	Ant1	Hop	2.880	112	0.323	≤0.4	PASS
2DH1	Ant1	Hop	0.390	317	0.124	≤0.4	PASS
2DH3	Ant1	Hop	1.640	165	0.271	≤0.4	PASS
2DH5	Ant1	Hop	2.890	108	0.312	≤0.4	PASS
3DH1	Ant1	Hop	0.390	318	0.124	≤0.4	PASS
3DH3	Ant1	Hop	1.640	165	0.271	≤0.4	PASS
3DH5	Ant1	Hop	2.890	106	0.306	≤0.4	PASS

8.5. Test graphs








DH5 Ant1 Hop




2DH1 Ant1 Hop





2DH3\_Ant1\_Hop








2DH5 Ant1 Hop




3DH1 Ant1 Hop





3DH3\_Ant1\_Hop






3DH5 Ant1 Hop





## 9. Number of Hopping Channel

### 9.1. Block diagram of test setup



### 9.2. Limits

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

### 9.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 7.8.3.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:

RBW:	RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
VBW:	VBW $\geq$ RBW.
Span:	The frequency band of operation
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold


- (5) Measure the hopping number and record the results in the report.
- (6) Measure and record the results in the report.

**9.4. Test result**

Test Engineer:	Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	22.9°C,49.0%RH	Test Date:	2024.01.12
Test Power Supply:	DC 3.3V	EUT:	Rock Speaker
Sample Number:	S23122113-03	Model No.:	ERS-1002


Test Mode	Antenna	Frequency [MHz]	Result [Num]	Limit [Num]	Verdict
DH5	Ant1	Hop	79	≥15	PASS
2DH5	Ant1	Hop	79	≥15	PASS
3DH5	Ant1	Hop	79	≥15	PASS

### 9.5. Test graphs



## 10. Band Edge Compliance (Conducted Method)

### 10.1. Block diagram of test setup



### 10.2. Limit

All restriction band should comply with 15.209, other emission should be at least 20dB below the fundamental.

### 10.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Establish a reference level by using the following procedure:
 

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
- (4) Then mark the maximum amplitude of all unwanted emissions outside of the authorized frequency band.

**10.4. Test result**

Test Engineer:	Zhongyao	Test Site:	RF Measurement System 3#
Ambient Condition:	22.9°C, 49.0%RH	Test Date:	2024.01.12
Test Power Supply:	DC 3.3V	EUT:	Rock Speaker
Sample Number:	S23122113-03	Model No.:	ERS-1002

Mode	Freq. (MHz)	Verdict
GFSK	Hopping off 2402	Pass
	Hopping off 2480	Pass
	Hopping on	Pass
$\pi/4$ -DQPSK	Hopping off 2402	Pass
	Hopping off 2480	Pass
	Hopping on	Pass
8DPSK	Hopping off 2402	Pass
	Hopping off 2480	Pass
	Hopping on	Pass