



FCC ID: 2AWIU-NGA
Report No.: T200818N03-RP1

Page: 1 / 7
Rev.: 02

KDB 447498 D03
47 C.F.R. Part 1, Subpart I, Section 1.1310
47 C.F.R. Part 2, Subpart J, Section 2.1091

RF EXPOSURE REPORT

For

Water sensor

Model: WS900



NEXTGENAGAIN

Trade Name:

Issued to

Nextgenagain

12274 oakview way, San Diego, California, United States, 92128

Issued By

Compliance Certification Services Inc.

**No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City 24891, Taiwan. (R.O.C.)**

Issued Date: November 20, 2020

Note: This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NIST or any government agencies. The test results in the report only apply to the tested sample.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

REVISION HISTORY

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	November 10, 2020	Initial Issue	ALL	Angel Cheng
01	November 19, 2020	See the following note rev.01	P.5	Angel Cheng
01	November 20, 2020	See the following note rev.02	P.5.7	Angel Cheng

Note:

- ※ Rev.00 Issue Date: November 10, 2020
Original Report.
- ※ Rev.01 Issue Date: November 19, 2020
Revised the typo.
- ※ Rev.02 Issue Date: November 20, 2020
Update the Tune-up Power.



Report No.: T200818N03-MF

Page: 3 / 7
Rev.: 02

TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION	4
2. LIMIT	5
3. EUT SPECIFICATION.....	5
4. TEST RESULTS.....	6
5. MAXIMUM PERMISSIBLE EXPOSURE.....	7

Report No.: T200818N03-MF

1. TEST RESULT CERTIFICATION

We hereby certify that:

The equipment has been tested by Compliance Certification Services Inc., and found compliance with the requirement of the applicable standards. The test record, data evaluation and Equipment under Test (EUT) configurations represented herein are true and accurate accounts of the measurement of the sample's RF characteristics under the conditions specified in this report.

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
KDB 447498 D03 47 C.F.R. Part 1, Subpart I, Section 1.1310 47 C.F.R. Part 2, Subpart J, Section 2.1091	No non-compliance noted
Statements of Conformity	
Determining compliance shall be based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.	

Approved by:




Kevin Tsai
Deputy Manager
Compliance Certification Services Inc.

Report No.: T200818N03-MF

2. LIMIT

According to §1.1310 (e) (B) Limits for General Population/Uncontrolled Exposure, the frequency range (MHz) for 300-1,500 of Power density(mW/cm²) should be **f/1500** .

3. EUT SPECIFICATION

EUT	Water sensor	
Model	WS900	
Trade Name	 NEXTGENAGAIN	
Model Discrepancy	N/A	
Frequency band (Operating)	<input type="checkbox"/> 802.11b/g/n HT20: 2412MHz ~ 2462MHz <input type="checkbox"/> 802.11n HT40: 2422MHz ~ 2452MHz <input checked="" type="checkbox"/> Others (900MHz)	
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others	
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=0.6mW/cm ²)	
Antenna Specification	Antenna Gain : -23.00 dBi (Numeric gain: 0.01)	
Maximum Average output power	900MHz	12.19 dBm (16.558 mW)
Maximum Tune up Power	900MHz	12.50 dBm (17.783 mW)
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A	
Frequency band (Operating)	<input type="checkbox"/> 802.11b/g/n HT20: 2412MHz ~ 2462MHz <input type="checkbox"/> 802.11n HT40: 2422MHz ~ 2452MHz <input checked="" type="checkbox"/> Others (900MHz)	

Note: RF power data reference report (T200818N03-RP1)

4. TEST RESULTS

No non-compliance noted.

Calculation

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{377}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

5. MAXIMUM PERMISSIBLE EXPOSURE

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where $P =$ Power in mW

$G =$ Numeric antenna gain

$S =$ Power density in mW / cm²

900MHz :

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)	Result
1	900	17.783	0.01	20	0.00004	0.6	Pass