

FCC Test Report

Report No.: AGC10590210302FE10

FCC ID : 2AWL3-TDM6

PRODUCT DESIGNATION: Two-way radio

BRAND NAME : TIDRADIO

MODEL NAME : TD-M6

APPLICANT : Quanzhou longtuo electronic technology co. ,Ltd

DATE OF ISSUE : Mar. 26, 2021

STANDARD(S) : FCC Part 95 Rules

REPORT VERSION: V 1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Sedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGE, the test result presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 2 of 36

REPORT REVISE RECORD

| Report Version | Revise Time | Issued Date | Valid Version | Notes |
|----------------|-------------|---------------|---------------|-----------------|
| V1.0 | 1 | Mar. 26, 2021 | Valid | Initial Release |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Festing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter appropriate the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issued of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 3 of 36

TABLE OF CONTENTS

| 1. | GENERAL INFORMATION | 5 |
|-------|----------------------------------------|----|
| 2. I | PRODUCT INFORMATION | 6 |
| | 2.1 PRODUCT TECHNICAL DESCRIPTION | |
| | 2.2 TEST FREQUENCY LIST | |
| | 2.3 RELATED SUBMITTAL(S) / GRANT (S) | 8 |
| | 2.4 TEST METHODOLOGY | 8 |
| | 2.5 CALCULATION OF EMISSION INDICATORS | |
| | 2.6 SPECIAL ACCESSORIES | |
| | 2.7 EQUIPMENT MODIFICATIONS | 3 |
| | 2.8 ANTENNA REQUIREMENT | g |
| 3 | TEST ENVIRONMENT | 10 |
| | 3.1 ADDRESS OF THE TEST LABORATORY | 10 |
| | 3.2 TEST FACILITY | 10 |
| | 3.3 ENVIRONMENTAL CONDITIONS | 11 |
| | 3.4 MEASUREMENT UNCERTAINTY | 11 |
| | 3.5 LIST OF EQUIPMENTS USED | |
| 4.5 | SYSTEM TEST CONFIGURATION | 13 |
| | 4.1 EUT CONFIGURATION | 13 |
| | 4.2 EUT EXERCISE | 13 |
| | 4.3 CONFIGURATION OF TESTED SYSTEM | 13 |
| | 4.4 EQUIPMENT USED IN TESTED SYSTEM | 13 |
| | 4.5 SUMMARY OF TEST RESULTS | 14 |
| 5. I | DESCRIPTION OF TEST MODES | 15 |
| 6.F | FREQUENCY STABILITY | 16 |
| | 6.1 PROVISIONS APPLICABLE | 16 |
| | 6.2 MEASUREMENT PROCEDURE | 16 |
| | 6.3 MEASUREMENT SETUP | 16 |
| | 6.4 MEASUREMENT RESULTS | 17 |
| 7. I | EMISSION BANDWIDTH | 18 |
| | 7.1 PROVISIONS APPLICABLE | 18 |
| | 7.2 MEASUREMENT PROCEDURE | 18 |
| | 7.3 MEASUREMENT SETUP | |
| | 7.4 MEASUREMENT RESULTS | |
| 8. \$ | SPURIOUS RATIATED EMISSION | |
| | 8 1 DDOVISIONS ADDITIONS E | |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Specificated Festing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter pathorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 4 of 36

| 8.2 MEASUREMENT PROCEDURE | 21 |
|---------------------------------------|----|
| 8.3 MEASUREMENT SETUP | |
| 8.4 MEASUREMENT RESULTS | 23 |
| 8.5 EMISSION MASK PLOT | 27 |
| 9. MAXIMUMN TRANSMITTER POWER | |
| 9.1 PROVISIONS APPLICABLE | 29 |
| 9.2 MEASUREMENT METHOD | |
| 9.3 MEASUREMENT SETUP | 30 |
| 9.4 MEASUREMENT RESULTS | 31 |
| 10.MODULATION CHARACTERISTICS | |
| 10.1 PROVISIONS APPLICABLE | 32 |
| 10.2 MEASUREMENT METHOD | |
| 10.3 MEASUREMENT SETUP | |
| 10.4 MEASUREMENT RESULTS | 33 |
| APPENDIX I: PHOTOGRAPHS OF TEST SETUP | |
| APPENDIX II: PHOTOGRAPHS OF TEST EUT | 36 |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 5 of 36

/Inspection

he test results

he test report.

1. GENERAL INFORMATION

| Applicant | Quanzhou longtuo electronic technology co. ,Ltd | | |
|-------------------------|------------------------------------------------------------------------------|--|--|
| Address | No.17-20, building 16, chenghui international zone B, xiamei quanzhou Fujian | | |
| Manufacturer | Quanzhou longtuo electronic technology co. ,Ltd | | |
| Address | No.17-20, building 16, chenghui international zone B, xiamei quanzhou Fujian | | |
| Factory | Quanzhou longtuo electronic technology co. ,Ltd | | |
| Address | No.17-20, building 16, chenghui international zone B, xiamei quanzhou Fujian | | |
| Product Designation | Two-way radio | | |
| Brand Name | TIDRADIO | | |
| Test Model | TD-M6 | | |
| Deviation from Standard | None | | |
| Date of Receipt | Mar. 08, 2021 | | |
| Date of Test | Mar. 08, 2021~Mar. 26, 2021 | | |
| Test Result | Pass | | |
| Test Report Form No | AGCTR-ER-FCC-XXV1.0 | | |

WE HEREBY CERTIFY THAT:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI/TIA-603-E-2016. The sample tested as described in this report is in compliance with the FCC Rules Part 95. The test results of this report relate only to the tested sample identified in this report.

Prepared By

Donjon Huang (Project Engineer)

Reviewed By

Calvin Liu (Reviewer)

Approved By

Forrest Lei Authorized Officer

Mar. 26, 2021

Mar. 26, 2021

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the speciated feat Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuence Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.



Page 6 of 36

2. PRODUCT INFORMATION

2.1 PRODUCT TECHNICAL DESCRIPTION

| Hardware Version | JC-003 Ver1.3 | | | | |
|-----------------------------------------|-----------------------------------------------------------------------------------------|--|--|--|--|
| Software Version | V1.3 | | | | |
| Power Supply | DC 3.7V, 800mAh by battery | | | | |
| Adapter Information | Input:100-240V 50/60Hz, 0.15A Output:5V 1A | | | | |
| Communication Type | Voice / Tone only | | | | |
| | 462.5625 - 462.7125MHz (1~7 channel) | | | | |
| Operation Frequency Range | 467.5625 - 467.7125MHz (8~14 channel) | | | | |
| | 462.5500 - 462.7250MHz (15~22 channel) | | | | |
| Modulation Type | FM | | | | |
| Channel Separation | 12.5 KHz | | | | |
| Emission Bandwidth | 11.00 KHz | | | | |
| Emission Designator | 11K0F3E | | | | |
| Number of Channels: | 22 Channels | | | | |
| Rated Output Power | 2W/0.5W (It was fixed by the manufacturer, any individual can't arbitrarily change it.) | | | | |
| Maximum Transmitter Power | FRS: 32.86dBm (2W-12.5KHz) FRS: 26.91dBm (0.5W-12.5KHz) | | | | |
| Antenna Designation Inseparable Antenna | | | | | |
| Antenna Gain | 1.5 dBi | | | | |
| Frequency Tolerance | 1.023ppm | | | | |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Festing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 7 of 36

2.2 TEST FREQUENCY LIST

According to ANSI C63.26 section 5.1.2.1:

Measurements of transmitters shall be performed and, if required, reported for each frequency band in which the EUT can be operated with the device transmitting at the number of frequencies in each band specified in Table 2.

| (8) | | | |
|-----------------------------------------|-----------------------|----------------------------------------------|--|
| Frequency range Over which EUT operates | Number of Frequencies | Location in frequency range of operation | |
| 1 MHz or less | 1 0 | Middle | |
| 1 MHz to 10 MHz | 2 | 1 near top and 1 near bottom | |
| More than 10 MHz | 3 | 1 near top, 1 near middle, and 1 near bottom | |

| Operation Frequency Each of Channel | | | | | |
|-------------------------------------|--------------|---------|--------------|---------|--------------|
| | FRS | F | FRS | FRS | |
| Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 1 | 462.5625 MHz | 8 | 467.5625 MHz | 15 | 462.5500 MHz |
| 2 | 462.5875 MHz | 9 | 467.5875 MHz | 16 | 462.5750 MHz |
| 3 | 462.6125 MHz | 10 | 467.6125 MHz | 17 | 462.6000 MHz |
| 4 | 462.6375 MHz | 11 | 467.6375 MHz | 18 | 462.6250 MHz |
| 5 | 462.6625 MHz | 12 | 467.6625 MHz | 19 | 462.6500 MHz |
| 6 | 462.6875 MHz | 13 | 467.6875 MHz | 20 | 462.6750 MHz |
| 7 | 462.7125 MHz | 14 | 467.7125 MHz | 21 | 462.7000 MHz |
| | | | (6) | 22 | 462.7250 MHz |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 8 of 36

2.3 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for FCC ID: **2AWL3-TDM6**, filing to comply with Part 2, Part 95 of the Federal Communication Commission rules.

2.4 TEST METHODOLOGY

The tests were performed according to following standards:

| No. | Identity | Document Title | |
|---------------------------------------------|-------------------|---------------------------------------------------------------------------------------------------|--|
| 1 FCC 47 CFR Part 95 | | PERSONAL RADIO SERVICES | |
| 2 | FCC 47 CFR Part 2 | Frequency allocations and radio treaty matters; general rules and regulations | |
| 3 ANSI C63.26-2015 4 ANSI/TIA-603-E-2016 | | American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services | |
| | | Land Mobile FM or PM Communications Equipment Measurement and Performance Standards | |
| 5 | KDB 888861 D01 | 888861 D01 Part 95 GMRS FRS v01 | |

2.5 CALCULATION OF EMISSION INDICATORS

FCC Rules and Regulations Part 2.202: Necessary Bandwidth and Emission Bandwidth

For FM Mode (ChannelSpacing: 12.5kHz)

Emission Designator 11K0F3E

In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation.

BW = 2(M+D) = 2*(3.0 kHz + 2.5 kHz) = 11 kHz = 11KO

F3E portion of the designator represents an FM voice transmission.

Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.

2.6 SPECIAL ACCESSORIES

Not available for this EUT intended for grant.

2.7 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC he test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 9 of 36

2.8 ANTENNA REQUIREMENT

Excerpt from §95.587 of the FCC Rules/Regulations:

The antenna of each FRS transmitter type must meet the following requirements.

- (1) The antenna must be a non-removable integral part of the FRS transmitter type.
- (2) The gain of the antenna must not exceed that of a half-wave dipole antenna.
- (3) The antenna must be designed such that the electric field of the emitted waves is vertically polarized when the unit is operated in the normal orientation.
- The antenna of this device is permanently attached.
- There are no provisions for connection to an external antenna.

Conclusion: The unit complies with the requirement of §95.587.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Feating/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of ACC he test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuence of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 10 of 36

3. TEST ENVIRONMENT

3.1 ADDRESS OF THE TEST LABORATORY

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the condicated restrouting portion of Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.



Page 11 of 36

3.3 ENVIRONMENTAL CONDITIONS

| | NORMAL CONDITIONS | EXTREME CONDITIONS |
|------------------------|-------------------|----------------------|
| Temperature range (°C) | 15 - 35 | -20 - 50 |
| Relative humidty range | 20 % - 75 % | 20 % - 75 % |
| Pressure range (kPa) | 86 - 106 | 86 - 106 |
| Power supply | DC 3.7V | LV:DC 3.15V/HV:4.26V |

Note: The Extreme Temperature and Extreme Voltages declared by the manufacturer.

3.4 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty

multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

| Test Items | Measurement Uncertainty | |
|-----------------------------------------|-------------------------|--|
| Frequency stability | ±0.5% | |
| Transmitter power conducted | ±0.8dB | |
| Transmitter power Radiated | ±1.3dB | |
| Conducted spurious emission 9kHz-40 GHz | ±2.7dB | |
| Conducted Emission | ±3.2 dB | |
| Radiated Emission below 1GHz | ±3.9 dB | |
| Radiated Emission above 1GHz | ±4.8 dB | |
| Occupied Channel Bandwidth | ±2 % | |
| FM deviation | ±2 % | |
| Audio level | ±0.98dB | |
| Low Pass Filter Response | ±0.65dB | |
| Modulation Limiting | 0.42 % | |
| Transient Frequency Behavior | 6.8 % | |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written exhorization of AGC he test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 12 of 36

3.5 LIST OF EQUIPMENTS USED

| Equipment | Manufacturer | Model | S/N | Cal. Date | Cal. Due |
|----------------------------------|----------------|-------------|--------------|---------------|---------------|
| TEST RECEIVER | R&S | ESCI | 10096 | May 15, 2020 | May 14, 2021 |
| EXA Signal Analyzer | Aglient | N9020A | W1312-60196 | Aug. 21, 2020 | Aug. 20, 2021 |
| EXA Signal Analyzer | Aglient | N9020A | MY52090123 | Sep. 03, 2020 | Sep. 02, 2021 |
| Horn antenna | SCHWARZBECK | BBHA 9170 | #768 | Sep.16, 2019 | Sep.15, 2021 |
| preamplifier | ChengYi | EMC184045SE | 980508 | Sep. 23, 2019 | Sep. 22, 2021 |
| Double-Ridged Waveguide Horn | ETS LINDGREN | 3117 | 00034609 | May. 17, 2019 | May. 16, 2021 |
| Broadband Preamplifier | SCHWARZBECK | BBV 9718 | 9718-205 | Jun. 09, 2020 | Jun. 08, 2021 |
| HORN ANTENNA | EM | EM-AH-10180 | | Feb.26, 2021 | Feb.25, 2022 |
| SIGNAL GENERATOR | AGILENT | E4421B | MY43351603 | Jun. 09, 2020 | Jun. 08, 2021 |
| SIGNAL GENERATOR | R&S | SMT03 | A0304261 | Jun. 09, 2020 | Jun. 08, 2021 |
| ANTENNA | SCHWARZBECK | VULB9168 | VULB9168-494 | Jan. 08, 2021 | Jan. 07, 2023 |
| ANTENNA | SCHWARZBECK | VULB9168 | D69250 | Sep. 20, 2019 | Sep. 19, 2021 |
| Active loop antenna (9K-30MHz) | ZHINAN | ZN30900C | 18051 | Jun. 11, 2020 | Jun. 10, 2021 |
| Modulation Domain Analyzer | HP | 53310A | 3121A02467 | Jul. 03, 2020 | Jul. 02, 2021 |
| Small environmental tester | ESPEC | SH-242 | · | Sep. 03, 2020 | Sep. 02, 2021 |
| RF Communication Test Set | HP | 8920B | = .0 | Jun. 09, 2020 | Jun. 08, 2021 |
| Attenuator | Weinachel Corp | 58-30-33 | ML030 | Oct. 28, 2019 | Oct. 27, 2020 |
| RF Cable | R&S | 1# | | Each time | N/A |
| RF Cable | R&S | 2# | (GC) | Each time | N/A |
| Fliter-UHF | Microwave | N25155M2 | 498705 | May 11, 2020 | May 10, 2021 |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 13 of 36

4.SYSTEM TEST CONFIGURATION

4.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT EXERCISE

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 CONFIGURATION OF TESTED SYSTEM

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

4.4 EQUIPMENT USED IN TESTED SYSTEM

The Following Peripheral Devices And Interface Cables Were Connected During The Measurement:

- ☐ Test Accessories Come From The Laboratory
- Test Accessories Come From The Manufacturer

| | Item | Equipment | Model No. | Identifier | Note |
|---|------|---------------|---------------|-----------------------------------------------------|-------------|
| 4 | 1 | Two-way radio | TD-M6 | FCC ID: 2AWL3-TDM6 | EUT |
| | 2 | Battery | BAT-R1 | DC 3.7V 800mAh | Accessories |
| | 3 | Back clip | N/A | N/A | Accessories |
| | 4 | Adapter | U282E0A050100 | Input: 100-240V, 50/60Hz, 0.15A Output: DC 5V 1A | Accessories |
| | 5 | USB Cable | N/A | N/A | Accessories |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Bedicated Restrog/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGE. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.



Page 14 of 36

4.5 SUMMARY OF TEST RESULTS

| Item | FCC Rules | Description of Test | Result | |
|------|------------------------|----------------------------|--------|--|
| 1 | FCC 47 CFR PART 95 | Antenna Equipment | Pass | |
| 2 | § 95.567& 2.1046(a) | Maximum Transmitter Power | Pass | |
| 3 | §95.575& 2.1047(a) (b) | Modulation Limit | Pass | |
| 4 | §95.575& 2.1047(a) | Audio Frequency Response | Pass | |
| 5 | §95.573& 2.1049 | Emission Bandwidth | Pass | |
| 6 | §95.579& 2.1049 | Emission Mask | Pass | |
| 7 | §95.565& 2.1055(a) (1) | Frequency Stability | Pass | |
| 8 | §95.579& 2.1053 | Spurious Ratiated Emission | Pass | |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Festing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 15 of 36

5. DESCRIPTION OF TEST MODES

The EUT (**Two-way radio**) has been tested under normal operating condition. (FRS TX) are chosen for testing at each channel separation.

| NO. | TEST MODE DESCRIPTION | CHANNEL SEPARATION | | |
|-----|-----------------------|--------------------|--|--|
| 1 6 | FRS TX CHANNEL 4 | 12.5 kHz | | |
| 2 | FRS TX CHANNEL 11 | 12.5 kHz | | |
| 3 | FRS TX CHANNEL 19 | 12.5 kHz | | |

Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. The battery is full-charged during the test.
- 3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 4. Manufacturers use computer PC programming software to switch and operate frequency points, refer to the instructions for details

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Festing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 16 of 36

6.FREQUENCY STABILITY

6.1 PROVISIONS APPLICABLE

Each FRS transmitter type must be designed such that the carrier frequencies remain within ±2.5 parts-per-million (ppm) of the channel center frequencies specified in §95.563 during normal operating conditions.

6.2 MEASUREMENT PROCEDURE


6.2.1 Frequency stability versus environmental temperature

- 1. Setup the configuration per figure 1 for frequencies measurement inside an environment chamber, Install new battery in the EUT.
- Turn on EUT and set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1kHz and Video Resolution Bandwidth to 1kHz and Frequency Span to 50kHz. Record this frequency as reference frequency.
- 3. Set the temperature of chamber to 50℃. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. While maintaining a constant temperature inside the chamber, turn the EUT on and measure the EUT operating frequency.
- 4. Repeat step 2 with a 10°C decreased per stage until the lowest temperature -30°C is measured, record all measured frequencies on each temperature step.

6.2.2 Frequency stability versus input voltage

- Setup the configuration per figure 1 for frequencies measured at temperature if it is within 15℃ to 25℃.
 Otherwise, an environment chamber set for a temperature of 20℃ shall be used. The EUT shall be powered by DC 3.7V.
- 2. Set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1 kHz and Video Resolution Bandwidth to 1kHz. Record this frequency as reference frequency.
- Supply the EUT primary voltage at the operating end point which is specified by manufacturer and record the frequency.

6.3 MEASUREMENT SETUP



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written exporization of AGC he test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc=cert.com.



Report No.: AGC10590210302FE10 Page 17 of 36

6.4 MEASUREMENT RESULTS

| Test | conditions | F | | | | |
|---------|------------|----------|----------------|----------|-------|------|
| Voltage | Temp | Т | Limit (ppm) | Result | | |
| (V) | (℃) | 462.6375 | 467.6375 | 462.6500 | (PP) | |
| | -30 | 0.652 | 0.743 | 0.811 | 100 | -0 |
| | -20 | 0.524 | 0.946 | 0.601 | | |
| | -10 | 0.955 | 0.429 | 0.300 | 30 | |
| | 0 | 0.456 | 0.541 | 0.924 | | |
| 3.70 | 10 | 0.796 | 0.841 | 0.664 | | |
| | 20 | 0.969 | 0.496 | 0.458 | 2.5 | Pass |
| | 30 | 0.890 | 0.510 | 0.372 | | |
| | 40 | 1.023 | 0.443 | 0.862 | | |
| | 50 | 0.370 | 0.894 | 0.796 | | |
| 4.26 | 20 | 0.652 | 0.743 | 0.811 | | |
| 3.15 | 20 | 0.524 | 0.946 | 0.601 | 100 V | |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Bedicated Pest Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issue of Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com. g/Inspection The test results ne test report.



Page 18 of 36

7. EMISSION BANDWIDTH

7.1 PROVISIONS APPLICABLE

FCC Part 95.573: FRS: The authorized bandwidth for an FRS unit is 12.5 kHz.

Occupied Bandwidth (Section 2.1049, 95.573): The EUT was connected to the audio signal generator and the spectrum analyzer via the main RF connector, and through an appropriate attenuator. The EUT was controlled to transmit its maximum power. Then the bandwidth of 99% power can be measured by the spectrum analyzer.

7.2 MEASUREMENT PROCEDURE

1.The EUT was modulated by 2.5kHz sine wave audio signal; the level of the audio signal employed is 16dB greater than that necessary to produce 50% of rated system deviation.

Rated system deviation is 2.5 kHz for 12.5kHz channel spacing).

2. Spectrum set as follow:

Centre frequency = fundamental frequency, span=50kHz for 12.5kHz channel spacing, RBW=300Hz, VBW=1KHz, Sweep = auto,


Detector function = peak, Trace = max hold

- 3.Set 99% Occupied Bandwidth and 26dB Occupied Bandwidth.
- 4. Measure and record the results in the test report.

7.3 MEASUREMENT SETUP





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the condicated restrouting portion of Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.







RADIATED BELOW1GHZ





RADIATED ABOVE 1 GHZ





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the specificated resting/inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter pathorization of AGC, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 20 of 36

g/Inspection


he test results

the test report.

7.4 MEASUREMENT RESULTS

| Emission Bandwidth Measurement Result-FRS | | | | | | | | | |
|-------------------------------------------|-----------------------------|--------------------|----------|--------|--|--|--|--|--|
| Operating Frequency | 12.5 kHz Channel Separation | | | | | | | | |
| | Occupied Bandwidth | Emission Bandwidth | Limits | Result | | | | | |
| 462.6375 MHz | 9.472 kHz | 11.00 kHz | 12.5 kHz | Pass | | | | | |
| 462.6500 MHz | 9.855 kHz | 10.53 kHz | 12.5 kHz | Pass | | | | | |
| 467.6375 MHz | 9.861 kHz | 10.53 kHz | 12.5 kHz | Pass | | | | | |

Test plot as follows:



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Festi Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



Page 21 of 36

8. SPURIOUS RATIATED EMISSION

8.1 PROVISIONS APPLICABLE

Standard Applicable [FCC Part 95.579] According to FCC section 95.579, the unwanted emission should be attenuated below TP by at least 43+10 log (Transmit Power) Db.


Each FRS transmitter type must be designed to satisfy the applicable unwanted emissions limits in this paragraph.

- (a) Attenuation requirements. The power of unwanted emissions must be attenuated below the carrier power output in Watts (P) by at least:
- (1) 25 dB (decibels) in the frequency band 6.25 kHz to 12.5 kHz removed from the channel center frequency.
- (2) 35 dB in the frequency band 12.5 kHz to 31.25 kHz removed from the channel center frequency.
- (3) 43 + 10 log (P) dB in any frequency band removed from the channel center frequency by more than 31.25 kHz

8.2 MEASUREMENT PROCEDURE

- 1) EUT was placed on a 0.8 or 1.5meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The disturbance of the transmitter was maximized on the test receiver display by raising and lowering from 1m to 4m the receive antenna and by rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made. The radiated emission measurements of all transmit frequencies in all channels were measured with peak detector.
- 2) A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
- 3) The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz for above 1GHz and RBW=100kHz, VBW=300kHz for 30MHz to 1GHz, And the maximum value of the receiver should be recorded as (Pr).
- 4) The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
- 5) A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (PcI) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test
- 6) The measurement results are obtained as described below: Power(EIRP)=PMea- PAg Pcl Ga The

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Dedicated Festiva/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuence of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc=cert.com.







measurement results are amend as described below:Power(EIRP)=PMea- Pcl - Ga

- 7) This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
- 8) ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP-2.15dBi.
- 9) Test the EUT in the lowest channel, the middle channel the Highest channel


8.3 MEASUREMENT SETUP

RADIATED BELOW1GHZ







Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Specificated Restriction Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter purporization of AGC, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.





RADIATED ABOVE 1 GHZ






8.4 MEASUREMENT RESULTS


| Preliminary calculation | Final Result |
|----------------------------------------------------|------------------------------------------------------|
| At least 43+10 log (P) =43+10log (2) =46.01 (dB) | Limit=P- Preliminary calculation=33.01-46.01=-13 dBm |
| At least 43+10 log (P) =43+10log (0.5) =43.00 (dB) | Limit=P- Preliminary calculation=30.00-43.00=-13 dBm |

- 1. Factor=Antenna Factor + Cable loss. (Below 1GHz)
- 2. Factor=Antenna Factor+ Cable loss -Pre-amplifier. (Above 1 GHz)
- 3. Margin=Limit- Level


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Restriction Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter pathorization of AGC, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.








| NO. | Freq. [MHz] | Reading [dBm] | Level [dBm] | Limit [dBm] | Margin [dB] | Factor [dB] | Angle [°] | Polarity |
|-----|----------------|------------------|----------------|----------------|----------------|----------------|--------------|------------|
| 1 | 925.3100 | -77.35 | -33.86 | -13.00 | 20.86 | 43.49 | 248 | Horizontal |
| 2 | 1387.7888 | -23.87 | -27.32 | -13.00 | 14.32 | -3.45 | 155 | Horizontal |
| 3 | 2313.7814 | -18.41 | -19.12 | -13.00 | 6.12 | -0.71 | 313 | Horizontal |
| 4 | 2775.6026 | -20.59 | -19.42 | -13.00 | 6.42 | 1.17 | 313 | Horizontal |
| 5 | 3238.5989 | -20.79 | -17.08 | -13.00 | 4.08 | 3.71 | 102 | Horizontal |
| 6 | 3701.5952 | -28.92 | -24.51 | -13.00 | 11.51 | 4.41 | 102 | Horizontal |




| NO. | Freq. [MHz] | Reading [dBm] | Level [dBm] | Limit [dBm] | Margin [dB] | Factor [dB] | Angle [°] | Polarity |
|-----|----------------|------------------|----------------|----------------|----------------|----------------|--------------|----------|
| 1 | 925.3100 | -69.59 | -26.02 | -13.00 | 13.02 | 43.57 | 333 | Vertical |
| 2 | 1387.7888 | -24.78 | -23.37 | -13.00 | 10.37 | 1.41 | 354 | Vertical |
| 3 | 1850.7851 | -27.21 | -26.28 | -13.00 | 13.28 | 0.93 | 254 | Vertical |
| 4 | 2313.7814 | -19.26 | -19.79 | -13.00 | 6.79 | -0.53 | 240 | Vertical |
| 5 | 2775.6026 | -23.57 | -22.29 | -13.00 | 9.29 | 1.28 | 42 | Vertical |
| 6 | 3238.5989 | -26.45 | -23.31 | -13.00 | 10.31 | 3.14 | 56 | Vertical |

Any leport having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Stedicated Restriction of Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc=cert.com.









- Limit # Final Test - Horizonta

| NO. | Freq. [MHz] | Reading [dBm] | Level [dBm] | Limit [dBm] | Margin [dB] | Factor [dB] | Angle [°] | Polarity |
|-----|----------------|------------------|----------------|----------------|----------------|----------------|--------------|------------|
| 1 | 925.3100 | -77.14 | -33.65 | -13.00 | 20.65 | 43.49 | 283 | Horizontal |
| 2 | 1387.7888 | -23.78 | -27.23 | -13.00 | 14.23 | -3.45 | 164 | Horizontal |
| 3 | 1850.7851 | -32.58 | -33.17 | -13.00 | 20.17 | -0.59 | 164 | Horizontal |
| 4 | 2313.7814 | -18.58 | -19.29 | -13.00 | 6.29 | -0.71 | 323 | Horizontal |
| 5 | 2775.6026 | -19.97 | -18.80 | -13.00 | 5.80 | 1.17 | 336 | Horizontal |
| 6 | 3238.5989 | -19.57 | -15.86 | -13.00 | 2.86 | 3.71 | 111 | Horizontal |





| NO. | Freq. [MHz] | Reading [dBm] | Level [dBm] | Limit [dBm] | Margin [dB] | Factor [dB] | Angle [°] | Polarity |
|-----|----------------|------------------|----------------|----------------|----------------|----------------|--------------|----------|
| 1 | 925.3100 | -69.29 | -25.72 | -13.00 | 12.72 | 43.57 | 315 | Vertical |
| 2 | 1387.7888 | -24.51 | -23.10 | -13.00 | 10.10 | 1.41 | 341 | Vertical |
| 3 | 2313.7814 | -18.13 | -18.66 | -13.00 | 5.66 | -0.53 | 223 | Vertical |
| 4 | 2775.6026 | -22.13 | -20.85 | -13.00 | 7.85 | 1.28 | 262 | Vertical |
| 5 | 3238.5989 | -25.66 | -22.52 | -13.00 | 9.52 | 3.14 | 37 | Vertical |
| 6 | 3701.5952 | -27.49 | -24.34 | -13.00 | 11.34 | 3.15 | 130 | Vertical |


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Stadiested Teating/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issued by the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.











| NO. | Freq. [MHz] | Reading [dBm] | Level [dBm] | Limit [dBm] | Margin [dB] | Factor [dB] | Angle [°] | Polarity |
|-----|----------------|------------------|----------------|----------------|----------------|----------------|--------------|----------|
| 1 | 935.9800 | -69.48 | -25.80 | -13.00 | 12.80 | 43.68 | 348 | Vertical |
| 2 | 1403.0653 | -23.19 | -21.67 | -13.00 | 8.67 | 1.52 | 324 | Vertical |
| 3 | 1870.7621 | -25.56 | -24.70 | -13.00 | 11.70 | 0.86 | 257 | Vertical |
| 4 | 2338.4588 | -21.51 | -22.12 | -13.00 | 9.12 | -0.61 | 204 | Vertical |
| 5 | 2806.1556 | -26.80 | -25.26 | -13.00 | 12.26 | 1.54 | 270 | Vertical |
| 6 | 3273.8524 | -27.87 | -24.74 | -13.00 | 11.74 | 3.13 | 72 | Vertical |

Any leport having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Bedicated Teather Institute authorization of AGE" the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc=cert.com.



Page 27 of 36


8.5 EMISSION MASK PLOT

The detailed procedure employed for Emission Mask measurements are specified as following:

- -Connect the equipment as illustrated.
- -Spectrum set as follow:
- 1. Centre frequency = fundamental frequency, Span=50kHz for 12.5kHz , RBW=300Hz, VBW=1000Hz ;
- 2. Sweep = auto, Detector function = peak, Trace = max hold
- 3. Key the transmitter, and set the level of the unmodulated carrier to a full scale reference line. This is the 0dB reference for the measurement.
- 4. Modulate the transmitter with a 2500 Hz sine wave at an input level 16 dB greater than that necessary to produce 50% of rated system deviation (Rated system deviation is 2.5 kHz for 12.5kHz channel spacing).
 - The input level shall be established at the frequency of maximum response of the audio modulating circuit.
- Transmitters employing digital modulation techniques that bypass the limiter and the audio low-pass filter shall be modulated as specified by the manufacturer.
- 6. Measure and record the results in the test report.




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Bedicated Residual Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written exporization of AGE, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc=cert.com.





Test plot as follows:



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written pathorization of AGC, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 29 of 36

9. MAXIMUMN TRANSMITTER POWER

9.1 PROVISIONS APPLICABLE

Each FRS transmitter type must be designed such that the effective radiated power (ERP) on channels 8 through 14 does not exceed 0.5 Watts and the ERP on channels 1 through 7 and 15 through 22 does not exceed 2.0 Watts.

9.2 MEASUREMENT METHOD

- 1) EUT was placed on a 0.8 or 1.5meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The disturbance of the transmitter was maximized on the test receiver display by raising and lowering from 1m to 4m the receive antenna and by rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made. The radiated emission measurements of all transmit frequencies in all channels were measured with peak detector.
- 2) A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
- 3) The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz for above 1GHz and RBW=100kHz, VBW=300kHz for 30MHz to 1GHz, And the maximum value of the receiver should be recorded as (Pr).
- 4) The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
- 5) A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (PcI) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test
- 6) The measurement results are obtained as described below: Power(EIRP)=PMea- PAg Pcl Ga The measurement results are amend as described below:Power(EIRP)=PMea- Pcl Ga
- 7) This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
- 8) ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP-2.15dBi.
- 9) Test the EUT in the lowest channel, the middle channel the Highest channel


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Festing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.




9.3 MEASUREMENT SETUP


EFFECTIVE RADIATED POWER:


Radiated Below1GHz





Radiated Above 1 GHz





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the specificated resting/inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter pathorization of AGC, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 31 of 36

//Inspection
The test results
the test report.

9.4 MEASUREMENT RESULTS

ERP RESULT:

| LINI INLOUL | | | | | | | | | |
|-------------|------------------|----------------|--------|---------------|-------------|-------------------|-------------------|-------|--------|
| Frequency | Reading Level | Antenna | S.G. | Cable Loss | Ant.Gain | Emission Level | Emission Level | Limit | Margin |
| (MHz) | (dBuv/m) | Polarization | (dBm) | (dB) | (dBi) | (dBm) | (W) | (W) | (W) |
| | 10 | 60 | Channe | Separat | ion:12.5KHz | | | C | (8) |
| 462.6375 | 101.87 | V | 26.64 | 0.38 | 6.6 | 32.86 | 1.93 | 2.0 | 0.07 |
| 462.6375 | 101.78 | _® Н | 26.55 | 0.38 | 6.6 | 32.77 | 1.89 | 2.0 | 0.11 |
| 462.6500 | 101.85 | V | 26.62 | 0.38 | 6.6 | 32.84 | 1.92 | 2.0 | 0.08 |
| 462.6500 | 101.72 | Н | 26.49 | 0.38 | 6.6 | 32.71 | 1.87 | 2.0 | 0.13 |
| 467.6375 | 95.92 | V | 20.69 | 0.38 | 6.6 | 26.91 | 0.49 | 0.5 | 0.01 |
| 467.6375 | 95.84 | Н | 20.61 | 0.38 | 6.6 | 26.83 | 0.48 | 0.5 | 0.02 |

NOTE: 1. Calculation Formula: Emission Level(dBm) = S.G. (dBm)- Cable Loss(dB)+ Ant.Gain(dBi)

2.The Ant. Gain including the correct factor 2.15 3.Margin (dB) = Limit(dBm)- Emission Level(dBm)

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Bedicated Passamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AG presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 32 of 36

10.MODULATION CHARACTERISTICS

10.1 PROVISIONS APPLICABLE

According to FCC§2.1047 and §95.575, for Voice Modulation Communication Equipment, the frequency response of the audio modulation circuit over a range of 100 to 5000Hz shall be measured.

Each FRS transmitter type must be designed such that the peak frequency deviation does not exceed 2.5 kHz, and the highest audio frequency contributing substantially to modulation must not exceed 3.125 kHz.

10.2 MEASUREMENT METHOD

10.2.1 Modulation Limit

- (1). Configure the EUT as shown in figure 1, adjust the audio input for 60% of rated system deviation at 1kHz using this level as a reference (0dB) and vary the input level from –20 to +20dB. Record the frequency deviation obtained as a function of the input level.
- (2). Repeat step 1 with input frequency changing to 300, 1000, 1500 and 3000Hz in sequence.

10.2.2 Audio Frequency Response

- (1). Configure the EUT as shown in figure 1.
- (2). Adjust the audio input for 20% of rated system deviation at 1 kHz using this level as a reference (0 dB).
- (3). Vary the Audio frequency from 100 Hz to 10 kHz and record the frequency deviation.
- (4). Audio Frequency Response = 20log10 (Deviation of test frequency/Deviation of 1 kHz reference).

10.3 MEASUREMENT SETUP




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the condicated resting/inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



10.4 MEASUREMENT RESULTS

(A). MODULATION LIMIT:

| 1 | 12.5kHz, FM modulati | on, Assigned Frequen | cy:462.6375MHz-2W | |
|-----------------------|--------------------------------------------|---------------------------------------------|---------------------------------------------|---------------------------------------------|
| Modulation Level (dB) | Peak Freq. Deviation At 300 Hz (kHz) | Peak Freq. Deviation At 1000 Hz (kHz) | Peak Freq. Deviation At 1500 Hz (kHz) | Peak Freq. Deviation At 3000 Hz (kHz) |
| -20 | 0.12 | 0.23 | 0.52 | 0.63 |
| -15 | 0.25 | 0.45 | 0.69 | 0.82 |
| -10 | 0.32 | 0.61 | 0.83 | 0.91 |
| -5 | 0.55 | 0.72 | 0.94 | 1.21 |
| 0 | 0.63 | 0.83 | 1.05 | 1.28 |
| +5 | 0.71 | 0.92 | 1.17 | 1.31 |
| +10 | 0.83 | 0.99 | 1.12 | 1.29 |
| +15 | 0.91 | 1.03 | 1.23 | 1.35 |
| +20 | 0.81 | 1.01 | 1.19 | 1.31 |



Note: All the modes had been tested, but only the worst data recorded in the report


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Restriction Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter pathorization of AGC, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



(B). AUDIO FREQUENCY RESPONSE:


| 12.5kHz, Analog modulation, Assigned Frequency:462.6375MHz-2W | | |
|---------------------------------------------------------------|-----------------|-----------------------------|
| Frequency (Hz) | Deviation (kHz) | Audio Frequency Response(dB |
| 100 | · · · · · · | |
| 200 | | |
| 300 | 0.25 | -13.98 |
| 400 | 0.43 | -9.27 |
| 500 | 0.69 | -5.16 |
| 600 | 0.82 | -3.66 |
| 700 | 0.93 | -2.57 |
| 800 | 1.05 | -1.51 |
| 900 | 1.13 | -0.88 |
| 1000 | 1.25 | 0.00 |
| 1200 | 1.47 | 1.41 |
| 1400 | 2.14 | 4.67 |
| 1600 | 2.37 | 5.56 |
| 1800 | 2.61 | 6.39 |
| 2000 | 2.99 | 7.58 |
| 2400 | 3.06 | 7.78 |
| 2500 | 3.13 | 7.97 |
| 2800 | 3.27 | 8.35 |
| 3000 | 2.85 | 7.16 |
| 3200 | 2.79 | 6.97 |
| 3600 | 1.79 | 3.12 |
| 4000 | 1.63 | 2.31 |
| 4500 | 1.52 | 1.70 |
| 5000 | 1.47 | 1.41 |
| 5500 | 1.33 | 0.54 |
| 6000 | 1.05 | -1.51 |
| 6500 | 0.63 | -5.95 |
| 7000 | 0.26 | -13.64 |
| 7500 | 0.13 | -19.66 |

12.5 KHz Channel Separations



Note: All the modes had been tested, but only the worst data recorded in the report.


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC, he test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.





APPENDIX I: PHOTOGRAPHS OF TEST SETUP

RADIATED EMISSION TEST SETUP



RADIATED EMISSION ABOVE 1G TEST SETUP



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the specificated resting/inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter pathorization of AGC, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Page 36 of 36

APPENDIX II: PHOTOGRAPHS OF TEST EUT

Refer to the Report No.: AGC10590210302AP01

----END OF REPORT----

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the special pedicated fresh dynapection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter appropriation of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3.The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. The non-CMA report issued by AGC is only permitted to be used by the client as internal reference use and shall not be used for public demonstration purpose.
- 5. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 6. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 7. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 8. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 9. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 10. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.

he test report.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the /Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter enhorization of AGE The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15da Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.