

## INTERTEK TESTING SERVICES

---

### RF Exposure

The equipment under test (EUT) is an Toy RC Gravity Rover Replaceable Batteries operating at 2.4G Band. The EUT can be powered by DC 6.0V (4 x 1.5V AA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -13.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -13.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 83.5dB $\mu$ V/m at 3m in the frequency 2405MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -11.73dBm  
which is within the production variation.

The Minimum peak radiated emission for the EUT is 79.6dB $\mu$ V/m at 3m in the frequency 2478MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -15.63dBm  
which is within the production variation.

The maximum conducted output power specified is -10.0dBm= 0.100mW

The source- based time-averaging conducted output power  
=0.100mW

The SAR Exclusion Threshold Level:

=  $3.0 \cdot (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$

=  $3.0 \cdot 5 / \text{sqrt} (2.478)$  mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.