



SAR TEST REPORT

For

Evolve 3 Holdings Pty Ltd

PO BOX 6222, NARRAWEENA NSW, Australia, 2099

FCC ID: 2AWLG-MEB116

Report Type: Original Report		Product Type: Maestro EBook	
Report Number:		RSZ200529002-SA	
Report Date:		2020-06-27	
Reviewed By:		Yates Li	<i>Yates Li</i>
		Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Attestation of Test Results			
EUT Information	EUT Description	Maestro EBook	
	Tested Model	Maestro-EBook11	
	FCC ID	2AWLG-MEB116	
	Serial Number	RSZ200529002-SA-S1	
	Test Date	2020/06/21 to 2020/06/24	
MODE		Max. SAR Level(s) Reported(W/kg)	Limit (W/kg)
WCDMA Band 2	1g Body SAR	0.75	1.6
WCDMA Band 5	1g Body SAR	0.30	
LTE Band 2	1g Body SAR	0.76	
LTE Band 4	1g Body SAR	0.43	
LTE Band 5	1g Body SAR	0.20	
LTE Band 12	1g Body SAR	0.46	
LTE Band 13	1g Body SAR	0.43	
LTE Band 66	1g Body SAR	0.63	
LTE Band 71	1g Body SAR	0.74	
WLAN 2.4G	1g Body SAR	0.39	
Simultaneous	1g Body SAR	0.86	
	1g Body SAR	0.86(Hotspot)	

Applicable Standards	<p>FCC 47 CFR part 2.1093 Radiofrequency radiation exposure evaluation: portable devices</p>
	<p>IEEE1528:2013 IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques</p>
	<p>IEC 62209-1:2016 Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz)</p>
	<p>KDB procedures KDB 447498 D01 General RF Exposure Guidance v06 KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04 KDB 865664 D02 RF Exposure Reporting v01r02 KDB 941225 D01 3G SAR Procedures v03r01 KDB 941225 D05 SAR for LTE Devices v02r05 KDB 248227 D01 802.11 Wi-Fi SAR v02r02 KDB 616217 D04 SAR for laptop and tablets v01r02 KDB 941225 D06 Hotspot Mode v02r01</p>
<p>Note: This wireless device has been shown to be capable of compliance for localized specific absorption rate (SAR) for General Population/Uncontrolled Exposure limits specified in FCC 47 CFR part 2.1093 and has been tested in accordance with the measurement procedures specified in IEEE 1528-2013 and RF exposure KDB procedures. The results and statements contained in this report pertain only to the device(s) evaluated.</p>	

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	5
EUT DESCRIPTION	6
TECHNICAL SPECIFICATION.....	6
REFERENCE, STANDARDS, AND GUIDELINES	7
SAR LIMITS	8
FACILITIES	9
DESCRIPTION OF TEST SYSTEM	10
EQUIPMENT LIST AND CALIBRATION	16
EQUIPMENTS LIST & CALIBRATION INFORMATION	16
SAR MEASUREMENT SYSTEM VERIFICATION	17
LIQUID VERIFICATION.....	17
SYSTEM ACCURACY VERIFICATION	19
SAR SYSTEM VALIDATION DATA	20
EUT TEST STRATEGY AND METHODOLOGY	25
CONDUCTED OUTPUT POWER MEASUREMENT	27
PROVISION APPLICABLE.....	27
TEST PROCEDURE.....	27
RADIO CONFIGURATION.....	27
MAXIMUM TARGET OUTPUT POWER.....	32
TEST RESULTS:.....	33
STANDALONE SAR TEST EXCLUSION CONSIDERATIONS	51
ANTENNA DISTANCE TO EDGE.....	51
SAR TEST EXCLUSION FOR THE EUT EDGE CONSIDERATIONS RESULT.....	52
SAR MEASUREMENT RESULTS	54
SAR TEST DATA	54
SAR MEASUREMENT VARIABILITY	60
SAR SIMULTANEOUS TRANSMISSION DESCRIPTION	61
SAR PLOTS	63
APPENDIX A MEASUREMENT UNCERTAINTY	64
APPENDIX B EUT TEST POSITION PHOTOS	66
APPENDIX C CALIBRATION CERTIFICATES	67

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	RSZ200529002-SA	Original Report	2020-06-27

EUT DESCRIPTION

This report has been prepared on behalf of *Evolve 3 Holdings Pty Ltd* and their product *Maestro EBook*, Model: *Maestro-EBook11*, FCC ID: **2AWLG-MEB116** or the EUT (Equipment under Test) as referred to in the rest of this report.

**All measurement and test data in this report was gathered from production sample serial number: RSZ200529002-SA-S1 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2020-06-01.*

Technical Specification

Device Type:	Notebook
Exposure Category:	Population / Uncontrolled
Antenna Type(s):	Internal Antenna
DTM Type:	Class B
Proximity sensor for SAR reduction:	None
Operation Mode :	WCDMA(R99 Data, HSDPA/HSUPA), FDD-LTE, WLAN, Bluetooth
Frequency Band:	WCDMA Band 2: 1850-1910 MHz(TX); 1930-1990 MHz(RX) WCDMA Band 5: 824-849 MHz(TX); 869-894 MHz(RX) LTE Band 2: 1850-1910 MHz(TX); 1930-1990 MHz(RX) LTE Band 4: 1710-1755 MHz(TX) ; 2110-2155 MHz(RX) LTE Band 5: 824-849 MHz(TX) ; 869-894 MHz(RX) LTE Band 12: 699-716MHz(TX); 729-746MHz(RX) LTE Band 13:: 777-787 MHz(TX) ; 746-756 MHz(RX) LTE Band 66: 1710-1780MHz(TX); 1710-1780MHz(RX) LTE Band 71: 663-698MHz(TX); 617-652MHz(RX) WLAN (2.4G): 2412 -2462 MHz Bluetooth : 2402 MHz-2480 MHz
Conducted RF Power:	WCDMA Band 2: 23.17 dBm WCDMA Band 5: 23.17 dBm LTE Band 2: 23.91 dBm LTE Band 4: 23.76 dBm LTE Band 5: 24.11 dBm LTE Band 12: 23.77 dBm LTE Band 13: 23.82 dBm LTE Band 66: 23.86 dBm LTE Band 71: 23.53 dBm WLAN (2.4G): 13.11 dBm Bluetooth(BDR/EDR): -2.88 dBm BLE: 0.47 dBm
Power Source:	Rechargeable Battery
Normal Operation:	Body-Support

REFERENCE, STANDARDS, AND GUIDELINES

FCC:

The Report and Order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g as recommended by the ANSI/IEEE standard C95.1-1992 [6] for an uncontrolled environment (Paragraph 65). According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in North America is 1.6 mW/g average over 1 gram of tissue mass.

CE:

The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 2 mW/g as recommended by EN62209-1 for an uncontrolled environment. According to the Standard, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in Europe is 2 mW/g average over 10 gram of tissue mass.

The test configurations were laid out on a specially designed test fixture to ensure the reproducibility of measurements. Each configuration was scanned for SAR. Analysis of each scan was carried out to characterize the above effects in the device.

SAR Limits

FCC Limit(1g Tissue)

EXPOSURE LIMITS	SAR (W/kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 1 g of tissue)	1.60	8.0
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0

CE Limit(10g Tissue)

EXPOSURE LIMITS	SAR (W/kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 10 g of tissue)	2.0	10
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0

Population/Uncontrolled Environments are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

General Population/Uncontrolled environments Spatial Peak limit 1.6W/kg (FCC) & 2 W/kg (CE) applied to the EUT.

FACILITIES


The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect data is located at 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.


DESCRIPTION OF TEST SYSTEM

These measurements were performed with the automated near-field scanning system DASY6 from Schmid & Partner Engineering AG (SPEAG) which is the Fifth generation of the system shown in the figure hereinafter:



DASY6 System Description

The DASY6 system for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot (Staubli TX=RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal application, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running Win7 professional operating system and the DASY52 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

DASY6 Measurement Server

The DASY6 measurement server is based on a PC/104 CPU board with a 400 MHz Intel ULV Celeron, 128 MB chip-disk and 128 MB RAM. The necessary circuits for communication with the DAE4 (or DAE3) electronics box, as well as the 16-bit AD converter system for optical detection and digital I/O interface are contained on the DASY6 I/O board, which is directly connected to the PC/104 bus of the CPU board.



The measurement server performs all real-time data evaluations of field measurements and surface detection, controls robot movements, and handles safety operations. The PC operating system cannot interfere with these time-critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with an expansion port, which is reserved for future applications. Please note that this expansion port does not have a standardized pinout, and therefore only devices provided by SPEAG can be connected. Connection of devices from any other supplier could seriously damage the measurement server.

Data Acquisition Electronics

The data acquisition electronics (DAE4) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of both the DAE4 as well as of the DAE3 box is 200M Ω ; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

EX3DV4 E-Field Probes

Frequency	10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)
Dynamic Range	10 µW/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 µW/g)
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.
Compatibility	DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI

SAM Twin Phantom

The SAM Twin Phantom (shown in front of DASY6) is a fiberglass shell phantom with shell thickness 2 mm, except in the ear region where the thickness is increased to 6 mm. The phantom has three measurement areas: 1) Left Head, 2) Right Head, and 3) Flat Section. For larger devices, the use of the ELI-Phantom (shown behind DASY6) is required. For devices such as glasses with a wireless link, the Face Down Phantom is the most suitable (between the SAM Twin and ELI phantoms).

When the phantom is mounted inside allocated slot of the DASY6 platform, phantom reference points can be taught directly in the DASY5 V5.2 software. When the DASY6 platform is used to mount the


Phantom, some of the phantom teaching points cannot be reached by the robot in DASY5 V5.2. A special tool called P1a-P2aX-Former is provided to transform two of the three points, P1 and P2, to reachable locations. To use these new teaching points, a revised phantom configuration file is required.

In addition to our standard broadband liquids, the phantom can be used with the following tissue simulating liquids:

Sugar-water-based liquids can be left permanently in the phantom. Always cover the liquid when the system is not in use to prevent changes in liquid parameters due to water evaporation.

DGBE-based liquids should be used with care. As DGBE is a softener for most plastics, the liquid should be taken out of the phantom, and the phantom should be dried when the system is not in use (desirable at least once a week).

Do not use other organic solvents without previously testing the solvent resistivity of the phantom. Approximately 25 liters of liquid is required to fill the SAM Twin phantom.



ELI Phantom

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30MHz to 6 GHz. ELI is fully compatible with the latest draft of the standard IEC 62209-2 and the use of all known tissue simulating liquids. ELI has been optimized for performance and can be integrated into a SPEAG standard phantom table. A cover is provided to prevent evaporation of water and changes in liquid parameters. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points.

The phantom can be used with the following tissue simulating liquids:

- Sugar-water-based liquids can be left permanently in the phantom. Always cover the liquid when the system is not in use to prevent changes in liquid parameters due to water evaporation.
- DGBE-based liquids should be used with care. As DGBE is a softener for most plastics, the liquid should be taken out of the phantom, and the phantom should be dried when the system is not in use (desirable at least once a week).
- Do not use other organic solvents without previously testing the solvent resistivity of the phantom.


Approximately 25 liters of liquid is required to fill the ELI phantom.

Robots

The DASY6 system uses the high-precision industrial robots TX60L, TX90XL, and RX160L from Staubli SA (France). The TX robot family - the successor of the well-known RX robot family - continues to offer the features important for DASY6 applications:

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements (brushless synchrony motors; no stepper motors)
- Low ELF interference (motor control fields shielded via the closed metallic construction shields)

The robots are controlled by the Staubli CS8c robot controllers. All information regarding the use and maintenance of the robot arm and the robot controller is provided



Calibration Frequency Points for EX3DV4 E-Field Probes SN: 7522 Calibrated: 2020/04/01

Calibration Frequency Point(MHz)	Frequency Range(MHz)		Conversion Factor		
	From	To	X	Y	Z
750 Head	650	850	9.92	9.92	9.92
900 Head	850	1000	9.4	9.4	9.4
1750 Head	1650	1850	8.21	8.21	8.21
1900 Head	1850	2000	7.95	7.95	7.95
2300 Head	2200	2400	7.53	7.53	7.53
2450 Head	2400	2550	7.15	7.15	7.15
2600 Head	2550	2700	7.04	7.04	7.04
5200 Head	5090	5250	5.2	5.2	5.2
5300 Head	5250	5410	4.96	4.96	4.96
5600 Head	5490	5700	4.55	4.55	4.55
5800 Head	5700	5910	4.65	4.65	4.65

Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 15mm 2 step integral, with 1.5mm interpolation used to locate the peak SAR area used for zoom scan assessments.

Where the system identifies multiple SAR peaks (which are within 25% of peak value) the system will provide the user with the option of assessing each peak location individually for zoom scan averaging.

Zoom Scan (Cube Scan Averaging)

The averaging zoom scan volume utilized in the DASY5 software is in the shape of a cube and the side dimension of a 1 g or 10 g mass is dependent on the density of the liquid representing the simulated tissue. A density of 1000 kg/m³ is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1g cube is 10mm, with the side length of the 10g cube is 21.5mm.

When the cube intersects with the surface of the phantom, it is oriented so that 3 vertices touch the surface of the shell or the center of a face is tangent to the surface. The face of the cube closest to the surface is modified in order to conform to the tangent surface.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications (including FCC) utilize a physical step of 7 x 7 x 7 (5mmx5mmx5mm) providing a volume of 30 mm in the X & Y & Z axis.

Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEC 62209-1:2016

Recommended Tissue Dielectric Parameters for Head and Body

Table A.3 – Dielectric properties of the head tissue-equivalent liquid

Frequency MHz	Relative permittivity ϵ_r	Conductivity (σ) S/m
300	45,3	0,87
450	43,5	0,87
<i>750</i>	<i>41,9</i>	<i>0,89</i>
835	41,5	0,90
900	41,5	0,97
1 450	40,5	1,20
<i>1 500</i>	<i>40,4</i>	<i>1,23</i>
<i>1 640</i>	<i>40,2</i>	<i>1,31</i>
<i>1 750</i>	<i>40,1</i>	<i>1,37</i>
1 800	40,0	1,40
1 900	40,0	1,40
2 000	40,0	1,40
<i>2 100</i>	<i>39,8</i>	<i>1,49</i>
<i>2 300</i>	<i>39,5</i>	<i>1,67</i>
2 450	39,2	1,80
<i>2 600</i>	<i>39,0</i>	<i>1,96</i>
3 000	38,5	2,40
<i>3 500</i>	<i>37,9</i>	<i>2,91</i>
<i>4 000</i>	<i>37,4</i>	<i>3,43</i>
<i>4 500</i>	<i>36,8</i>	<i>3,94</i>
<i>5 000</i>	<i>36,2</i>	<i>4,45</i>
<i>5 200</i>	<i>36,0</i>	<i>4,66</i>
<i>5 400</i>	<i>35,8</i>	<i>4,86</i>
<i>5 600</i>	<i>35,5</i>	<i>5,07</i>
<i>5 800</i>	<i>35,3</i>	<i>5,27</i>
6 000	35,1	5,48

NOTE For convenience, permittivity and conductivity values at those frequencies which are not part of the original data provided by Drossos et al. [33] or the extension to 5 800 MHz are provided (i.e. the values shown *in italics*). These values were linearly interpolated between the values in this table that are immediately above and below these values, except the values at 6 000 MHz that were linearly extrapolated from the values at 3 000 MHz and 5 800 MHz.


EQUIPMENT LIST AND CALIBRATION

Equipments List & Calibration Information

Equipment	Model	S/N	Calibration Date	Calibration Due Date
DASY5 Test Software	DASY52 52.10.2	N/A	NCR	NCR
DASY6 Measurement Server	DASY6 6.0.31	N/A	NCR	NCR
Data Acquisition Electronics	DAE4	1562	2020/03/03	2021/03/02
E-Field Probe	EX3DV4	7522	2020/04/01	2021/03/31
Mounting Device	MD4HHTV5	SD 000 H01 KA	NCR	NCR
SAM Twin Phantom	SAM-Twin V8.0	1962	NCR	NCR
Dipole, 750MHz	D750V3	1194	2020/1/13	2023/1/12
Dipole, 1800MHz	D1800V2	2d018	2017/10/11	2020/10/10
Dipole, 1900MHz	D1900V2	5d231	2020/1/14	2023/1/13
Dipole,2450MHz	D2450V2	751	2017/10/12	2020/10/11
Simulated Tissue Liquid Head	HBBL600-10000V6	180622-2	Each Time	
Network Analyzer	8753D	3410A08288	2019/7/22	2020/7/21
Dielectric Assessment Kit	DAK-3.5	1248	NCR	NCR
Anritsu Signal Generator	68369B	4114	2019/7/9	2020/7/8
USB wideband power sensor	U2021XA	MY54250003	2019/7/10	2020/7/9
Power Amplifier	5S1G4	71377	NCR	NCR
Directional Coupler	4242-10	3307	NCR	NCR
Attenuator	3dB	5402	NCR	NCR
Attenuator	10dB	AU 3842	NCR	NCR
Wireless communication tester	8960	MY48367501	2019/9/12	2020/9/11
WIDEBAND RADIO COMMUNICATION TESTER	CMW500	116218	2019/8/13	2020/8/12

SAR MEASUREMENT SYSTEM VERIFICATION

Liquid Verification



Liquid Verification Setup Block Diagram

Liquid Verification Results

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$	
673	Head	43.312	0.885	42.30	0.89	2.39	-0.56	± 5
683	Head	43.295	0.882	42.28	0.89	2.4	-0.9	± 5
688	Head	43.267	0.878	42.25	0.89	2.41	-1.35	± 5
704	Head	43.158	0.875	42.18	0.89	2.32	-1.69	± 5
707.5	Head	42.965	0.87	42.16	0.89	1.91	-2.25	± 5
711	Head	43.075	0.871	42.15	0.89	2.19	-2.13	± 5
750	Head	42.815	0.864	41.90	0.89	2.18	-2.92	± 5
782	Head	41.528	0.864	41.73	0.89	-0.048	-2.91	± 5
826.4	Head	40.672	0.864	41.54	0.90	-2.09	-4	± 5
829	Head	40.938	0.863	41.53	0.90	-1.43	-4.11	± 5
836.5	Head	40.772	0.879	41.5	0.90	-1.75	-2.33	± 5
836.6	Head	40.87	0.875	41.5	0.90	-1.52	-2.78	± 5
844	Head	40.996	0.908	41.5	0.91	-1.21	-0.22	± 5
846.6	Head	40.856	0.91	41.5	0.91	-1.55	0	± 5

*Liquid Verification above was performed on 2020/06/21.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$	
1720	Head	40.413	1.347	40.13	1.35	0.71	-0.22	±5
1732.5	Head	40.875	1.356	40.12	1.36	1.88	-0.29	±5
1745	Head	40.512	1.363	40.1	1.37	1.03	-0.51	±5
1770	Head	39.974	1.372	40.06	1.38	-0.21	-0.58	±5
1800	Head	39.882	1.383	40.0	1.40	-0.3	-1.21	±5

*Liquid Verification above was performed on 2020/06/24.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$	
1852.4	Head	39.706	1.375	40.0	1.40	-0.73	-1.79	±5
1880	Head	40.142	1.393	40.0	1.40	0.36	-0.5	±5
1900	Head	39.923	1.417	40.0	1.40	-0.19	1.21	±5
1907.6	Head	40.035	1.421	40.0	1.40	0.09	1.5	±5

*Liquid Verification above was performed on 2020/06/22.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$	
1860	Head	39.884	1.383	40.0	1.40	-0.29	-1.21	±5
1880	Head	40.017	1.396	40.0	1.40	0.04	-0.29	±5
1900	Head	39.956	1.428	40.0	1.40	-0.11	2	±5

*Liquid Verification above was performed on 2020/06/23.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$	
2412	Head	39.187	1.786	39.28	1.77	-0.24	0.9	±5
2437	Head	39.132	1.797	39.22	1.79	-0.22	0.39	±5
2450	Head	39.074	1.838	39.2	1.80	-0.32	2.11	±5
2462	Head	39.037	1.867	39.17	1.82	-0.34	2.58	±5

*Liquid Verification above was performed on 2020/06/21


System Accuracy Verification

Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of $\pm 10\%$. The validation results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

The spacing distances in the **System Verification Setup Block Diagram** is given by the following:

- a) $s = 15 \text{ mm} \pm 0,2 \text{ mm}$ for $300 \text{ MHz} \leq f \leq 1 \text{ 000 MHz}$;
- b) $s = 10 \text{ mm} \pm 0,2 \text{ mm}$ for $1 \text{ 000 MHz} < f \leq 3 \text{ 000 MHz}$;
- c) $s = 10 \text{ mm} \pm 0,2 \text{ mm}$ for $3 \text{ 000 MHz} < f \leq 6 \text{ 000 MHz}$.

System Verification Setup Block Diagram



System Accuracy Check Results

Date	Frequency Band (MHz)	Liquid Type	Input Power (mW)	Measured SAR (W/kg)	Normalized to 1W (W/kg)	Target Value (W/Kg)	Delta (%)	Tolerance (%)
2020/06/21	750	Head	100	1g 0.868	8.68	8.55	1.520	± 10
2020/06/24	1800	Head	100	1g 3.83	38.3	38.5	-0.519	± 10
2020/06/22	1900	Head	100	1g 3.97	39.7	40.3	-1.489	± 10
2020/06/23	1900	Head	100	1g 4.06	40.6	40.3	0.744	± 10
2020/06/21	2450	Head	100	1g 5.21	52.1	52.5	-0.762	± 10

*The SAR values above are normalized to 1 Watt forward power.

SAR SYSTEM VALIDATION DATA

System Performance 750 MHz Head

DUT: Dipole 750MHz; Type: D750V3; Serial: 1194


Communication System: UID 0, CW (0); Frequency: 750 MHz;Duty Cycle: 1:1
 Medium parameters used: $f = 750 \text{ MHz}$; $\sigma = 0.864 \text{ S/m}$; $\epsilon_r = 42.815$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7522; ConvF(9.92, 9.92, 9.92) @ 750 MHz;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1562; Calibrated: 3/3/2020
- Phantom: SAM-Twin V8.0 P1aP2a; Type: QD 000 P41 AA ; Serial: 1962
- Measurement SW: DASY52, Version 52.10 (2);

Head 750MHz Pin=100mW/Area Scan (71x111x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$
 Maximum value of SAR (interpolated) = 0.894 W/kg

Head 750MHz Pin=100mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
 Reference Value = 45.71 V/m ; Power Drift = -0.12 dB
 Peak SAR (extrapolated) = 1.25 W/kg
SAR(1 g) = 0.868 W/kg ; SAR(10 g) = 0.542 W/kg
 Maximum value of SAR (measured) = 0.883 W/kg



0 dB = $0.883 \text{ W/kg} = -0.54 \text{ dBW/kg}$

System Performance 1800 MHz Head

DUT: Dipole 1800 MHz; Type: D1800V2; Serial: 2d018

Communication System: UID 0, CW (0); Frequency: 1800 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 1800 \text{ MHz}$; $\sigma = 1.383 \text{ S/m}$; $\epsilon_r = 39.882$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7522; ConvF(8.21, 8.21, 8.21) @ 1800 MHz;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1562; Calibrated: 3/3/2020
- Phantom: SAM-Twin V8.0 P1aP2a; Type: QD 000 P41 AA ; Serial: 1962
- Measurement SW: DASY52, Version 52.10 (2);


Head 1800MHz Pin=100mW 2/Area Scan (81x101x1): Interpolated grid: $dx=1.200 \text{ mm}$, $dy=1.200 \text{ mm}$
 Maximum value of SAR (interpolated) = 5.65 W/kg

Head 1800MHz Pin=100mW 2/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
 Reference Value = 48.57 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 6.97 W/kg

SAR(1 g) = 3.83 W/kg; SAR(10 g) = 2.25 W/kg

Maximum value of SAR (measured) = 4.27 W/kg



0 dB = 4.27 W/kg = 6.30 dBW/kg

System Performance 1900 MHz Head (Test on 2020/06/22)

DUT: Dipole 1900MHz; Type: D1900V2; Serial: 5d231


Communication System: UID 0, CW (0); Frequency: 1900 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 1900 \text{ MHz}$; $\sigma = 1.417 \text{ S/m}$; $\epsilon_r = 39.923$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7522; ConvF(7.95, 7.95, 7.95) @ 1900 MHz;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1562; Calibrated: 3/3/2020
- Phantom: SAM-Twin V8.0 P1aP2a; Type: QD 000 P41 AA ; Serial: 1962
- Measurement SW: DASY52, Version 52.10 (2);

Head 1900MHz Pin=100mW 2/Area Scan (81x121x1): Interpolated grid: $dx=1.000 \text{ mm}$, $dy=1.000 \text{ mm}$
 Maximum value of SAR (interpolated) = 5.87 W/kg

Head 1900MHz Pin=100mW 2/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
 Reference Value = 57.29 V/m; Power Drift = -0.02 dB
 Peak SAR (extrapolated) = 7.56 W/kg
SAR(1 g) = 3.97 W/kg; SAR(10 g) = 2.08 W/kg
 Maximum value of SAR (measured) = 4.61 W/kg



0 dB = 4.61 W/kg = 6.61 dBW/kg

System Performance 1900 MHz Head (Test on 2020/06/23)

DUT: Dipole 1900MHz; Type: D1900V2; Serial: 5d231


Communication System: UID 0, CW (0); Frequency: 1900 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 1900 \text{ MHz}$; $\sigma = 1.428 \text{ S/m}$; $\epsilon_r = 39.956$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7522; ConvF(7.95, 7.95, 7.95) @ 1900 MHz;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1562; Calibrated: 3/3/2020
- Phantom: SAM-Twin V8.0 P1aP2a; Type: QD 000 P41 AA ; Serial: 1962
- Measurement SW: DASY52, Version 52.10 (2);

Head 1900MHz Pin=100mW 2/Area Scan (81x121x1): Interpolated grid: $dx=1.000 \text{ mm}$, $dy=1.000 \text{ mm}$
 Maximum value of SAR (interpolated) = 5.95 W/kg

Head 1900MHz Pin=100mW 2/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
 Reference Value = 58.19 V/m; Power Drift = -0.06 dB
 Peak SAR (extrapolated) = 7.28 W/kg
SAR(1 g) = 4.06 W/kg; SAR(10 g) = 2.38 W/kg
 Maximum value of SAR (measured) = 4.82 W/kg



0 dB = 4.82 W/kg = 6.83 dBW/kg

System Performance 2450 MHz Head

DUT: Dipole 2450MHz; Type: D2450V2; Serial: 751

Communication System: UID 0, CW (0); Frequency: 2450 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 2450 \text{ MHz}$; $\sigma = 1.838 \text{ S/m}$; $\epsilon_r = 39.074$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7522; ConvF(7.15, 7.15, 7.15) @ 2450 MHz;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1562; Calibrated: 3/3/2020
- Phantom: SAM-Twin V8.0 P1aP2a; Type: QD 000 P41 AA ; Serial: 1962
- Measurement SW: DASY52, Version 52.10 (2);


Head 2450MHz Pin=100mW 2/Area Scan (81x121x1): Interpolated grid: $dx=1.000 \text{ mm}$, $dy=1.000 \text{ mm}$
 Maximum value of SAR (interpolated) = 8.23 W/kg

Head 2450MHz Pin=100mW 2/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
 Reference Value = 43.28 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 13.1 W/kg

SAR(1 g) = 5.21 W/kg; SAR(10 g) = 2.18 W/kg

Maximum value of SAR (measured) = 5.47 W/kg



0 dB = 5.47 W/kg = 7.83 dBW/kg


EUT TEST STRATEGY AND METHODOLOGY

Test positions for Body-supported device

A typical example of a body supported device is a wireless enabled laptop device that among other orientations may be supported on the thighs of a sitting user. To represent this orientation, the device shall be positioned with its base against the flat phantom. Other orientations may be specified by the manufacturer in the user instructions. If the intended use is not specified, the device shall be tested directly against the flat phantom in all usable orientations.

The screen portion of the device shall be in an open position at a 90° angle as seen in Figure below (left side), or at an operating angle specified for intended use by the manufacturer in the operating instructions. Where a body supported device has an integral screen required for normal operation, then the screen-side will not need to be tested if it ordinarily remains 200 mm from the body. Where a screen mounted antenna is present, this position shall be repeated with the screen against the flat phantom as shown in Figure below (right side), if this is consistent with the intended use.

Other devices that fall into this category include tablet type portable computers and credit card transaction authorisation terminals, point-of-sale and/or inventory terminals. Where these devices may be torso or limb-supported, the same principles for body-supported devices are applied.



a) Portable computer with external antenna plug-in-radio-card (left side) or with internal antenna located in screen section (right side)

SAR Evaluation Procedure

The evaluation was performed with the following procedure:

Step 1: Measurement of the SAR value at a fixed location above the ear point or central position was used as a reference value for assessing the power drop. The SAR at this point is measured at the start of the test and then again at the end of the testing.

Step 2: The SAR distribution at the exposed side of the head was measured at a distance of 4 mm from the inner surface of the shell. The area covered the entire dimension of the head or EUT and the horizontal grid spacing was 10 mm x 10 mm. Based on these data, the area of the maximum absorption was determined by spline interpolation. The first Area Scan covers the entire dimension of the EUT to ensure that the hotspot was correctly identified.

Step 3: Around this point, a volume of 30 mm x 30 mm x 30 mm was assessed by measuring 7x 7 x 7 points. On the basis of this data set, the spatial peak SAR value was evaluated under the following procedure:

- 1) The data at the surface were extrapolated, since the center of the dipoles is 1.2 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.3 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axis. This polynomial was then used to evaluate the points between the surface and the probe tip.

- 2) The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g or 10 g) were computed by the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one dimensional splines with the "Not a knot"-condition (in x, y and z-directions). The volume was integrated with the trapezoidal-algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the averages. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

Step 4: Re-measurement of the SAR value at the same location as in Step 1. If the value changed by more than 5%, the evaluation was repeated.


CONDUCTED OUTPUT POWER MEASUREMENT

Provision Applicable

The measured peak output power should be greater and within 5% than EMI measurement.

Test Procedure

The RF output of the transmitter was connected to the input of the EMI Test Receiver through Connector.



WCDMA/LTE

Radio Configuration

The power measurement was configured by the Wireless Communication Test Set.

WCDMA Release 99

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification. The EUT has a nominal maximum output power of 24dBm (+1.7/-3.7).

WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β_c/β_d	8/15

HSDPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode Subset	HSDPA 1	HSDPA 2	HSDPA 3	HSDPA 4
WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm2			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	$\beta_d(SF)$	64			
	β_c/β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
	MPR(dB)	0	0	0.5	0.5
HSDPA Specific Settings	DACK	8			
	DNAK	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback	4ms			
	CQI Repetition Factor	2			
	$A_{hs}=\beta_{hs}/\beta_c$	30/15			

HSUPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA
	Subset	1	2	3	4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{cc}	209/225	12/15	30/15	2/15	5/15
	β_c / β_d	11/15	6/15	15/9	2/15	-
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	CM(dB)	1.0	3.0	2.0	3.0	1.0
MPR(dB)	0	2	1	2	0	
HSDPA Specific Settings	DACK	8				
	DNAK	8				
	DCQI	8				
	Ack-Nack repetition factor	3				
	CQI Feedback	4ms				
	CQI Repetition Factor	2				
	$A_{hs} = \beta_{hs} / \beta_c$	30/15				
HSUPA Specific Settings	DE-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E_FCIs	E-TFCI 11 E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E-TFCI PO4 E-TFCI 92 E-TFCI PO 18	E-TFCI 11 E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27		

DC-HSDPA

The following tests were conducted according to the test requirements in Table C.8.1.12 of 3GPP TS 34.121-1

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1:	The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.	
Note 2:	Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.	

FDD-LTE

For UE Power Class 1 and 3, the allowed Maximum Power Reduction (MPR) for the maximum output power in Table 6.2.2-1 due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1 and 3

Modulation	Channel bandwidth / Transmission bandwidth (N_{RB})						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

For UE Power Class 1 and 3 the specific requirements and identified sub clauses are specified in Table 6.2.4-1 along with the allowed A-MPR values that may be used to meet these requirements. The allowed A-MPR values specified below in Table 6.2.4.-1 to 6.2.4-15 are in addition to the allowed MPR requirements specified in sub clause 6.2.3.

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (subclause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	N/A
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
NS_05	6.6.3.3.1	1	10, 15, 20	Table 6.2.4-4	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	N/A
NS_07	6.6.2.2.3	13	10	Table 6.2.4-2	
6.6.3.3.2					
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
				Table 6.2.4-3	
NS_11	6.6.2.2.1	23	1.4, 3, 5, 10, 15, 20	Table 6.2.4-5	
NS_12	6.6.3.3.5	26	1.4, 3, 5	Table 6.2.4-6	
NS_13	6.6.3.3.6	26	5	Table 6.2.4-7	
NS_14	6.6.3.3.7	26	10, 15	Table 6.2.4-8	
NS_15	6.6.3.3.8	26	1.4, 3, 5, 10, 15	Table 6.2.4-9 Table 6.2.4-10	
NS_16	6.6.3.3.9	27	3, 5, 10	Table 6.2.4-11, Table 6.2.4-12, Table 6.2.4-13	
NS_17	6.6.3.3.10	28	5, 10	Table 5.6-1	N/A
NS_18	6.6.3.3.11	28	5	≥ 2	≤ 1
			10, 15, 20	≥ 1	≤ 4
NS_19	6.6.3.3.12	44	10, 15, 20	Table 6.2.4-14	
NS_20	6.2.2 6.6.2.2.1 6.6.3.2	23	5, 10, 15, 20	Table 6.2.4-15	
...					
NS_32	-	-	-	-	-

Maximum Target Output Power

Max Target Power(dBm)			
Mode/Band	Channel		
	Low	Middle	High
WCDMA Band 2	25	25	25
WCDMA Band 5	25	25	25
LTE Band 2	25	25	25
LTE Band 4	25	25	25
LTE Band 5	25	25	25
LTE Band 12	25	25	25
LTE Band 13	25	25	25
LTE Band 66	25	25	25
LTE Band 71	25	25	25
WLAN 2.4G(802.11b)	13.0	13.5	13.5
WLAN 2.4G(802.11g)	8.0	8.5	8.0
WLAN 2.4G(802.11n HT20)	6.0	6.0	6.5
WLAN 2.4G(802.11n HT40)	6.5	7.0	7.0
Bluetooth BDR/EDR	-3.0	-3.5	-2.5
Bluetooth BLE	0.0	0.0	0.5

Test Results:

WCDMA Band 2:

Test Condition	Test Mode	3GPP Sub Test	Averaged Mean Power (dBm)		
			Low Frequency	Mid Frequency	High Frequency
Normal	RMC12.2k		24.17	24.80	23.83
	HSDPA	1	22.20	22.08	22.02
		2	22.18	22.07	21.99
		3	22.79	21.65	21.48
		4	21.74	21.54	21.58
	HSUPA	1	22.23	22.10	22.01
		2	21.75	21.58	21.58
		3	22.16	22.10	22.01
		4	22.39	22.21	22.21
		5	22.19	22.15	22.04
	DC- HSDPA	1	23.04	23.02	22.98
		2	23.16	22.98	22.96
		3	22.63	22.45	22.44
		4	22.53	22.46	22.47

WCDMA Band 5:

Test Condition	Test Mode	3GPP Sub Test	Averaged Mean Power (dBm)		
			Low Frequency	Mid Frequency	High Frequency
Normal	RMC12.2k		23.17	23.11	23.14
	HSDPA	1	22.20	22.24	22.32
		2	22.17	22.23	22.24
		3	21.77	21.66	21.68
		4	21.71	21.61	21.70
	HSUPA	1	22.07	22.32	22.24
		2	21.72	21.62	21.77
		3	22.16	22.28	22.25
		4	22.23	22.27	22.18
		5	22.22	22.16	22.21
	DC- HSDPA	1	23.03	23.03	23.07
		2	23.16	23.04	23.03
		3	22.61	22.57	22.61
		4	22.68	22.46	22.54

Note:

1. The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2 kbps RMC (reference measurement Channel) Configured in Test Loop Model 1.
2. KDB 941225 D01-Body SAR is not required for HSDPA/HSUPA when the maximum average output of each RF channel is less than ¼ dB higher than measured 12.2kbps RMC or the maximum SAR for 12.2kbps RMC is < 75% of SAR limit.

LTE Band 2:

BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1850.7MHz	1880MHz	1909.3MHz
1.4	QPSK	RB Size=1, RB Offset=0	0	0	23.37	23.40	22.96
		RB Size=1, RB Offset=2	0	0	23.47	23.73	22.98
		RB Size=1, RB Offset=5	0	0	23.29	23.19	22.94
		RB Size=3, RB Offset=0	1	1	23.32	23.22	23.08
		RB Size=3, RB Offset=2	1	1	22.18	23.11	23.28
		RB Size=3, RB Offset=3	1	1	23.36	23.27	22.91
		RB Size=6, RB Offset=0	1	1	22.27	22.52	22.05
	16QAM	RB Size=1, RB Offset=0	1	1	22.44	22.88	22.75
		RB Size=1, RB Offset=2	1	1	22.34	22.91	23.04
		RB Size=1, RB Offset=5	1	1	22.18	22.95	23.06
		RB Size=3, RB Offset=0	2	2	22.31	22.26	22.24
		RB Size=3, RB Offset=2	2	2	22.39	22.16	22.04
		RB Size=3, RB Offset=3	2	2	22.24	22.36	22.08
		RB Size=6, RB Offset=0	2	2	21.42	21.30	21.32
BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1851.5MHz	1880MHz	1908.5MHz
3	QPSK	RB Size=1, RB Offset=0	0	0	23.38	23.44	23.09
		RB Size=1, RB Offset=7	0	0	23.44	23.78	23.09
		RB Size=1, RB Offset=14	0	0	23.36	23.35	22.98
		RB Size=8, RB Offset=0	1	1	22.41	22.33	22.32
		RB Size=8, RB Offset=4	1	1	22.35	22.19	22.32
		RB Size=8, RB Offset=7	1	1	22.50	22.45	22.05
		RB Size=15, RB Offset=0	1	1	22.20	22.47	22.08
	16QAM	RB Size=1, RB Offset=0	1	1	22.47	22.96	22.62
		RB Size=1, RB Offset=7	1	1	22.42	23.07	23.04
		RB Size=1, RB Offset=14	1	1	22.22	22.99	23.09
		RB Size=8, RB Offset=0	2	2	21.44	21.27	21.28
		RB Size=8, RB Offset=4	2	2	21.53	21.34	21.12
		RB Size=8, RB Offset=7	2	2	21.50	21.34	21.11
		RB Size=15, RB Offset=0	2	2	21.47	21.37	21.33

BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1852.5MHz	1880MHz	1907.5MHz
5	QPSK	RB Size=1, RB Offset=0	0	0	23.28	23.51	23.00
		RB Size=1, RB Offset=13	0	0	23.46	23.74	23.04
		RB Size=1, RB Offset=24	0	0	23.34	23.26	22.99
		RB Size=12, RB Offset=0	1	1	22.43	23.37	22.16
		RB Size=12, RB Offset=6	1	1	22.26	22.15	22.35
		RB Size=12, RB Offset=13	1	1	22.38	22.33	21.87
		RB Size=25, RB Offset=0	1	1	22.29	22.52	22.08
	16QAM	RB Size=1, RB Offset=0	1	1	22.44	22.98	22.63
		RB Size=1, RB Offset=13	1	1	22.35	23.05	22.97
		RB Size=1, RB Offset=24	1	1	22.14	23.01	22.94
		RB Size=12, RB Offset=0	2	2	21.38	21.36	21.23
		RB Size=12, RB Offset=6	2	2	21.55	21.24	21.16
		RB Size=12, RB Offset=13	2	2	21.42	21.42	21.12
		RB Size=25, RB Offset=0	2	2	21.45	21.25	21.23
BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1855MHz	1880MHz	1905MHz
10	QPSK	RB Size=1, RB Offset=0	0	0	23.33	23.51	22.95
		RB Size=1, RB Offset=25	0	0	23.50	23.91	23.05
		RB Size=1, RB Offset=49	0	0	23.31	23.30	23.01
		RB Size=25, RB Offset=0	1	1	22.39	22.38	22.28
		RB Size=25, RB Offset=13	1	1	22.27	22.19	22.28
		RB Size=25, RB Offset=25	1	1	22.54	22.38	22.04
		RB Size=50, RB Offset=0	1	1	22.32	22.53	22.11
	16QAM	RB Size=1, RB Offset=0	1	1	22.43	22.93	22.74
		RB Size=1, RB Offset=25	1	1	22.43	23.01	23.04
		RB Size=1, RB Offset=49	1	1	22.14	23.03	23.10
		RB Size=25, RB Offset=0	2	2	21.40	21.39	21.31
		RB Size=25, RB Offset=13	2	2	21.51	21.24	21.13
		RB Size=25, RB Offset=25	2	2	21.45	21.48	21.25
		RB Size=50, RB Offset=0	2	2	21.43	21.32	21.38

BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1857.5MHz	1880MHz	1902.5MHz
15	QPSK	RB Size=1, RB Offset=0	0	0	23.39	23.45	23.07
		RB Size=1, RB Offset=38	0	0	23.36	23.87	22.93
		RB Size=1, RB Offset=74	0	0	23.37	23.20	22.95
		RB Size=36, RB Offset=0	1	1	22.35	22.41	22.22
		RB Size=36, RB Offset=18	1	1	22.33	22.10	22.22
		RB Size=36, RB Offset=39	1	1	22.45	22.31	21.99
		RB Size=75, RB Offset=0	1	1	22.28	22.57	22.01
	16QAM	RB Size=1, RB Offset=0	1	1	22.31	22.93	22.66
		RB Size=1, RB Offset=38	1	1	22.47	22.96	23.01
		RB Size=1, RB Offset=74	1	1	22.23	23.03	22.97
		RB Size=36, RB Offset=0	2	2	21.41	21.36	21.27
		RB Size=36, RB Offset=18	2	2	21.42	21.27	21.15
		RB Size=36, RB Offset=39	2	2	21.38	21.42	21.08
		RB Size=75, RB Offset=0	2	2	21.35	21.28	21.27
BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1860MHz	1880MHz	1900MHz
20	QPSK	RB Size=1, RB Offset=0	0	0	23.82	24.1	23.18
		RB Size=1, RB Offset=50	0	0	23.40	23.72	23.03
		RB Size=1, RB Offset=99	0	0	23.33	23.16	22.82
		RB Size=50, RB Offset=0	1	1	23.44	23.6	23.15
		RB Size=50, RB Offset=25	1	1	22.27	22.15	22.23
		RB Size=50, RB Offset=50	1	1	22.43	22.25	22.01
		RB Size=100, RB Offset=0	1	1	22.24	22.39	22.04
	16QAM	RB Size=1, RB Offset=0	0	0	22.33	22.84	22.55
		RB Size=1, RB Offset=50	0	0	22.35	22.93	23.05
		RB Size=1, RB Offset=99	0	0	22.19	22.92	23.05
		RB Size=50, RB Offset=0	1	1	21.42	21.25	21.18
		RB Size=50, RB Offset=25	1	1	21.50	21.15	21.08
		RB Size=50, RB Offset=50	1	1	21.38	21.33	21.13
		RB Size=100, RB Offset=0	1	1	21.33	21.24	21.32

LTE Band 4:

BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1710.7MHz	1732.5MHz	1754.3MHz
1.4	QPSK	RB Size=1, RB Offset=0	0	0	23.51	23.19	23.48
		RB Size=1, RB Offset=2	0	0	23.36	23.53	23.52
		RB Size=1, RB Offset=5	0	0	23.27	23.57	23.61
		RB Size=3, RB Offset=0	1	1	23.29	23.26	23.47
		RB Size=3, RB Offset=2	1	1	23.28	23.27	23.38
		RB Size=3, RB Offset=3	1	1	23.28	23.40	23.47
	16QAM	RB Size=6, RB Offset=0	1	1	22.38	22.42	22.70
		RB Size=1, RB Offset=0	1	1	22.39	22.18	23.30
		RB Size=1, RB Offset=2	1	1	22.58	22.72	23.13
		RB Size=1, RB Offset=5	1	1	22.38	23.01	23.34
		RB Size=3, RB Offset=0	2	2	22.26	22.28	22.52
		RB Size=3, RB Offset=2	2	2	22.28	22.37	22.18
		RB Size=3, RB Offset=3	2	2	22.33	22.49	22.47
		RB Size=6, RB Offset=0	2	2	21.29	21.47	21.62
BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1711.5MHz	1732.5MHz	1753.5MHz
3	QPSK	RB Size=1, RB Offset=0	0	0	23.63	23.28	23.40
		RB Size=1, RB Offset=7	0	0	23.46	23.66	23.47
		RB Size=1, RB Offset=14	0	0	23.18	23.54	23.71
		RB Size=8, RB Offset=0	1	1	22.50	22.41	22.67
		RB Size=8, RB Offset=4	1	1	22.48	22.38	22.55
		RB Size=8, RB Offset=7	1	1	22.32	22.58	22.52
		RB Size=15, RB Offset=0	1	1	22.28	22.40	22.60
	16QAM	RB Size=1, RB Offset=0	1	1	22.51	22.25	23.29
		RB Size=1, RB Offset=7	1	1	22.52	22.80	23.14
		RB Size=1, RB Offset=14	1	1	22.47	23.02	23.37
		RB Size=8, RB Offset=0	2	2	21.36	21.53	21.50
		RB Size=8, RB Offset=4	2	2	21.41	21.49	21.30
		RB Size=8, RB Offset=7	2	2	21.55	21.65	21.58
		RB Size=15, RB Offset=0	2	2	21.43	21.58	21.78

BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1712.5MHz	1732.5MHz	1752.5MHz
5	QPSK	RB Size=1, RB Offset=0	0	0	23.57	23.27	23.48
		RB Size=1, RB Offset=13	0	0	23.45	23.55	23.51
		RB Size=1, RB Offset=24	0	0	23.22	23.61	23.76
		RB Size=12, RB Offset=0	1	1	22.34	22.36	22.60
		RB Size=12, RB Offset=6	1	1	22.38	22.35	22.55
		RB Size=12, RB Offset=13	1	1	22.35	22.56	22.47
		RB Size=25, RB Offset=0	1	1	22.22	22.38	22.71
	16QAM	RB Size=1, RB Offset=0	1	1	22.36	22.30	23.20
		RB Size=1, RB Offset=13	1	1	22.57	22.86	23.17
		RB Size=1, RB Offset=24	1	1	22.33	23.07	23.37
		RB Size=12, RB Offset=0	2	2	21.30	21.48	21.44
		RB Size=12, RB Offset=6	2	2	21.34	21.53	21.34
		RB Size=12, RB Offset=13	2	2	21.38	21.46	21.51
		RB Size=25, RB Offset=0	2	2	21.34	21.54	21.71
BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1715MHz	1732.5MHz	1750MHz
10	QPSK	RB Size=1, RB Offset=0	0	0	23.53	23.23	23.45
		RB Size=1, RB Offset=25	0	0	23.41	23.64	23.47
		RB Size=1, RB Offset=49	0	0	23.16	23.63	23.63
		RB Size=25, RB Offset=0	1	1	22.40	22.35	22.60
		RB Size=25, RB Offset=13	1	1	22.41	22.49	22.49
		RB Size=25, RB Offset=25	1	1	22.35	22.52	22.55
		RB Size=50, RB Offset=0	1	1	22.31	22.49	22.74
	16QAM	RB Size=1, RB Offset=0	1	1	22.45	22.25	23.26
		RB Size=1, RB Offset=25	1	1	22.62	22.94	23.18
		RB Size=1, RB Offset=49	1	1	22.38	23.08	23.38
		RB Size=25, RB Offset=0	2	2	21.27	21.53	21.53
		RB Size=25, RB Offset=13	2	2	21.44	21.44	21.43
		RB Size=25, RB Offset=25	2	2	21.51	21.52	21.55
		RB Size=50, RB Offset=0	2	2	21.36	21.53	21.69

BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1717.5MHz	1732.5MHz	1747.5MHz
15	QPSK	RB Size=1, RB Offset=0	0	0	23.52	23.19	23.46
		RB Size=1, RB Offset=38	0	0	23.54	23.65	23.51
		RB Size=1, RB Offset=74	0	0	23.17	23.52	23.63
		RB Size=36, RB Offset=0	1	1	22.38	22.33	22.64
		RB Size=36, RB Offset=18	1	1	22.44	22.36	22.41
		RB Size=36, RB Offset=39	1	1	22.39	22.45	22.50
		RB Size=75, RB Offset=0	1	1	22.45	22.34	22.56
	16QAM	RB Size=1, RB Offset=0	1	1	22.42	22.30	23.25
		RB Size=1, RB Offset=38	1	1	22.52	22.86	23.16
		RB Size=1, RB Offset=74	1	1	22.29	22.95	23.34
		RB Size=36, RB Offset=0	2	2	21.37	21.44	21.53
		RB Size=36, RB Offset=18	2	2	21.37	21.50	21.30
		RB Size=36, RB Offset=39	2	2	21.45	21.56	21.49
		RB Size=75, RB Offset=0	2	2	21.37	21.54	21.58
BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1720MHz	1732.5MHz	1745MHz
20	QPSK	RB Size=1, RB Offset=0	0	0	23.52	23.12	23.34
		RB Size=1, RB Offset=50	0	0	23.38	23.60	23.52
		RB Size=1, RB Offset=99	0	0	23.12	23.54	23.61
		RB Size=50, RB Offset=0	1	1	22.38	22.19	22.61
		RB Size=50, RB Offset=25	1	1	22.42	22.38	22.39
		RB Size=50, RB Offset=50	1	1	22.42	22.54	22.41
		RB Size=100, RB Offset=0	1	1	22.32	22.34	22.54
	16QAM	RB Size=1, RB Offset=0	1	1	22.40	22.25	23.17
		RB Size=1, RB Offset=50	1	1	22.42	22.87	23.20
		RB Size=1, RB Offset=99	1	1	22.29	22.93	23.27
		RB Size=50, RB Offset=0	2	2	21.29	21.42	21.49
		RB Size=50, RB Offset=25	2	2	21.38	21.49	21.38
		RB Size=50, RB Offset=50	2	2	21.48	21.56	21.60
		RB Size=100, RB Offset=0	2	2	21.41	21.42	21.55

LTE Band 5:

BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					824.7MHz	836.5MHz	848.3MHz
1.4	QPSK	RB Size=1, RB Offset=0	0	0	23.80	23.99	23.87
		RB Size=1, RB Offset=2	0	0	23.88	23.84	24.05
		RB Size=1, RB Offset=5	0	0	23.92	23.82	23.76
		RB Size=3, RB Offset=0	1	1	23.72	23.71	23.70
		RB Size=3, RB Offset=2	1	1	23.68	23.82	23.75
		RB Size=3, RB Offset=3	1	1	23.81	23.78	23.82
		RB Size=6, RB Offset=0	1	1	22.83	22.95	22.93
	16QAM	RB Size=1, RB Offset=0	1	1	23.52	23.03	22.76
		RB Size=1, RB Offset=2	1	1	23.12	23.38	22.69
		RB Size=1, RB Offset=5	1	1	23.31	23.00	22.66
		RB Size=3, RB Offset=0	2	2	22.63	22.61	22.83
		RB Size=3, RB Offset=2	2	2	22.77	22.65	22.66
		RB Size=3, RB Offset=3	2	2	22.77	22.66	22.60
		RB Size=6, RB Offset=0	2	2	23.80	23.99	23.87
BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					825.5MHz	836.5MHz	847.5MHz
3	QPSK	RB Size=1, RB Offset=0	0	0	23.80	23.89	23.77
		RB Size=1, RB Offset=7	0	0	23.84	23.88	24.11
		RB Size=1, RB Offset=14	0	0	24.02	23.97	23.85
		RB Size=8, RB Offset=0	1	1	22.84	22.84	22.94
		RB Size=8, RB Offset=4	1	1	22.76	22.81	22.91
		RB Size=8, RB Offset=7	1	1	22.99	22.82	22.81
		RB Size=15, RB Offset=0	1	1	22.77	22.95	22.87
	16QAM	RB Size=1, RB Offset=0	1	1	23.43	23.05	22.86
		RB Size=1, RB Offset=7	1	1	23.10	23.51	22.77
		RB Size=1, RB Offset=14	1	1	23.24	23.10	22.73
		RB Size=8, RB Offset=0	2	2	21.67	21.74	21.93
		RB Size=8, RB Offset=4	2	2	21.97	21.82	21.75
		RB Size=8, RB Offset=7	2	2	21.92	21.74	21.72
		RB Size=15, RB Offset=0	2	2	21.76	21.83	21.81

BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					826.5MHz	836.5MHz	846.5MHz
5	QPSK	RB Size=1, RB Offset=0	0	0	23.84	23.94	23.80
		RB Size=1, RB Offset=13	0	0	23.85	23.93	24.07
		RB Size=1, RB Offset=24	0	0	23.93	23.91	23.79
		RB Size=12, RB Offset=0	1	1	22.68	22.77	22.77
		RB Size=12, RB Offset=6	1	1	22.82	22.80	22.82
		RB Size=12, RB Offset=13	1	1	22.95	22.90	22.79
		RB Size=25, RB Offset=0	1	1	22.84	22.97	22.82
	16QAM	RB Size=1, RB Offset=0	1	1	23.36	23.06	22.80
		RB Size=1, RB Offset=13	1	1	23.20	23.51	22.65
		RB Size=1, RB Offset=24	1	1	23.27	23.07	22.62
		RB Size=12, RB Offset=0	2	2	21.70	21.75	21.83
		RB Size=12, RB Offset=6	2	2	21.80	21.63	21.75
		RB Size=12, RB Offset=13	2	2	21.87	21.77	21.58
		RB Size=25, RB Offset=0	2	2	21.66	21.83	21.73
BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					829MHz	836.5MHz	844MHz
10	QPSK	RB Size=1, RB Offset=0	0	0	23.73	23.88	23.82
		RB Size=1, RB Offset=25	0	0	23.91	23.96	23.97
		RB Size=1, RB Offset=49	0	0	23.96	23.91	23.81
		RB Size=25, RB Offset=0	1	1	22.74	22.65	22.77
		RB Size=25, RB Offset=13	1	1	22.74	22.73	22.74
		RB Size=25, RB Offset=25	1	1	22.80	22.75	22.76
		RB Size=50, RB Offset=0	1	1	22.83	22.92	22.83
	16QAM	RB Size=1, RB Offset=0	1	1	23.25	22.99	22.74
		RB Size=1, RB Offset=25	1	1	23.17	23.39	22.72
		RB Size=1, RB Offset=49	1	1	23.26	22.97	22.68
		RB Size=25, RB Offset=0	2	2	21.74	21.81	21.77
		RB Size=25, RB Offset=13	2	2	21.77	21.69	21.70
		RB Size=25, RB Offset=25	2	2	21.89	21.68	21.62
		RB Size=50, RB Offset=0	2	2	21.65	21.69	21.68

LTE Band 12:

BW	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					699.7MHz	707.5MHz	715.3MHz
1.4M	QPSK	RB Size=1, RB Offset=0	0	0	23.59	23.56	23.56
		RB Size=1, RB Offset=2	0	0	23.65	23.59	23.63
		RB Size=1, RB Offset=5	0	0	23.67	23.51	23.64
		RB Size=3, RB Offset=0	1	1	23.56	23.59	23.60
		RB Size=3, RB Offset=2	1	1	23.39	23.49	23.53
		RB Size=3, RB Offset=3	1	1	23.74	23.66	23.58
		RB Size=6, RB Offset=0	1	1	22.62	22.57	22.66
	16QAM	RB Size=1, RB Offset=0	1	1	22.94	22.26	23.02
		RB Size=1, RB Offset=2	1	1	22.97	22.57	23.17
		RB Size=1, RB Offset=5	1	1	22.68	22.40	22.91
		RB Size=3, RB Offset=0	2	2	22.64	22.57	22.79
		RB Size=3, RB Offset=2	2	2	22.56	22.52	22.55
		RB Size=3, RB Offset=3	2	2	22.44	22.58	22.48
		RB Size=6, RB Offset=0	2	2	21.71	21.58	21.76
BW	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					700.5MHz	707.5MHz	714.5MHz
3M	QPSK	RB Size=1, RB Offset=0	0	0	23.73	23.63	23.58
		RB Size=1, RB Offset=7	0	0	23.67	23.66	23.68
		RB Size=1, RB Offset=14	0	0	23.60	23.60	23.75
		RB Size=8, RB Offset=0	1	1	22.56	22.57	22.71
		RB Size=8, RB Offset=4	1	1	22.64	22.61	22.63
		RB Size=8, RB Offset=7	1	1	22.78	22.65	22.66
		RB Size=15, RB Offset=0	1	1	22.61	22.55	22.74
	16QAM	RB Size=1, RB Offset=0	1	1	22.96	22.20	23.07
		RB Size=1, RB Offset=7	1	1	22.99	22.55	23.25
		RB Size=1, RB Offset=14	1	1	22.81	22.47	22.80
		RB Size=8, RB Offset=0	2	2	21.62	21.72	21.90
		RB Size=8, RB Offset=4	2	2	21.55	21.67	21.61
		RB Size=8, RB Offset=7	2	2	21.70	21.74	21.55
		RB Size=15, RB Offset=0	2	2	21.69	21.65	21.88

BW	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					701.5MHz	707.5MHz	713.5MHz
5M	QPSK	RB Size=1, RB Offset=0	0	0	23.57	23.68	23.63
		RB Size=1, RB Offset=13	0	0	23.75	23.69	23.77
		RB Size=1, RB Offset=24	0	0	23.63	23.53	23.62
		RB Size=12, RB Offset=0	1	1	22.57	22.59	22.77
		RB Size=12, RB Offset=6	1	1	22.56	22.50	22.59
		RB Size=12, RB Offset=13	1	1	22.75	22.77	22.63
		RB Size=25, RB Offset=0	1	1	22.65	22.51	22.73
	16QAM	RB Size=1, RB Offset=0	1	1	22.99	22.21	22.98
		RB Size=1, RB Offset=13	1	1	23.00	22.64	23.22
		RB Size=1, RB Offset=24	1	1	22.73	22.30	22.85
		RB Size=12, RB Offset=0	2	2	21.62	21.79	21.81
		RB Size=12, RB Offset=6	2	2	21.60	21.64	21.61
		RB Size=12, RB Offset=13	2	2	21.68	21.58	21.58
		RB Size=25, RB Offset=0	2	2	21.78	21.57	21.90
BW	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					704MHz	707.5MHz	711MHz
10M	QPSK	RB Size=1, RB Offset=0	0	0	23.66	23.52	23.64
		RB Size=1, RB Offset=25	0	0	23.63	23.56	23.60
		RB Size=1, RB Offset=49	0	0	23.62	23.55	23.68
		RB Size=25, RB Offset=0	1	1	22.52	22.60	22.71
		RB Size=25, RB Offset=13	1	1	22.52	22.58	22.67
		RB Size=25, RB Offset=25	1	1	22.65	22.73	22.68
		RB Size=50, RB Offset=0	1	1	22.65	22.52	22.69
	16QAM	RB Size=1, RB Offset=0	1	1	22.85	22.13	22.86
		RB Size=1, RB Offset=25	1	1	22.98	22.58	23.14
		RB Size=1, RB Offset=49	1	1	22.66	22.39	22.87
		RB Size=25, RB Offset=0	2	2	21.61	21.76	21.77
		RB Size=25, RB Offset=13	2	2	21.64	21.54	21.63
		RB Size=25, RB Offset=25	2	2	21.57	21.64	21.46
		RB Size=50, RB Offset=0	2	2	21.65	21.65	21.74

LTE Band 13:

BW	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					779.5MHz	782MHz	784.5MHz
5M	QPSK	RB Size=1, RB Offset=0	0	0	23.68	23.56	23.77
		RB Size=1, RB Offset=13	0	0	23.82	23.68	23.75
		RB Size=1, RB Offset=24	0	0	23.51	23.75	23.59
		RB Size=12, RB Offset=0	1	1	22.89	22.78	22.84
		RB Size=12, RB Offset=6	1	1	22.83	22.73	22.91
		RB Size=12, RB Offset=13	1	1	22.82	22.84	22.78
		RB Size=25, RB Offset=0	1	1	22.87	22.67	22.76
	16QAM	RB Size=1, RB Offset=0	1	1	23.06	22.42	22.66
		RB Size=1, RB Offset=13	1	1	23.19	22.37	22.30
		RB Size=1, RB Offset=24	1	1	23.10	22.11	22.40
		RB Size=12, RB Offset=0	2	2	21.56	21.49	21.74
		RB Size=12, RB Offset=6	2	2	21.61	21.79	21.60
		RB Size=12, RB Offset=13	2	2	21.73	21.57	21.53
		RB Size=25, RB Offset=0	2	2	21.69	21.94	21.58
BW	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					/	782MHz	/
10M	QPSK	RB Size=1, RB Offset=0	0	0	/	23.76	/
		RB Size=1, RB Offset=25	0	0	/	23.80	/
		RB Size=1, RB Offset=49	0	0	/	23.66	/
		RB Size=25, RB Offset=0	1	1	/	22.86	/
		RB Size=25, RB Offset=13	1	1	/	22.73	/
		RB Size=25, RB Offset=25	1	1	/	22.91	/
		RB Size=50, RB Offset=0	1	1	/	22.77	/
	16QAM	RB Size=1, RB Offset=0	1	1	/	23.17	/
		RB Size=1, RB Offset=25	1	1	/	23.40	/
		RB Size=1, RB Offset=49	1	1	/	22.97	/
		RB Size=25, RB Offset=0	2	2	/	21.70	/
		RB Size=25, RB Offset=13	2	2	/	21.86	/
		RB Size=25, RB Offset=25	2	2	/	21.84	/
		RB Size=50, RB Offset=0	2	2	/	21.80	/

LTE Band 66:

BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1710.7MHz	1745MHz	1779.3MHz
1.4	QPSK	RB Size=1, RB Offset=0	0	0	23.42	23.52	23.53
		RB Size=1, RB Offset=2	0	0	23.31	23.68	23.53
		RB Size=1, RB Offset=5	0	0	23.45	23.60	23.37
		RB Size=3, RB Offset=0	1	1	23.49	23.63	23.22
		RB Size=3, RB Offset=2	1	1	23.30	23.78	23.37
		RB Size=3, RB Offset=3	1	1	23.53	23.60	23.33
	16QAM	RB Size=6, RB Offset=0	1	1	22.52	22.71	22.31
		RB Size=1, RB Offset=0	1	1	22.87	22.42	22.14
		RB Size=1, RB Offset=2	1	1	22.39	22.72	22.58
		RB Size=1, RB Offset=5	1	1	22.58	22.41	22.27
		RB Size=3, RB Offset=0	2	2	22.55	22.65	22.33
		RB Size=3, RB Offset=2	2	2	22.31	22.80	22.46
		RB Size=3, RB Offset=3	2	2	22.67	22.57	22.48
		RB Size=6, RB Offset=0	2	2	21.62	21.84	21.43
BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1711.5MHz	1745MHz	1778.5MHz
3	QPSK	RB Size=1, RB Offset=0	0	0	23.35	23.67	23.53
		RB Size=1, RB Offset=7	0	0	23.39	23.86	23.57
		RB Size=1, RB Offset=14	0	0	23.36	23.68	23.48
		RB Size=8, RB Offset=0	1	1	22.59	22.68	22.44
		RB Size=8, RB Offset=4	1	1	22.41	22.84	22.43
		RB Size=8, RB Offset=7	1	1	22.66	22.73	22.47
		RB Size=15, RB Offset=0	1	1	22.53	22.75	22.37
	16QAM	RB Size=1, RB Offset=0	1	1	22.90	22.42	22.17
		RB Size=1, RB Offset=7	1	1	22.38	22.82	22.59
		RB Size=1, RB Offset=14	1	1	22.58	22.44	22.32
		RB Size=8, RB Offset=0	2	2	21.68	21.74	21.36
		RB Size=8, RB Offset=4	2	2	21.47	21.97	21.55
		RB Size=8, RB Offset=7	2	2	21.73	21.74	21.53
		RB Size=15, RB Offset=0	2	2	21.64	21.93	21.48

BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1712.5MHz	1745MHz	1777.5MHz
5	QPSK	RB Size=1, RB Offset=0	0	0	23.41	23.55	23.52
		RB Size=1, RB Offset=13	0	0	23.39	23.75	23.62
		RB Size=1, RB Offset=24	0	0	23.29	23.64	23.50
		RB Size=12, RB Offset=0	1	1	22.48	22.63	22.36
		RB Size=12, RB Offset=6	1	1	22.45	22.85	22.43
		RB Size=12, RB Offset=13	1	1	22.61	22.56	22.43
		RB Size=25, RB Offset=0	1	1	22.49	22.74	22.30
	16QAM	RB Size=1, RB Offset=0	1	1	22.91	22.33	22.22
		RB Size=1, RB Offset=13	1	1	22.46	22.80	22.51
		RB Size=1, RB Offset=24	1	1	22.50	22.39	22.29
		RB Size=12, RB Offset=0	2	2	21.67	21.72	21.39
		RB Size=12, RB Offset=6	2	2	21.45	21.90	21.59
		RB Size=12, RB Offset=13	2	2	21.84	21.70	21.48
		RB Size=25, RB Offset=0	2	2	21.69	21.90	21.43
BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1715MHz	1745MHz	1775MHz
10	QPSK	RB Size=1, RB Offset=0	0	0	23.50	23.64	23.52
		RB Size=1, RB Offset=25	0	0	23.29	23.78	23.65
		RB Size=1, RB Offset=49	0	0	23.35	23.74	23.47
		RB Size=25, RB Offset=0	1	1	22.49	22.75	22.31
		RB Size=25, RB Offset=13	1	1	22.52	22.93	22.39
		RB Size=25, RB Offset=25	1	1	22.75	22.60	22.55
		RB Size=50, RB Offset=0	1	1	22.55	22.77	22.45
	16QAM	RB Size=1, RB Offset=0	1	1	22.82	22.37	22.21
		RB Size=1, RB Offset=25	1	1	22.38	22.88	22.56
		RB Size=1, RB Offset=49	1	1	22.66	22.38	22.16
		RB Size=25, RB Offset=0	2	2	21.62	21.64	21.44
		RB Size=25, RB Offset=13	2	2	21.50	21.82	21.60
		RB Size=25, RB Offset=25	2	2	21.81	21.67	21.63
		RB Size=50, RB Offset=0	2	2	21.72	21.88	21.42

BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1717.5MHz	1745MHz	1772.5MHz
15	QPSK	RB Size=1, RB Offset=0	0	0	23.36	23.53	23.55
		RB Size=1, RB Offset=38	0	0	23.37	23.82	23.55
		RB Size=1, RB Offset=74	0	0	23.35	23.58	23.39
		RB Size=36, RB Offset=0	1	1	22.58	22.60	22.39
		RB Size=36, RB Offset=18	1	1	22.42	22.83	22.41
		RB Size=36, RB Offset=39	1	1	22.64	22.73	22.48
		RB Size=75, RB Offset=0	1	1	22.51	22.69	22.33
	16QAM	RB Size=1, RB Offset=0	1	1	22.80	22.38	22.21
		RB Size=1, RB Offset=38	1	1	22.43	22.74	22.66
		RB Size=1, RB Offset=74	1	1	22.48	22.37	22.24
		RB Size=36, RB Offset=0	2	2	21.69	21.73	21.39
		RB Size=36, RB Offset=18	2	2	21.44	21.80	21.51
		RB Size=36, RB Offset=39	2	2	21.78	21.74	21.54
		RB Size=75, RB Offset=0	2	2	21.67	21.87	21.38
BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					1720MHz	1745MHz	1770MHz
20	QPSK	RB Size=1, RB Offset=0	0	0	23.39	23.58	23.60
		RB Size=1, RB Offset=50	0	0	23.30	23.80	23.61
		RB Size=1, RB Offset=99	0	0	23.34	23.59	23.39
		RB Size=50, RB Offset=0	1	1	22.55	22.61	22.29
		RB Size=50, RB Offset=25	1	1	22.36	22.70	22.33
		RB Size=50, RB Offset=50	1	1	22.62	22.64	22.38
		RB Size=100, RB Offset=0	1	1	22.53	22.74	22.27
	16QAM	RB Size=1, RB Offset=0	1	1	22.74	22.32	22.13
		RB Size=1, RB Offset=50	1	1	22.44	22.84	22.56
		RB Size=1, RB Offset=99	1	1	22.48	22.46	22.26
		RB Size=50, RB Offset=0	2	2	21.58	21.65	21.26
		RB Size=50, RB Offset=25	2	2	21.43	21.84	21.52
		RB Size=50, RB Offset=50	2	2	21.75	21.61	21.56
		RB Size=100, RB Offset=0	2	2	21.65	21.86	21.45

LTE Band 71:

BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					665.5MHz	680.5MHz	695.5MHz
5	QPSK	RB Size=1, RB Offset=0	0	0	23.09	23.29	23.05
		RB Size=1, RB Offset=13	0	0	23.38	23.15	23.04
		RB Size=1, RB Offset=24	0	0	23.18	23.04	23.10
		RB Size=12, RB Offset=0	1	1	22.17	22.39	22.29
		RB Size=12, RB Offset=6	1	1	22.12	22.19	22.17
		RB Size=12, RB Offset=13	1	1	22.44	22.34	22.41
	16QAM	RB Size=25, RB Offset=0	1	1	22.11	22.33	22.18
		RB Size=1, RB Offset=0	1	1	22.06	22.66	22.93
		RB Size=1, RB Offset=13	1	1	22.28	22.79	22.88
		RB Size=1, RB Offset=24	1	1	22.14	22.42	22.82
		RB Size=12, RB Offset=0	2	2	21.30	21.27	21.03
		RB Size=12, RB Offset=6	2	2	21.23	21.27	21.21
		RB Size=12, RB Offset=13	2	2	21.41	21.19	21.12
		RB Size=25, RB Offset=0	2	2	21.39	21.50	21.35
BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					668MHz	680.5MHz	693MHz
10	QPSK	RB Size=1, RB Offset=0	0	0	23.21	23.25	23.04
		RB Size=1, RB Offset=25	0	0	23.53	23.23	23.12
		RB Size=1, RB Offset=49	0	0	23.24	23.03	23.11
		RB Size=25, RB Offset=0	1	1	22.19	22.34	22.25
		RB Size=25, RB Offset=13	1	1	22.19	22.24	22.30
		RB Size=25, RB Offset=25	1	1	22.47	22.41	22.32
		RB Size=50, RB Offset=0	1	1	22.20	22.39	22.17
	16QAM	RB Size=1, RB Offset=0	1	1	22.07	22.66	22.84
		RB Size=1, RB Offset=25	1	1	22.28	22.93	22.97
		RB Size=1, RB Offset=49	1	1	22.33	22.53	22.82
		RB Size=25, RB Offset=0	2	2	21.34	21.32	21.14
		RB Size=25, RB Offset=13	2	2	21.29	21.40	21.31
		RB Size=25, RB Offset=25	2	2	21.36	21.34	21.17
		RB Size=50, RB Offset=0	2	2	21.37	21.63	21.28

BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					670.5MHz	680.5MHz	690.5MHz
15	QPSK	RB Size=1, RB Offset=0	0	0	23.12	22.94	23.03
		RB Size=1, RB Offset=38	0	0	23.43	23.16	23.13
		RB Size=1, RB Offset=74	0	0	23.28	23.12	23.02
		RB Size=36, RB Offset=0	1	1	22.16	22.22	22.36
		RB Size=36, RB Offset=18	1	1	22.14	22.24	22.16
		RB Size=36, RB Offset=39	1	1	22.33	22.06	22.26
		RB Size=75, RB Offset=0	1	1	22.23	22.16	22.17
	16QAM	RB Size=1, RB Offset=0	1	1	22.09	22.03	22.90
		RB Size=1, RB Offset=38	1	1	22.21	22.15	23.00
		RB Size=1, RB Offset=74	1	1	22.17	22.15	22.80
		RB Size=36, RB Offset=0	2	2	21.28	21.29	21.08
		RB Size=36, RB Offset=18	2	2	21.25	21.17	21.20
		RB Size=36, RB Offset=39	2	2	21.32	21.07	21.18
		RB Size=75, RB Offset=0	2	2	21.34	21.12	21.38
BW (MHz)	Modulation	Resource Block Size & Resource Block Offset	Target MPR	Meas MPR	Ave Tx Power (dBm)		
					Low Channel	Mid Channel	High Channel
					673MHz	683MHz	688MHz
20	QPSK	RB Size=1, RB Offset=0	0	0	23.11	23.64	22.95
		RB Size=1, RB Offset=50	0	0	23.49	23.17	23.08
		RB Size=1, RB Offset=99	0	0	23.29	23.04	23.09
		RB Size=50, RB Offset=0	1	1	22.06	22.27	22.23
		RB Size=50, RB Offset=25	1	1	22.18	22.23	22.17
		RB Size=50, RB Offset=50	1	1	22.34	22.25	22.29
		RB Size=100, RB Offset=0	1	1	22.28	22.33	22.17
	16QAM	RB Size=1, RB Offset=0	1	1	22.11	22.57	22.92
		RB Size=1, RB Offset=50	1	1	22.12	22.78	22.87
		RB Size=1, RB Offset=99	1	1	22.12	22.37	22.84
		RB Size=50, RB Offset=0	2	2	21.30	21.29	20.99
		RB Size=50, RB Offset=25	2	2	21.14	21.18	21.27
		RB Size=50, RB Offset=50	2	2	21.38	21.13	21.13
		RB Size=100, RB Offset=0	2	2	21.35	21.54	21.21

Note:

1. SAR for LTE band exposure configurations is measured according to the procedures of KDB 941225 D05 SAR for LTE Devices v02.
2. The CMW500 Wideband Radio Communication tester is used for LTE output power measurements and SAR testing. Closed loop power control is used to keep the radio transmitters the max output power during the test.

WLAN 2.4G:

Mode	Channel frequency (MHz)	Data Rate	RF Output Power(dBm)
802.11b	2412	1Mbps	12.85
	2437		13.11
	2462		13.07
802.11g	2412	6Mbps	7.83
	2437		8.05
	2462		7.98
802.11n HT20	2412	MCS0	5.98
	2437		5.99
	2462		6.14
802.11n HT40	2422	MCS0	6.47
	2437		6.56
	2452		6.55


Bluetooth:

Mode	Channel frequency (MHz)	RF Output Power (dBm)
DH1	2402	-4.00
	2441	-3.83
	2480	-3.60
2DH1	2402	-3.69
	2441	-3.88
	2480	-2.97
3DH1	2402	-3.20
	2441	-3.56
	2480	-2.88
Bluetooth LE	2402	-0.10
	2440	-0.21
	2480	0.47

Standalone SAR test exclusion considerations

Antennas Location:

Top



Bottom

Antenna Distance To Edge

Antenna Distance To Edge(mm)					
Antenna	Back	Left	Right	Top	Bottom
WWAN(WCDMA/LTE)	< 5	177	30	< 5	164
WLAN/BT Antenna	< 5	< 5	264	112	48

Standalone SAR test exclusion considerations

Mode	Frequency (MHz)	P _{avg} (dBm)	P _{avg} (mW)	Distance (mm)	Calculated value	Threshold (1-g)	SAR Test Exclusion
WLAN 2.4G	2437	13.5	22.39	0	7.0	3	No
Bluetooth	2480	0.5	1.12	0	0.4	3	Yes

NOTE:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- f(GHz) is the RF channel transmit frequency in GHz.
- Power and distance are rounded to the nearest mW and mm before calculation.
- The result is rounded to one decimal place for comparison.
- When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Standalone SAR estimation:

Mode	Frequency (MHz)	Pavg (dBm)	Pavg (mW)	Distance (mm)	Estimated 1-g (W/kg)
Bluetooth Body-Support	2480	0.5	1.12	0	0.05

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion: $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})} / x] \text{ W/kg}$ for test separation distances $\leq 50 \text{ mm}$; where $x = 7.5$ for 1-g SAR. When the minimum test separation distance is $< 5 \text{ mm}$, a distance of 5 mm is applied to determine SAR test Exclusion.

Standalone SAR test exclusion considerations

Mode	Frequency (MHz)	P _{avg} (dBm)	P _{avg} (mW)	Exclusion Distance (mm)
WCDMA B2	1907.6	25	316.23	71
WCDMA B5	846.6	25	316.23	77
LTE B2	1900	25	316.23	71
LTE B4	1745	25	316.23	71
LTE B5	844	25	316.23	77
LTE B12	711	25	316.23	79
LTE B13	782	25	316.23	78
LTE B66	1770	25	316.23	71
LTE B71	688	25	316.23	80
WLAN	2472	13.5	22.39	12

SAR test exclusion for the EUT edge considerations Result

Exclusion Result					
Mode	Back	Left	Right	Top	Bottom
WCDMA B2	Required	Exclusion	Required	Required	Exclusion
WCDMA B5	Required	Exclusion	Required	Required	Exclusion
LTE B2	Required	Exclusion	Required	Required	Exclusion
LTE B4	Required	Exclusion	Required	Required	Exclusion
LTE B5	Required	Exclusion	Required	Required	Exclusion
LTE B12	Required	Exclusion	Required	Required	Exclusion
LTE B13	Required	Exclusion	Required	Required	Exclusion
LTE B66	Required	Exclusion	Required	Required	Exclusion
LTE B71	Required	Exclusion	Required	Required	Exclusion
WLAN 2.4G	Required	Required	Exclusion	Exclusion	Exclusion
BT	Exclusion*	Exclusion*	Exclusion*	Exclusion*	Exclusion*

NOTE:

1. The laptop is evaluated closely, with no additional evaluation of the hot spot mode.
2. Required: The distance is less than Test Exclusion Distance, the SAR test is required.
 Exclusion: The distance is large than Test Exclusion Distance, SAR test is not required.
 Exclusion*: SAR test exclusion evaluation has been done above.

SAR test exclusion for the EUT edge considerations detail:

Distance < 50mm (To Edges)

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances $\leq 50 \text{ mm}$ are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.
5. The Time based average Power is used for calculation

Distance > 50mm (To Edges)

At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following:

- a) [Power allowed at numeric threshold for 50 mm in step 1) + (test separation distance - 50 mm) · ($f(\text{MHz})/150$)] mW, at 100 MHz to 1500 MHz
- b) [Power allowed at numeric threshold for 50 mm in step 1) + (test separation distance - 50 mm) · 10] mW at > 1500 MHz and ≤ 6 GHz.

SAR MEASUREMENT RESULTS

This page summarizes the results of the performed dosimetric evaluation.

SAR Test Data

Environmental Conditions

Temperature:	22.3-23.9 °C	22.6-23.7 °C	23.6-24.5 °C	23.6-24.5 °C
Relative Humidity:	50-53 %	56-61 %	53-57 %	53-55 %
ATM Pressure:	101.3 kPa	101.3 kPa	101.2 kPa	101.2 kPa
Test Date:	2020/06/21	2020/06/22	2020/06/23	2020/06/24

Testing was performed by Seven Liang, Ricardo Lan, Thomas Deng.

WCDMA Band 2: (Test on 2020/06/22)

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	24.8	25	1.047	0.718	0.75	1#
	1907.6	RMC	/	/	/	/	/	/
Body Right (0mm)	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	24.8	25	1.047	0.024	0.03	2#
	1907.6	RMC	/	/	/	/	/	/
Body Top (0mm)	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	24.8	25	1.047	0.024	0.03	3#
	1907.6	RMC	/	/	/	/	/	/

WCDMA Band 5: (Test on 2020/06/21)

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.11	23.5	1.545	0.195	0.30	4#
	846.6	RMC	/	/	/	/	/	/
Body Right (0mm)	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.11	23.5	1.094	0.011	0.01	5#
	846.6	RMC	/	/	/	/	/	/
Body Top (0mm)	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.11	23.5	1.545	0.037	0.06	6#
	846.6	RMC	/	/	/	/	/	/

Note:

1. When the 1-g SAR is $\leq 0.8\text{W/Kg}$, testing for other channels are optional.
2. The EUT transmit and receive through the same antenna while testing SAR.
3. The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2 kbps RMC (reference measurement Channel) Configured in Test Loop Model.
4. KDB 941225 D01-Body SAR is not required for HSDPA/HSUPA when the maximum average output of each RF channel is less than $\frac{1}{4}$ dB higher than measured 12.2kbps RMC or the maximum SAR for 12.2kbps RMC is $< 75\%$ of SAR limit.
5. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.

LTE Band 2: (Test on 2020/06/23)

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	24.1	25	1.230	0.371	0.46	7#
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	23.6	25	1.380	0.301	0.42	8#
Body Right (0mm)	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	24.1	25	1.230	0.222	0.27	9#
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	23.6	25	1.380	0.188	0.26	10#
Body Top (0mm)	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	24.1	25	1.230	0.621	0.76	11#
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	23.6	25	1.380	0.535	0.74	12#

LTE Band 4: (Test on 2020/06/24)

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	1720	20	1RB	/	/	/	/	/	/
	1732.5	20	1RB	23.88	25	1.294	0.297	0.38	13#
	1745	20	1RB	/	/	/	/	/	/
	1732.5	20	50%RB	22.65	25	1.718	0.249	0.43	14#
Body Right (0mm)	1720	20	1RB	/	/	/	/	/	/
	1732.5	20	1RB	23.88	25	1.294	0.130	0.17	15#
	1745	20	1RB	/	/	/	/	/	/
	1732.5	20	50%RB	22.65	25	1.718	0.108	0.19	16#
Body Top (0mm)	1720	20	1RB	/	/	/	/	/	/
	1732.5	20	1RB	23.12	25	1.542	0.041	0.06	17#
	1745	20	1RB	/	/	/	/	/	/
	1732.5	20	50%RB	22.19	25	1.910	0.036	0.07	18#

LTE Band 5: (Test on 2020/06/21)

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	23.88	25	1.294	0.123	0.16	19#
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	22.65	25	1.718	0.117	0.20	20#
Body Right (0mm)	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	23.88	25	1.294	0.012	0.02	21#
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	22.65	25	1.718	0.017	0.03	22#
Body Top (0mm)	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	23.88	25	1.294	0.042	0.05	23#
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	22.65	25	1.718	0.037	0.06	24#

LTE Band 12: (Test on 2020/06/21)

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	23.52	25	1.406	0.327	0.46	25#
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.60	25	1.738	0.26	0.45	26#
Body Right (0mm)	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	23.52	25	1.406	0.030	0.04	27#
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.60	25	1.738	0.022	0.04	28#
Body Top (0mm)	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	23.52	25	1.406	0.086	0.12	29#
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.60	25	1.738	0.076	0.13	30#

LTE Band 13: (Test on 2020/06/21)

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	/	/	/	/	/	/	/	/	/
	782	10	1RB	23.76	25	1.330	0.327	0.43	31#
	/	/	/	/	/	/	/	/	/
	782	10	50%RB	22.86	25	1.637	0.263	0.43	32#
Body Right (0mm)	/	/	/	/	/	/	/	/	/
	782	10	1RB	23.76	25	1.330	0.014	0.02	33#
	/	/	/	/	/	/	/	/	/
	782	10	50%RB	22.86	25	1.637	0.011	0.02	34#
Body Top (0mm)	/	/	/	/	/	/	/	/	/
	782	10	1RB	23.76	25	1.330	0.111	0.15	35#
	/	/	/	/	/	/	/	/	/
	782	10	50%RB	22.86	25	1.637	0.099	0.16	36#

LTE Band 66: (Test on 2020/06/24)

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	23.58	25	1.387	0.451	0.63	37#
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	22.61	25	1.734	0.354	0.61	38#
Body Right (0mm)	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	23.58	25	1.387	0.114	0.16	39#
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	22.61	25	1.734	0.091	0.16	40#
Body Top (0mm)	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	23.58	25	1.387	0.047	0.07	41#
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	22.61	25	1.734	0.038	0.07	42#

LTE Band 71: (Test on 2020/06/21)

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	673	20	1RB	/	/	/	/	/	/
	683	20	1RB	23.64	25	1.368	0.382	0.52	43#
	688	20	1RB	/	/	/	/	/	/
	683	20	50%RB	22.27	25	1.875	0.319	0.60	44#
Body Right (0mm)	673	20	1RB	/	/	/	/	/	/
	683	20	1RB	23.64	25	1.368	0.031	0.04	45#
	688	20	1RB	/	/	/	/	/	/
	683	20	50%RB	22.27	25	1.875	0.031	0.06	46#
Body Top (0mm)	673	20	1RB	/	/	/	/	/	/
	683	20	1RB	23.64	25	1.368	0.538	0.74	47#
	688	20	1RB	/	/	/	/	/	/
	683	20	50%RB	22.27	25	1.875	0.368	0.69	48#

Note:

- When the 1-g SAR is $\leq 0.8\text{W/Kg}$, testing for other channels are optional.
- SAR for LTE band exposure configurations is measured according to the procedures of KDB 941225 D05 SAR for LTE Devices v02.
- KDB941225D05-SAR for higher order modulation is required only when the highest maximum output power for the configuration in the higher order modulation is $> 0.5\text{ dB}$ higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is $> 1.45\text{ W/kg}$
- KDB941225D05-For QPSK with 100% RB allocation, when the reported SAR measured for the Highest output power channel is $< 1.45\text{ W/kg}$, tests for the remaining required test channels are optional.
- KDB941225D05- For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are $\leq 0.8\text{ W/kg}$.
- KDB941225D05- Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offset the upper edge, middle and lower edge of each required test channel.
- KDB941225D05- other channel bandwidths SAR test is required when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is $> 0.5\text{ dB}$ higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is $> 1.45\text{ W/kg}$.
- Worst case SAR for 50% RB allocation is selected to be tested.
- KDB 648474 D04-When the peak SAR located in regions that probe is unable to access, a flat phantom is used for SAR measurement.

WLAN 2.4G: (Test on 2020/06/21)

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Back (0mm)	2412	802.11b	/	/	/	/	/	/
	2437	802.11b	13.11	13.5	1.094	0.102	0.11	49#
	2462	802.11b	/	/	/	/	/	/
Body Left (0mm)	2412	802.11b	/	/	/	/	/	
	2437	802.11b	13.11	13.5	1.094	0.354	0.39	50#
	2462	802.11b	/	/	/	/	/	

Note:

1. When the 1-g SAR is ≤ 0.8 W/Kg, testing for other channels are optional.
2. When the highest *reported* SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, OFDM SAR is not required.
3. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.

SAR Measurement Variability

In accordance with published RF Exposure KDB procedure 865664 D01 SAR measurement 100 MHz to 6 GHz v01. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20.

Note: The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.

The Highest Measured SAR Configuration in Each Frequency Band

Head

SAR probe calibration point	Frequency Band	Freq.(MHz)	EUT Position	Meas. SAR (W/kg)		Largest to Smallest SAR Ratio
				Original	Repeated	
/	/	/	/	/	/	/

Body

SAR probe calibration point	Frequency Band	Freq.(MHz)	EUT Position	Meas. SAR (W/kg)		Largest to Smallest SAR Ratio
				Original	Repeated	
/	/	/	/	/	/	/

Note:

1. Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is not > 1.20.
2. The measured SAR results do not have to be scaled to the maximum tune-up tolerance to determine if repeated measurements are required.
3. SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements..

SAR SIMULTANEOUS TRANSMISSION DESCRIPTION

Simultaneous Transmission:

Description of Simultaneous Transmit Capabilities		
Transmitter Combination	Simultaneous?	Hotspot?
WWAN(GSM/WCDMA) + Bluetooth	√	×
WWAN(GSM/WCDMA) + WLAN	√	√

Simultaneous and Hotspot SAR test exclusion considerations:

Mode(SAR1+SAR2)	Position	Reported SAR(W/kg)		ΣSAR < 1.6W/kg
		SAR1	SAR2	
WCDMA Band 2+Bluetooth	Body Back	0.75	0.05	0.80
	Body Left	/	0.05	0.05
	Body Right	0.03	/	0.03
	Body Top	0.07	/	0.07
WCDMA Band 5+Bluetooth	Body Back	0.30	0.05	0.35
	Body Left	/	0.05	0.05
	Body Right	0.01	/	0.01
	Body Top	0.06	/	0.06
LTE Band 2+Bluetooth	Body Back	0.46	0.05	0.51
	Body Left	/	0.05	0.05
	Body Right	0.27	/	0.27
	Body Top	0.76	/	0.76
LTE Band 4+Bluetooth	Body Back	0.43	0.05	0.48
	Body Left	/	0.05	0.05
	Body Right	0.19	/	0.19
	Body Top	0.07	/	0.07
LTE Band 5+Bluetooth	Body Back	0.20	0.05	0.25
	Body Left	/	0.05	0.05
	Body Right	0.03	/	0.03
	Body Top	0.06	/	0.06
LTE Band 12+Bluetooth	Body Back	0.46	0.05	0.51
	Body Left	/	0.05	0.05
	Body Right	0.04	/	0.04
	Body Top	0.13	/	0.13
LTE Band 13+Bluetooth	Body Back	0.43	0.05	0.48
	Body Left	/	0.05	0.05
	Body Right	0.02	/	0.02
	Body Top	0.16	/	0.16
LTE Band 66+Bluetooth	Body Back	0.63	0.05	0.68
	Body Left	/	0.05	0.05
	Body Right	0.16	/	0.16
	Body Top	0.07	/	0.07
LTE Band 71+Bluetooth	Body Back	0.60	0.05	0.65
	Body Left	/	0.05	0.05
	Body Right	0.06	/	0.06
	Body Top	0.74	/	0.74

Mode(SAR1+SAR2)	Position	Reported SAR(W/kg)		ΣSAR < 1.6W/kg
		SAR1	SAR2	
WCDMA Band 2+ WLAN(2.4G)(Hotspot)	Body Back	0.75	0.11	0.86
	Body Left	/	0.39	0.39
	Body Right	0.03	/	0.03
	Body Top	0.07	/	0.07
WCDMA Band 5+ WLAN(2.4G) (Hotspot)	Body Back	0.30	0.11	0.41
	Body Left	/	0.39	0.39
	Body Right	0.01	/	0.01
	Body Top	0.06	/	0.06
LTE Band 2+ WLAN(2.4G) (Hotspot)	Body Back	0.46	0.11	0.57
	Body Left	/	0.39	0.39
	Body Right	0.27	/	0.27
	Body Top	0.76	/	0.76
LTE Band 4+ WLAN(2.4G) (Hotspot)	Body Back	0.43	0.11	0.54
	Body Left	/	0.39	0.39
	Body Right	0.19	/	0.19
	Body Top	0.07	/	0.07
LTE Band 5+ WLAN(2.4G) (Hotspot)	Body Back	0.20	0.11	0.31
	Body Left	/	0.39	0.39
	Body Right	0.03	/	0.03
	Body Top	0.06	/	0.06
LTE Band 12+ WLAN(2.4G) (Hotspot)	Body Back	0.46	0.11	0.57
	Body Left	/	0.39	0.39
	Body Right	0.04	/	0.04
	Body Top	0.13	/	0.13
LTE Band 13+ WLAN(2.4G) (Hotspot)	Body Back	0.43	0.11	0.54
	Body Left	/	0.39	0.39
	Body Right	0.02	/	0.02
	Body Top	0.16	/	0.16
LTE Band 66+ WLAN(2.4G) (Hotspot)	Body Back	0.63	0.11	0.74
	Body Left	/	0.39	0.39
	Body Right	0.16	/	0.16
	Body Top	0.07	/	0.07
LTE Band 71+ WLAN(2.4G) (Hotspot)	Body Back	0.60	0.11	0.71
	Body Left	/	0.39	0.39
	Body Right	0.06	/	0.06
	Body Top	0.74	/	0.74

Note:

1. Hotspot mode SAR is measured for all edges and surfaces of the device with a transmitting antenna located within 25 mm from that surface or edge; for the data modes, wireless technologies and frequency bands supporting hotspot mode..

Conclusion:

Sum of SAR: $\Sigma \text{SAR} \leq 1.6 \text{ W/kg}$ therefore simultaneous transmission SAR with Volume Scans is **not required**.

SAR Plots

Please Refer to the Attachment.

APPENDIX A MEASUREMENT UNCERTAINTY

The uncertainty budget has been determined for the measurement system and is given in the following Table.
Measurement uncertainty evaluation for IEEE1528-2013 SAR test

Source of uncertainty	Tolerance/uncertainty ± %	Probability distribution	Divisor	ci (1 g)	ci (10 g)	Standard uncertainty ± %, (1 g)	Standard uncertainty ± %, (10 g)
Measurement system							
Probe calibration	6.55	N	1	1	1	6.6	6.6
Axial Isotropy	4.7	R	√3	1	1	2.7	2.7
Hemispherical Isotropy	9.6	R	√3	0	0	0.0	0.0
Boundary effect	1.0	R	√3	1	1	0.6	0.6
Linearity	4.7	R	√3	1	1	2.7	2.7
Detection limits	1.0	R	√3	1	1	0.6	0.6
Readout electronics	0.3	N	1	1	1	0.3	0.3
Response time	0.0	R	√3	1	1	0.0	0.0
Integration time	0.0	R	√3	1	1	0.0	0.0
RF ambient conditions – noise	1.0	R	√3	1	1	0.6	0.6
RF ambient conditions–reflections	1.0	R	√3	1	1	0.6	0.6
Probe positioner mech. Restrictions	0.8	R	√3	1	1	0.5	0.5
Probe positioning with respect to phantom shell	6.7	R	√3	1	1	3.9	3.9
Post-processing	2.0	R	√3	1	1	1.2	1.2
Test sample related							
Test sample positioning	2.8	N	1	1	1	2.8	2.8
Device holder uncertainty	6.3	N	1	1	1	6.3	6.3
Drift of output power	5.0	R	√3	1	1	2.9	2.9
Phantom and set-up							
Phantom uncertainty (shape and thickness tolerances)	4.0	R	√3	1	1	2.3	2.3
Liquid conductivity target)	5.0	R	√3	0.64	0.43	1.8	1.2
Liquid conductivity meas.)	2.5	N	1	0.64	0.43	1.6	1.1
Liquid permittivity target)	5.0	R	√3	0.6	0.49	1.7	1.4
Liquid permittivity meas.)	2.5	N	1	0.6	0.49	1.5	1.2
Combined standard uncertainty		RSS				12.2	12.0
Expanded uncertainty 95 % confidence interval)						24.3	23.9

Measurement uncertainty evaluation for IEC62209-2 SAR test

Source of uncertainty	Tolerance/ uncertainty ± %	Probability distribution	Divisor	ci (1 g)	ci (10 g)	Standard uncertainty ± %, (1 g)	Standard uncertainty ± %, (10 g)
Measurement system							
Probe calibration	6.55	N	1	1	1	6.6	6.6
Axial Isotropy	4.7	R	√3	1	1	2.7	2.7
Hemispherical Isotropy	9.6	R	√3	0	0	0.0	0.0
Linearity	4.7	R	√3	1	1	2.7	2.7
Modulation Response	0.0	R	√3	1	1	0.0	0.0
Detection limits	1.0	R	√3	1	1	0.6	0.6
Boundary effect	1.0	R	√3	1	1	0.6	0.6
Readout electronics	0.3	N	1	1	1	0.3	0.3
Response time	0.0	R	√3	1	1	0.0	0.0
Integration time	0.0	R	√3	1	1	0.0	0.0
RF ambient conditions – noise	1.0	R	√3	1	1	0.6	0.6
RF ambient conditions–reflections	1.0	R	√3	1	1	0.6	0.6
Probe positioner mech. Restrictions	0.8	R	√3	1	1	0.5	0.5
Probe positioning with respect to phantom shell	6.7	R	√3	1	1	3.9	3.9
Post-processing	2.0	R	√3	1	1	1.2	1.2
Test sample related							
Device holder Uncertainty	6.3	N	1	1	1	6.3	6.3
Test sample positioning	2.8	N	1	1	1	2.8	2.8
Power scaling	4.5	R	√3	1	1	2.6	2.6
Drift of output power	5.0	R	√3	1	1	2.9	2.9
Phantom and set-up							
Phantom uncertainty (shape and thickness tolerances)	4.0	R	√3	1	1	2.3	2.3
Algorithm for correcting SAR for deviations in permittivity and conductivity	1.9	N	1	1	0.84	1.1	0.9
Liquid conductivity (meas.)	2.5	N	1	0.64	0.43	1.6	1.1
Liquid permittivity (meas.)	2.5	N	1	0.6	0.49	1.5	1.2
Temp. unc. - Conductivity	1.7	R	√3	0.78	0.71	0.8	0.7
Temp. unc. - Permittivity	0.3	R	√3	0.23	0.26	0.0	0.0
Combined standard uncertainty		RSS				12.2	12.1
Expanded uncertainty 95 % confidence interval)						24.5	24.2

APPENDIX B EUT TEST POSITION PHOTOS

Please Refer to the Attachment.

APPENDIX C CALIBRATION CERTIFICATES

Please Refer to the Attachment.

******* END OF REPORT *******