



Operation Manual for Smart Hygrothermograph (Mini)



Product Overview




Installation

You can use and install your monitor in the following ways:

- Placing: Directly place the monitor on the surface of the furniture such as table, bookshelf.
- Using the adhesive sticker: Remove the release liner from one side of the adhesive sticker to stick it on the back of the monitor, then remove the release liner from the other side to stick it at the desired place on the wall.




Display Description



Symbol Instructions


Temperature \ Humidity	Less than 19°C	Between 19°C and 27°C	More than 27°C
Less than 20%	(°^°)	(°^°)	(°^°)
Between 20% and 85%	(°^°)	(°°)	(°^°)
More than 85%	(°^°)	(°^°)	(°^°)

Low Battery Notification

When the battery is at a low level, the symbol "  " appears on the display. Please replace the battery.

Switching temperature unit

Remove the back cover when the monitor is working normally, and use a conductive material to connect the two contact points for about 3 seconds, and then the temperature will be changed between °C and °F.




Smart Connection

Connect with Mi Home/Xiaomi Home App

This product works with Mi Home/Xiaomi Home app *. Control your device, and interact it and other smart home devices with Mi Home/Xiaomi Home app.


Scan the QR code to download and install the app. You will be directed to the connection setup page if the app is installed already. Or search "Mi Home/Xiaomi Home" in the app store to download and install it.



Daily Care & Maintenance

Installing the Battery

Remove the cover from the cover opening of the monitor, and place a CR2032 battery with the positive (+) side facing upwards, then reinstall the cover.



Cleaning

- Please prevent water from getting into the monitor when cleaning it.
- When the surface of the monitor is dirty, it can be wiped clean using a damp soft cloth with some neutral detergent.

Precautions

- Do not immerse the ventilation holes into any liquid.
- Do not remove the monitor from a wall with force if it is attached with the adhesive sticker, so as to avoid damage to the wall or the monitor.
- This monitor is not suitable for use in environments with temperatures below 0°C. Please keep it away from harsh environments with high temperatures or high humidity.
- The battery that comes packaged with this product is for trial use only and is not guaranteed to have the same lifespan as a standard new battery.
- This monitor is designed to facilitate a healthy lifestyle, but should not be used as a measuring tool.

Specifications

Name: Smart Hygrothermograph (Mini)

Model: MHO-C122

CMIIT ID : XXXXXXXXXX

FCC ID: 2AWMOMHOC122

Materials: ABS

Dimensions: 44.5 × 44.5 × 13 mm

Net Weight: 24 g

Operating Voltage: DC 3.0 V

Battery Type: CR2032

Temperature Measurement Range: 0°C to 60°C

Humidity Measurement Range: 0–99% RH

Wireless Connectivity: Bluetooth 5.0 Bluetooth

Low Energy

FCC Caution.

§ 15.19 Labelling requirements.

This device complies with part 15 of the FCC Rules.

Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

§ 15.21 Information to user.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

§ 15.105 Information to the user.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This

equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:
-Reorient or relocate the receiving antenna.
-Increase the separation between the equipment and receiver.
-Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
-Consult the dealer or an experienced radio/TV technician for help.

* RF warning for Portable device:

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.