



FCC RADIO TEST REPORT

FCC ID : 2AWNEKDE20102
Equipment : Home Entertainment Hub
Brand Name : E1 by Ericsson
Model Name : KDE20102
Applicant : Ericsson AB
21-23 Torshamnsgatan Stockholm, 16480 Sweden
Manufacturer : CyberTAN Technology Inc.
No. 99, Park Avenue III Science-based Industrial Park
Hsinchu Taiwan 308
Standard : 47 CFR FCC Part 15.247

The product was received on Mar. 27, 2020, and testing was started from Apr. 07, 2020 and completed on May 22, 2020. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Sam Chen

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....3

Summary of Test Result.....4

1 General Description5

1.1 Information.....5

1.2 Applicable Standards7

1.3 Testing Location Information7

1.4 Measurement Uncertainty7

2 Test Configuration of EUT8

2.1 Test Channel Mode8

2.2 The Worst Case Measurement Configuration9

2.3 EUT Operation during Test10

2.4 Accessories11

2.5 Support Equipment.....12

2.6 Test Setup Diagram14

3 Transmitter Test Result17

3.1 AC Power-line Conducted Emissions17

3.2 DTS Bandwidth.....19

3.3 Maximum Conducted Output Power20

3.4 Power Spectral Density22

3.5 Emissions in Non-restricted Frequency Bands24

3.6 Emissions in Restricted Frequency Bands.....25

4 Test Equipment and Calibration Data29

Appendix A. Test Results of AC Power-line Conducted Emissions

Appendix B. Test Results of DTS Bandwidth

Appendix C. Test Results of Maximum Conducted Output Power

Appendix D. Test Results of Power Spectral Density

Appendix E. Test Results of Emissions in Non-restricted Frequency Bands

Appendix F. Test Results of Emissions in Restricted Frequency Bands

Appendix G. Test Results of Radiated Emission Co-location

Appendix H. Test Photos

Photographs of EUT v01



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.1.2	15.203	Antenna Requirement	PASS	-
3.1	15.207	AC Power-line Conducted Emissions	PASS	-
3.2	15.247(a)	DTS Bandwidth	PASS	-
3.3	15.247(b)	Maximum Conducted Output Power	PASS	-
3.4	15.247(e)	Power Spectral Density	PASS	-
3.5	15.247(d)	Emissions in Non-restricted Frequency Bands	PASS	-
3.6	15.247(d)	Emissions in Restricted Frequency Bands	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

1. The test configuration, test mode and test software were written in this test report are declared by the manufacturer.
2. The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Sam Chen

Report Producer: Cindy Peng



1 General Description

1.1 Information

1.1.1 RF General Information

Frequency Range (MHz)	IEEE Std.	Ch. Frequency (MHz)	Channel Number
2400-2483.5	802.15.4	2405-2475	11-25 [15]

Band	Mode	BWch (MHz)	Nant
2.4-2.4835GHz	Zigbee	5	1TX

Note:

- ♦ Zigbee uses a O-QPSK (250kbps) modulation.
- ♦ BWch is the nominal channel bandwidth.

1.1.2 Antenna Information

For WLAN 2.4GHz / WLAN 5GHz / Bluetooth / Zigbee function:

Ant.	Port		Brand	Model Name	Type	Connector	Gain (dBi)	
	WLAN 2.4GHz	WLAN 5GHz B1					WLAN 2.4GHz	WLAN 5GHz B1
1	1	1	Airgain	N2420DSRD	PCB	I-PEX	2.2	3.1
2	2	2	Airgain	N2420DSRF	PCB	I-PEX	2.7	3.3
Ant.	Port		Brand	Model Name	Type	Connector	Gain (dBi)	
	WLAN 5GHz B4	Zigbee					WLAN 5GHz B4	Zigbee
3	1	1	Airgain	N2420DSRC	PCB	I-PEX	3.1	2.8
Ant.	Port		Brand	Model Name	Type	Connector	Gain (dBi)	
	WLAN 5GHz B4	Bluetooth					WLAN 5GHz B4	Bluetooth
4	2	1	Airgain	N2420DSRE	PCB	I-PEX	3.1	2.7

Note1: B1 means band 1, B4 means band 4.

Note2: The above information was declared by manufacturer.

Note3: For WLAN 2.4GHz function (2TX/2RX):

The WLAN 2.4GHz supports the b, g, n, VHT.

Port 1 and Port 2 could transmit/receive simultaneously.

Note4: For WLAN 5GHz Band 1 function (2TX/2RX):

The WLAN 5GHz Band 1 supports the a, n, ac.

Port 1 and Port 2 could transmit/receive simultaneously.

Note5: For WLAN 5GHz Band 4 function (2TX/2RX):

The WLAN 5GHz Band 4 supports the a, n, ac.

Port 1 and Port 2 could transmit/receive simultaneously.

Note6: For Zigbee function (1TX/1RX):

Only Port 1 can be used as transmitting/receiving.

Note7: For Bluetooth function (1TX/1RX):

Only Port 1 can be used as transmitting/receiving.



1.1.3 Mode Test Duty Cycle

Mode	DC	DCF(dB)	T(s)	VBW(Hz) ≥ 1/T
Zigbee	1	0	n/a (DC>=0.98)	n/a (DC>=0.98)

Note:

- ◆ DC is Duty Cycle.
- ◆ DCF is Duty Cycle Factor.

1.1.4 EUT Operational Condition

EUT Power Type	From power adapter		
Function	<input checked="" type="checkbox"/> Point-to-multipoint	<input type="checkbox"/> Point-to-point	
Test Software Version	Telnet		

Note: The above information was declared by manufacturer.

1.1.5 Table of WWAN Module

The EUT contains a LTE module, the detail information as following.

Brand Name	Model Name	FCC ID	Function
Telit	LN960A16	RI7LN960A16	LTE: Band 2/4/5/7/12/13/14/17/25/26/30/38/41/66

1.1.6 Table for EUT Supports Functions

Function	Support Type
AP	Master
Mesh	Master
Bridge	Master

Note: The "AP mode" has been selected to test and recorded in the test report by manufacturer.



1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ ANSI C63.10-2013

The following reference test guidance is not within the scope of accreditation of TAF.

- ♦ FCC KDB 558074 D01 v05r02
- ♦ FCC KDB 662911 D01 v02r01
- ♦ FCC KDB 414788 D01 v01r01

1.3 Testing Location Information

Testing Location		
<input type="checkbox"/>	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL : 886-3-327-3456 FAX : 886-3-327-0973
<input checked="" type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
RF Conducted	TH03-CB	Owen Hsu	23.5~25.5°C / 53~55%	Apr. 10, 2020~May 08, 2020
Radiated Below 1GHz (Mode 1~Mode 3)	03CH06-CB	JN Du	22.7~23.5°C / 53~57%	Apr. 13, 2020~May 22, 2020
Radiated Below 1GHz (Mode 4~Mode 6)	03CH06-CB	Eason Chen	22.7~23.5°C / 53~57%	Apr. 09, 2020~May 14, 2020
Radiated Above 1GHz	03CH03-CB, 03CH02-CB, 03CH04-CB	Eason Chen	22.7~23.5°C / 53~57%	Apr. 09, 2020~May 14, 2020
AC Conduction	CO01-CB	Ryo Fan	21~22°C / 60~63%	Apr. 07, 2020

Test site Designation No. TW0006 with FCC.
Test site registered number IC 4086D with Industry Canada.

1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	2.0 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	4.3 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	4.3 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	5.1 dB	Confidence levels of 95%
Conducted Emission	2.4 dB	Confidence levels of 95%
Output Power Measurement	1.5 dB	Confidence levels of 95%
Power Density Measurement	2.4 dB	Confidence levels of 95%
Bandwidth Measurement	2%	Confidence levels of 95%



2 Test Configuration of EUT

2.1 Test Channel Mode

Mode	Power Setting
Zigbee	-
2405MHz	08
2440MHz	07
2475MHz	-6



2.2 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral
Operating Mode	Normal Link
1	AP mode with LTE Link: Band 2 – EUT + Adapter 1 + Power cable
2	AP mode with LTE Link: Band 4 – EUT + Adapter 2 + Power cable
For operating mode 2 is the worst case and it was record in this test report.	

The Worst Case Mode for Following Conformance Tests	
Tests Item	DTS Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in Non-restricted Frequency Bands
Test Condition	Conducted measurement at transmit chains

The Worst Case Mode for Following Conformance Tests	
Tests Item	Emissions in Restricted Frequency Bands
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.
Operating Mode < 1GHz	CTX
1	WLAN 2.4GHz + Adapter 1
2	WLAN 5GHz Band 1 + Adapter 1
3	WLAN 5GHz Band 4 + Adapter 1
4	Bluetooth + Adapter 1
5	Zigbee + Adapter 1
Mode 4 has been evaluated to be the worst case among Mode 1~5, thus measurement for Mode 6 will follow this same test mode.	
6	Bluetooth + Adapter 2
For operating mode 6 is the worst case and it was record in this test report.	
Operating Mode > 1GHz	CTX



The Worst Case Mode for Following Conformance Tests	
Tests Item	Simultaneous Transmission Analysis - Radiated Emission Co-location
Test Condition	Radiated measurement
Operating Mode	Normal Link
The Operating Mode of Radiated Emission Co-location as below: 1. WLAN 2.4GHz + WLAN 5GHz Band 1 2. WLAN 5GHz Band 4 + Bluetooth 3. WLAN 5GHz Band 4 + Zigbee After evaluating, the full function generated the worst case, thus the measurement will follow this same test configuration.	
1	WLAN 2.4GHz + WLAN 5GHz Band 1 + WLAN 5GHz Band 4 + Bluetooth + Zigbee
Refer to Appendix G for Radiated Emission Co-location.	

The Worst Case Mode for Following Conformance Tests	
Tests Item	Simultaneous Transmission Analysis - Co-location RF Exposure Evaluation
Operating Mode	
1	WLAN 2.4GHz + WLAN 5GHz Band 1 + WLAN 5GHz Band 4 + Bluetooth + Zigbee + LTE
Refer to Sporton Test Report No.: FA031609 for Co-location RF Exposure Evaluation.	

Note: The EUT can only be used Z axis.

2.3 EUT Operation during Test

For CTX Mode:

The EUT was programmed to be in continuously transmitting mode.

For Normal Link:

During the test, the EUT operation to normal function.



2.4 Accessories

Accessories					
No.	Equipment Name	Brand Name	Model Name	Rating	Remark
1	Adapter 1	FSP	FSP100-A1AR3	INPUT: 100-240V~50-60Hz, 1.4A OUTPUT: 5V, 3A / 9V, 3A 12V, 3A / 15V, 3A 20V, 5.0A 100W MAX.	With the cable: Non-shielded, 1.6m
2	Adapter 2	DELTA	ADH-100CR B	INPUT: 100-240V~1.8A, 50-60Hz OUTPUT: 5.0V, 3.0A, 15.0W or 9.0V, 3.0A 15.0V, 3.0A or 20.0V, 5.0A 100.0W.	With the cable: Non-shielded, 1.6m
Others					
3	HDMI cable*1: Shielded, 1.5m				
4	USB-C to USB-A cable*1: Shielded, 0.1m				
5	Power cable*1: Non-shielded, 1m				



2.5 Support Equipment

For AC Conduction:

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	TV	ASUS	VP28U	N/A
B	Micro SD card	Transcend	TS16GUSDHC10	N/A
C	SIM card	N/A	N/A	N/A
D	LAN NB	DELL	E6430	N/A
E	WAN NB	DELL	E6430	N/A
F	2.4G NB	DELL	E6430	N/A
G	5G-1 NB	DELL	E6430	N/A
H	5G-2 NB	DELL	E6430	N/A
I	Bluetooth speaker	Wei Xuan	S06B	N/A
J	Zigbee device	N/A	N/A	N/A
K	LTE base station	Anritsu	MT8820C	N/A
L	Air mouse	HENGCHUANGYU	HCY-57B	2AOBUHCY-57B

For Radiated (below 1GHz):

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	LCD Monitor	DELL	1704FPTt	N/A
B	USB Hub	IOTNPCI	HB-16	N/A
C	Keyboard	iCooky	SK068	N/A
D	Mouse	Logitech	M-U0026	N/A

For Radiated (above 1GHz):


Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	LCD Monitor	DELL	1704FPTt	N/A
B	USB Hub	IOTNPCI	HB-16	N/A
C	Keyboard	iCooky	SK068	N/A
D	Mouse	Logitech	M-U0026	N/A
E	Debug adapter ISA3	SILICON LABS	EM-ISA3-01	N/A




For RF Conducted:

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	NB	DELL	E4300	N/A

2.6 Test Setup Diagram




Test Setup Diagram - Radiated Test < 1GHz



Item	Connection	Shielded	Length
1	Power cable	No	2.6m
2	Power cable	No	1.5m
3	HDMI cable	Yes	1.5m
4	USB cable	Yes	0.1m
5	USB cable	Yes	1.8m
6	USB cable	Yes	1.8m
7	USB cable	Yes	0.9m

Test Setup Diagram - Radiated Test > 1GHz



Item	Connection	Shielded	Length
1	Power cable	No	2.6m
2	Power cable	No	1.5m
3	HDMI cable	Yes	1.5m
4	USB cable	Yes	0.1m
5	USB cable	Yes	1.8m
6	USB cable	Yes	1.8m
7	USB cable	Yes	1m
8	RJ-45 cable	No	1.5m
9	USB cable	Yes	0.9m



3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> Refer as ANSI C63.10-2013, clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup



3.1.5 Test Result of AC Power-line Conducted Emissions

Refer as Appendix A

3.2 DTS Bandwidth

3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit
Systems using digital modulation techniques:
<ul style="list-style-type: none"> ▪ 6 dB bandwidth \geq 500 kHz.


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method
<ul style="list-style-type: none"> ▪ For the emission bandwidth shall be measured using one of the options below:
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 8.2 & C63.10 clause 11.8.1 Option 1 for 6 dB bandwidth measurement.
<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.2 & C63.10 clause 11.8.2 Option 2 for 6 dB bandwidth measurement.
<input type="checkbox"/> Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.

3.2.4 Test Setup



3.2.5 Test Result of Emission Bandwidth

Refer as Appendix B



3.3 Maximum Conducted Output Power

3.3.1 Maximum Conducted Output Power Limit

Maximum Conducted Output Power Limit	
	<ul style="list-style-type: none"> ▪ If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W)
	<ul style="list-style-type: none"> ▪ Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm
	<ul style="list-style-type: none"> ▪ Point-to-point systems (P2P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	<ul style="list-style-type: none"> ▪ Smart antenna system (SAS):
	<ul style="list-style-type: none"> - Single beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	<ul style="list-style-type: none"> - Overlap beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	<ul style="list-style-type: none"> - Aggregate power on all beams: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3 + 8$ dB dBm
P_{Out} = maximum peak conducted output power or maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi.	

3.3.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method	
	<ul style="list-style-type: none"> ▪ Maximum Peak Conducted Output Power
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.3.1.1 & C63.10 clause 11.9.1.1 (RBW \geq EBW method).
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.3.1.3 & C63.10 clause 11.9.1.3 (peak power meter).
	<ul style="list-style-type: none"> ▪ Maximum Conducted Output Power
	[duty cycle \geq 98% or external video / power trigger]
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.2 Method AVGSA-1.
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.3 Method AVGSA-1A. (alternative)
	duty cycle < 98% and average over on/off periods with duty factor
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.4 Method AVGSA-2.
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.5 Method AVGSA-2A (alternative)
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.6 Method AVGSA-3
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.7 Method AVGSA-3A (alternative)
	Measurement using a power meter (PM)
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.3.2.3 & C63.10 clause 11.9.2.3.1 Method AVGPM (using an RF average power meter).
	<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 8.3.2.3 & C63.10 clause 11.9.2.3.2 Method AVGPM-G (using an gate RF average power meter).

<ul style="list-style-type: none"> For conducted measurement. 	
	<ul style="list-style-type: none"> If the EUT supports multiple transmit chains using options given below: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.
	<ul style="list-style-type: none"> If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$

3.3.4 Test Setup



3.3.5 Test Result of Maximum Conducted Output Power

Refer as Appendix C



3.4 Power Spectral Density

3.4.1 Power Spectral Density Limit

Power Spectral Density Limit
<ul style="list-style-type: none"> Power Spectral Density (PSD) \leq 8 dBm/3kHz


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

Test Method
<ul style="list-style-type: none"> Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 8.4 & C63.10 clause 11.10 Method Max. PSD.
<ul style="list-style-type: none"> For conducted measurement. <ul style="list-style-type: none"> If The EUT supports multiple transmit chains using options given below: <ul style="list-style-type: none"> <input type="checkbox"/> Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the NTX output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace. <input type="checkbox"/> Option 2: Measure and sum spectral maxima across the outputs. With this technique, spectra are measured at each output of the device at the required resolution bandwidth. The maximum value (peak) of each spectrum is determined. These maximum values are then summed mathematically in linear power units across the outputs. These operations shall be performed separately over frequency spans that have different out-of-band or spurious emission limits, <input type="checkbox"/> Option 3: Measure and add 10 log(N) dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with 10 log(N). Or each transmit chains shall be add 10 log(N) to compared with the limit.

3.4.4 Test Setup



3.4.5 Test Result of Power Spectral Density

Refer as Appendix D

3.5 Emissions in Non-restricted Frequency Bands

3.5.1 Emissions in Non-restricted Frequency Bands Limit

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dBc)
Peak output power procedure	20
Average output power procedure	30

Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.


3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures

Test Method
<ul style="list-style-type: none"> Refer as FCC KDB 558074, clause 8.5 for unwanted emissions into non-restricted bands.

3.5.4 Test Setup



3.5.5 Test Result of Emissions in Non-restricted Frequency Bands

Refer as Appendix E



3.6 Emissions in Restricted Frequency Bands

3.6.1 Emissions in Restricted Frequency Bands Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m.

3.6.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.




3.6.3 Test Procedures

Test Method	
<ul style="list-style-type: none"> ▪ The average emission levels shall be measured in [duty cycle \geq 98 or duty factor]. 	
<ul style="list-style-type: none"> ▪ Refer as ANSI C63.10, clause 6.10.3 band-edge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band. 	
<ul style="list-style-type: none"> ▪ For the transmitter unwanted emissions shall be measured using following options below: 	
	<ul style="list-style-type: none"> ▪ Refer as FCC KDB 558074, clause 8.6 for unwanted emissions into restricted bands.
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.1(trace averaging for duty cycle \geq 98%).
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.2(trace averaging + duty factor).
	<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.3(Reduced VBW \geq 1/T).
	<input type="checkbox"/> Refer as ANSI C63.10, clause 11.12.2.5.3 (Reduced VBW). VBW \geq 1/T, where T is pulse time.
	<input type="checkbox"/> Refer as ANSI C63.10, clause 7.5 average value of pulsed emissions.
	<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.4 measurement procedure peak limit.
<ul style="list-style-type: none"> ▪ For the transmitter band-edge emissions shall be measured using following options below: 	
	<ul style="list-style-type: none"> ▪ Refer as FCC KDB 558074 clause 8.7 & c63.10 clause 11.13.1, When the performing peak or average radiated measurements, emissions within 2 MHz of the authorized band edge may be measured using the marker-delta method described below.
	<ul style="list-style-type: none"> ▪ Refer as FCC KDB 558074, clause 8.7 (ANSI C63.10, clause 6.10.6) for marker-delta method for band-edge measurements.
	<ul style="list-style-type: none"> ▪ Refer as FCC KDB 558074, clause 8.7 for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels (i.e., 1 MHz).
	<ul style="list-style-type: none"> ▪ For conducted unwanted emissions into restricted bands (absolute emission limits). Devices with multiple transmit chains using options given below: (1) Measure and sum the spectra across the outputs or (2) Measure and add 10 log(N) dB
	<ul style="list-style-type: none"> ▪ For FCC KDB 662911 The methodology described here may overestimate array gain, thereby resulting in apparent failures to satisfy the out-of-band limits even if the device is actually compliant. In such cases, compliance may be demonstrated by performing radiated tests around the frequencies at which the apparent failures occurred.

3.6.4 Test Setup





3.6.5 Measurement Results Calculation

The measured Level is calculated using:

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.6.6 Emissions in Restricted Frequency Bands (Below 30MHz)

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to KDB414788 Radiated Test Site, and the result came out very similar.

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

The radiated emissions were investigated from 9 kHz or the lowest frequency generated within the device, up to the 10 harmonic or 40 GHz, whichever is appropriate.

3.6.7 Test Result of Emissions in Restricted Frequency Bands

Refer as Appendix F



4 Test Equipment and Calibration Data

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
EMI Receiver	Agilent	N9038A	My52260123	9kHz ~ 8.45GHz	Feb. 26, 2020	Feb. 25, 2021	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Dec. 25, 2019	Dec. 24, 2020	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Feb. 25, 2020	Feb. 24, 2021	Conduction (CO01-CB)
Pulse Limiter	Rohde&Schwarz	ESH3-Z2	100430	9kHz ~ 30MHz	Jan. 31, 2020	Jan. 30, 2021	Conduction (CO01-CB)
COND Cable	Woken	Cable	Low cable-CO01	9kHz ~ 30MHz	May 21, 2019	May 20, 2020	Conduction (CO01-CB)
Software	Audix	E3	6.120210n	-	N.C.R.	N.C.R.	Conduction (CO01-CB)
Loop Antenna	Teseq	HLA 6120	31244	9kHz - 30 MHz	Mar. 16, 2020	Mar. 15, 2021	Radiation (03CH06-CB)
Bilog Antenna with 6 dB attenuator	TESEQ & EMCI	CBL6112D & N-6-06	37878 & AT-N0606	20MHz ~ 2GHz	Aug. 03, 2019	Aug. 02, 2020	Radiation (03CH06-CB)
Pre-Amplifier	Agilent	310N	187290	0.1MHz ~ 1GHz	May 07, 2019	May 06, 2020	Radiation (03CH06-CB)
Pre-Amplifier	Agilent	310N	187290	0.1MHz ~ 1GHz	Apr. 28, 2020	Apr. 27, 2021	Radiation (03CH06-CB)
Spectrum analyzer	R&S	FSP40	100080	9kHz~40GHz	Oct. 21, 2019	Oct. 20, 2020	Radiation (03CH06-CB)
EMI Test Receiver	R&S	ESCS	826547/017	9kHz ~ 2.75GHz	May 15, 2019	May 14, 2020	Radiation (03CH06-CB)
EMI Test Receiver	R&S	ESCS	826547/017	9kHz ~ 2.75GHz	May 13, 2020	May 12, 2021	Radiation (03CH06-CB)
RF Cable-low	HUBER+SUHNER	RG402	Low Cable-05+24	30MHz~1GHz	Oct. 07, 2019	Oct. 06, 2020	Radiation (03CH06-CB)
Horn Antenna	ETS · Lindgren	3115	6821	750MHz~18GHz	Jan. 20, 2020	Jan. 19, 2021	Radiation (03CH03-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Jun. 27, 2019	Jun. 26, 2020	Radiation (03CH03-CB)
Pre-Amplifier	Agilent	8449B	3008A02097	1GHz ~ 26.5GHz	Dec. 19, 2019	Dec. 18, 2020	Radiation (03CH03-CB)
Pre-Amplifier	MITEQ	TTA1840-35-HG	1864479	18GHz ~ 40GHz	Jul. 03, 2019	Jul. 02, 2020	Radiation (03CH03-CB)
Spectrum Analyzer	R&S	FSP40	100019	9kHz ~ 40GHz	Jun. 19, 2019	Jun. 18, 2020	Radiation (03CH03-CB)
RF Cable-high	Woken	RG402	High Cable-20+27	1GHz ~ 18GHz	Oct. 07, 2019	Oct. 06, 2020	Radiation (03CH03-CB)
RF Cable-high	Woken	RG402	High Cable-27	1GHz ~ 18GHz	Oct. 07, 2019	Oct. 06, 2020	Radiation (03CH03-CB)
RF Cable-high	Woken	RG402	High Cable-40G#1	18GHz ~ 40 GHz	Jul. 24, 2019	Jul. 23, 2020	Radiation (03CH03-CB)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
RF Cable-high	Woken	RG402	High Cable-40G#2	18GHz ~ 40 GHz	Jul. 24, 2019	Jul. 23, 2020	Radiation (03CH03-CB)
Horn Antenna	EMCO	3115	9610-4976	1GHz ~ 18GHz	Apr. 24, 2019	Apr. 23, 2020	Radiation (03CH02-CB)
Horn Antenna	EMCO	3115	9610-4976	1GHz ~ 18GHz	Apr. 21, 2020	Apr. 20, 2021	Radiation (03CH02-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Jun. 27, 2019	Jun. 26, 2020	Radiation (03CH02-CB)
Pre-Amplifier	Agilent	83017A	MY39501305	1GHz ~ 26.5GHz	Aug. 21, 2019	Aug. 20, 2020	Radiation (03CH02-CB)
Pre-Amplifier	MITEQ	TTA1840-35-H G	1864479	18GHz ~ 40GHz	Jul. 03, 2019	Jul. 02, 2020	Radiation (03CH02-CB)
Spectrum Analyzer	R&S	FSP40	100304	9kHz ~ 40GHz	Aug. 15, 2019	Aug. 14, 2020	Radiation (03CH02-CB)
High Cable	Woken	RG402	High Cable-18	1GHz ~ 18GHz	Oct. 07, 2019	Oct. 06, 2020	Radiation (03CH02-CB)
High Cable	Woken	RG402	High Cable-18+19	1GHz ~ 18GHz	Oct. 07, 2019	Oct. 06, 2020	Radiation (03CH02-CB)
RF Cable-high	Woken	RG402	High Cable-40G#1	18GHz ~ 40 GHz	Jul. 24, 2019	Jul. 23, 2020	Radiation (03CH02-CB)
RF Cable-high	Woken	RG402	High Cable-40G#2	18GHz ~ 40 GHz	Jul. 24, 2019	Jul. 23, 2020	Radiation (03CH02-CB)
Horn Antenna	ETS · Lindgren	3115	00143147	750MHz~18GHz	Oct. 22, 2019	Oct. 21, 2020	Radiation (03CH04-CB)
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170507	15GHz ~ 40GHz	Jun. 12, 2019	Jun. 11, 2020	Radiation (03CH04-CB)
Pre-Amplifier	Agilent	83017A	MY53270063	0.5GHz ~ 26.5GHz	Mar. 11, 2020	Mar. 10, 2021	Radiation (03CH04-CB)
Pre-Amplifier	MITEQ	TTA1840-35-H G	1864479	18GHz ~ 40GHz	Jul. 03, 2019	Jul. 02, 2020	Radiation (03CH04-CB)
Spectrum Analyzer	R&S	FSP40	100142	9kHz~40GHz	Dec. 18, 2019	Dec. 17, 2020	Radiation (03CH04-CB)
RF Cable-high	Woken	RG402	High Cable-21	1GHz - 18GHz	Oct. 07, 2019	Oct. 06, 2020	Radiation (03CH04-CB)
RF Cable-high	Woken	RG402	High Cable-21+22	1GHz - 18GHz	Oct. 07, 2019	Oct. 06, 2020	Radiation (03CH04-CB)
RF Cable-high	Woken	RG402	High Cable-40G#1	18GHz ~ 40 GHz	Jul. 24, 2019	Jul. 23, 2020	Radiation (03CH04-CB)
RF Cable-high	Woken	RG402	High Cable-40G#2	18GHz ~ 40 GHz	Jul. 24, 2019	Jul. 23, 2020	Radiation (03CH04-CB)
Spectrum analyzer	R&S	FSV40	101028	9kHz~40GHz	Nov. 01, 2019	Oct. 31, 2020	Conducted (TH03-CB)
Power Sensor	Anritsu	MA2411B	1726195	300MHz~40GHz	Aug. 13, 2019	Aug. 12, 2020	Conducted (TH03-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Aug. 13, 2019	Aug. 12, 2020	Conducted (TH03-CB)
RF Cable-high	Woken	RG402	High Cable-11	1 GHz ~ 26.5 GHz	Oct. 07, 2019	Oct. 06, 2020	Conducted (TH03-CB)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
RF Cable-high	Woken	RG402	High Cable-12	1 GHz – 26.5 GHz	Oct. 07, 2019	Oct. 06, 2020	Conducted (TH03-CB)
RF Cable-high	Woken	RG402	High Cable-13	1 GHz – 26.5 GHz	Oct. 07, 2019	Oct. 06, 2020	Conducted (TH03-CB)
RF Cable-high	Woken	RG402	High Cable-14	1 GHz – 26.5 GHz	Oct. 07, 2019	Oct. 06, 2020	Conducted (TH03-CB)
RF Cable-high	Woken	RG402	High Cable-15	1 GHz – 26.5 GHz	Oct. 07, 2019	Oct. 06, 2020	Conducted (TH03-CB)


Note: Calibration Interval of instruments listed above is one year.


N.C.R. means Non-Calibration required.



Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Factor (dB)	Condition
Mode 2	Pass	QP	159k	57.62	65.52	-7.90	9.90	Line







Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
Zigbee	1.594M	2.48M	2M48G1D	1.575M	2.43M



Max-N dB = Maximum 6dB down bandwidth; **Max-OBW** = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;




Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
Zigbee	-	-	-	-
2405MHz	Pass	500k	1.588M	2.43M
2440MHz	Pass	500k	1.594M	2.48M
2475MHz	Pass	500k	1.575M	2.433M

Port X-N dB = Port X 6dB down bandwidth; **Port X-OBW** = Port X 99% occupied bandwidth;







Average Power Result

Appendix C

Summary

Mode	Total Power (dBm)	Total Power (W)
2.4-2.4835GHz	-	-
Zigbee	23.03	0.20091



Average Power Result

Result

Mode	Result	DG (dBi)	Port 1 (dBm)	Total Power (dBm)	Power Limit (dBm)
Zigbee	-	-	-	-	-
2405MHz	Pass	2.80	23.03	23.03	30.00
2440MHz	Pass	2.80	22.98	22.98	30.00
2475MHz	Pass	2.80	14.82	14.82	30.00

DG = Directional Gain; Port X = Port X output power



Summary

Mode	PD (dBm/RBW)
2.4-2.4835GHz	-
Zigbee	7.98

RBW = 500 kHz for 5.725-5.85GHz band / 1MHz for other band;






Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)
Zigbee	-	-	-	-	-
2405MHz	Pass	2.80	7.98	7.98	8.00
2440MHz	Pass	2.80	7.37	7.37	8.00
2475MHz	Pass	2.80	1.43	1.43	8.00

DG = Directional Gain; **RBW** = 500 kHz for 5.725-5.85GHz band / 1MHz for other band;

PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; **Port X** = Port X power density;







Summary


Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Zigbee	Pass	2.40472G	18.57	-11.43	2.30563G	-54.88	2.39992G	-22.48	2.4G	-23.86	2.48613G	-54.85	7.21424G	-48.99	1



Result

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
Zigbee	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
2405MHz	Pass	2.40472G	18.57	-11.43	2.30563G	-54.88	2.39992G	-22.48	2.4G	-23.86	2.48613G	-54.85	7.21424G	-48.99	1
2440MHz	Pass	2.40472G	18.57	-11.43	2.30003G	-55.05	2.39989G	-53.60	2.4G	-54.42	2.48796G	-54.98	23.59897G	-49.41	1
2475MHz	Pass	2.40472G	18.57	-11.43	2.03394G	-55.46	2.39393G	-54.77	2.4835G	-53.21	2.48389G	-42.83	24.94655G	-48.97	1








Summary


Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Condition
Mode 6	Pass	QP	30M	39.75	40.00	-0.25	Horizontal

14/05/2020



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	Raw (dBuV/m)	AF (dB/m)	CL (dB)	PA (dB)
QP	31.94M	39.52	40.00	-0.48	-7.46	3	Vertical	323	2.00	"Worst"	46.98	23.40	1.54	32.40
PK	54.25M	33.89	40.00	-6.11	-18.38	3	Vertical	348	3.00	-	52.27	12.80	1.48	32.66
PK	60.07M	34.74	40.00	-5.26	-18.69	3	Vertical	254	1.00	-	53.43	12.23	1.60	32.52
PK	94.02M	39.61	43.50	-3.89	-14.81	3	Vertical	201	4.00	-	54.42	15.52	2.00	32.33
PK	108.57M	36.65	43.50	-6.85	-12.85	3	Vertical	354	1.00	-	49.50	17.41	2.19	32.45
PK	480.08M	37.25	46.00	-8.75	-4.40	3	Vertical	284	1.25	-	41.65	23.28	4.48	32.16

14/05/2020



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	Raw (dBuV/m)	AF (dB/m)	CL (dB)	PA (dB)
QP	30M	39.75	40.00	-0.25	-6.64	3	Horizontal	88	3.00	"Worst"	46.39	24.21	1.50	32.35
PK	94.02M	39.67	43.50	-3.83	-14.81	3	Horizontal	45	4.00	-	54.48	15.52	2.00	32.33
PK	103.72M	36.31	43.50	-7.19	-13.28	3	Horizontal	98	2.00	-	49.59	16.98	2.14	32.40
PK	110.51M	36.90	43.50	-6.60	-12.71	3	Horizontal	245	1.25	-	49.61	17.56	2.21	32.48
PK	480.08M	38.63	46.00	-7.37	-4.40	3	Horizontal	162	1.25	-	43.03	23.28	4.48	32.16
PK	521.79M	39.48	46.00	-6.52	-4.19	3	Horizontal	293	4.00	-	43.67	23.41	4.73	32.33



Summary


Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-
Zigbee	Pass	AV	12.02756G	52.97	54.00	-1.03	3	Horizontal	64	1.00	-



Zigbee

09/04/2020

2405MHz_TX



Lim.PK
 PK
 Lim.AV
 AV

EUT Z_1TX
Setting 08
03-B-W-3


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.3898G	62.13	74.00	-11.87	30.12	3	Vertical	306	2.37	-	28.28	3.73	-
AV	2.39G	50.57	54.00	-3.43	18.56	3	Vertical	306	2.37	-	28.28	3.73	-
PK	2.4054G	120.14	Inf	-Inf	88.08	3	Vertical	306	2.37	-	28.32	3.74	-
AV	2.405G	115.73	Inf	-Inf	83.67	3	Vertical	306	2.37	-	28.32	3.74	-



Zigbee

09/04/2020

2405MHz_TX




EUT Z_1TX
Setting 08
03-B-W-3

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.3892G	61.43	74.00	-12.57	29.42	3	Horizontal	228	2.24	-	28.28	3.73	-
AV	2.39G	49.64	54.00	-4.36	17.63	3	Horizontal	228	2.24	-	28.28	3.73	-
PK	2.4054G	118.13	Inf	-Inf	86.07	3	Horizontal	228	2.24	-	28.32	3.74	-
AV	2.405G	113.71	Inf	-Inf	81.65	3	Horizontal	228	2.24	-	28.32	3.74	-

Zigbee

09/04/2020

2405MHz_TX




EUT_Z_1TX
Setting 08
03-B-W-3

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.80902G	52.68	74.00	-21.32	47.43	3	Vertical	133	2.53	-	33.52	6.56	34.83
AV	4.80898G	41.53	54.00	-12.47	36.28	3	Vertical	133	2.53	-	33.52	6.56	34.83
PK	12.02758G	60.23	74.00	-13.77	45.52	3	Vertical	237	2.31	-	39.21	10.24	34.74
AV	12.02742G	48.07	54.00	-5.93	33.36	3	Vertical	237	2.31	-	39.21	10.24	34.74

Zigbee

09/04/2020

2405MHz_TX




EUT_Z_1TX
Setting 08
03-B-W-3

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.80882G	50.78	74.00	-23.22	45.53	3	Horizontal	80	1.89	-	33.52	6.56	34.83
AV	4.80902G	37.79	54.00	-16.21	32.54	3	Horizontal	80	1.89	-	33.52	6.56	34.83
PK	12.0225G	64.04	74.00	-9.96	49.34	3	Horizontal	64	1.00	-	39.20	10.24	34.74
AV	12.02756G	52.97	54.00	-1.03	38.26	3	Horizontal	64	1.00	-	39.21	10.24	34.74

Zigbee

2440MHz_TX

09/04/2020




EUT Z_1TX
Setting 08
03-B-W-3

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.3716G	59.13	74.00	-14.87	27.17	3	Vertical	308	2.23	-	28.24	3.72	-
AV	2.39G	46.77	54.00	-7.23	14.76	3	Vertical	308	2.23	-	28.28	3.73	-
PK	2.4404G	120.62	Inf	-Inf	88.44	3	Vertical	308	2.23	-	28.42	3.76	-
AV	2.44G	116.09	Inf	-Inf	83.91	3	Vertical	308	2.23	-	28.42	3.76	-
PK	2.4988G	60.58	74.00	-13.42	28.18	3	Vertical	308	2.23	-	28.60	3.80	-
AV	2.498G	47.48	54.00	-6.52	15.09	3	Vertical	308	2.23	-	28.59	3.80	-

Zigbee

09/04/2020

2440MHz_TX



EUT Z_1TX
Setting 08
03-B-W-3


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.3584G	59.64	74.00	-14.36	27.70	3	Horizontal	227	1.72	-	28.22	3.72	-
AV	2.388G	46.73	54.00	-7.27	14.72	3	Horizontal	227	1.72	-	28.28	3.73	-
PK	2.4404G	118.56	Inf	-Inf	86.38	3	Horizontal	227	1.72	-	28.42	3.76	-
AV	2.44G	114.01	Inf	-Inf	81.83	3	Horizontal	227	1.72	-	28.42	3.76	-
PK	2.484G	59.33	74.00	-14.67	26.99	3	Horizontal	227	1.72	-	28.55	3.79	-
AV	2.492G	47.47	54.00	-6.53	15.09	3	Horizontal	227	1.72	-	28.58	3.80	-



Zigbee

09/04/2020

2440MHz_TX



EUT_Z_1TX
Setting 08
03-B-W-3


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.87899G	51.58	74.00	-22.42	46.12	3	Vertical	169	2.73	-	33.66	6.58	34.78
AV	4.88112G	39.96	54.00	-14.04	34.50	3	Vertical	169	2.73	-	33.66	6.58	34.78
PK	7.31842G	54.53	74.00	-19.47	44.90	3	Vertical	317	2.03	-	36.82	7.87	35.06
AV	7.32148G	40.23	54.00	-13.77	30.60	3	Vertical	317	2.03	-	36.82	7.87	35.06
PK	12.19748G	57.38	74.00	-16.62	42.36	3	Vertical	20	1.00	-	39.24	10.31	34.53
AV	12.19736G	45.26	54.00	-8.74	30.24	3	Vertical	20	1.00	-	39.24	10.31	34.53



Zigbee

09/04/2020

2440MHz_TX



EUT_Z_1TX
Setting 08
03-B-W-3


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.88016G	51.32	74.00	-22.68	45.86	3	Horizontal	253	2.67	-	33.66	6.58	34.78
AV	4.87894G	38.38	54.00	-15.62	32.92	3	Horizontal	253	2.67	-	33.66	6.58	34.78
PK	7.32154G	53.04	74.00	-20.96	43.41	3	Horizontal	165	2.03	-	36.82	7.87	35.06
AV	7.32146G	40.40	54.00	-13.60	30.77	3	Horizontal	165	2.03	-	36.82	7.87	35.06
PK	12.19706G	57.14	74.00	-16.86	42.12	3	Horizontal	267	2.20	-	39.24	10.31	34.53
AV	12.20264G	44.65	54.00	-9.35	29.62	3	Horizontal	267	2.20	-	39.24	10.31	34.52



Zigbee

09/04/2020

2475MHz_TX



EUT_Z_1TX
Setting -6
02-D-E-2


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.4746G	110.25	Inf	-Inf	76.63	3	Vertical	306	2.12	-	30.05	3.57	-
AV	2.475G	105.80	Inf	-Inf	72.17	3	Vertical	306	2.12	-	30.05	3.58	-
PK	2.4836G	60.80	74.00	-13.20	27.12	3	Vertical	306	2.12	-	30.10	3.58	-
AV	2.4835G	50.95	54.00	-3.05	17.27	3	Vertical	306	2.12	-	30.10	3.58	-



Zigbee

09/04/2020

2475MHz_TX



EUT_Z_1TX
Setting -6
02-D-E-2


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	2.4744G	111.48	Inf	-Inf	77.86	3	Horizontal	64	2.43	-	30.05	3.57	-
AV	2.4752G	107.17	Inf	-Inf	73.54	3	Horizontal	64	2.43	-	30.05	3.58	-
PK	2.4835G	62.22	74.00	-11.78	28.54	3	Horizontal	64	2.43	-	30.10	3.58	-
AV	2.4835G	52.40	54.00	-1.60	18.72	3	Horizontal	64	2.43	-	30.10	3.58	-



Zigbee

09/04/2020

2475MHz_TX



EUT_Z_1TX
Setting -6
02-D-E-2


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.95078G	49.98	74.00	-24.02	40.34	3	Vertical	169	1.70	-	34.10	5.88	30.34
AV	4.94912G	38.92	54.00	-15.08	29.29	3	Vertical	169	1.70	-	34.10	5.87	30.34



Zigbee

09/04/2020

2475MHz_TX



EUT_Z_1TX
Setting -6
02-D-E-2


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)
PK	4.94902G	50.22	74.00	-23.78	40.59	3	Horizontal	310	2.65	-	34.10	5.87	30.34
AV	4.94904G	37.57	54.00	-16.43	27.94	3	Horizontal	310	2.65	-	34.10	5.87	30.34



Summary


Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Condition
Mode 1	Pass	AV	1.33521G	50.00	54.00	-4.00	Vertical

14/05/2020



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
PK	1.03881G	50.86	74.00	-23.14	-11.49	3	Vertical	213	1.50	-	62.35	23.68	2.25	37.42
AV	1.0384G	46.00	54.00	-8.00	-11.50	3	Vertical	213	1.50	-	57.50	23.68	2.25	37.43
PK	1.33518G	55.72	74.00	-18.28	-8.31	3	Vertical	185	1.42	-	64.03	25.28	2.55	36.14
AV	1.33521G	50.00	54.00	-4.00	-8.31	3	Vertical	185	1.42	"Worst"	58.31	25.28	2.55	36.14
PK	1.48352G	50.65	74.00	-23.35	-7.32	3	Vertical	152	1.00	-	57.97	25.60	2.68	35.60
AV	1.48357G	43.54	54.00	-10.46	-7.32	3	Vertical	152	1.00	-	50.86	25.60	2.68	35.60
PK	1.91991G	46.77	74.00	-27.23	-4.97	3	Vertical	127	1.57	-	51.74	27.00	3.08	35.05
AV	1.92017G	39.23	54.00	-14.77	-4.97	3	Vertical	127	1.57	-	44.20	27.00	3.08	35.05
PK	3.56057G	51.75	74.00	-22.25	0.72	3	Vertical	213	1.00	-	51.03	30.62	4.22	34.12
AV	3.56037G	47.23	54.00	-6.77	0.72	3	Vertical	213	1.00	-	46.51	30.62	4.22	34.12

14/05/2020



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
PK	1.03849G	52.63	74.00	-21.37	-11.50	3	Horizontal	52	1.28	-	64.13	23.68	2.25	37.43
AV	1.03849G	47.40	54.00	-6.60	-11.50	3	Horizontal	52	1.28	-	58.90	23.68	2.25	37.43
PK	1.33518G	54.17	74.00	-19.83	-8.31	3	Horizontal	59	1.24	-	62.48	25.28	2.55	36.14
AV	1.33521G	49.63	54.00	-4.37	-8.31	3	Horizontal	59	1.24	"Worst"	57.94	25.28	2.55	36.14
PK	1.4836G	49.96	74.00	-24.04	-7.32	3	Horizontal	240	1.00	-	57.28	25.60	2.68	35.60
AV	1.48349G	42.27	54.00	-11.73	-7.32	3	Horizontal	240	1.00	-	49.59	25.60	2.68	35.60
PK	1.92005G	45.94	74.00	-28.06	-4.97	3	Horizontal	141	1.00	-	50.91	27.00	3.08	35.05
AV	1.92015G	40.23	54.00	-13.77	-4.97	3	Horizontal	141	1.00	-	45.20	27.00	3.08	35.05
PK	3.56036G	50.83	74.00	-23.17	0.72	3	Horizontal	151	1.00	-	50.11	30.62	4.22	34.12
AV	3.56035G	44.54	54.00	-9.46	0.72	3	Horizontal	151	1.00	-	43.82	30.62	4.22	34.12