

FCC ID: 2AWNGFT101V40

Maximum Permissible Exposure (MPE)

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

Measurement Result

BT:

Operation Frequency: 2402MHz~2480MHz

Power density limited: $1\text{mW}/\text{cm}^2$

Antenna Type: External Antenna

WIFI antenna gain: 1.8dBi;

R=20cm

$\text{mW}=10^{(\text{dBm}/10)}$

antenna gain Numeric= $10^{(\text{dBi}/10)}=10^{(1.8/10)}=1.51$

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain	Power density(mW/cm^2)	(mW/cm2)
				(dBm)	(mW)	Numeric		
2402	GFSK	-1.574	-2±1	-1	0.794328	1.51	0.00024	1
2441		-2.002	-2±1	-1	0.794328	1.51	0.00024	1
2480		-2.295	-2±1	-1	0.794328	1.51	0.00024	1
2402	π/4-DQPSK,	-0.185	-1±1	0	1	1.51	0.00030	1
2441		-0.481	-1±1	0	1	1.51	0.00030	1
2480		-0.744	-1±1	0	1	1.51	0.00030	1
2402	8DPSK	0.049	0±1	1	1.258925	1.51	0.00038	1
2441		0.011	0±1	1	1.258925	1.51	0.00038	1
2480		-0.47	0±1	1	1.258925	1.51	0.00038	1
2402	BLE(GFSK)	3.756	3±1	4	2.511886	1.51	0.00075	1
2440		3.604	3±1	4	2.511886	1.51	0.00075	1
2480		3.784	3±1	4	2.511886	1.51	0.00075	1

2.4G WIFI:

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,

WIFI 802.11n HT40:2422-2452MHz

Power density limited: $1\text{mW}/\text{cm}^2$

Antenna Type: External Antenna

WIFI antenna gain: 1.8dBi;

R=20cm

$\text{mW}=10^{(\text{dBm}/10)}$

antenna gain Numeric= $10^{(\text{dBi}/10)}=10^{(1.8/10)}=1.51$

SISO

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain	Power density(mW/cm^2)	(mW/cm2)
				(dBm)	(mW)	Numeric		
2412	802.11b	12.51	12±1	13	19.95262	1.51	0.00599	1
2437		12.41	12±1	13	19.95262	1.51	0.00599	1
2462		12.31	12±1	13	19.95262	1.51	0.00599	1
2412	802.11g	11.78	11±1	12	15.84893	1.51	0.00476	1
2437		11.97	11±1	12	15.84893	1.51	0.00476	1
2462		11.78	11±1	12	15.84893	1.51	0.00476	1
2412	802.11n H20	11.53	11±1	12	15.84893	1.51	0.00476	1
2437		11.77	11±1	12	15.84893	1.51	0.00476	1
2462		11.8	11±1	12	15.84893	1.51	0.00476	1
2422	802.11n H40	11.48	11±1	12	15.84893	1.51	0.00476	1
2437		10.92	11±1	12	15.84893	1.51	0.00476	1
2452		11.74	11±1	12	15.84893	1.51	0.00476	1

Conclusion:

For the max result : $0.00599 \leq 1$ for Max Power Density, Compliance the RF Exposure requirement.

Signature:

Date: 2021-04-22



NAME AND TITLE (Please print or type): alex li/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.