



Report No.: FCS202011035W02

## FCC RF Exposure

**EUT Description: Home Security Camera** 

ModelNo.:PC420,PC430,PC440,PC450,PC460,PC470,PC480,PC490,MC120,MC140,MC160,MC180,

PC420 Pro,PC430 Pro,PC440 Pro,PC450 Pro,PC460 Pro

FCC ID: 2AWNK-PC420

Equipment type: fixed equipment

## 1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)			
(A) Limits for Occupational/Controlled Exposures							
0.3-3.0	614	1.63	*(100)	6			
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6			
30–300	61.4	0.163	1.0	6			
300–1500			f/300	6			
1500-100,000			5	6			
	(B) Limits fo	r General Population/Uncontroll	ed Exposure				
0.3-1.34	614	1.63	*(100)	30			
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30			
30–300	27.5	0.073	0.2	30			
300-1500			f/1500	30			
1500-100,000			1.0	30			

F = frequency in MHz

Formula: Pd = (Pout\*G)/(4\*  $\pi$  \*r<sup>2</sup>)

Where:

 $Pd = power density in mW/cm^2$ ,

Pout = output power to antenna in mW;

G = gain of antenna in linear scale,

 $\pi = 3.14$ ;

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

## 2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



Report No.: FCS202011035W02

## 3. Test Result of RF Exposure Evaluation

	Output power	Antenna	Power Density	Limit	Result
	(dBm/mW)	Gain(dBi)	at R=20cm	(mW/cm <sup>2</sup> )	
			(mW/cm <sup>2</sup> )		
802.11b	16.38/43.4510	1.0	0.01089	1.0	Pass
802.11g	16.37/43.3510	1.0	0.01086	1.0	Pass
802.11n(20MHz)	16.11/40.8319	1.0	0.01023	1.0	Pass
802.11n(40MHz)	15.16/32.8095	1.0	0.00822	1.0	Pass

Turn-up power			
Mode Peak power range(dBm)			
WIFI	15.00-18.00		

WIFI	Output power (dBm/mW)	Antenna Gain(dBi)	Power Density at R=20cm	Limit (mW/cm²)	Result
	(0.211)	,	(mW/cm <sup>2</sup> )	, , ,	
	18.00/63.0957	1.0	0.01581	1.0	Pass

Conclusion: No SAR is required