

Registration number: W6M22111-21326-C-1

FCC ID: 2AWP5WMD3F1

3.2 Equivalent Isotropic Radiated Power (EIRP)

FCC Rule: 15.247(b)(3)

EIRP=max. conducted output power + antenna gain

WiFi

EIRP=8.62 dBm+1.38 dBi [antenna gain claimed by manufacturer]=10.00 dBm=10.00 mW

BLE

EIRP=1.83 dBm+1.38 dBi [antenna gain claimed by manufacturer]=3.21 dBm=2.09 mW

3.3 Exemption Limits for Routine Evaluation according to FCC KDB Publication

RESULT:

Test standard : FCC KDB Publication
447498 D01 General RF Exposure Guidance v06

3.3.1 Exemption Limits for Routine Evaluation – SAR Evaluation

SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table .

Table: SAR evaluation — Exemption limits for routine evaluation based on frequency and separation distance

WiFi

MHz	5	10	15	20	25	mm
2412	10.07	19.21	29.28	38.41	48.41	SAR Test Exclusion Threshold (mW)

MHz	30	35	40	45	50	mm
2412	57.55	67.62	77.69	86.83	96.90	SAR Test Exclusion Threshold (mW)


Output power level shall be the higher of the maximum conducted or equivalent isotropically radiated power (e.i.r.p.) source-based, time-averaged output power.

Established separation distance is 5 mm.

Operating frequency band : 2412-2462 MHz

Max. output power level at 5 mm separation distance at 2412 MHz according to table is: 10.07 mW

The product is exempt from SAR Evaluation/Testing because the output power of 10.00 mW is below the exemption limit of 10.07 mW.



Registration number: W6M22111-21326-C-1

FCC ID: 2AWP5WMD3F1

BLE

MHz	5	10	15	20	25	mm
2402	10.09	19.26	29.35	38.52	48.52	SAR Test Exclusion Threshold (mW)

MHz	30	35	40	45	50	mm
2402	57.70	67.79	77.87	87.05	97.13	SAR Test Exclusion Threshold (mW)

Output power level shall be the higher of the maximum conducted or equivalent isotropically radiated power (e.i.r.p.) source-based, time-averaged output power.

Established separation distance is 5 mm.

Operating frequency band : 2402-2480 MHz

Max. output power level at 5 mm separation distance at 2402 MHz according to table is: 10.09 mW

The product is exempt from SAR Evaluation/Testing because the output power of 2.09 mW is below the exemption limit of 10.09 mW.