




Test Data

Maximum Conducted Output Power


Condition	Mode	Frequency	Antenna	Conducted Power	Duty Factor	Total Power	Limit	Verdict
		(MHz)		(dBm)	(dB)	(dBm)	(dBm)	
NVNT	BLE	2402	Ant1	1.485	0	1.485	30	Pass
NVNT	BLE	2442	Ant1	1.813	0	1.813	30	Pass
NVNT	BLE	2480	Ant1	0.926	0	0.926	30	Pass

Tel: +86-755-23118282, Fax: +86-755-23116366 Page 1 of 19














-6dB Bandwidth

Condition	on Mode Frequency (MHz)		Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE	2402	Ant1	0.658	0.5	Pass
NVNT	BLE	2442	Ant1	0.658	0.5	Pass
NVNT	BLE	2480	Ant1	0.663	0.5	Pass













Occupied Channel Bandwidth

Condition Mode		Frequency (MHz)	Antenna	99% OBW (MHz)	
NVNT	BLE	2402	Ant1	1.037905834	
NVNT	BLE	2442	Ant1	1.036942899	
NVNT	BLE	2480	Ant1	1.034021979	













Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	BLE	2402	Ant1	-14.615	8	Pass
NVNT	BLE	2442	Ant1	-14.287	8	Pass
NVNT	BLE	2480	Ant1	-15.345	8	Pass















Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE	2402	Ant1	-47.42	-20	Pass
NVNT	BLE	2480	Ant1	-56.82	-20	Pass













Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE	2402	Ant1	-51.17	-20	Pass
NVNT	BLE	2442	Ant1	-51.53	-20	Pass
NVNT	BLE	2480	Ant1	-50.2	-20	Pass











